# Sika® Primer MB Part A



Version Revision Date: SDS Number: 1.1 02/06/2017 000000604464

#### **SECTION 1. IDENTIFICATION**

Product name : Sika® Primer MB Part A

Manufacturer or supplier's details

Sika Canada Inc. Company name

601, avenue Delmar

Pointe-Claire, QC H9R 4A9

Canada www.sika.ca

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax (514) 694-2792

Health and Safety Services's : ehs@ca.sika.com

e-mail address

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

#### Recommended use of the chemical and restrictions on use

For further information, refer to product data sheet.

#### **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitization : Category 1

**GHS label elements** 

Hazard pictograms



Signal Word : Warning

**Hazard Statements** : H315 Causes skin irritation.

> H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

**Precautionary Statements** : Prevention:

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

# Sika® Primer MB Part A



 Version
 Revision Date:
 SDS Number:

 1.1
 02/06/2017
 000000604464

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P337 + P313 If eye irritation persists: Get medical advice/ atten-

tion.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Warning : Reports have associated repeated and prolonged exposure to

some of the chemicals in this product with permanent brain, liver, kidney and nervous system damage. Intentional misuse by deliberate concentration and inhalation of vapors may be harmful

or fatal.

#### Other hazards

None known.

#### **Supplemental information**

If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### **Hazardous ingredients**

Chemical name	CAS-No.	Concentration (% w/w)
bisphenol-A-(epichlorhydrin) epoxy resin	25068-38-6	>= 70 - < 80
bisphenol-F-(epichlorhydrin) epoxy resin	9003-36-5	>= 5 - < 10
oxirane, mono[(C12-14-	68609-97-2	>= 2 - < 5
alkyloxy)methyl]derivatives		
Benzyl alcohol	100-51-6	>= 2 - < 5
(R)-p-mentha-1,8-diene	5989-27-5	>= 0 - < 1

### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in attend-

ance.

If inhaled : Move to fresh air.

# Sika® Primer MB Part A



Version Revision Date: SDS Number: 1.1 02/06/2017 000000604464

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

> Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Clean mouth with water and drink afterwards plenty of water.

Do not induce vomiting without medical advice.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

: irritant effects sensitizing effects

Allergic reactions Excessive lachrymation

Erythema **Dermatitis** 

See Section 11 for more detailed information on health effects

and symptoms. Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

Notes to physician : Treat symptomatically.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for fire-fighters

: In the event of fire, wear self-contained breathing apparatus.

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec- : Use personal protective equipment. tive equipment and emergency procedures

Deny access to unprotected persons.

Environmental precautions

: Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages

# Sika® Primer MB Part A



 Version
 Revision Date:
 SDS Number:

 1.1
 02/06/2017
 000000604464

cannot be contained.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapors or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage

: Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Store in accordance with local regulations.

### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

### Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

**Engineering measures** 

: Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommend-

ed or statutory limits.

#### Personal protective equipment

Respiratory protection

: Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as-

sessment indicates this is necessary.

The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapor/aerosol/particulates) that may arise when han-

# Sika® Primer MB Part A



 Version
 Revision Date:
 SDS Number:

 1.1
 02/06/2017
 000000604464

dling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling

the product.

Remove contaminated clothing and protective equipment

before entering eating areas. Wash thoroughly after handling.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Color : blue

Odor : odorless

Odor Threshold : No data available

pH : No data available

Melting point/range / Freezing

ooint

: No data available

Boiling point/boiling range : No data available

Flash point :  $> 100 \, ^{\circ}\text{C} \, (> 212 \, ^{\circ}\text{F})$ 

Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapor pressure : 0.003 hpa (0.002 mmHg)

# Sika® Primer MB Part A



 Version
 Revision Date:
 SDS Number:

 1.1
 02/06/2017
 000000604464

Relative vapor density : No data available

Density : 1.1 g/cm3 (20 °C (68 °F) ())

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : ca. > 20.5 mm2/s (40  $^{\circ}$ C)

Explosive properties : No data available

Molecular weight : No data available

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac-

tions

: Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

No decomposition if stored and applied as directed.

### **SECTION 11. TOXICOLOGICAL INFORMATION**

### **Acute toxicity**

Not classified based on available information.

**Product:** 

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 10 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

# Sika® Primer MB Part A



 Version
 Revision Date:
 SDS Number:

 1.1
 02/06/2017
 000000604464

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

**Ingredients:** 

bisphenol-A-(epichlorhydrin) epoxy resin:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

Benzyl alcohol:

Acute oral toxicity : LD50 Oral (Rat): 1,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization: May cause an allergic skin reaction.

Respiratory sensitization: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC Group 2B: Possibly carcinogenic to humans

titanium dioxide 13463-67-7

NTP Not applicable

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

**Aspiration toxicity** 

Not classified based on available information.

# Sika® Primer MB Part A



Version **Revision Date:** SDS Number: 1.1 02/06/2017 000000604464

#### **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

#### Ingredients:

bisphenol-A-(epichlorhydrin) epoxy resin:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.8 mg/l

Exposure time: 48 h

Benzyl alcohol:

: LC50 (Fish): > 100 mg/l Toxicity to fish

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

### Persistence and degradability

No data available

## Bioaccumulative potential

No data available

#### Mobility in soil

No data available

### Other adverse effects

#### **Product:**

Additional ecological infor-

mation

: Do not empty into drains; dispose of this material and its con-

tainer in a safe way.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

Toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

May be harmful to the environment if released in large quanti-

ties.

Water polluting material.

### **SECTION 13. DISPOSAL CONSIDERATIONS**

#### Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should

> at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

: Empty containers should be taken to an approved waste han-Contaminated packaging

dling site for recycling or disposal.

# Sika® Primer MB Part A



Version Revision Date: SDS Number: 1.1 02/06/2017 000000604464

#### **SECTION 14. TRANSPORT INFORMATION**

#### **Domestic regulation**

#### TDG (road/train)

Not regulated as a dangerous good

### **International Regulations**

**IATA-DGR** 

UN/ID No. : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

(epoxy resin)

: 9 Class Packing group : 111

Labels : Miscellaneous Dangerous Goods

Packing instruction (cargo

aircraft)

Packing instruction (passen-: 964

ger aircraft)

**IMDG-Code** 

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(epoxy resin)

: 9 Class Packing group : III Labels 9 EmS Code F-A, S-F Marine pollutant : yes

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### **SECTION 15. REGULATORY INFORMATION**

#### **Canadian lists**

No substances are subject to a Significant New Activity Notification.

#### **SECTION 16. OTHER INFORMATION**

**Revision Date** : 02/06/2017

Prepared by : R & D of Sika Canada Inc.

Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other mate-

## Sika® Primer MB Part A



 Version
 Revision Date:
 SDS Number:

 1.1
 02/06/2017
 000000604464

rial, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

#### Full text of other abbreviations

ADR Accord européen relatif au transport international des marchandises

Dangereuses par Route

CAS Chemical Abstracts Service
DNEL Derived no-effect level

EC50 Half maximal effective concentration

GHS Globally Harmonized System

IATA International Air Transport Association

IMDG International Maritime Code for Dangerous Goods

LD50 Median lethal dosis (the amount of a material, given all at once, which

causes the death of 50% (one half) of a group of test animals)

LC50 Median lethal concentration (concentrations of the chemical in air that

kills 50% of the test animals during the observation period)

MARPOL International Convention for the Prevention of Pollution from Ships, 1973

as modified by the Protocol of 1978

OEL Occupational Exposure Limit

PBT Persistent, bioaccumulative and toxic
PNEC Predicted no effect concentration

REACH Regulation (EC) No 1907/2006 of the European Parliament and of the

Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a

European Chemicals Agency

SVHC Substances of Very High Concern

vPvB Very persistent and very bioaccumulative

CA / Z8

# Sika® Primer MB Part B



Version Revision Date: SDS Number: 1.2 12/16/2016 000000606331

#### **SECTION 1. IDENTIFICATION**

Product name : Sika® Primer MB Part B

Manufacturer or supplier's details

Sika Canada Inc. Company name

601, avenue Delmar

Pointe-Claire, QC H9R 4A9

Canada www.sika.ca

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax (514) 694-2792

Health and Safety Services's : ehs@ca.sika.com

e-mail address

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

#### Recommended use of the chemical and restrictions on use

For further information, refer to product data sheet.

### **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Flammable liquids : Category 4

Acute toxicity (Oral) : Category 4

Acute toxicity (Inhalation) : Category 4

Skin corrosion : Category 1B

Serious eye damage : Category 1

Skin sensitization : Sub-category 1A

**GHS** label elements

Hazard pictograms





Signal Word : Danger

**Hazard Statements** : H227 Combustible liquid.

## Sika® Primer MB Part B



 Version
 Revision Date:
 SDS Number:

 1.2
 12/16/2016
 000000606331

H302 + H332 Harmful if swallowed or if inhaled. H314 Causes severe skin burns and eve damage.

H317 May cause an allergic skin reaction.

**Precautionary Statements** 

#### : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

#### Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

#### Storage:

P403 Store in a well-ventilated place.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Warning

: Reports have associated repeated and prolonged exposure to some of the chemicals in this product with permanent brain,liver, kidney and nervous system damage. Intentional misuse by deliberate concentration and inhalation of vapors may be harmful or fatal.

### Other hazards

None known.

#### **Supplemental information**

# Sika® Primer MB Part B



 Version
 Revision Date:
 SDS Number:

 1.2
 12/16/2016
 000000606331

If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

### **Hazardous ingredients**

Chemical name	CAS-No.	Concentration (% w/w)
Benzyl alcohol	100-51-6	>= 40 - < 50
Isophoronediamine	2855-13-2	>= 10 -< 20
m-phenylenebis(methylamine)	1477-55-0	>= 10 -< 20
3,6,9-triazaundecamethylenediamine	112-57-2	>= 10 -< 20
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	>= 5 - < 10
Trimethylhexamethylenediamine-1,6 cyanethyl-	93941-62-9	>= 2 - < 5
ated		
Trimethylhexamethylenediamine	25620-58-0	>= 1 - < 2

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in attend-

ance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul-

ty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not induce vomiting without medical advice.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

: Health injuries may be delayed.

corrosive effects sensitizing effects

Gastrointestinal discomfort Respiratory disorder

### SAFFTY DATA SHFFT

# Sika® Primer MB Part B



Version **Revision Date:** SDS Number: 1.2 12/16/2016 000000606331

> Allergic reactions Headache **Dermatitis**

See Section 11 for more detailed information on health effects

and symptoms.

Harmful if swallowed or if inhaled. May cause an allergic skin reaction. Causes serious eye damage.

Causes severe burns.

Notes to physician : Treat symptomatically.

**SECTION 5. FIRE-FIGHTING MEASURES** 

Suitable extinguishing media : Carbon dioxide (CO2)

Unsuitable extinguishing

media

: Water

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

for fire-fighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : Use personal protective equipment. tive equipment and emer-

gency procedures

Deny access to unprotected persons.

: Do not flush into surface water or sanitary sewer system. Environmental precautions

If the product contaminates rivers and lakes or drains inform

respective authorities.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

**SECTION 7. HANDLING AND STORAGE** 

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapors or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

# Sika® Primer MB Part B



 Version
 Revision Date:
 SDS Number:

 1.2
 12/16/2016
 000000606331

Do not get in eyes, on skin, or on clothing.

For personal protection see section 8.

Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Smoking, eating and drinking should be prohibited in the application area.

Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage : Store in original container.

Keep in a well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

#### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

### Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type	Control parame-	Basis
		(Form of	ters / Permissible	
		exposure)	concentration	
m-phenylenebis(methylamine)	1477-55-0	(c)	0.1 mg/m3	CA AB OEL
		С	0.1 mg/m3	CA BC OEL
		С	0.1 mg/m3	CA QC OEL
		С	0.1 mg/m3	ACGIH

### **Engineering measures**

: Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

### Personal protective equipment

Respiratory protection

: Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection

# Sika® Primer MB Part B



 Version
 Revision Date:
 SDS Number:

 1.2
 12/16/2016
 000000606331

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling

the product.

Remove respiratory and skin/eye protection only after vapors

have been cleared from the area.

Remove contaminated clothing and protective equipment

before entering eating areas. Wash thoroughly after handling.

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Color : amber

Odor : amine-like

Odor Threshold : No data available

pH : not determined

Melting point/range / Freezing

point

: No data available

Boiling point/boiling range : No data available

Flash point : ca. 85 ℃ (185 °F)

Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapor pressure : 19.9983 hpa (15.000 mmHg)

Relative vapor density : No data available

Density : 1.004 g/ml (23 °C (73 °F) ())

# Sika® Primer MB Part B



 Version
 Revision Date:
 SDS Number:

 1.2
 12/16/2016
 000000606331

Solubility(ies)

Water solubility : partly soluble

Partition coefficient: n-

octanol/water

: No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 7 mm2/s (40 °C)

Explosive properties : No data available

Molecular weight : No data available

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac-

tions

: Stable under recommended storage conditions.

Conditions to avoid : Extremes of temperature and direct sunlight.

Incompatible materials : No data available

No decomposition if stored and applied as directed.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Acute toxicity**

Harmful if swallowed or if inhaled.

**Product:** 

Acute oral toxicity : Acute toxicity estimate: 1,282 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 4.43 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: 4,536 mg/kg

Method: Calculation method

# Sika® Primer MB Part B



 Version
 Revision Date:
 SDS Number:

 1.2
 12/16/2016
 000000606331

**Ingredients:** 

Benzyl alcohol:

Acute oral toxicity : LD50 Oral (Rat): 1,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Isophoronediamine:

Acute oral toxicity : LD50 Oral (Rat): 1,030 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg

m-phenylenebis(methylamine):

Acute oral toxicity : LD50 Oral (Rat): 930 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1.34 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rat): > 3,100 mg/kg

3,6,9-triazaundecamethylenediamine:

Acute oral toxicity : LD50 Oral (Rat): 1,716.2 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): 1,260 mg/kg

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization: May cause an allergic skin reaction.

Respiratory sensitization: Not classified based on available information.

**Ingredients:** 

Isophoronediamine:

Assessment: The product is a skin sensitizer, sub-category 1A. Result: The product is a skin sensitizer, sub-category 1A.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC Not applicable

NTP Not applicable

Reproductive toxicity

Not classified based on available information.

# Sika® Primer MB Part B



 Version
 Revision Date:
 SDS Number:

 1.2
 12/16/2016
 000000606331

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

**Aspiration toxicity** 

Not classified based on available information.

#### **SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity** 

Ingredients:

Benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Isophoronediamine:

Toxicity to algae : ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100

mg/l

Exposure time: 72 h

m-phenylenebis(methylamine):

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l

Exposure time: 48 h

2,4,6-tris(dimethylaminomethyl)phenol:

Toxicity to algae : EC50 (Scenedesmus capricornutum (fresh water algae)): > 10

- 100 mg/l

Exposure time: 72 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

**Product:** 

Additional ecological infor-

mation

: Do not empty into drains; dispose of this material and its con-

tainer in a safe way.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

# Sika® Primer MB Part B



 Version
 Revision Date:
 SDS Number:

 1.2
 12/16/2016
 000000606331

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

#### **SECTION 14. TRANSPORT INFORMATION**

#### **Domestic regulation**

TDG (road/train)

UN number : UN 3066

Proper shipping name : PAINT RELATED MATERIAL

Class : 8
Packing group : III
Labels : 8

**International Regulations** 

IATA-DGR

UN/ID No. : UN 3066

Proper shipping name : Paint related material

Class : 8 Packing group : III

Labels : Corrosives

Packing instruction (cargo : 856

aircraft)

Packing instruction (passen: 852

ger aircraft)

..

IMDG-Code

UN number : UN 3066

Proper shipping name : PAINT RELATED MATERIAL

Class : 8
Packing group : III
Labels : 8
EmS Code : F-A, S-B
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## Sika® Primer MB Part B



 Version
 Revision Date:
 SDS Number:

 1.2
 12/16/2016
 000000606331

#### **SECTION 15. REGULATORY INFORMATION**

#### **Canadian lists**

No substances are subject to a Significant New Activity Notification.

#### **SECTION 16. OTHER INFORMATION**

Revision Date : 12/16/2016

Prepared by : R & D of Sika Canada Inc.

#### Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

#### Full text of other abbreviations

ADR Accord européen relatif au transport international des marchandises

Dangereuses par Route

CAS Chemical Abstracts Service DNEL Derived no-effect level

EC50 Half maximal effective concentration

GHS Globally Harmonized System

IATA International Air Transport Association

IMDG International Maritime Code for Dangerous Goods

LD50 Median lethal dosis (the amount of a material, given all at once, which

causes the death of 50% (one half) of a group of test animals)

LC50 Median lethal concentration (concentrations of the chemical in air that

kills 50% of the test animals during the observation period)

MARPOL International Convention for the Prevention of Pollution from Ships, 1973

as modified by the Protocol of 1978

OEL Occupational Exposure Limit

PBT Persistent, bioaccumulative and toxic PNEC Predicted no effect concentration

REACH Regulation (EC) No 1907/2006 of the European Parliament and of the

Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a





Version 1.2	Revision Date: 12/16/2016	SDS Number: 000000606331	
SVHC vPvB	European Chemicals Agency Substances of Very High Concern Very persistent and very bioaccumulative		
CA / Z8			