

**SECTION 1. IDENTIFICATION**

Product name : Sikagard® Color A50 Lo-VOC

Other means of identification : No data available

Company name : 601, avenue Delmar  
Canada  
Pointe-Claire, QC H9R 4A9  
Sika Canada Inc.  
www.sika.ca

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

E-mail address : ehs@ca.sika.com

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the Hazardous Products Regulations**

Flammable liquids : Category 3

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitization : Sub-category 1B

Reproductive toxicity : Category 2

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

**GHS label elements**

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : H226 Flammable liquid and vapor.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.



H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H361 Suspected of damaging fertility or the unborn child.

Precautionary Statements :

**Prevention:**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P261 Avoid breathing mist or vapors.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Additional Labeling**

There are no ingredients with unknown acute toxicity used in a mixture at a concentration  $\geq 1\%$ .

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Components**

Chemical name	CAS-No.	Classification	Concentration (% w/w)
4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene	98-56-6	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Skin Sens. 1B; H317 STOT SE 3; H335	$\geq 30 - < 60$
trimethoxy(2-methylpropyl)silane	18395-30-7	Acute Tox. 4; H302	$\geq 1 - < 5$
toluene	108-88-3	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361 STOT SE 3; H336 STOT RE 2; H373 Asp. Tox. 1; H304	$\geq 0.1 - < 1$
methanol	67-56-1	Flam. Liq. 2; H225 Acute Tox. 3; H301 Acute Tox. 3; H331 Acute Tox. 3; H311 STOT SE 1; H370 Repr. 1B; H360	$\geq 0.1 - < 1$

Actual concentration or concentration range is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.



Do not induce vomiting without medical advice.  
 Do not give milk or alcoholic beverages.  
 Never give anything by mouth to an unconscious person.  
 Obtain medical attention.

Most important symptoms and effects, both acute and delayed : irritant effects  
 sensitizing effects  
 Cough  
 Respiratory disorder  
 Allergic reactions  
 Excessive lachrymation  
 Erythema  
 Dermatitis  
 Causes skin irritation.  
 May cause an allergic skin reaction.  
 Causes serious eye irritation.  
 May cause respiratory irritation.  
 Suspected of damaging fertility or the unborn child.

Notes to physician : Treat symptomatically.

**SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam  
 Carbon dioxide (CO<sub>2</sub>)  
 Dry chemical

Unsuitable extinguishing media : Water  
 High volume water jet

Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.

Further information : Use water spray to cool unopened containers.  
 Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
 Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
 Remove all sources of ignition.  
 Deny access to unprotected persons.  
 Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.  
 If the product contaminates rivers and lakes or drains inform



respective authorities.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**SECTION 7. HANDLING AND STORAGE**

Advice on protection against fire and explosion : Use explosion-proof equipment.  
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
Take precautionary measures against electrostatic discharges.

Advice on safe handling : Do not breathe vapors or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharge.  
Open drum carefully as content may be under pressure.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).  
Follow standard hygiene measures when handling chemical products.

Conditions for safe storage : Store in original container.  
Keep in a well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Store in accordance with local regulations.

Materials to avoid : Explosives  
Oxidizing agents  
Poisonous gases  
Poisonous liquids

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Ingredients with workplace control parameters**

Components	CAS-No.	Value type	Control parame-	Basis
------------	---------	------------	-----------------	-------



		(Form of exposure)	ters / Permissible concentration	
toluene	108-88-3	TWA	50 ppm 188 mg/m3	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	20 ppm	CA QC OEL
		TWA	20 ppm	ACGIH
methanol	67-56-1	TWA	200 ppm 262 mg/m3	CA AB OEL
		STEL	250 ppm 328 mg/m3	CA AB OEL
		TWA	200 ppm	CA BC OEL
		STEL	250 ppm	CA BC OEL
		TWAEV	200 ppm 262 mg/m3	CA QC OEL
		STEV	250 ppm 328 mg/m3	CA QC OEL

**Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.  
The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

**Personal protective equipment**

**Respiratory protection** : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

**Skin and body protection** : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

**Hygiene measures** : Avoid contact with skin, eyes and clothing.  
Wash hands before breaks and immediately after handling the product.  
Remove respiratory and skin/eye protection only after vapors



have been cleared from the area.  
Remove contaminated clothing and protective equipment  
before entering eating areas.  
Wash thoroughly after handling.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	:	liquid
Color	:	colored
Odor	:	irritating
Odor Threshold	:	No data available
pH	:	not determined
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	28 °C (82 °F) (Method: closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	7.066066 hpa
Relative vapor density	:	No data available
Density	:	1.020 g/ml (23 °C (73 °F))
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available



Viscosity, kinematic : not determined  
Explosive properties : No data available  
Oxidizing properties : No data available

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No dangerous reaction known under conditions of normal use.  
Chemical stability : The product is chemically stable.  
Possibility of hazardous reactions : Stable under recommended storage conditions.  
Vapors may form explosive mixture with air.  
Conditions to avoid : Heat, flames and sparks.  
Incompatible materials : No data available  
Hazardous decomposition products : No decomposition if stored and applied as directed.

---

**SECTION 11. TOXICOLOGICAL INFORMATION**

**Acute toxicity**

Not classified based on available information.

**Components:**

**4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene:**

Acute oral toxicity : LD50 Oral (Rat): > 13,000 mg/kg

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Respiratory or skin sensitization**

**Skin sensitization**

May cause an allergic skin reaction.

**Respiratory sensitization**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.





<b>IARC</b>	Group 2B: Possibly carcinogenic to humans 4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene	98-56-6
	Group 2B: Possibly carcinogenic to humans Titanium dioxide	13463-67-7
<b>OSHA</b>	OSHA specifically regulated carcinogen silicon dioxide (crystalline silica)	7631-86-9
<b>NTP</b>	Not applicable	

**Reproductive toxicity**

Suspected of damaging fertility or the unborn child.

**STOT-single exposure**

May cause respiratory irritation.

**STOT-repeated exposure**

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Aspiration toxicity**

Not classified based on available information.

---

**SECTION 12. ECOLOGICAL INFORMATION**
**Ecotoxicity****Components:****4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene:**

Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): 3 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 2 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (green algae)): > 0.41 mg/l Exposure time: 72 h

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects****Product:**

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.



Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.  
 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
 May be harmful to the environment if released in large quantities.  
 Water polluting material.

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

- Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### IATA-DGR

- UN/ID No. : UN 1263  
 Proper shipping name : Paint  
 Class : 3  
 Packing group : III  
 Labels : Flammable Liquids  
 Packing instruction (cargo aircraft) : 366  
 Packing instruction (passenger aircraft) : 355

##### IMDG-Code

- UN number : UN 1263  
 Proper shipping name : PAINT  
 Class : 3  
 Packing group : III  
 Labels : 3  
 EmS Code : F-E, S-E  
 Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Domestic regulation

##### TDG

- UN number : UN 1263  
 Proper shipping name : PAINT  
 Class : 3  
 Packing group : III



Labels : 3  
 ERG Code : 128  
 Marine pollutant : no

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

**SECTION 15. REGULATORY INFORMATION****Canadian lists**

No substances are subject to a Significant New Activity Notification.

**SECTION 16. OTHER INFORMATION****Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
 CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)  
 CA BC OEL : Canada. British Columbia OEL  
 CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants  
 ACGIH / TWA : 8-hour, time-weighted average  
 CA AB OEL / TWA : 8-hour Occupational exposure limit  
 CA AB OEL / STEL : 15-minute occupational exposure limit  
 CA BC OEL / TWA : 8-hour time weighted average  
 CA BC OEL / STEL : short-term exposure limit  
 CA QC OEL / TWAEV : Time-weighted average exposure value  
 CA QC OEL / STEV : Short-term exposure value

ADR : Accord européen relatif au transport international des marchandises Dangereuses par Route

CAS : Chemical Abstracts Service  
 DNEL : Derived no-effect level  
 EC50 : Half maximal effective concentration  
 GHS : Globally Harmonized System  
 IATA : International Air Transport Association  
 IMDG : International Maritime Code for Dangerous Goods  
 LD50 : Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)

LC50 : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)

MARPOL : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

**Sikagard® Color A50 Lo-VOC**



Revision Date 09/14/2022

Print Date 09/14/2022

- PBT : Persistent, bioaccumulative and toxic
- PNEC : Predicted no effect concentration
- REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
- SVHC : Substances of Very High Concern
- vPvB : Very persistent and very bioaccumulative

Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sika.ca](http://www.sika.ca) or 514-697-2610.

- Revision Date : 09/14/2022
- Date format : mm/dd/yyyy
- Prepared by : R & D of Sika Canada Inc.
- Material number : 458,770

CA / Z8