

Revision Date 11/25/2020

SECTION 1. IDENTIFICATION

Product name : Sikasil® WS-305 CN

Other means of identification : No data available

Company name : 601, avenue Delmar

Canada

Pointe-Claire, QC H9R 4A9

Sika Canada Inc. www.sika.ca

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

E-mail address : ehs@ca.sika.com

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

Recommended use of the chemical and restrictions on

use

For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids : Category 4

Skin sensitization : Category 1

Carcinogenicity (Inhalation) : Category 1A

Reproductive toxicity : Category 2

Specific target organ toxicity

- repeated exposure

Category 2

GHS label elements

Hazard pictograms :





Signal Word : Danger

Hazard Statements : H227 Combustible liquid.

H317 May cause an allergic skin reaction. H350 May cause cancer by inhalation.

H361 Suspected of damaging fertility or the unborn child. H373 May cause damage to organs through prolonged or re-



Revision Date 11/25/2020 Print Date 11/25/2020

peated exposure.

Precautionary Statements

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 Store in a well-ventilated place.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Classification	Concentra- tion (% w/w)
butan-2-one O,O',O"- (methylsilylidyne)trioxime	22984-54-9	Eye Irrit. 2A; H319 Skin Sens. 1; H317 STOT RE 2; H373	>= 1 - < 5
Quartz (SiO2)	14808-60-7	Carc. 1A; H350i STOT RE 1; H372 STOT SE 3; H335	>= 0.1 - < 1

Actual concentration or concentration range is withheld as a trade secret



Revision Date 11/25/2020 Print Date 11/25/2020

SECTION 4. FIRST AID MEASURES

General advice Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in attend-

ance.

If inhaled Move to fresh air.

Consult a physician after significant exposure.

Take off contaminated clothing and shoes immediately. In case of skin contact

> Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Clean mouth with water and drink afterwards plenty of water.

Do not induce vomiting without medical advice.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms

and effects, both acute and

delayed

sensitizing effects Allergic reactions

May cause an allergic skin reaction. May cause cancer by inhalation.

Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated

exposure.

Treat symptomatically. Notes to physician

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Carbon dioxide (CO2)

Unsuitable extinguishing

media

Water

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

for fire-fighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES



Revision Date 11/25/2020 Print Date 11/25/2020

Personal precautions, protec- : tive equipment and emer-

gency procedures

Use personal protective equipment. Deny access to unprotected persons.

Environmental precautions

Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform

respective authorities.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

fire and explosion

Advice on protection against : Normal measures for preventive fire protection.

Advice on safe handling Do not breathe vapors or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage Store in original container.

> Keep in a well-ventilated place. Observe label precautions.

Store in accordance with local regulations.

Materials to avoid **Explosives**

> Oxidizing agents Poisonous gases Poisonous liquids

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis
		(Form of	ters / Permissible	
		exposure)	concentration	
Quartz (SiO2)	14808-60-7	TWA (Res-	0.025 mg/m3	CA AB OEL
		pirable par-		



Revision Date 11/25/2020 Print Date 11/25/2020

ticulates)		
TWA (Respirable fraction)	0.1 mg/m3	CA ON OEL
TWAEV (respirable dust)	0.1 mg/m3	CA QC OEL
TWA (Respirable)	0.025 mg/m3 (Silica)	CA BC OEL
TWA (Respirable)	0.025 mg/m3	CA BC OEL
TWA (Respirable)	0.025 mg/m3 (Silica)	CA BC OEL
TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH

Engineering measures

Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

Personal protective equipment

Respiratory protection

Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.



Revision Date 11/25/2020 Print Date 11/25/2020

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling

the product.

Remove respiratory and skin/eye protection only after vapors

have been cleared from the area.

Remove contaminated clothing and protective equipment

before entering eating areas. Wash thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Color : various

Odor : mild, musty

Odor Threshold : No data available

pH : Not applicable

Melting point/range / Freezing :

noint

No data available

Boiling point/boiling range : No data available

Flash point : 88 °C (190 °F)

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapor pressure : 0.01 hpa

Relative vapor density : No data available

Density : ca. 1.4 g/cm3 (23 °C (73 °F))

Solubility(ies)



Revision Date 11/25/2020

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : $> 20.5 \text{ mm2/s} (40 ^{\circ}\text{C} (104 ^{\circ}\text{F}))$

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds

(VOC) content

16 g/l

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac-

tions

Stable under recommended storage conditions.

Conditions to avoid : Extremes of temperature and direct sunlight.

Incompatible materials : No data available

Hazardous decomposition

products

No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.



Revision Date 11/25/2020

Print Date 11/25/2020

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer by inhalation.

IARC Group 1: Carcinogenic to humans

Quartz (SiO2) 14808-60-7

(Silica dust, crystalline)

Group 2B: Possibly carcinogenic to humans

Carbon black, amorphous 1333-86-4

Group 2B: Possibly carcinogenic to humans

Titanium dioxide 13463-67-7

OSHA OSHA specifically regulated carcinogen

Quartz (SiO2) 14808-60-7

(crystalline silica)

NTP Known to be human carcinogen

Quartz (SiO2) 14808-60-7

(Silica, Crystalline (Respirable Size))

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Product:

Reproductive toxicity - As- : Suspected human reproductive toxicant

sessment

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

Print Date 11/25/2020

Revision Date 11/25/2020

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

Do not empty into drains; dispose of this material and its con-

tainer in a safe way.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

Not regulated as a dangerous good



Revision Date 11/25/2020 Print Date 11/25/2020

SECTION 15. REGULATORY INFORMATION

Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)

CA BC OEL : Canada. British Columbia OEL

CA ON OEL : Ontario Table of Occupational Exposure Limits made under

the Occupational Health and Safety Act.

CA QC OEL : Québec. Regulation respecting occupational health and safe-

ty, Schedule 1, Part 1: Permissible exposure values for air-

borne contaminants

ACGIH / TWA : 8-hour, time-weighted average
CA AB OEL / TWA : 8-hour Occupational exposure limit
CA BC OEL / TWA : 8-hour time weighted average
CA ON OEL / TWA : Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEV : Time-weighted average exposure value

ADR : Accord européen relatif au transport international des

marchandises Dangereuses par Route

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative



Revision Date 11/25/2020

Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

Revision Date : 11/25/2020 Date format : mm/dd/yyyy

Prepared by : R & D of Sika Canada Inc.

Material number : 664352

CA / Z8