



## PRODUCT DATA SHEET

# SikaProof® Sandwich Tape

### DOUBLE-SIDED ADHESIVE OVERLAP TAPE FOR THE SIKAPROOF® A+ MEMBRANE SYSTEM

#### PRODUCT DESCRIPTION

SikaProof® Sandwich Tape is a double-sided adhesive tape based on a polyacrylic adhesive sandwiched between release liners.

#### WHERE TO USE

SikaProof® Sandwich Tape may only be used by experienced professionals.

- Sealing and bonding of overlap joints and details within the SikaProof® A+ membrane system

#### CHARACTERISTICS / ADVANTAGES

- High adhesion and sealing capability
- High durability
- Simple and fast to install

#### APPROVALS / CERTIFICATES

- Watertightness of a Surface Sealing System SikaProof® A+ 12 / SikaProof® Sandwich Tape, WISSBAU, Test report No. 2018-276

#### PRODUCT INFORMATION

CSC MasterFormat®	07 13 00   SHEET WATERPROOFING	
Packaging	5 rolls packed in one cardboard box	
	Individual roll size	Length: 25 m Width: 50 mm
Appearance / Colour	Transparent polyacrylic adhesive and white release liners	
Shelf Life	18 months from date of production	
Storage Conditions	Product must be stored in original unopened and undamaged sealed packaging in dry conditions and temperatures between 5°C and 30 °C. Always refer to packaging.	
Thickness	1.00 mm (±5 %)	

#### SYSTEMS

System Structure	SikaProof® Sandwich Tape is a system component for sealing overlap joints of the SikaProof® A+ membrane system. For more detailed information, refer to Sika® Method Statement: SikaProof® A+ System
------------------	--

## Compatibility

For materials in direct contact (such as any synthetics etc.) the compatibility must be evaluated before full project application.  
Contact Sika® Technical Services for more information.

---

## APPLICATION INFORMATION

---

**Ambient Air Temperature** 5 °C min. / 45 °C max.

**Substrate Temperature** 5 °C min. / 60 °C max.

---

## BASIS OF PRODUCT DATA

Product properties are typically averages, obtained under laboratory conditions. Reasonable variations can be expected on-site due to local factors, including environment, preparation, application, curing and test methods.

## OTHER DOCUMENTS

- Sika® Method Statement: SikaProof® A+
- Product Data Sheet: SikaProof® A+ 08/12

## LIMITATIONS

Installation work must only be carried out by Sika® trained, approved or competent contractors experienced in this type of application.

- Do not install SikaProof® Sandwich Tape during continuous or prolonged rain or snowfall.
- The substrate quality and conditions must be fulfilled or appropriate measures must be taken.
- SikaProof® Sandwich Tape is not permanently UV resistant.
- The structural concrete must be placed within 90 days after the SikaProof® A+ membrane system is installed.

## ENVIRONMENT, HEALTH & SAFETY

### HAZARDOUS PRODUCT ACT - SECTION 2

This product is a manufactured article that does not require Safety Data Sheets to be marketed, transported or applied at the jobsite, according to the Hazardous Product Act - Section 2. Based on our current knowledge, this product is not classified as dangerous and does not contain any hazardous materials. Always wear personal protective equipment (including safety goggles and gloves) to manipulate and install Sika® products.

## APPLICATION INSTRUCTIONS

### SUBSTRATE QUALITY

The contact surfaces must be dry, clean and free of materials that could impair the adhesion. Contaminants, such as dirt, dust, oil, bitumen and de-bonding agents, such as surfactants and silicones must be removed.

### APPLICATION METHOD / TOOLS

Strictly follow installation procedures as defined in method statements, application manuals and working instructions which must always be adjusted to the actual site conditions.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

## LEGAL NOTES

The information contained herein and any other advice are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. The information only applies to the application(s) and product(s) expressly referred to herein and is based on laboratory tests which do not replace practical tests. In case of changes in the parameters of the application, such as changes in substrates etc., or in case of a different application, consult Sika's Technical Service prior to using Sika products. The information contained herein does not relieve the user of the products from testing them for the intended application and purpose. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or may be downloaded from our website at: [www.sika.ca](http://www.sika.ca).

### Sika Canada Inc.

Head Office  
601, avenue Delmar  
Pointe-Claire, Quebec  
H9R 4A9

### Other locations

Boisbriand (Quebec)  
Brantford; Cambridge;  
Sudbury; Toronto (Ontario)  
Edmonton (Alberta)  
Surrey (British Columbia)

### 1-800-933-SIKA

[www.sika.ca](http://www.sika.ca)



### Product Data Sheet

SikaProof® Sandwich Tape  
March 2021, Version 02.01  
020720308000000008

SikaProofSandwichTape-en-CA-(03-2021)-2-1.pdf

