



PRODUCT DATA SHEET

Sikafloor® SCO Color Additive

CONCENTRATED CASTOR OIL BASED COLOR ADDITIVES

PRODUCT DESCRIPTION

Sikafloor® SCO Color Additive are concentrated castor oil-based pigment blends specifically used for tinting the Sikafloor® 510 N LPL polyaspartic resin system.

WHERE TO USE

Sikafloor® SCO Color Additive may only be used by experienced professionals.

Sikafloor® SCO Color Additive is typically used in conjunction with Sikafloor® 510 N LPL polyaspartic resin system as a concrete primer, binder, and sealer especially when fast cure times and UV resistance are required. Do not use with any other Sikafloor® products.

PRODUCT INFORMATION

Packaging	Packaged in a 1 L can. 4 cans per carton.	
Appearance / Colour	Jet Black Traffic Blue Oxide Red Signal Yellow Light Gray Basalt Gray Beige Rose Raffia Beige Gray Beige	Signal White Pale Green Traffic Red Window Gray Traffic Gray Silver Gray Tan Beige
Shelf Life	24 months in original unopened container under proper storage conditions.	
Storage Conditions	Store dry between 4 - 32°C (40 - 90°F). Condition product at temperatures between 18 and 24 °C (65 and 75 °F) before using.	

CHARACTERISTICS / ADVANTAGES

- 100% solids; VOC compliant.
- Chemically stable, superior to solvent based pigment.
- Reduces inventory requirements.
- Excellent opacity at recommended dosage rates.
- Excellent dispersion properties during mixing.

ENVIRONMENTAL INFORMATION

- Potential contribution for LEED® projects.

APPROVALS / CERTIFICATES

- Meets the requirements of CFIA and UDSA for use in food plants.

BASIS OF PRODUCT DATA

Product properties are typically averages, obtained under laboratory conditions. Reasonable variations can be expected on-site due to local factors, including environment, preparation, application, curing and test methods.

LIMITATIONS

- Sikafloor® SCO Color Additive is currently approved for use with Sikafloor® 510 N LPL; do not use with any other Sikafloor® product.
- Do not use Sikafloor® SCO Color Additive with any other manufacturer's product.
- The use of solvent or thinners in the color additive is not recommended.
- Bright or light colors applied on dark substrates may require additional coats to achieve opacity.
- Using more Sikafloor® SCO Color Additive than the recommended dosage rate will reduce physical properties such as chemical and abrasion resistance.
- For a complete list of Application Instructions and Limitations please refer to the most current version of the Sikafloor® 510 N LPL product data sheet.

ENVIRONMENT, HEALTH & SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

Refer to the most current Sikafloor® 510 N LPL product data sheet for complete mixing and application instructions.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any recommendations, or from any other advice offered. The information contained herein does not relieve the user of the products from testing them for the intended application and purpose. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or may be downloaded from our website at: www.sika.ca

Sika Canada Inc.

Head Office
601, avenue Delmar
Pointe-Claire, Quebec
H9R 4A9
1-800-933-SIKA
www.sika.ca

Other locations

Boisbriand (Quebec)
Brantford; Cambridge;
Sudbury; Toronto (Ontario)
Edmonton (Alberta)
Surrey (British Columbia)