

PRODUCT DATA SHEET

Sarnafelt

A NON-WOVEN POLYESTER LEVELING AND/OR SEPERATION LAYER

PRODUCT DESCRIPTION

Sarnafelt is a non-woven polyester leveling and/or separation layer provided for use within Sarnafil® and Sikaplan® roofing systems.

WHERE TO USE

To act as a leveling layer for irregular surfaces and separate the membrane from existing non-compatible substrates.

Areas of Application

- Walls
- Curbs
- Substrates

CHARACTERISTICS / ADVANTAGES

Not applicable

PRODUCT INFORMATION

Composition / Manufacturing	Sarnafelt is composed of non-woven unsaturated polyester.
Packaging	Wrapped in clear polyethylene, 31.8 kg (70 lb) per roll
Appearance / Colour	White
Shelf Life	Not applicable
Storage Conditions	Store Sarnafelt in a cool, dry location away from inclement weather conditions.
Dimensions	Width: 2 m (82") Length: 41.1 m (135 ft)
Unit weight	370 g/m² (11.0 oz./yd²)
-	

Product Data Sheet

Sarnafelt
November 2021, Version 04.01
020945051050000010

BASIS OF PRODUCT DATA

Product properties are typically averages, obtained under laboratory conditions. Reasonable variations can be expected on-site due to local factors, including environment, preparation, application, curing and test methods.

OTHER DOCUMENTS

Availability

Sarnafelt is available directly from Sika Canada Authorized Applicators when used within a Sika® Sarnafil® Roofing or Waterproofing System. Contact Sika Canada or visit our website at www.sika.ca for further information.

Warranty

Upon successful completion of the installed roof by the Sika Canada Authorized Applicator, Sika Canada can provide a Warranty to the Building Owner via the Authorized Applicator.

ENVIRONMENT, HEALTH & SAFETY

This product is a manufactured article that does not require Safety Data Sheets to be marketed, transported or applied at the jobsite, according to the Hazardous Product Act - Section 2. Based on our current knowledge, this product is not classified as dangerous and does not contain any hazardous materials. Always wear personal protective equipment (including safety goggles and gloves) to manipulate and install Sika® products.

MAINTENANCE

As a prudent preventative measure, Sika Canada recommends that the Owner or that the Owner's designated representative inspect the installed roof system for damage, flashings, plugged drains, weathered sealants, etc. at least twice a year and after each storm.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

Sika Canada Inc.

Head Office 601, avenue Delmar Pointe-Claire, Quebec H9R 4A9 1-800-933-SIKA www.sika.ca

Other locations

Boisbriand (Quebec) Brantford; Cambridge; Sudbury; Toronto (Ontario) Edmonton (Alberta) Surrey (British Columbia)

LEGAL NOTES

The information, and in particular, the recommendations relating to the application and enduse of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any recommendations, or from any other advice offered. The information contained herein does not relieve the user of the products from testing them for the intended application and purpose. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or may be downloaded from our website at: www.sika.ca

Sarnafelt-en-CA-(11-2021)-4-1.pdf

