

SAFETY DATA SHEET

Sikaflex HY 100 aluminum grey Formerly MSeal NP 100 Alum Gry



Version 1.0 Revision Date: 07/28/2020 SDS Number: 000000586261 Date of last issue: -
Date of first issue: 07/28/2020

SECTION 1. IDENTIFICATION

Product name : Sikaflex HY 100 aluminum grey Formerly MSeal NP 100 Alum Gry

Product code : 000000000050392911

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE
Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Skin sensitization : 1A

Reproductive toxicity : 1B

Reproductive toxicity : 1B

Carcinogenicity : 1A

Short-term (acute) aquatic hazard : 3

Long-term (chronic) aquatic hazard : 3

GHS label elements

Hazard pictograms : The hazard pictograms consist of two red diamond-shaped symbols. The first contains a black exclamation mark, and the second contains a black silhouette of a person with a starburst on their chest, indicating a health hazard.

Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.
H350 May cause cancer.
H360 May damage fertility or the unborn child.

SAFETY DATA SHEET

Sikaflex HY 100 aluminum grey Formerly MSeal NP 100 Alum Gry



Version 1.0 Revision Date: 07/28/2020 SDS Number: 000000586261 Date of last issue: -
Date of first issue: 07/28/2020

H402 Harmful to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements :

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P201 Obtain special instructions before use.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P202 Do not handle until all safety precautions have been read and understood.
P273 Avoid release to the environment.
P272 Contaminated work clothing should not be allowed out of the workplace.

Response:

P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.
P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Sealant

Components

Chemical name	CAS-No.	Concentration (% w/w)
dibutyltin dilaurate	77-58-7	>= 0 - < 1
Quartz (SiO2)	14808-60-7	>= 0 - < 1
2-(2H-Benzotriazol-2-yl)-4,6-ditertpentylphenol	25973-55-1	>= 0 - < 3
bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	41556-26-7	>= 0 - < 3
bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate	52829-07-9	>= 0.2 - < 3
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	82919-37-7	>= 0 - < 1
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	1760-24-3	>= 0.2 - < 3

SAFETY DATA SHEET

Sikaflex HY 100 aluminum grey Formerly MSeal NP 100 Alum Gry



Version 1.0 Revision Date: 07/28/2020 SDS Number: 000000586261 Date of last issue: -
Date of first issue: 07/28/2020

Trimethoxyvinylsilane	2768-02-7	>= 0.3 - < 3
Dibutylbis(pentane-2,4-dionato-O,O')tin	22673-19-4	>= 0 - < 1
calcium carbonate	471-34-1	>= 3 - < 50
Limestone	1317-65-3	>= 3 - < 50
Titanium dioxide	13463-67-7	>= 0 - < 15
carbon black	1333-86-4	>= 0 - < 1
stearic acid	57-11-4	>= 0.1 - < 7

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this material safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Keep patient calm, remove to fresh air, seek medical attention.

Call a physician or poison control center immediately.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Induce vomiting immediately and call a physician.
Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.
May cause cancer.
May damage fertility or the unborn child.
- Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Foam
Dry powder
Carbon dioxide (CO2)

SAFETY DATA SHEET

Sikaflex HY 100 aluminum grey Formerly MSeal NP 100 Alum Gry



Version 1.0 Revision Date: 07/28/2020 SDS Number: 000000586261 Date of last issue: -
Date of first issue: 07/28/2020

- Unsuitable extinguishing media : High volume water jet
 - Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
 - Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
 - Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Avoid dust formation.
Avoid breathing dust.
Ensure adequate ventilation.
 - Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
 - Methods and materials for containment and cleaning up : Keep in suitable, closed containers for disposal.
-

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Avoid dust formation.
Provide appropriate exhaust ventilation at places where dust is formed.
- Advice on safe handling : Avoid formation of respirable particles.
Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

SAFETY DATA SHEET

Sikaflex HY 100 aluminum grey Formerly MSeal NP 100 Alum Gry



Version 1.0 Revision Date: 07/28/2020 SDS Number: 000000586261 Date of last issue: -
Date of first issue: 07/28/2020

place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Keep only in the original container in a cool, well-ventilated place.
Protect from direct sunlight.
Store protected against freezing.

Materials to avoid : Observe VCI storage rules.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
stearic acid	57-11-4	TWA value (Inhalable fraction)	10 mg/m ³	ACGIHTLV
		TWA value (Respirable fraction)	3 mg/m ³	ACGIHTLV
		TWA (Inhalable particulate matter)	10 mg/m ³	ACGIH
		TWA (Respirable particulate matter)	3 mg/m ³	ACGIH
dibutyltin dilaurate	77-58-7	TWA value	0.1 mg/m ³ (tin (Sn))	ACGIHTLV
		STEL value	0.2 mg/m ³ (tin (Sn))	ACGIHTLV
		REL value	0.1 mg/m ³ (tin (Sn))	NIOSH
		PEL	0.1 mg/m ³ (tin (Sn))	29 CFR 1910.1000 (Table Z-1)
		TWA value	0.1 mg/m ³ (tin (Sn))	29 CFR 1910.1000 (Table Z-1-A)
		TWA	0.1 mg/m ³ (Tin)	OSHA Z-1
		TWA	0.1 mg/m ³	ACGIH

SAFETY DATA SHEET

Sikaflex HY 100 aluminum grey Formerly MSeal NP 100 Alum Gry



Version
1.0

Revision Date:
07/28/2020

SDS Number:
000000586261

Date of last issue: -
Date of first issue: 07/28/2020

			(Tin)	
		STEL	0.2 mg/m3 (Tin)	ACGIH
		TWA	0.1 mg/m3 (Tin)	OSHA P0
		TWA	0.1 mg/m3 (Tin)	NIOSH REL
ethylenediamine	107-15-3	TWA value	10 ppm	ACGIHTLV
		REL value	10 ppm 25 mg/m3	NIOSH
		PEL	10 ppm 25 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	10 ppm 25 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	10 ppm	ACGIH
		TWA	10 ppm 25 mg/m3	NIOSH REL
		TWA	10 ppm 25 mg/m3	OSHA Z-1
		TWA	10 ppm 25 mg/m3	OSHA P0
Limestone	1317-65-3	REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL

SAFETY DATA SHEET

Sikaflex HY 100 aluminum grey Formerly MSeal NP 100 Alum Gry



Version 1.0 Revision Date: 07/28/2020 SDS Number: 000000586261 Date of last issue: -
Date of first issue: 07/28/2020

			(Calcium carbonate)	
carbon black	1333-86-4	TWA value (Inhalable fraction)	3 mg/m3	ACGIHTLV
		PEL	3.5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	3.5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		REL value	0.1 mg/m3 (Polycyclic aromatic hydrocarbons (PAH))	NIOSH
		TWA (Inhalable particulate matter)	3 mg/m3	ACGIH
		TWA	3.5 mg/m3	NIOSH REL
		TWA	3.5 mg/m3	OSHA Z-1
		TWA	3.5 mg/m3	OSHA P0
		TWA	0.1 mg/m3 (PAHs)	NIOSH REL
Titanium dioxide	13463-67-7	TWA value	10 mg/m3	ACGIHTLV
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
Quartz (SiO2)	14808-60-7	TWA value (Respirable fraction)	0.025 mg/m3	ACGIHTLV
		TWA value	0.05 mg/m3 (Respirable dust)	29 CFR 1910.1001-1050
		OSHA Action level	0.025 mg/m3 (Respirable dust)	29 CFR 1910.1001-1050
		REL value (Respirable dust)	0.05 mg/m3	NIOSH
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3

SAFETY DATA SHEET

Sikaflex HY 100 aluminum grey Formerly MSeal NP 100 Alum Gry



Version 1.0 Revision Date: 07/28/2020 SDS Number: 000000586261 Date of last issue: -
Date of first issue: 07/28/2020

		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
		TWA (respirable dust fraction)	0.1 mg/m ³	OSHA P0
		TWA (Respirable particulate matter)	0.025 mg/m ³ (Silica)	ACGIH
		PEL (respirable)	0.05 mg/m ³	OSHA CARC
		TWA (Respirable dust)	0.05 mg/m ³ (Silica)	NIOSH REL

Personal protective equipment

- Respiratory protection : Wear respiratory protection if ventilation is inadequate.
- Hand protection
- Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Protective measures : Avoid contact with the skin, eyes and clothing.
No special measures necessary if stored and handled correctly.
Handle in accordance with good building materials hygiene and safety practice.
Wearing of closed work clothing is recommended.
- Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : paste
- Color : gray
- pH : No data available
- Boiling point : No applicable information available.

SAFETY DATA SHEET

Sikaflex HY 100 aluminum grey Formerly MSeal NP 100 Alum Gry



Version 1.0	Revision Date: 07/28/2020	SDS Number: 000000586261	Date of last issue: - Date of first issue: 07/28/2020
----------------	------------------------------	-----------------------------	--

Flash point : > 253 °F / > 123 °C
Method: Standard Method of Test for Flash Point by Setaflash Closed Tester does not flash

Evaporation rate : No applicable information available.

Flammability (solid, gas) : not determined

Self-ignition : not self-igniting

Upper explosion limit / Upper flammability limit : No applicable information available.

Lower explosion limit / Lower flammability limit : No applicable information available.

Vapor pressure : No applicable information available.

Relative vapor density : No applicable information available.

Relative density : No applicable information available.

Density : 11.65 lb/USg (73 - 77 °F / 23 - 25 °C)

Solubility(ies)
Water solubility : insoluble (59 °F / 15 °C)
Solubility in other solvents : No applicable information available.

Partition coefficient: n-octanol/water : No applicable information available.

Autoignition temperature : No applicable information available.

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity
Viscosity, dynamic : No applicable information available.
Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive

Oxidizing properties : Not an oxidizer.

Self-heating substances : No data available

Sublimation point : No applicable information available.

Molecular weight : No data available

SAFETY DATA SHEET

Sikaflex HY 100 aluminum grey Formerly MSeal NP 100 Alum Gry



Version 1.0 Revision Date: 07/28/2020 SDS Number: 000000586261 Date of last issue: -
Date of first issue: 07/28/2020

SECTION 10. STABILITY AND REACTIVITY

- Reactivity : No decomposition if stored and applied as directed.
- Chemical stability : No decomposition if stored and applied as directed.
- Possibility of hazardous reactions : No decomposition if stored and applied as directed.
- Conditions to avoid : Avoid moisture.
See SDS section 7 - Handling and storage.
- Incompatible materials : Strong acids
Strong bases
Strong oxidizing agents
Strong reducing agents
- Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.
-

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

- Acute oral toxicity : Remarks: No applicable information available.
- Acute inhalation toxicity : Remarks: No applicable information available.
- Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Not classified based on available information.

Product:

- Remarks : May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

- Remarks : May cause irreversible eye damage.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

SAFETY DATA SHEET

Sikaflex HY 100 aluminum grey Formerly MSeal NP 100 Alum Gry



Version 1.0 Revision Date: 07/28/2020 SDS Number: 000000586261 Date of last issue: -
Date of first issue: 07/28/2020

Respiratory sensitization

Not classified based on available information.

Product:

Remarks : Causes sensitization.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer.

Reproductive toxicity

May damage fertility or the unborn child.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration hazard expected.

Further information

Product:

Remarks : The product has not been tested. The statement has been derived from the properties of the individual components.

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Components:

dibutyltin dilaurate:

Partition coefficient: n-octanol/water : log Pow: 3.17 (69.4 °F / 20.8 °C)
pH: 6.1 - 6.3
Method: Partition coefficient (n-octanol/water), Shake-flask method
GLP: yes

SAFETY DATA SHEET

Sikaflex HY 100 aluminum grey Formerly MSeal NP 100 Alum Gry



Version 1.0 Revision Date: 07/28/2020 SDS Number: 000000586261 Date of last issue: -
Date of first issue: 07/28/2020

Quartz (SiO₂):

Partition coefficient: n-octanol/water : Remarks: not applicable

2-(2H-Benzotriazol-2-yl)-4,6-ditertpentylphenol:

Partition coefficient: n-octanol/water : log Pow: > 6.5 (73 °F / 23 °C)
pH: 6.4
Method: Partition coefficient (n-octanol/water), HPLC method.

log Pow: 7.3 (77 °F / 25 °C)
Method: other (calculated)

bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate:

Partition coefficient: n-octanol/water : Remarks: No data available.

bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate:

Partition coefficient: n-octanol/water : log Pow: 0.35 (77 °F / 25 °C)
pH: 7
Method: Partition coefficient (n-octanol/water), Shake-flask method

Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

Partition coefficient: n-octanol/water : Remarks: No data available.

N-(3-(Trimethoxysilyl)propyl)ethylenediamine:

Partition coefficient: n-octanol/water : log Pow: -0.82
Method: other (calculated)

Trimethoxyvinylsilane:

Partition coefficient: n-octanol/water : log Pow: 1.1 (68 °F / 20 °C)

Dibutylbis(pentane-2,4-dionato-O,O')tin:

Partition coefficient: n-octanol/water : Remarks: Study technically not feasible.

calcium carbonate:

Partition coefficient: n-octanol/water : GLP: no
Remarks: The value has not been determined because the substance is inorganic.

Titanium dioxide:

Partition coefficient: n-octanol/water : Remarks: not applicable

SAFETY DATA SHEET

Sikaflex HY 100 aluminum grey Formerly MSeal NP 100 Alum Gry



Version 1.0 Revision Date: 07/28/2020 SDS Number: 000000586261 Date of last issue: -
Date of first issue: 07/28/2020

octanol/water

carbon black:

Partition coefficient: n-octanol/water : Remarks: not applicable

stearic acid:

Partition coefficient: n-octanol/water : Remarks: No data available.

log Pow: 8.23
Method: other (measured)

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life.
Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with national, state and local regulations.
Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

SAFETY DATA SHEET

Sikaflex HY 100 aluminum grey Formerly MSeal NP 100 Alum Gry



Version 1.0 Revision Date: 07/28/2020 SDS Number: 000000586261 Date of last issue: -
Date of first issue: 07/28/2020

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

Clean Air Act

:

CA TAC

:

HON HAP (US)

:

:

HON SOC (US)

: Group IV

Maximum allowable concentration::

VOC AE (US)

Reactivity factor::

VOC (US)

:

VOC EQ (US)

:

CA MIR

Maximum Incremental Reactivity (MIR) value::

CAA (US)

:

:

:

CA TAC

:

HON HAP (US)

:

:

Threshold for emissions from stacks less than 25 ft::

Ambient air standard::

Threshold for emissions from stacks less than 25 ft::

Threshold for emissions from stacks 40 to less than 75 ft::

Threshold for emissions from stacks 25 to less than 40 ft::

Threshold for emissions from stacks greater than or equal to

SAFETY DATA SHEET

Sikaflex HY 100 aluminum grey Formerly MSeal NP 100 Alum Gry



Version 1.0 Revision Date: 07/28/2020 SDS Number: 000000586261 Date of last issue: -
Date of first issue: 07/28/2020

75 ft::

Ambient air standard::

Threshold for emissions from stacks 40 to less than 75 ft::

Threshold for emissions from stacks 25 to less than 40 ft::

Threshold for emissions from stacks greater than or equal to 75 ft::

HON SOC (US) : Group I

:

Maximum allowable concentration::

VOC AE (US) Reactivity factor::

VOC (US) :

VOC EQ (US) :

CA MIR Maximum Incremental Reactivity (MIR) value::

CAA (US) :

:

US State Regulations

Pennsylvania Right To Know

ethylenediamine	107-15-3
calcium carbonate	471-34-1
Limestone	1317-65-3
Titanium dioxide	13463-67-7
Di-isononylphthalate	28553-12-0
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	68515-48-0

New Jersey Right To Know

ethylenediamine	107-15-3
Limestone	1317-65-3
Titanium dioxide	13463-67-7
carbon black	1333-86-4

California Prop. 65

WARNING: This product can expose you to chemicals including lead, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

SAFETY DATA SHEET

Sikaflex HY 100 aluminum grey Formerly MSeal NP 100 Alum Gry



Version 1.0 Revision Date: 07/28/2020 SDS Number: 000000586261 Date of last issue: -
Date of first issue: 07/28/2020

TSCA : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.


DSL : This product contains the following components that are not on the Canadian DSL nor NDSL.

Proprietary Polymer

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH		
FLAMMABILITY		
PHYSICAL HAZARD		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

- 29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)
- 29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
- 29 CFR 1910.1001-1050 : OSHA - Specifically Regulated Substances (29 CFR 1910.1001-1050)
- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)
- NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens
- OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

SAFETY DATA SHEET

Sikaflex HY 100 aluminum grey Formerly MSeal NP 100 Alum Gry



Version 1.0 Revision Date: 07/28/2020 SDS Number: 000000586261 Date of last issue: -
Date of first issue: 07/28/2020

eral Dusts
29 CFR 1910.1000 (Table Z-1-A) / TWA value : Time Weighted Average (TWA):
29 CFR 1910.1000 (Table Z-1) / PEL : Permissible exposure limit
29 CFR 1910.1001-1050 / OSHA Action level : OSHA Action level:
29 CFR 1910.1001-1050 / TWA value : Time Weighted Average (TWA):
ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
ACGIHTLV / STEL value : Short Term Exposure Limit (STEL):
ACGIHTLV / TWA value : Time Weighted Average (TWA):
NIOSH / REL value : Recommended exposure limit (REL):
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour
workday during a 40-hour workweek
OSHA CARC / PEL : Permissible exposure limit (PEL)
OSHA P0 / TWA : 8-hour time weighted average
OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

SAFETY DATA SHEET

Sikaflex HY 100 aluminum grey Formerly MSeal NP 100 Alum Gry



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/28/2020	000000586261	Date of first issue: 07/28/2020

Revision Date : 07/28/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN