

SAFETY DATA SHEET

Sikafloor®-165 FS Part A



Version
1.0

Revision Date:
06/13/2017

SDS Number:
100000016306

SECTION 1. IDENTIFICATION

Product name : Sikafloor®-165 FS Part A

Manufacturer or supplier's details

Company name : 601, avenue Delmar
Canada
Pointe-Claire, QC H9R 4A9
Sika Canada Inc.
www.sika.ca

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

Health and Safety Services's
e-mail address : ehs@ca.sika.com

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

Recommended use of the chemical and restrictions on use

For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitization : Category 1

GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

Precautionary Statements : **Prevention:**
P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264 Wash skin thoroughly after handling.

Version
1.0Revision Date:
06/13/2017SDS Number:
10000016306

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

Supplemental information

If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**Hazardous ingredients**

| Chemical name | CAS-No. | Concentration (% w/w) |
|---|------------|-----------------------|
| bisphenol-A-(epichlorhydrin) epoxy resin | 25068-38-6 | >= 55 - < 65 |
| bisphenol-F-(epichlorhydrin) epoxy resin | 28064-14-4 | >= 25 - < 35 |
| oxirane, mono[(C12-14-alkyloxy)methyl]derivatives | 68609-97-2 | >= 10 - < 20 |

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.

Version
1.0Revision Date:
06/13/2017SDS Number:
100000016306

| | |
|---|--|
| | Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. |
| If swallowed | : Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting without medical advice. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Obtain medical attention. |
| Most important symptoms and effects, both acute and delayed | : irritant effects sensitizing effects Allergic reactions Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed information on health effects and symptoms. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. |
| Notes to physician | : Treat symptomatically. |

SECTION 5. FIRE-FIGHTING MEASURES

| | |
|--|---|
| Suitable extinguishing media | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Further information | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. |
| Special protective equipment for fire-fighters | : In the event of fire, wear self-contained breathing apparatus. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

| | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment. Deny access to unprotected persons. |
| Environmental precautions | : Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained. |
| Methods and materials for containment and cleaning up | : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. |

SECTION 7. HANDLING AND STORAGE

Version
1.0Revision Date:
06/13/2017SDS Number:
10000016306

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Do not breathe vapors or spray mist.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

- Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protective equipment

- Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
- The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection

- Remarks : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Version
1.0Revision Date:
06/13/2017SDS Number:
10000016306

| | |
|--------------------------|---|
| Eye protection | : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary. |
| Skin and body protection | : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. |
| Hygiene measures | : Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Remove contaminated clothing and protective equipment before entering eating areas. Wash thoroughly after handling. |

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--------------------------------------|---|
| Appearance | : liquid |
| Color | : light yellow |
| Odor | : characteristic |
| Odor Threshold | : No data available |
| pH | : Not applicable |
| Melting point/range / Freezing point | : No data available |
| Boiling point/boiling range | : No data available |
| Flash point | : ca. 125 °C (257 °F) Method: closed cup |
| Evaporation rate | : No data available |
| Flammability (solid, gas) | : No data available |
| Upper explosion limit | : No data available |
| Lower explosion limit | : No data available |
| Vapor pressure | : 0.01 hpa (0.01 mmHg) |
| Relative vapor density | : No data available |
| Density | : ca. 1.14 g/cm ³ (23.7 °C (74.7 °F) ()) |
| Solubility(ies) Water solubility | : insoluble |
| Partition coefficient: n- | : No data available |

Version
1.0Revision Date:
06/13/2017SDS Number:
100000016306

octanol/water

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20.5 mm²/s (40 °C)

Explosive properties : No data available

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reactions : Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Ingredients:**bisphenol-A-(epichlorhydrin) epoxy resin:**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

bisphenol-F-(epichlorhydrin) epoxy resin:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization: May cause an allergic skin reaction.

Version
1.0Revision Date:
06/13/2017SDS Number:
100000016306

Respiratory sensitization: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC Not applicable

NTP Not applicable

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Ingredients:****bisphenol-A-(epichlorhydrin) epoxy resin:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.8 mg/l
aquatic invertebrates Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
May be harmful to the environment if released in large quanti-

Version
1.0Revision Date:
06/13/2017SDS Number:
10000016306

ties.
Water polluting material.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

- Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION**Domestic regulation****TDG (road/train)**

Not regulated as a dangerous good

International Regulations**IATA-DGR**

- UN/ID No. : UN 3082
- Proper shipping name : Environmentally hazardous substance, liquid, n.o.s. (epoxy resin)
- Class : 9
- Packing group : III
- Labels : Miscellaneous Dangerous Goods
- Packing instruction (cargo aircraft) : 964
- Packing instruction (passenger aircraft) : 964

IMDG-Code

- UN number : UN 3082
- Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)
- Class : 9
- Packing group : III
- Labels : 9
- EmS Code : F-A, S-F
- Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Version
1.0Revision Date:
06/13/2017SDS Number:
100000016306**SECTION 15. REGULATORY INFORMATION****Canadian lists**

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Revision Date : 06/13/2017
Prepared by : R & D of Sika Canada Inc.

Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

Full text of other abbreviations

| | |
|--------|--|
| ADR | Accord européen relatif au transport international des marchandises Dangereuses par Route |
| CAS | Chemical Abstracts Service |
| DNEL | Derived no-effect level |
| EC50 | Half maximal effective concentration |
| GHS | Globally Harmonized System |
| IATA | International Air Transport Association |
| IMDG | International Maritime Code for Dangerous Goods |
| LD50 | Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals) |
| LC50 | Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period) |
| MARPOL | International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978 |
| OEL | Occupational Exposure Limit |
| PBT | Persistent, bioaccumulative and toxic |
| PNEC | Predicted no effect concentration |
| REACH | Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a |

SAFETY DATA SHEET

Sikafloor®-165 FS Part A



Version
1.0

Revision Date:
06/13/2017

SDS Number:
10000016306

SVHC
vPvB

European Chemicals Agency
Substances of Very High Concern
Very persistent and very bioaccumulative

CA / Z8

SAFETY DATA SHEET

Sikafloor®-165 FS Part B



Version
1.0

Revision Date:
06/13/2017

SDS Number:
100000016307

SECTION 1. IDENTIFICATION

Product name : Sikafloor®-165 FS Part B

Manufacturer or supplier's details

Company name : 601, avenue Delmar
Canada
Pointe-Claire, QC H9R 4A9
Sika Canada Inc.
www.sika.ca

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

Health and Safety Services's
e-mail address : ehs@ca.sika.com

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

Recommended use of the chemical and restrictions on use

For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity (Oral) : Category 4
Acute toxicity (Inhalation) : Category 4
Skin corrosion : Category 1B
Serious eye damage : Category 1
Skin sensitization : Sub-category 1A
Reproductive toxicity : Category 2
Specific target organ system-
ic toxicity - repeated expo-
sure : Category 1

GHS label elements

SAFETY DATA SHEET

Sikafloor®-165 FS Part B



Version
1.0

Revision Date:
06/13/2017

SDS Number:
100000016307

Hazard pictograms



Signal Word

: Danger

Hazard Statements

: H302 + H332 Harmful if swallowed or if inhaled.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H361 Suspected of damaging fertility or the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.

Precautionary Statements

: **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
Storage:
P405 Store locked up.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Warning

: Reports have associated repeated and prolonged exposure to some of the chemicals in this product with permanent brain,liver,

Version
1.0Revision Date:
06/13/2017SDS Number:
10000016307

kidney and nervous system damage. Intentional misuse by deliberate concentration and inhalation of vapors may be harmful or fatal.

Other hazards

None known.

Supplemental information

If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**Hazardous ingredients**

| Chemical name | CAS-No. | Concentration (% w/w) |
|---------------------------------------|------------|-----------------------|
| Benzyl alcohol | 100-51-6 | >= 40 - < 50 |
| m-phenylenebis(methylamine) | 1477-55-0 | >= 10 - < 20 |
| 2-piperazin-1-ylethylamine | 140-31-8 | >= 10 - < 20 |
| 2,4,6-tris(dimethylaminomethyl)phenol | 90-72-2 | >= 5 - < 10 |
| 4,4'-isopropylidenediphenol | 80-05-7 | >= 5 - < 10 |
| Phenol, 4-nonyl, branched | 84852-15-3 | >= 3 - < 5 |
| Salicylic acid | 69-72-7 | >= 3 - < 5 |
| Isophoronediamine | 2855-13-2 | >= 2 - < 3 |
| Benzyl dimethylamine | 103-83-3 | >= 1 - < 2 |
| bis[(dimethylamino)methyl]phenol | 71074-89-0 | >= 1 - < 2 |

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.

Version
1.0Revision Date:
06/13/2017SDS Number:
10000016307

| | |
|---|--|
| If swallowed | : Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting without medical advice. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Take victim immediately to hospital. |
| Most important symptoms and effects, both acute and delayed | : Health injuries may be delayed. corrosive effects sensitizing effects Gastrointestinal discomfort Respiratory disorder Allergic reactions Headache Dermatitis See Section 11 for more detailed information on health effects and symptoms. Harmful if swallowed or if inhaled. May cause an allergic skin reaction. Causes serious eye damage. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Causes severe burns. |
| Notes to physician | : Treat symptomatically. |

SECTION 5. FIRE-FIGHTING MEASURES

| | |
|--|---|
| Suitable extinguishing media | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Further information | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. |
| Special protective equipment for fire-fighters | : In the event of fire, wear self-contained breathing apparatus. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

| | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment. Deny access to unprotected persons. |
| Environmental precautions | : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities. Local authorities should be advised if significant spillages cannot be contained. |
| Methods and materials for | : Soak up with inert absorbent material (e.g. sand, silica gel, |

Version
1.0Revision Date:
06/13/2017SDS Number:
10000016307

containment and cleaning up : acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Follow standard hygiene measures when handling chemical products.

Conditions for safe storage : Store in original container.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Ingredients with workplace control parameters

| Ingredients | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|-----------------------------|-----------|-------------------------------|--|-----------|
| m-phenylenebis(methylamine) | 1477-55-0 | (c) | 0.1 mg/m ³ | CA AB OEL |
| | | C | 0.1 mg/m ³ | CA BC OEL |
| | | C | 0.1 mg/m ³ | CA QC OEL |
| | | C | 0.1 mg/m ³ | ACGIH |

Engineering measures : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as-

Version
1.0Revision Date:
06/13/2017SDS Number:
10000016307

assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection

Remarks : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eye protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

Skin and body protection

: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Hygiene measures

: Avoid contact with skin, eyes and clothing.
Wash hands before breaks and immediately after handling the product.
Remove contaminated clothing and protective equipment before entering eating areas.
Wash thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--------------------------------------|--|
| Appearance | : liquid |
| Color | : yellow |
| Odor | : amine-like |
| Odor Threshold | : No data available |
| pH | : Not applicable |
| Melting point/range / Freezing point | : No data available |
| Boiling point/boiling range | : No data available |
| Flash point | : ca. 95 °C (203 °F) Method: closed cup |
| Evaporation rate | : No data available |
| Flammability (solid, gas) | : No data available |
| Upper explosion limit | : No data available |

SAFETY DATA SHEET

Sikafloor®-165 FS Part B



Version
1.0

Revision Date:
06/13/2017

SDS Number:
10000016307

| | |
|--|--|
| Lower explosion limit | : No data available |
| Vapor pressure | : 19.9983 hpa (15.000 mmHg) |
| Relative vapor density | : No data available |
| Density | : ca. 1.05 g/cm ³ (23.7 °C (74.7 °F) ()) |
| Solubility(ies) | |
| Water solubility | : insoluble |
| Partition coefficient: n-octanol/water | : No data available |
| Autoignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Viscosity | |
| Viscosity, dynamic | : No data available |
| Viscosity, kinematic | : > 20.5 mm ² /s (40 °C) |
| Explosive properties | : No data available |
| Molecular weight | : No data available |

SECTION 10. STABILITY AND REACTIVITY

| | |
|---|---|
| Reactivity | : No dangerous reaction known under conditions of normal use. |
| Chemical stability | : The product is chemically stable. |
| Possibility of hazardous reactions | : Stable under recommended storage conditions. |
| Conditions to avoid | : No data available |
| Incompatible materials | : No data available |
| No decomposition if stored and applied as directed. | |

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed or if inhaled.

Product:

| | |
|---------------------|--|
| Acute oral toxicity | : Acute toxicity estimate: 1,485 mg/kg Method: Calculation method |
|---------------------|--|

Version
1.0Revision Date:
06/13/2017SDS Number:
10000016307

Acute inhalation toxicity : Acute toxicity estimate: 3.89 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: 4,243 mg/kg
Method: Calculation method

Ingredients:**Benzyl alcohol:**

Acute oral toxicity : LD50 Oral (Rat): 1,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist**m-phenylenebis(methylamine):**

Acute oral toxicity : LD50 Oral (Rat): 930 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1.34 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rat): > 3,100 mg/kg

2-piperazin-1-ylethylamine:

Acute oral toxicity : LD50 Oral (Rabbit): ca. 2,097 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): ca. 866 mg/kg

Phenol, 4-nonyl, branched:

Acute dermal toxicity : LD50 Dermal (Rabbit): 3,160 mg/kg

Salicylic acid:

Acute oral toxicity : LD50 Oral (Rat): 891 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): > 2,000 mg/kg

Isophoronediamine:

Acute oral toxicity : LD50 Oral (Rat): 1,030 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg

Benzyl dimethylamine:

Acute oral toxicity : LD50 Oral (Rat): 579 mg/kg

Acute inhalation toxicity : LC50 (Rat): 2.05 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 Dermal (Rabbit): 1,477 mg/kg

Version
1.0Revision Date:
06/13/2017SDS Number:
10000016307**Skin corrosion/irritation**

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization: May cause an allergic skin reaction.

Respiratory sensitization: Not classified based on available information.

Ingredients:**Isophoronediamine:**

Assessment: The product is a skin sensitizer, sub-category 1A.

Result: The product is a skin sensitizer, sub-category 1A.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC Not applicable**NTP** Not applicable**Reproductive toxicity**

Suspected of damaging fertility or the unborn child.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Ingredients:****Benzyl alcohol:**Toxicity to fish : LC50 (Fish): > 100 mg/l
Exposure time: 96 hToxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l
aquatic invertebrates Exposure time: 48 h**m-phenylenebis(methylamine):**Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l
Exposure time: 96 hToxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l
aquatic invertebrates Exposure time: 48 h

Version
1.0Revision Date:
06/13/2017SDS Number:
100000016307**2-piperazin-1-ylethylamine:**Toxicity to fish : LC50 (Fish): > 100 mg/l
Exposure time: 96 h**2,4,6-tris(dimethylaminomethyl)phenol:**Toxicity to algae : EC50 (Scenedesmus capricornutum (fresh water algae)): > 10
- 100 mg/l
Exposure time: 72 h**Phenol, 4-nonyl, branched:**

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 10

Isophoronediamine:Toxicity to algae : ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100
mg/l
Exposure time: 72 h**Persistence and degradability**

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects**Product:**Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
May be harmful to the environment if released in large quantities.
Water polluting material.**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste han-

Version
1.0Revision Date:
06/13/2017SDS Number:
10000016307

ding site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION**Domestic regulation****TDG (road/train)**

UN number : UN 3066

Proper shipping name : PAINT

Class : 8

Packing group : II

Labels : 8

International Regulations**IATA-DGR**

UN/ID No. : UN 3066

Proper shipping name : Paint
(4-nonylphenol, branched)

Class : 8

Packing group : II

Labels : Corrosives

Packing instruction (cargo
aircraft) : 855Packing instruction (passen-
ger aircraft) : 851**IMDG-Code**

UN number : UN 3066

Proper shipping name : PAINT
(4-nonylphenol, branched)

Class : 8

Packing group : II

Labels : 8

EmS Code : F-A, S-B

Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15. REGULATORY INFORMATION**Canadian lists**

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Revision Date : 06/13/2017

SAFETY DATA SHEET

Sikafloor®-165 FS Part B



Version
1.0

Revision Date:
06/13/2017

SDS Number:
100000016307

Prepared by : R & D of Sika Canada Inc.

Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

Full text of other abbreviations

| | |
|--------|--|
| ADR | Accord européen relatif au transport international des marchandises Dangereuses par Route |
| CAS | Chemical Abstracts Service |
| DNEL | Derived no-effect level |
| EC50 | Half maximal effective concentration |
| GHS | Globally Harmonized System |
| IATA | International Air Transport Association |
| IMDG | International Maritime Code for Dangerous Goods |
| LD50 | Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals) |
| LC50 | Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period) |
| MARPOL | International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978 |
| OEL | Occupational Exposure Limit |
| PBT | Persistent, bioaccumulative and toxic |
| PNEC | Predicted no effect concentration |
| REACH | Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency |
| SVHC | Substances of Very High Concern |
| vPvB | Very persistent and very bioaccumulative |

CA / Z8