Sikafloor® Level-50



Version Revision Date: SDS Number: 1.2 10/17/2017 100000004433

SECTION 1. IDENTIFICATION

Product name Sikafloor® Level-50

Manufacturer or supplier's details

Company name 601, avenue Delmar

Canada

Pointe-Claire, QC H9R 4A9

Sika Canada Inc. www.sika.ca

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax (514) 694-2792

Health and Safety Services's : ehs@ca.sika.com

e-mail address

CANUTEC (collect) (613) 996-6666 (24 hours) Emergency telephone

Recommended use of the chemical and restrictions on use

For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Skin corrosion : Category 1C

Serious eye damage : Category 1

Skin sensitization : Category 1

Carcinogenicity (Inhalation) : Category 1A

Specific target organ systemic toxicity - single exposure

: Category 3 (Respiratory system)

Specific target organ system-

ic toxicity - repeated expo-

sure

: Category 1 (Lungs)

GHS label elements

Hazard pictograms







Sikafloor® Level-50



 Version
 Revision Date:
 SDS Number:

 1.2
 10/17/2017
 100000004433

Signal Word : Danger

Hazard Statements : H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. H350i May cause cancer by inhalation.

H372 Causes damage to organs (Lungs) through prolonged or

repeated exposure.

Precautionary Statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of

the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT

induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately

all contaminated clothing. Rinse skin with water.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON

CENTER/doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/doctor.

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/

attention.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Other hazards

None known.

Supplemental information

If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.

Sikafloor® Level-50



 Version
 Revision Date:
 SDS Number:

 1.2
 10/17/2017
 100000004433

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Quartz (SiO2)	14808-60-7	>= 30 - < 40
Portland cement	65997-15-1	>= 5 - < 10
Quartz (SiO2) <5µm	14808-60-7	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in attend-

ance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul-

ty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not induce vomiting without medical advice.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

Health injuries may be delayed.

corrosive effects irritant effects

sensitizing effects carcinogenic effects

Cough

Respiratory disorder Allergic reactions

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation.

Sikafloor® Level-50



Version Revision Date: SDS Number: 1.2 10/17/2017 100000004433

May cause cancer by inhalation.

Causes damage to organs through prolonged or repeated

exposure.

Causes severe burns.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for fire-fighters

: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

tive equipment and emer-

gency procedures

Personal precautions, protec- : Use personal protective equipment.

Avoid breathing dust.

Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for

containment and cleaning up

: Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

: Avoid dust formation. Provide appropriate exhaust ventilation

at places where dust is formed.

Advice on safe handling : Avoid formation of respirable particles.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Sikafloor® Level-50



 Version
 Revision Date:
 SDS Number:

 1.2
 10/17/2017
 100000004433

Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage : Prevent unauthorized access.

Store in original container. Keep in a well-ventilated place. Observe label precautions.

Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz (SiO2)	14808-60-7	TWA (Respirable fraction)	0.1 mg/m3	CA ON OEL
		TWA (Respirable particulates)	0.025 mg/m3	CA AB OEL
		TWAEV (respirable dust)	0.1 mg/m3	CA QC OEL
		TWA (Respirable)	0.025 mg/m3 (Silica)	CA BC OEL
		TWA (Respirable fraction)	0.025 mg/m3 (Silica)	ACGIH
Limestone	1317-65-3	TWA	10 mg/m3	CA AB OEL
		STEL	20 mg/m3	CA BC OEL
		TWAEV (to- tal dust)	10 mg/m3	CA QC OEL
		TWA (Total dust)	10 mg/m3	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m3	CA BC OEL
Portland cement	65997-15-1	TWA	10 mg/m3	CA AB OEL
		TWAEV (respirable dust)	5 mg/m3	CA QC OEL
		TWAEV (to- tal dust)	10 mg/m3	CA QC OEL
		TWA (Res- pirable)	1 mg/m3	CA BC OEL
		TWA (Respirable fraction)	1 mg/m3	ACGIH
calcium sulfate	7778-18-9	TWA (Inhal- able)	10 mg/m3	CA BC OEL
		TWAEV	5 mg/m3	CA QC OEL

Sikafloor® Level-50



 Version
 Revision Date:
 SDS Number:

 1.2
 10/17/2017
 100000004433

		(respirable dust) TWAEV (to-	10 mg/m3	CA QC OEL
		tal dust)	3	
		TWA	10 mg/m3	CA AB OEL
		TWA	10 mg/m3 (Calcium)	CA AB OEL
		TWA	10 mg/m3 (Calcium)	CA AB OEL
		TWA (Inhalable fraction)	10 mg/m3 (Calcium)	ACGIH
		TWA (Inhal- able fraction)	10 mg/m3 (Calcium)	ACGIH
Quartz (SiO2) <5μm	14808-60-7	TWA (Res- pirable frac- tion)	0.1 mg/m3	CA ON OEL
		TWA (Res- pirable par- ticulates)	0.025 mg/m3	CA AB OEL
		TWAEV (respirable dust)	0.1 mg/m3	CA QC OEL
		TWA (Res- pirable)	0.025 mg/m3 (Silica)	CA BC OEL
		TWA (Respirable fraction)	0.025 mg/m3 (Silica)	ACGIH

Engineering measures

: Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protective equipment

Respiratory protection

: Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

Sikafloor® Level-50



 Version
 Revision Date:
 SDS Number:

 1.2
 10/17/2017
 100000004433

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling

the product.

Remove contaminated clothing and protective equipment

before entering eating areas. Wash thoroughly after handling.

Avoid breathing dust.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder

Color : gray

Odor : odorless

Odor Threshold : No data available

pH : Not applicable

Melting point/range / Freezing

point

: No data available

Boiling point/boiling range : No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Density : Not applicable

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Autoignition temperature : No data available

Sikafloor® Level-50



 Version
 Revision Date:
 SDS Number:

 1.2
 10/17/2017
 100000004433

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : Not applicable

Explosive properties : No data available

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac-

tions

: Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization: May cause an allergic skin reaction.

Respiratory sensitization: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer by inhalation.

IARC Group 1: Carcinogenic to humans

Quartz (SiO2) 14808-60-7

Quartz (SiO2) <5µm 14808-60-7

Sikafloor® Level-50



 Version
 Revision Date:
 SDS Number:

 1.2
 10/17/2017
 100000004433

NTP Known to be human carcinogen

Quartz (SiO2) 14808-60-7

Quartz (SiO2) <5µm 14808-60-7

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

: Do not empty into drains; dispose of this material and its con-

tainer in a safe way.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

Sikafloor® Level-50



 Version
 Revision Date:
 SDS Number:

 1.2
 10/17/2017
 100000004433

SECTION 14. TRANSPORT INFORMATION

Domestic regulation

TDG (road/train)

Not dangerous goods

International Regulations

IATA-DGR

Not dangerous goods

IMDG-Code

Not dangerous goods

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15. REGULATORY INFORMATION

Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Revision Date : 10/17/2017

Prepared by : R & D of Sika Canada Inc.

Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

Full text of other abbreviations

ADR Accord européen relatif au transport international des marchandises

Dangereuses par Route

CAS Chemical Abstracts Service
DNEL Derived no-effect level

EC50 Half maximal effective concentration





Version	Revision Date:	SDS Number:	
1.2	10/17/2017	10000004433	
CHC	Clabally Harmanizad System		
GHS	Globally Harmonized System		
IATA	International Air Transport Association		
IMDG	International Maritime Code for Dangerous Goods		
LD50	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)		
LC50	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)		
MARPOL	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978		
OEL	Occupational Exposure Limit		
PBT	Persistent, bioaccumulative and toxic		
PNEC	Predicted no effect concentration		
REACH	Regulation (EC) No 1907/2006 of Council of 18 December 2006 of	of the European Parliament and of the oncerning the Registration, Evaluation, Chemicals (REACH), establishing a	
SVHC	Substances of Very High Conce	rn	
vPvB	Very persistent and very bioaccu		

CA / Z8