

Sikagard®-62 Part A

Revision Date 01/24/2025

Print Date 01/24/2025

SECTION 1. IDENTIFICATION

Product name	:	Sikagard [®] -62 Part A
Other means of identification	:	No data available
Company name	:	www.sika.ca Canada Pointe-Claire, QC H9R 4A9 601, avenue Delmar Sika Canada Inc.
Telephone	:	(514) 697-2610 / 1 (800) 933-7452
Telefax	:	(514) 694-2792
E-mail address	:	ehs@ca.sika.com
Emergency telephone	:	CANUTEC (collect) (613) 996-6666 (24 hours)
Recommended use of the chemical and restrictions on use	:	For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products RegulationsSkin irritation: Category 2		
Eye irritation	:	Category 2A
Skin sensitization	:	Category 1
GHS label elements Hazard pictograms	:	
Signal Word	:	Warning
Hazard Statements	:	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.
Precautionary Statements	:	Prevention:



Revision Date 01/24/2025 Print Date 01/24/2025 P261 Avoid breathing mist or vapors. P264 Wash skin thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/ eye protection/ face protection. **Response:** P302 + P352 IF ON SKIN: Wash with plenty of water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P362 + P364 Take off contaminated clothing and wash it before reuse. Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Classification	Concentra- tion (% w/w)
bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	25068-38-6	Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Skin Sens. 1; H317	>= 80 - <= 100
Solvent naphtha (petroleum), heavy arom.	64742-94-5	Flam. Liq. 4; H227 STOT SE 3; H336 Asp. Tox. 1; H304	>= 5 - < 10

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice

Move out of dangerous area. Consult a physician.

Show this material safety data sheet to the doctor in attendance.

2/11



Revision Date 01/24/2025		Print Date 01/24/2025
If inhaled		ve to fresh air. Isult a physician after significant exposure.
In case of skin contact	Wa	e off contaminated clothing and shoes immediately. sh off with soap and plenty of water. /mptoms persist, call a physician.
In case of eye contact	Rer Kee	nediately flush eye(s) with plenty of water. nove contact lenses. ep eye wide open while rinsing. /e irritation persists, consult a specialist.
If swallowed	Do Do Nev	an mouth with water and drink afterwards plenty of water. not induce vomiting without medical advice. not give milk or alcoholic beverages. rer give anything by mouth to an unconscious person. ain medical attention.
Most important symptoms and effects, both acute and delayed	sen Alle Exc Eryt Der Cau May	ant effects sitizing effects rgic reactions essive lachrymation thema matitis uses skin irritation. / cause an allergic skin reaction. uses serious eye irritation.
Notes to physician	: Trea	at symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec-	:	Use personal protective equipment.	
tive equipment and emer-		Deny access to unprotected persons.	
gency procedures			

Sikagard®-62 Part A



Revision Date 01/24/2025		Print Date 01/24/2025
Environmental precautions	:	Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
SECTION 7. HANDLING AND STO	DR	AGE
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products.
Conditions for safe storage	:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as-



Revision Date 01/24/2025	Print Date 01/24/2025
	sessment indicates this is necessary.
	The filter class for the respirator must be suitable for the max- imum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when han- dling the product. If this concentration is exceeded, self- contained breathing apparatus must be used.
Hand protection	 Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec- essary.
Eye protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin and body protection	: Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe- cific work-place.
Hygiene measures	 Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Remove contaminated clothing and protective equipment before entering eating areas. Wash thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Color	:	clear, straw-like
Odor	:	aromatic
Odor Threshold	:	No data available
рН	:	Not applicable
Melting point/ range / Freez- ing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	179.4 °C (354.9 °F) (Method: closed cup)



Revision Date 01/24/2025			Print Date 01/24/2025
Evaporation rate	:	No data available	
Flammability (solid, gas)	:	No data available	
Upper explosion limit / Upper flammability limit	:	No data available	
Lower explosion limit / Lower flammability limit	:	No data available	
Vapor pressure	:	10 hpa	
Relative vapor density	:	No data available	
Density	:	ca. 1.14 g/cm3 (23 °C (73 °F))	
Solubility(ies) Water solubility	:	insoluble	
Solubility in other solvents	:	No data available	
Partition coefficient: n- octanol/water	:	No data available	
Autoignition temperature	:	No data available	
Decomposition temperature	:	No data available	
Viscosity Viscosity, dynamic	:	No data available	
Viscosity, kinematic	:	> 20.5 mm2/s (40 °C (104 °F))	
Explosive properties	:	No data available	
Oxidizing properties	:	No data available	
Volatile organic compounds (VOC) content	:	20 g/l A+B Combined	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reac- tions	:	Stable under recommended storage conditions.



Revision Date 07	1/24/2025			Print Date 01/24/2025
Conditions	to avoid	:	No data available	
Incompatib	le materials	:	No data available	
Hazardous products	decomposition	:	No decomposition if stored and applied as direc	cted.
SECTION 11. T	OXICOLOGICAL	INFC	DRMATION	
Acute toxi Not classifi <u>Compone</u>	ed due to lack of c	lata.		
bisphenol Acute oral			boxy resin (number average molecular weight LD50 Oral (Rat): > 5,000 mg/kg	<= 700):
Acute derm	nal toxicity	:	LD50 Dermal (Rabbit): > 20,000 mg/kg	
Skin corro Causes ski	sion/irritation			
-	/e damage/eye irr rious eye irritation.		on	
Respirato	ry or skin sensitiz	zatio	n	
Skin sens i May cause	i tization an allergic skin re	actic	n.	
Respirator	r y sensitization ed due to lack of c			
	mutagenicity ed due to lack of c	lata.		
Carcinoge Not classifi IARC	nicity ed due to lack of c Not applicabl			
OSHA	Not applicabl	le		
NTP	Not applicabl	e		
-	t ive toxicity ed due to lack of c	lata		
	jle exposure			
	ed due to lack of c	lata		

Sikagard®-62 Part A

Revision Date 01/24/2025

Print Date 01/24/2025

STOT-repeated exposure

Not classified due to lack of data. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Aspiration toxicity

Not classified due to lack of data.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700):				
Toxicity to fish :	LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Exposure time: 96 h			
Toxicity to daphnia and other : aquatic invertebrates	EC50 (Daphnia magna (Water flea)): 1.8 mg/l Exposure time: 48 h			
Persistence and degradability No data available				
Bioaccumulative potential No data available				
Mobility in soil				
No data available				
Other adverse effects				
Product:				
Additional ecological infor- :	Do not empty into drains; dispose of this material and its con-			
mation	tainer in a safe way. Avoid dispersal of spilled material and runoff and contact with			
	soil, waterways, drains and sewers.			
	Toxic to aquatic organisms, may cause long-term adverse			
	effects in the aquatic environment. May be harmful to the environment if released in large quanti-			
	ties.			
	Water polluting material.			

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods		
Waste from residues	:	Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
		8 / 11



Revision Date 01/24/2025	Print Date 01/24/2025				
Contaminated packaging :	Empty containers should be taken to an approved waste han- dling site for recycling or disposal.				
SECTION 14. TRANSPORT INFORMATION					
International Regulations					
IATA-DGR UN/ID No. : Proper shipping name : Class : Packing group : Labels : Packing instruction (cargo : aircraft) Packing instruction (passen- : ger aircraft)	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (epoxy resin) 9 III Miscellaneous 964 964				
IMDG-Code UN number : Proper shipping name : Class : Packing group : Labels : EmS Code : Marine pollutant :	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin) 9 III 9 F-A, S-F yes				

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

IMDG: For Limited Quantity special provisions reference IMDG Code Chapter 3.4

TDG

Not regulated as a dangerous good

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Canadian lists

No substances are subject to a Significant New Activity Notification.



SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ADR CAS DNEL EC50 GHS IATA IMDG LD50		Accord européen relatif au transport international des marchandises Dangereuses par Route Chemical Abstracts Service Derived no-effect level Half maximal effective concentration Globally Harmonized System International Air Transport Association International Maritime Code for Dangerous Goods Median lethal dosis (the amount of a material, given all at
LC50	:	once, which causes the death of 50% (one half) of a group of test animals) Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.



Revision Date 01/24/2025

Print Date 01/24/2025

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

Revision Date Date format	: 01/24/2025 : mm/dd/yyyy
Prepared by	: R & D of Sika Canada Inc.
Material number	: 460,066

CA / Z8