BUILDING TRUST
CONSTRUIRE LA CONFIANCE

PRODUCT DATA SHEET

Sikafloor® Epoxy Pigment Pack CA

CONCENTRATED EPOXY BASED COLOUR ADDITIVES

PRODUCT DESCRIPTION

Sikafloor® Epoxy Pigment Pack CA are highly concentrated colour additives specifically designed for use with Sikafloor® epoxy flooring products. Refer to the technical data sheets for each product for the correct quantities and mixing instructions.

WHERE TO USE

For professional use only by experienced and properly trained applicators.

Sikafloor® Epoxy Pigment Pack CA is compatible with the following epoxy floor coatings:
- Sikafloor®-219 UTE
- CTM ECTR

CHARACTERISTICS / ADVANTAGES

- 100% solids
- Excellent dispersion properties during mixing
- Excellent opacity at recommended dosage rates
- Low odour

PRODUCT INFORMATION

Packaging	Packaged in 946 ml metal can. Carton contains 4 cans.	
Appearance / Colour	Available in:	White, Silver, Light Grey, Medium Grey, Basalt Grey, Safety Yellow, Safety Blue, Safety Red and Safety Green
Shelf Life	12 months in original unopened container under proper storage conditions.	
Storage Conditions	Store in a dry place, protected from freezing at a temperature between 5 °C and 32 °C (41 °F and 90 °F). Protect from freezing. If Sikafloor® Epoxy Pigment Pack CA has frozen, contact Sika Canada.	
CSC MasterFormat®	**09 67 00 | FLUID-APPLIED FLOORING**	
Consumption	**When used with Sikafloor®-219 UTE :** ▪ One (1) 946 mL can of Sikafloor® Epoxy Pigment Pack CA added to 7.57 L (Part A resin) per 11.35 L **Standard** format unit. ▪ Two (2) 946 mL cans of Sikafloor® Epoxy Pigment Pack CA added to 18.9 L (Part A resin) per 28.35 L **Meidum** format unit. **When used with CTM ECTR :** ▪ One (1) 946 mL can of Sikafloor® Epoxy Pigment Pack CA added to 7.57 L	

(Part A resin) per 11.35 L unit.

BASIS OF PRODUCT DATA

Product properties are typically averages, obtained under laboratory conditions. Reasonable variations can be expected on-site due to local factors, including environment, preparation, application, curing and test methods.

LIMITATIONS

NOTE: The user is solely responsible for the proper use of the product. Site visits carried out by Sika® personnel are intended solely, when requested by user, to provide written technical application recommendations based on Sika® documentation. They are in no way intended to supervise, approve or control the quality of the work performed on site. The information contained herein does not relieve the user of the products from testing them for the intended application and purpose.

- Use of more colour additive than recommended will result in changes in cure times and other physical properties
- Do not exceed the recommended amount of Sikafloor® Epoxy Pigment Pack CA stated in this document.
- Do not use Sikafloor® Epoxy Pigment Pack CA in any other Sikafloor® products other than those listed or products of other manufacturers
- Sikafloor® Epoxy Pigment Pack CA is not intended to be used alone.
- Do not hand mix Sikafloor® materials. Mechanically mix only.
- Do not thin this product. Addition of diluents (e.g., water, solvent, etc.) will slow cure and reduce ultimate properties of this product. Use of diluents will void any applicable Sika warranty.

IMPORTANT: Consult the complete list of product limitations specific to Sikafloor® 219 UTE or CTM ECTR by referring to the most current version of the respective product data sheet.

As well, Sika® recommends:

- That when using bright colours, additional coats may be required to achieve the desired opacity.
- That consideration should be given to include a mock-up of at least 10 m² in a discrete area in the project specifications (as part of section 09 67 00). It should also be specified whether the mock-up will remain permanently on the work area and be an integral part of the installation to verify that it meets the owner's expectations regarding appearance, slip resistance, and performance.

ENVIRONMENT, HEALTH & SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

MIXING

Mix each component individually, including the Sikafloor® Epoxy Pigment Pack CA, to ensure product uniformity.

When used with Sikafloor®-219 UTE (all colours):
- **11.35 L unit:** One (1) 946 mL container of Sikafloor® Epoxy Pigment Pack CA added to 7.57 L (Comp. A resin)
- **28.35 L unit:** Two (2) 946 mL containers of Sikafloor® Epoxy Pigment Pack CA added to 18.9 L (Comp. A resin)

When used with CTM ECTR (all colours):
- **11.35 L unit:** One (1) 946 mL container of Sikafloor® Epoxy Pigment Pack CA added to 7.57 L (Comp. A resin)

Mix at low speed (300 to 450 rpm) using a drill equipped with an Exomixer® or Jiffy-type mixing paddle for three (3) minutes, until a uniform colour is achieved. Avoid introducing air bubbles into the colour paste during mixing.

APPLICATION

Please refer to the most current version of the local Sikafloor® 219 UTE or CTM ECTR product data sheet for Substrate Preparation, Mixing, and Application Instructions.

CLEAN UP

Clean all tools and equipment with a non-flammable solvent. Once hardened, product can only be removed mechanically.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any recommendations, or from any other advice offered. The information contained herein does not relieve the user of the products from testing them for the intended application and purpose. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or may be downloaded from our website at: www.sika.ca

Sika Canada Inc.
Head Office
601, avenue Delmar
Pointe-Claire, Quebec
H9R 4A9
1-800-933-SIKA
www.sika.ca

Other locations
Boisbriand (Quebec)
Brantford; Cambridge;
Sudbury; Toronto (Ontario)
Edmonton (Alberta)
Surrey (British Columbia)