

**SECTION 1. IDENTIFICATION**

|   |   |  |
|---|---|--|
| Product name  | : | Sikalastic®-641 Lo-VOC   |
| Other means of identification                           | : | No data available  |
| Company name  | : | 601, avenue Delmar<br>Canada<br>Pointe-Claire, QC H9R 4A9<br>Sika Canada Inc.<br>www.sika.ca |
| Telephone   | : | (514) 697-2610 / 1 (800) 933-7452  |
| Telefax   | : | (514) 694-2792   |
| E-mail address  | : | ehs@ca.sika.com  |
| Emergency telephone                                     | : | CANUTEC (collect) (613) 996-6666 (24 hours)  |
| Recommended use of the chemical and restrictions on use | : | For further information, refer to product data sheet.  |

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the Hazardous Products Regulations**

|                             |   |                 |
|-----------------------------|---|-----------------|
| Flammable liquids           | : | Category 4      |
| Acute toxicity (Inhalation) | : | Category 4      |
| Skin irritation             | : | Category 2      |
| Eye irritation              | : | Category 2A     |
| Respiratory sensitization   | : | Category 1      |
| Skin sensitization          | : | Sub-category 1A |
| Reproductive toxicity       | : | Category 1B     |

**GHS label elements**

|                   |   |   |
|-------------------|---|---|
| Hazard pictograms | : |  |
|-------------------|---|---|

|                   |   |  |
|-------------------|---|--|
| Signal Word       | : | Danger   |
| Hazard Statements | : | H227 Combustible liquid.<br>H315 Causes skin irritation. |



H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H360 May damage fertility or the unborn child.

Precautionary Statements :

**Prevention:**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing mist or vapors.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P284 In case of inadequate ventilation wear respiratory protection.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 Store in a well-ventilated place.  
P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Additional Labeling**

There are no ingredients with unknown acute toxicity used in a mixture at a concentration  $\geq$  1%.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Components**

| Chemical name   | CAS-No.      | Classification  | Concentration (% w/w) |
|---|--------------|---|-----------------------|
| 4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene      | 98-56-6      | Flam. Liq. 3; H226<br>Skin Irrit. 2; H315<br>Eye Irrit. 2A; H319<br>Skin Sens. 1B; H317<br>STOT SE 3; H335                    | $\geq$ 10 - < 30      |
| Hardener MTJ (Polyoxypropylene-tri(morpholinoaldimine)) | 1379822-00-0 | Skin Sens. 1B; H317   | $\geq$ 5 - < 10       |
| Hardener MI (Isophoronedimorpholinoaldimine)            | 1217271-02-7 | Skin Irrit. 2; H315<br>Eye Irrit. 2A; H319<br>Skin Sens. 1; H317  | $\geq$ 1 - < 5        |
| Isophorondiisocyanate homopolymer                       | 53880-05-0   | Skin Sens. 1B; H317<br>STOT SE 3; H335  | $\geq$ 1 - < 5        |
| tris(methylphenyl) phosphate                            | 1330-78-5    | Repr. 2; H361   | $\geq$ 0.1 - < 1      |
| 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate | 4098-71-9    | Acute Tox. 1; H330<br>Skin Corr. 1C; H314<br>Eye Dam. 1; H318<br>Resp. Sens. 1; H334<br>Skin Sens. 1; H317<br>STOT SE 3; H335 | $\geq$ 0.1 - < 1      |
| Pentamethyl piperidylsebacate                           | 41556-26-7   | Skin Sens. 1A; H317<br>Repr. 2; H361  | $\geq$ 0.1 - < 1      |
| N-methyl-2-pyrrolidone                                  | 872-50-4     | Skin Irrit. 2; H315<br>Eye Irrit. 2A; H319<br>Repr. 1B; H360<br>STOT SE 3; H335   | $\geq$ 0.1 - < 1      |
| 4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT)        | 64359-81-5   | Acute Tox. 4; H302<br>Acute Tox. 2; H330<br>Skin Corr. 1; H314<br>Eye Dam. 1; H318<br>Skin Sens. 1A; H317                     | $\geq$ 0.1 - < 1      |
| Salicylic acid, o-hydroxybenzoic acid                   | 69-72-7      | Acute Tox. 4; H302<br>Eye Dam. 1; H318<br>Repr. 2; H361   | $\geq$ 0.1 - < 1      |

Actual concentration or concentration range is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attend-



- ance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
  - In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
  - In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
  - If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not induce vomiting without medical advice.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Obtain medical attention.
  - Most important symptoms and effects, both acute and delayed : irritant effects  
sensitizing effects  
toxic effects for reproduction  
Asthmatic appearance  
Respiratory disorder  
Allergic reactions  
Excessive lachrymation  
Erythema  
Headache  
Dermatitis  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Harmful if inhaled.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May damage fertility or the unborn child.
  - Notes to physician : Treat symptomatically.

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Carbon dioxide (CO2)
- Unsuitable extinguishing media : Water
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.



**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Deny access to unprotected persons.
  
- Environmental precautions : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.  
Local authorities should be advised if significant spillages cannot be contained.
  
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
  
- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapors or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Pregnant women or women of child-bearing age should not be exposed to this product.  
Follow standard hygiene measures when handling chemical products.  
Precautions should be taken to prevent odors and/or vapors from entering the building/structure, including but not limited to turning off and sealing air intake vents or other means of ingress for odors and/or vapors into the building/structure during product application and cure.
  
- Avoid formation of aerosol.  
Do not breathe vapors or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitization problems or asthma,



ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
 Smoking, eating and drinking should be prohibited in the application area.  
 Provide sufficient air exchange and/or exhaust in work rooms.  
 Pregnant women or women of child-bearing age should not be exposed to this product.  
 Follow standard hygiene measures when handling chemical products.

- Conditions for safe storage : Store in original container.  
 Keep in a well-ventilated place.  
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
 Observe label precautions.  
 Store in accordance with local regulations.
- Materials to avoid : Explosives  
 Oxidizing agents  
 Poisonous gases  
 Poisonous liquids

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Ingredients with workplace control parameters**

| Components  | CAS-No.   | Value type (Form of exposure)      | Control parameters / Permissible concentration | Basis     |
|---|-----------|------------------------------------|--|-----------|
| barium sulfate  | 7727-43-7 | TWA                                | 10 mg/m3                                       | CA AB OEL |
|   |           | TWA (Inhalable)                    | 5 mg/m3  | CA BC OEL |
|   |           | TWAEV (inhalable dust)             | 5 mg/m3  | CA QC OEL |
|   |           | TWA (Inhalable particulate matter) | 5 mg/m3  | ACGIH     |
| triphenyl phosphate                                     | 115-86-6  | TWA                                | 3 mg/m3  | CA AB OEL |
|   |           | TWA                                | 3 mg/m3  | CA BC OEL |
|   |           | TWAEV                              | 3 mg/m3  | CA QC OEL |
|   |           | TWA                                | 3 mg/m3  | ACGIH     |
| 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate | 4098-71-9 | TWA                                | 0.005 ppm<br>0.05 mg/m3                        | CA AB OEL |
|   |           | TWA                                | 0.005 ppm                                      | CA BC OEL |
|   |           | C                                  | 0.01 ppm                                       | CA BC OEL |
|   |           | TWA                                | 0.005 ppm                                      | CA ON OEL |
|   |           | C                                  | 0.02 ppm                                       | CA ON OEL |
|   |           | TWAEV                              | 0.005 ppm<br>0.045 mg/m3                       | CA QC OEL |
| N-methyl-2-pyrrolidone                                  | 872-50-4  | TWA                                | 400 mg/m3                                      | CA ON OEL |

**Engineering measures** : Use of adequate ventilation should be sufficient to control



worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

**Personal protective equipment**

**Respiratory protection** : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

**Skin and body protection** : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

**Hygiene measures** : Avoid contact with skin, eyes and clothing.  
 Wash hands before breaks and immediately after handling the product.  
 Remove respiratory and skin/eye protection only after vapors have been cleared from the area.  
 Remove contaminated clothing and protective equipment before entering eating areas.  
 Wash thoroughly after handling.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : liquid
- Color : various
- Odor : fruity
- Odor Threshold : No data available
- pH : Not applicable
- Melting point/range / Freezing : No data available



|  |  |
|--|--|
| point  |  |
| Boiling point/boiling range                      | : No data available                                |
| Flash point                                      | : ca. 65.55 °C (149.99 °F)<br>(Method: closed cup) |
| Evaporation rate                                 | : No data available                                |
| Flammability (solid, gas)                        | : No data available                                |
| Upper explosion limit / Upper flammability limit | : No data available                                |
| Lower explosion limit / Lower flammability limit | : No data available                                |
| Vapor pressure                                   | : 7.066066 hpa                                     |
| Relative vapor density                           | : No data available                                |
| Density  | : ca. 1.44 g/cm <sup>3</sup> (23 °C (73 °F))       |
| Solubility(ies)                                  |  |
| Water solubility                                 | : insoluble  |
| Solubility in other solvents                     | : No data available                                |
| Partition coefficient: n-octanol/water           | : No data available                                |
| Autoignition temperature                         | : No data available                                |
| Decomposition temperature                        | : No data available                                |
| Viscosity  |  |
| Viscosity, dynamic                               | : No data available                                |
| Viscosity, kinematic                             | : > 20.5 mm <sup>2</sup> /s ( 40 °C (104 °F))      |
| Explosive properties                             | : No data available                                |
| Oxidizing properties                             | : No data available                                |
| Volatile organic compounds (VOC) content         | : 38 g/l   |

---

**SECTION 10. STABILITY AND REACTIVITY**

|                                    |   |
|------------------------------------|---|
| Reactivity                         | : No dangerous reaction known under conditions of normal use. |
| Chemical stability                 | : The product is chemically stable.                           |
| Possibility of hazardous reactions | : Stable under recommended storage conditions.                |





|                                  |   |   |
|----------------------------------|---|---|
| Conditions to avoid              | : | Extremes of temperature and direct sunlight.        |
| Incompatible materials           | : | No data available                                   |
| Hazardous decomposition products | : | No decomposition if stored and applied as directed. |

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Harmful if inhaled.

**Components:****4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene:**

Acute oral toxicity : LD50 Oral (Rat): &gt; 13,000 mg/kg

**Hardener MTJ (Polyoxypropylenetri(morpholinoaldimine)):**

Acute oral toxicity : LD50 Oral (Rat): &gt; 2,001 mg/kg

**Hardener MI (Isophoronedim(morpholinoaldimine)):**

Acute oral toxicity : LD50 Oral (Rat): &gt; 2,001 mg/kg

**tris(methylphenyl) phosphate:**

Acute oral toxicity : LD50 Oral (Rat): &gt; 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 3,700 mg/kg

**3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate:**

Acute oral toxicity : LD50 Oral (Rat): 4,814 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0.031 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rat): &gt; 7,000 mg/kg

**N-methyl-2-pyrrolidone:**

Acute oral toxicity : LD50 Oral (Rat): 4,150 mg/kg

Acute inhalation toxicity : LC50 (Rat): 5.1 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rabbit): &gt; 5,000 mg/kg

**4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT):**

Acute oral toxicity : Acute toxicity estimate: 567 mg/kg



Method: Acute toxicity estimate according to Regulation (EC)  
No. 1272/2008

Acute inhalation toxicity : Acute toxicity estimate: 0.16 mg/l  
Test atmosphere: dust/mist  
Method: Acute toxicity estimate according to Regulation (EC)  
No. 1272/2008

**Salicylic acid, o-hydroxybenzoic acid:**

Acute oral toxicity : LD50 Oral (Rat): 891 mg/kg  
Acute dermal toxicity : LD50 Dermal (Rat): > 2,000 mg/kg

**Skin corrosion/irritation**

Causes skin irritation.

**Components:**

**Hardener MI (Isophoronedimethacrylate(morpholinoaldimine)):**

Method : Regulation (EC) No. 440/2008, Annex, B.46  
Result : Skin irritation

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Components:**

**Hardener MI (Isophoronedimethacrylate(morpholinoaldimine)):**

Result : Eye irritation  
Method : OECD Test Guideline 405

**Respiratory or skin sensitization**

**Skin sensitization**

May cause an allergic skin reaction.

**Respiratory sensitization**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Components:**

**Hardener MI (Isophoronedimethacrylate(morpholinoaldimine)):**

Method : Regulation (EC) No. 440/2008, Annex, B.42 (LLNA)  
Result : May cause sensitization by skin contact.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**IARC** Group 2B: Possibly carcinogenic to humans  
4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene

98-56-6



|  |            |
|--|------------|
| Group 2B: Possibly carcinogenic to humans<br>Titanium dioxide        | 13463-67-7 |
| Group 2B: Possibly carcinogenic to humans<br>Carbon black, amorphous | 1333-86-4  |

**OSHA** Not applicable

**NTP** Not applicable

**Reproductive toxicity**

May damage fertility or the unborn child.

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Aspiration toxicity**

Not classified based on available information.

---

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

**Components:**

**4-chloro- $\alpha,\alpha,\alpha$ -trifluorotoluene:**

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): 3 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 2 mg/l  
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata (green algae)): > 0.41  
plants mg/l  
Exposure time: 72 h

**Hardener MTJ (Polyoxypropylenetri(morpholinoaldimine)):**

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 45.1 mg/l  
aquatic invertebrates Exposure time: 48 h

NOEC (Daphnia magna (Water flea)): 12.5 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata (green algae)): 1.56  
plants mg/l  
Exposure time: 72 h

**Hardener MI (Isophoronedim(morpholinoaldimine)):**

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 40.2 mg/l  
aquatic invertebrates Exposure time: 48 h



NOEC (Daphnia magna (Water flea)): 17.1 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 89 mg/l  
Exposure time: 72 h

**tris(methylphenyl) phosphate:**

**4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT):**

Toxicity to fish : LC50 (Fish): 0.0027 mg/l  
Exposure time: 96 h

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

**Product:**

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.  
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
May be harmful to the environment if released in large quantities.  
Water polluting material.

**Global warming potential**

**Assessment Report of the Intergovernmental Panel on Climate Change (IPCC) of the United Nations Framework Convention on Climate Change (UNFCCC)**

**Components:**

**octamethylcyclotetrasiloxane:**

20-year global warming potential: 2.66  
100-year global warming potential: 0.739  
500-year global warming potential: 0.211  
Atmospheric lifetime: 0.027 yr  
Radiative efficiency: 0.12 Wm<sup>2</sup>ppb  
Further information: Miscellaneous compounds



### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

- Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### IATA-DGR

- UN/ID No. : UN 3082
- Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.  
(diphenyl tolyl phosphate)
- Class : 9
- Packing group : III
- Labels : Miscellaneous
- Packing instruction (cargo aircraft) : 964
- Packing instruction (passenger aircraft) : 964

##### IMDG-Code

- UN number : UN 3082
- Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S.  
(diphenyl tolyl phosphate)
- Class : 9
- Packing group : III
- Labels : 9
- EmS Code : F-A, S-F
- Marine pollutant : yes

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Domestic regulation

IMDG: For Limited Quantity special provisions reference IMDG Code Chapter 3.4

#### TDG

Not regulated as a dangerous good

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.




---

**SECTION 15. REGULATORY INFORMATION**
**Canadian lists**

The following substance(s) is/are subject to a Significant New Activity Notification:  
 Bis(2-propylheptyl) phthalate 53306-54-0

---

**SECTION 16. OTHER INFORMATION**
**Full text of other abbreviations**

|                   |   |  |
|-------------------|---|--|
| ACGIH             | : | USA. ACGIH Threshold Limit Values (TLV)  |
| CA AB OEL         | : | Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)  |
| CA BC OEL         | : | Canada. British Columbia OEL   |
| CA ON OEL         | : | Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.   |
| CA QC OEL         | : | Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants   |
| ACGIH / TWA       | : | 8-hour, time-weighted average  |
| CA AB OEL / TWA   | : | 8-hour Occupational exposure limit   |
| CA BC OEL / TWA   | : | 8-hour time weighted average   |
| CA BC OEL / C     | : | ceiling limit  |
| CA ON OEL / C     | : | Ceiling Limit (C)  |
| CA ON OEL / TWA   | : | Time-Weighted Average Limit (TWA)  |
| CA QC OEL / TWAEV | : | Time-weighted average exposure value   |
| ADR               | : | Accord européen relatif au transport international des marchandises Dangereuses par Route  |
| CAS               | : | Chemical Abstracts Service   |
| DNEL              | : | Derived no-effect level  |
| EC50              | : | Half maximal effective concentration   |
| GHS               | : | Globally Harmonized System   |
| IATA              | : | International Air Transport Association  |
| IMDG              | : | International Maritime Code for Dangerous Goods  |
| LD50              | : | Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)  |
| LC50              | : | Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)   |
| MARPOL            | : | International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978  |
| OEL               | : | Occupational Exposure Limit  |
| PBT               | : | Persistent, bioaccumulative and toxic  |
| PNEC              | : | Predicted no effect concentration  |
| REACH             | : | Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency |



SVHC : Substances of Very High Concern  
vPvB : Very persistent and very bioaccumulative

Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sika.ca](http://www.sika.ca) or 514-697-2610.

Revision Date : 12/02/2022  
Date format : mm/dd/yyyy  
Prepared by : R & D of Sika Canada Inc.  
Material number : 494,912

CA / Z8