



Sikadur®-31 SBA Cold Weather Part B

Revision Date 01/21/2025

Print Date 01/21/2025

SECTION 1. IDENTIFICATION

Product name : Sikadur®-31 SBA Cold Weather Part B

Other means of identification : No data available

Company name : www.sika.ca
Canada
Pointe-Claire, QC H9R 4A9
601, avenue Delmar
Sika Canada Inc.

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

E-mail address : ehs@ca.sika.com

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Skin corrosion : Category 1C

Serious eye damage : Category 1

Respiratory sensitization : Category 1

Skin sensitization : Sub-category 1A

Germ cell mutagenicity : Category 2

Carcinogenicity (Inhalation) : Category 1A

Reproductive toxicity : Category 2

Specific target organ toxicity : Category 2
- repeated exposure


GHS label elements



Sikadur®-31 SBA Cold Weather Part B

Revision Date 01/21/2025

Print Date 01/21/2025

Hazard pictograms	:	
Signal Word	:	Danger
Hazard Statements	:	<p>H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H341 Suspected of causing genetic defects. H350 May cause cancer by inhalation. H361 Suspected of damaging fertility or the unborn child. H373 May cause damage to organs through prolonged or repeated exposure.</p>
Precautionary Statements	:	<p>Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P260 Do not breathe mist or vapors. P264 Wash skin thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection. P284 In case of inadequate ventilation wear respiratory protection.</p> <p>Response: P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor. P362 + P364 Take off contaminated clothing and wash it before reuse.</p>



Sikadur®-31 SBA Cold Weather Part B

Revision Date 01/21/2025

Print Date 01/21/2025

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration $\geq 1\%$.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
P-tert-butylphenol (PTBP)	98-54-4	Skin Irrit. 2; H315 Eye Dam. 1; H318 Repr. 2; H361	$\geq 10 - < 30$
m-phenylenebis(methylamine)	1477-55-0	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Skin Sens. 1B; H317	$\geq 10 - < 30$
Trimethylhexane-1,6-diamine	25620-58-0	Acute Tox. 4; H302 Skin Corr. 1A; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317	$\geq 5 - < 10$
Phenol, 4-nonyl, branched	84852-15-3	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Repr. 2; H361	$\geq 5 - < 10$
phenol	108-95-2	Acute Tox. 3; H301 Acute Tox. 3; H331 Acute Tox. 3; H311 Skin Corr. 1B; H314 Muta. 2; H341 STOT RE 2; H373	$\geq 1 - < 5$
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2A; H319	$\geq 1 - < 5$
2,2'-iminodiethylamine	111-40-0	Acute Tox. 4; H302 Acute Tox. 2; H330 Acute Tox. 4; H312 Skin Corr. 1B; H314 Skin Sens. 1; H317	$\geq 0.1 - < 1$



Sikadur®-31 SBA Cold Weather Part B

Revision Date 01/21/2025

Print Date 01/21/2025

Quartz (SiO ₂) >5µm	14808-60-7	STOT SE 3; H335 Carc. 1A; H350 STOT RE 1; H372 STOT SE 3; H335	>= 0.1 - < 1
---------------------------------	------------	---	--------------

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not induce vomiting without medical advice.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Health injuries may be delayed.
corrosive effects
sensitizing effects
Asthmatic appearance
Allergic reactions
Dermatitis
May cause an allergic skin reaction.
Causes serious eye damage.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Suspected of causing genetic defects.
May cause cancer by inhalation.
Suspected of damaging fertility or the unborn child.
May cause damage to organs through prolonged or repeated



Sikadur®-31 SBA Cold Weather Part B

Revision Date 01/21/2025

Print Date 01/21/2025

exposure.
Causes severe burns.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Avoid formation of aerosol.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.



Sikadur®-31 SBA Cold Weather Part B

Revision Date 01/21/2025

Print Date 01/21/2025

Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products.

Conditions for safe storage : Store in original container.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Store in accordance with local regulations.

Materials to avoid : Explosives
Oxidizing agents
Poisonous gases
Dangerous when wet
Flammable solids
Organic peroxides
Poisonous liquids
Spontaneously Combustible Substances

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Calcium carbonate	471-34-1	TWAEV (total dust)	10 mg/m ³	CA QC OEL
		TWA	10 mg/m ³ (Calcium carbonate)	CA AB OEL
m-phenylenebis(methylamine)	1477-55-0	(c)	0.1 mg/m ³	CA AB OEL
		C	0.1 mg/m ³	CA BC OEL
		C	0.1 mg/m ³	CA QC OEL
		C	0.018 ppm	ACGIH
phenol	108-95-2	TWA	5 ppm 19 mg/m ³	CA AB OEL
		TWA	5 ppm	CA BC OEL
		TWAEV	5 ppm 19 mg/m ³	CA QC OEL
		TWA	5 ppm	ACGIH
2,2'-iminodiethylamine	111-40-0	TWA	1 ppm 4.2 mg/m ³	CA AB OEL
		TWA	1 ppm	CA BC OEL
		TWAEV	1 ppm 4.2 mg/m ³	CA QC OEL



Sikadur®-31 SBA Cold Weather Part B

Revision Date 01/21/2025

Print Date 01/21/2025

Quartz (SiO ₂) >5µm	14808-60-7	TWA	1 ppm	ACGIH
		TWA (Respirable particulates)	0.025 mg/m ³	CA AB OEL
		TWA (Respirable fraction)	0.1 mg/m ³	CA ON OEL
		TWA (Respirable)	0.025 mg/m ³ (Silica)	CA BC OEL
		TWAEV (respirable dust)	0.05 mg/m ³	CA QC OEL
		TWA (Respirable)	0.025 mg/m ³	CA BC OEL
		TWA (Respirable)	0.025 mg/m ³ (Silica)	CA BC OEL
		TWA (Respirable particulate matter)	0.025 mg/m ³	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m ³ (Silica)	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m ³	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m ³ (Silica)	ACGIH

Engineering measures : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.



Sikadur®-31 SBA Cold Weather Part B

Revision Date 01/21/2025

Print Date 01/21/2025

- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Avoid contact with skin, eyes and clothing.
Wash hands before breaks and immediately after handling the product.
Remove contaminated clothing and protective equipment before entering eating areas.
Wash thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : dark gray
- Odor : amine-like
- Odor Threshold : No data available
- pH : Not applicable
- Melting point/ range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : > 100 °C (> 212 °F)
(Method: closed cup)
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit / Upper flammability limit : No data available



Sikadur®-31 SBA Cold Weather Part B

Revision Date 01/21/2025

Print Date 01/21/2025

Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	0.05 hpa
Relative vapor density	:	No data available
Density	:	1.45 g/cm ³ (23 °C (73 °F))
Solubility(ies)		
Water solubility	:	partly soluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20.5 mm ² /s (40 °C (104 °F))
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds (VOC) content	:	2 g/l A+B Combined

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	No data available
Hazardous decomposition products	:	No decomposition if stored and applied as directed.



Sikadur®-31 SBA Cold Weather Part B

Revision Date 01/21/2025

Print Date 01/21/2025

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Components:

m-phenylenebis(methylamine):

- Acute oral toxicity : LD50 Oral (Rat): 930 mg/kg
- Acute inhalation toxicity : LC50 (Rat): 1.34 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Corrosive to the respiratory tract.
- Acute dermal toxicity : LD50 Dermal (Rat): > 3,100 mg/kg

Phenol, 4-nonyl, branched:

- Acute oral toxicity : LD50 Oral (Rat): 1,412 mg/kg
- Acute dermal toxicity : LD50 Dermal (Rabbit): 3,160 mg/kg

phenol:

- Acute oral toxicity : LD50 Oral (Rat): 300 mg/kg
- Acute inhalation toxicity : LC50 (Rat): > 0.9 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
- Acute dermal toxicity : LD50 Dermal: 660 mg/kg

2,4,6-tris(dimethylaminomethyl)phenol:

- Acute oral toxicity : LD50 Oral (Rat): 2,169 mg/kg

2,2'-iminodiethylamine:

- Acute oral toxicity : LD50 Oral (Rat): 1,553 mg/kg
- Acute inhalation toxicity : LC50 (Rat): 0.071 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
- Acute dermal toxicity : LD50 Dermal (Rat): 1,045 mg/kg

Skin corrosion/irritation

Causes severe burns.



Sikadur®-31 SBA Cold Weather Part B

Revision Date 01/21/2025

Print Date 01/21/2025

Product:

Method : In Vitro Membrane Barrier Test Method for Skin Corrosion -
CORROSITEX
Result : Corrosive after 1 to 4 hours of exposure

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Species : Rabbit
Assessment : Corrosive
Method : OECD Test Guideline 404

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Species : Rabbit
Assessment : Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Suspected of causing genetic defects.

Carcinogenicity

May cause cancer by inhalation.

IARC	Group 1: Carcinogenic to humans Quartz (SiO ₂) >5µm (Silica dust, crystalline)	14808-60-7
OSHA	OSHA specifically regulated carcinogen Talc (crystalline silica)	14807-96-6
	OSHA specifically regulated carcinogen Quartz (SiO ₂) >5µm (crystalline silica)	14808-60-7
NTP	Known to be human carcinogen Quartz (SiO ₂) >5µm (Silica, Crystalline (Respirable Size))	14808-60-7



Sikadur®-31 SBA Cold Weather Part B

Revision Date 01/21/2025

Print Date 01/21/2025

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT-single exposure

Not classified due to lack of data.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.
Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Aspiration toxicity

Not classified due to lack of data.

Further information

Product:

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

m-phenylenebis(methylamine):

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l
aquatic invertebrates Exposure time: 48 h

Phenol, 4-nonyl, branched:

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.
Avoid dispersal of spilled material and runoff and contact with



Sikadur®-31 SBA Cold Weather Part B

Revision Date 01/21/2025

Print Date 01/21/2025

soil, waterways, drains and sewers.
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
May be harmful to the environment if released in large quantities.
Water polluting material.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

- UN/ID No. : UN 3267
Proper shipping name : Corrosive liquid, basic, organic, n.o.s.
(m-phenylenebis(methylamine), 4-nonylphenol, branched)
Class : 8
Packing group : III
Labels : Corrosive
Packing instruction (cargo aircraft) : 856
Packing instruction (passenger aircraft) : 852

IMDG-Code

- UN number : UN 3267
Proper shipping name : CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.
(m-phenylenebis(methylamine), 4-nonylphenol, branched)
Class : 8
Packing group : III
Labels : 8
EmS Code : F-A, S-B
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation



Sikadur®-31 SBA Cold Weather Part B

Revision Date 01/21/2025

Print Date 01/21/2025

TDG

UN number : UN 3267
Proper shipping name : CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.
(m-phenylenebis(methylamine), Phenol, 4-nonyl, branched)
Class : 8
Packing group : III
Labels : 8
ERG Code : 153
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL : Canada. British Columbia OEL
CA ON OEL : Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA : 8-hour, time-weighted average
ACGIH / C : Ceiling limit
CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / (c) : ceiling occupational exposure limit
CA BC OEL / TWA : 8-hour time weighted average
CA BC OEL / C : ceiling limit
CA ON OEL / TWA : Time-Weighted Average Limit (TWA)
CA QC OEL / TWA EV : Time-weighted average exposure value
CA QC OEL / C : Ceiling

ADR : Accord européen relatif au transport international des marchandises Dangereuses par Route



Sikadur®-31 SBA Cold Weather Part B

Revision Date 01/21/2025

Print Date 01/21/2025

CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

Revision Date : 01/21/2025
Date format : mm/dd/yyyy

Prepared by : R & D of Sika Canada Inc.



Sikadur®-31 SBA Cold Weather Part B

Revision Date 01/21/2025

Print Date 01/21/2025

Material number : 459,396

CA / Z8