



Sikafloor[®]-297 CF

EPOXY CRACK FILLER



3 L (0.8 US gal) Kit

Sikafloor[®]-297 CF is a two-component, 100 % solids, low VOC, sag resistant, epoxy gel used to fill vertical and horizontal, non-moving joints and cracks. It has excellent adhesion to properly prepared concrete, masonry, wood, and metal.

ADVANTAGES

- Non-sag characteristic allows horizontal and vertical applications
- Very good mechanical and chemical resistance
- Excellent adhesion on a wide variety of prepared substrates
- Ideal to form round or flat fillet between horizontal and vertical surfaces
- Tack-free in 5 hours at 23 °C (73 °F)
- Low VOC / low odour suitable for application in occupied facilities

TO LEARN MORE



Our most current General Sales Conditions shall apply.
Please consult the most current local Product Data Sheet prior to any use.

Sika Canada Inc.
Head Office
601, avenue Delmar
Pointe-Claire, Quebec
H9R 4A9

Other locations
Boisbriand (QC)
Brantford; Cambridge;
Sudbury; Toronto (ON)
Edmonton (AB) Surrey (BC)

1-800-933-SIKA
www.sika.ca

© Sika Canada Inc. / 09.2024

**BUILDING TRUST
CONSTRUIRE LA CONFIANCE**

