



## Sika® Primer-215

Revision Date 03/14/2024

Print Date 10/12/2024

### SECTION 1. IDENTIFICATION

Product name : Sika® Primer-215

Other means of identification : No data available

Company name : www.sika.ca  
Canada  
Pointe-Claire, QC H9R 4A9  
601, avenue Delmar  
Sika Canada Inc.

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

E-mail address : ehs@ca.sika.com

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids : Category 2

Eye irritation : Category 2A

Skin sensitization : Sub-category 1A

Carcinogenicity (Inhalation) : Category 2

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

Specific target organ toxicity - repeated exposure (Inhalation) : Category 2

#### GHS label elements

Hazard pictograms :





## Sika® Primer-215

Revision Date 03/14/2024

Print Date 10/12/2024

Signal Word	:	Danger
Hazard Statements	:	H225 Highly flammable liquid and vapor. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer if inhaled. H373 May cause damage to organs through prolonged or repeated exposure if inhaled.
Precautionary Statements	:	<b>Prevention:</b> P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges. P260 Do not breathe mist or vapors. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection. <b>Response:</b> P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P362 + P364 Take off contaminated clothing and wash it before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. <b>Storage:</b>



## Sika® Primer-215

Revision Date 03/14/2024

Print Date 10/12/2024

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration  $\geq 1\%$ .

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
ethyl acetate	141-78-6	Flam. Liq. 2; H225 Eye Irrit. 2A; H319 STOT SE 3; H336	$\geq 30 - < 60$
butanone	78-93-3	Flam. Liq. 2; H225 Eye Irrit. 2A; H319 STOT SE 3; H336	$\geq 10 - < 30$
Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane	85702-90-5	Skin Sens. 1A; H317	$\geq 5 - < 10$
n-butyl acetate	123-86-4	Flam. Liq. 3; H226 STOT SE 3; H336	$\geq 5 - < 10$
Aromatic Polyisocyanate-Prepolymer	68958-67-8	Eye Irrit. 2A; H319 Skin Sens. 1; H317	$\geq 1 - < 5$
2-methoxy-1-methylethyl acetate	108-65-6	Flam. Liq. 3; H226 STOT SE 3; H336	$\geq 1 - < 5$
xylene	1330-20-7	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 STOT SE 3; H335 STOT RE 2; H373 Asp. Tox. 1; H304	$\geq 1 - < 5$
ethylbenzene	100-41-4	Flam. Liq. 2; H225 Acute Tox. 4; H332 STOT RE 2; H373 Asp. Tox. 1; H304 Carc. 2; H351	$\geq 0.1 - < 1$



## Sika® Primer-215

Revision Date 03/14/2024

Print Date 10/12/2024

		Eye Irrit. 2A; H319	
--	--	---------------------	--

Actual concentration or concentration range is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not induce vomiting without medical advice.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : irritant effects  
sensitizing effects  
Respiratory disorder  
Allergic reactions  
Excessive lachrymation  
Loss of balance  
Vertigo  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Suspected of causing cancer if inhaled.  
May cause damage to organs through prolonged or repeated exposure if inhaled.
- Notes to physician : Treat symptomatically.

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical



## Sika® Primer-215

Revision Date 03/14/2024

Print Date 10/12/2024

- Unsuitable extinguishing media : Water  
High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.
- Further information : Use water spray to cool unopened containers.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Remove all sources of ignition.  
Deny access to unprotected persons.  
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

---

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Use explosion-proof equipment.  
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
Take precautionary measures against electrostatic discharges.
- Advice on safe handling : Do not breathe vapors or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being



**Sika® Primer-215**

Revision Date 03/14/2024

Print Date 10/12/2024

used.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharge.  
Open drum carefully as content may be under pressure.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).  
Follow standard hygiene measures when handling chemical products.

Conditions for safe storage : Store in original container.  
Store in cool place.  
Keep in a well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Store in accordance with local regulations.

Materials to avoid : Explosives  
Oxidizing agents  
Poisonous gases  
Poisonous liquids

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethyl acetate	141-78-6	TWA	400 ppm 1,440 mg/m3	CA AB OEL
		TWA	150 ppm	CA BC OEL
		TWAEV	400 ppm 1,440 mg/m3	CA QC OEL
butanone	78-93-3	TWA	200 ppm 590 mg/m3	CA AB OEL
		STEL	300 ppm 885 mg/m3	CA AB OEL
		TWA	50 ppm	CA BC OEL
		STEL	100 ppm	CA BC OEL
		TWAEV	50 ppm 150 mg/m3	CA QC OEL
		STEV	100 ppm 300 mg/m3	CA QC OEL
n-butyl acetate	123-86-4	TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH
		TWA	150 ppm 713 mg/m3	CA AB OEL
		STEL	200 ppm	CA AB OEL



**Sika® Primer-215**

Revision Date 03/14/2024

Print Date 10/12/2024

			950 mg/m3	
		TWAEV	50 ppm	CA QC OEL
		STEV	150 ppm	CA QC OEL
		TWA	50 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
2-methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm	CA BC OEL
		STEL	75 ppm	CA BC OEL
		TWA	50 ppm 270 mg/m3	CA ON OEL
xylene	1330-20-7	TWA	100 ppm 434 mg/m3	CA AB OEL
		STEL	150 ppm 651 mg/m3	CA AB OEL
		TWAEV	100 ppm 434 mg/m3	CA QC OEL
		STEV	150 ppm 651 mg/m3	CA QC OEL
		TWA	100 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		TWA	20 ppm	ACGIH
ethylbenzene	100-41-4	TWA	100 ppm 434 mg/m3	CA AB OEL
		STEL	125 ppm 543 mg/m3	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	20 ppm	CA QC OEL
		TWA	20 ppm	ACGIH

**Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.  
The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

**Personal protective equipment**

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.



## Sika® Primer-215

Revision Date 03/14/2024

Print Date 10/12/2024

- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Avoid contact with skin, eyes and clothing.  
Wash hands before breaks and immediately after handling the product.  
Remove respiratory and skin/eye protection only after vapors have been cleared from the area.  
Remove contaminated clothing and protective equipment before entering eating areas.  
Wash thoroughly after handling.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : colorless
- Odor : ester-like
- Odor Threshold : No data available
- pH : Not applicable substance/mixture is non-soluble (in water)
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : 77 °C (171 °F)
- Flash point : -8 °C (18 °F)  
(Method: closed cup)
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available





## Sika® Primer-215

Revision Date 03/14/2024

Print Date 10/12/2024

Upper explosion limit / Upper flammability limit	:	Upper flammability limit 12 %(V)
Lower explosion limit / Lower flammability limit	:	Lower flammability limit 2 %(V)
Vapor pressure	:	ca. 60 hpa
Relative vapor density	:	No data available
Density	:	ca. 1 g/cm <sup>3</sup> (20 °C (68 °F))
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	333 °C
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 7 mm <sup>2</sup> /s ( 40 °C (104 °F))
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds (VOC) content	:	661.1 g/l

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions. Vapors may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	No data available
Hazardous decomposition products	:	No decomposition if stored and applied as directed.



## Sika® Primer-215

Revision Date 03/14/2024

Print Date 10/12/2024

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified due to lack of data.

#### Components:

##### **ethyl acetate:**

- Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg
- Acute inhalation toxicity : LC50 (Rat): ca. 1,600 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor
- Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

##### **butanone:**

- Acute oral toxicity : LD50 Oral (Rat): 3,300 mg/kg
- Acute inhalation toxicity : LC50 (Rat): 36 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor
- Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

##### **n-butyl acetate:**

- Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg
- Acute inhalation toxicity : LC50 (Rat): 23.4 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor
- Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

##### **2-methoxy-1-methylethyl acetate:**

- Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg
- Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

##### **xylene:**

- Acute oral toxicity : LD50 Oral (Rat): 3,523 mg/kg

##### **ethylbenzene:**

- Acute oral toxicity : LD50 Oral (Rat): 3,500 mg/kg
- Acute dermal toxicity : LD50 Dermal (Rabbit): 5,510 mg/kg



## Sika® Primer-215

Revision Date 03/14/2024

Print Date 10/12/2024

### Skin corrosion/irritation

Not classified due to lack of data.

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

#### Respiratory sensitization

Not classified due to lack of data.

#### Germ cell mutagenicity

Not classified due to lack of data.

#### Carcinogenicity

Suspected of causing cancer if inhaled.

<b>IARC</b>	Group 2B: Possibly carcinogenic to humans ethylbenzene	100-41-4
-------------	---	----------

<b>OSHA</b>	Not applicable
-------------	----------------

<b>NTP</b>	Not applicable
------------	----------------

#### Reproductive toxicity

Not classified due to lack of data.

#### STOT-single exposure

May cause drowsiness or dizziness.

#### STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

#### Aspiration toxicity

Not classified due to lack of data.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

**Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane:**

Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
------------------	---	--



## Sika® Primer-215

Revision Date 03/14/2024

Print Date 10/12/2024

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

### **n-butyl acetate:**

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 647.7 mg/l

### **Aromatic Polyisocyanate-Prepolymer:**

Toxicity to microorganisms : EC50 (Natural microorganism): > 10,000 mg/l  
Method: OECD Test Guideline 209  
Remarks: Information taken from reference works and the literature.

### **xylene:**

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l  
Exposure time: 56 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia): 1.17 mg/l  
Exposure time: 7 d

### **Persistence and degradability**

No data available

### **Bioaccumulative potential**

No data available

### **Mobility in soil**

No data available

### **Other adverse effects**

#### **Product:**

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

---

## **SECTION 13. DISPOSAL CONSIDERATIONS**

### **Disposal methods**

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental



## Sika® Primer-215

Revision Date 03/14/2024

Print Date 10/12/2024

protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### IATA-DGR

UN/ID No. : UN 1866  
Proper shipping name : Resin solution  
Class : 3  
Packing group : II  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 364  
Packing instruction (passenger aircraft) : 353

##### IMDG-Code

UN number : UN 1866  
Proper shipping name : RESIN SOLUTION  
  
Class : 3  
Packing group : II  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Domestic regulation

##### TDG

UN number : UN 1866  
Proper shipping name : RESIN SOLUTION  
  
Class : 3  
Packing group : II  
Labels : 3  
ERG Code : 127  
Marine pollutant : no

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.



## Sika® Primer-215

Revision Date 03/14/2024

Print Date 10/12/2024

---

### SECTION 15. REGULATORY INFORMATION

#### Canadian lists

No substances are subject to a Significant New Activity Notification.

---

### SECTION 16. OTHER INFORMATION

#### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value
ADR	:	Accord européen relatif au transport international des marchandises Dangereuses par Route
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament



## Sika® Primer-215

Revision Date 03/14/2024

Print Date 10/12/2024

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern  
vPvB : Very persistent and very bioaccumulative

### Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sika.ca](http://www.sika.ca) or 514-697-2610.

Revision Date : 03/14/2024  
Date format : mm/dd/yyyy

Prepared by : R & D of Sika Canada Inc.

Material number : 117,571

CA / Z8