Revision Date 01/17/2023



### **SECTION 1. IDENTIFICATION**

Product name	:	SikaQuick <sup>®</sup> -1000
Other means of identification	:	No data available
Company name	:	601, avenue Delmar Canada Pointe-Claire, QC H9R 4A9 Sika Canada Inc. www.sika.ca
Telephone	:	(514) 697-2610 / 1 (800) 933-7452
Telefax	:	(514) 694-2792
E-mail address	:	ehs@ca.sika.com
Emergency telephone	:	CANUTEC (collect) (613) 996-6666 (24 hours)
Recommended use of the chemical and restrictions on use	:	For further information, refer to product data sheet.

## **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with the Hazardous Products Regulations         Skin corrosion       : Category 1C				
Serious eye damage	:	Category 1		
Skin sensitization	:	Category 1		
Carcinogenicity (Inhalation)	:	Category 1A		
Specific target organ toxicity - single exposure	:	Category 3 (Respiratory system)		
Specific target organ toxicity - repeated exposure	:	Category 1 (Lungs)		
GHS label elements				
Hazard pictograms	:			
Signal Word	:	Danger		
Hazard Statements	:	H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction.		

Revision Date 01/17/2023



	H335 May cause respiratory irritation. H350 May cause cancer by inhalation. H372 Causes damage to organs (Lungs) through prolonged or repeated exposure.
Precautionary Statements	<ul> <li>Prevention:</li> <li>P201 Obtain special instructions before use.</li> <li>P202 Do not handle until all safety precautions have been read and understood.</li> <li>P260 Do not breathe dust.</li> <li>P264 Wash skin thoroughly after handling.</li> <li>P270 Do not eat, drink or smoke when using this product.</li> <li>P271 Use only outdoors or in a well-ventilated area.</li> <li>P272 Contaminated work clothing should not be allowed out of the workplace.</li> <li>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</li> </ul>
	<ul> <li>Response:</li> <li>P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.</li> <li>P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.</li> <li>P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.</li> <li>P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.</li> <li>P308 + P313 IF exposed or concerned: Get medical advice/ attention.</li> <li>P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.</li> <li>P362 + P364 Take off contaminated clothing and wash it before reuse.</li> </ul>
	<b>Storage:</b> P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.
	<b>Disposal:</b> P501 Dispose of contents/ container to an approved waste dis-

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Revision Date 01/17/2023



Substance / Mixture : Mixture

Components			
Chemical name	CAS-No.	Classification	Concentra-
			tion (% w/w)
Quartz (SiO2) >5µm	14808-60-7	Carc. 1A; H350	>= 60 - < 80
		STOT RE 1; H372	
		STOT SE 3; H335	
Portland Cement	65997-15-1	Skin Corr. 1C; H314	>= 10 - < 30
		Eye Dam. 1; H318	
		Skin Sens. 1; H317	
		STOT SE 3; H335	

Actual concentration or concentration range is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

General advice	:	Move out of dangerous area. Consult a physician. Show this material safety data sheet to the doctor in attend- ance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul- ty.
In case of eye contact	:	Small amounts splashed into eyes can cause irreversible tis- sue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing.
If swallowed	:	Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting without medical advice. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	:	Cough Respiratory disorder Allergic reactions Dermatitis Health injuries may be delayed. corrosive effects irritant effects sensitizing effects May cause an allergic skin reaction.





		Causes serious eye damage. May cause respiratory irritation. May cause cancer by inhalation. Causes damage to organs through prolonged or repeated exposure. Causes severe burns.
Notes to physician	:	Treat symptomatically.

## SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	Use personal protective equipment. Avoid breathing dust. Deny access to unprotected persons.
Environmental precautions	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for solutions to the second s	Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.

#### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.
Advice on safe handling	:	<ul> <li>Avoid formation of respirable particles.</li> <li>Avoid exceeding the given occupational exposure limits (see section 8).</li> <li>Do not get in eyes, on skin, or on clothing.</li> <li>For personal protection see section 8.</li> <li>Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being</li> </ul>

Revision Date 01/17/2023



	used. Smoking, eating and drinking should be prohibited in the ap- plication area. Follow standard hygiene measures when handling chemical products.
Conditions for safe storage	<ul> <li>Store in original container.</li> <li>Keep in a well-ventilated place.</li> <li>Observe label precautions.</li> <li>Store in accordance with local regulations.</li> </ul>
Materials to avoid	: Explosives Oxidizing agents Poisonous gases Dangerous when wet Flammable solids Organic peroxides Poisonous liquids Spontaneously Combustible Substances
Further information on stor- age stability	: Keep in a dry place. No decomposition if stored and applied as directed.

# SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Quartz (SiO2) >5µm	14808-60-7	TWA (Res- pirable par- ticulates)	0.025 mg/m3	CA AB OEL
		TWA (Res- pirable frac- tion)	0.1 mg/m3	CA ON OEL
		TWAEV (respirable dust)	0.1 mg/m3	CA QC OEL
		TWA (Res- pirable)	0.025 mg/m3 (Silica)	CA BC OEL
		TWA (Res- pirable)	0.025 mg/m3	CA BC OEL
		TWA (Res- pirable)	0.025 mg/m3 (Silica)	CA BC OEL
		TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m3	ACGIH
		TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m3 (Silica)	ACGIH
		TWA (Res-	0.025 mg/m3	ACGIH

# Ingredients with workplace control parameters

Print Date 01/17/2023

Revision Date 01/17/2023

		pirable par-		
		ticulate mat-		
		ter) TWA (Res-	0.025 mg/m3	ACGIH
		pirable par-	(Silica)	ACGIH
		ticulate mat-	(Silica)	
		ter)		
Portland Cement	65997-15-1	TWA	10 mg/m3	CA AB OEL
		TWA (Res-	1 mg/m3	CA BC OEL
		pirable)	1	0,100 022
		TWAEV	5 mg/m3	CA QC OEL
		(respirable	Ŭ	
		dust)		
		TWAEV (to-	10 mg/m3	CA QC OEL
		tal dust)		
		TWA (Res-	1 mg/m3	ACGIH
		pirable par-		
		ticulate mat-		
		ter)		
calcium sulfate, natural	7778-18-9	TWA (Inhal-	10 mg/m3	CA BC OEL
		able)	40	
		TWA	10 mg/m3	CA AB OEL
		TWAEV (in-	(Calcium) 10 mg/m3	CA QC OEL
		halable dust)	10 mg/ms	CA QC UEL
		TWA (Inhal-	10 mg/m3	ACGIH
		able particu-	(Calcium)	AUGIN
		late matter)	(Galolani)	
aluminium oxide	1344-28-1	TWA	10 mg/m3	CA AB OEL
	-	TWAEV (to-	10 mg/m3	CA QC OEL
		tal dust) `	(Aluminum)	
		TWA (Res-	1 mg/m3	CA BC OEL
		pirable)	(Aluminum)	
		TWA (Res-	1 mg/m3	ACGIH
		pirable par-	(Aluminum)	
		ticulate mat-		
		ter)		

#### Particles of nuisance dust

Form of exposure	Value type	Control parameters	Basis
total dust	TWA	15 mg/m3	OSHA Z-3
respirable fraction	TWA	5 mg/m3	OSHA Z-3

Engineering measures	Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use pro- cess enclosures, local exhaust ventilation or other engineer- ing controls to keep worker exposure below any recommend- ed or statutory limits.
Dave and protective equips	

#### Personal protective equipment

Respiratory protection	:	Use a properly fitted NIOSH approved air-purifying or air-fed
------------------------	---	---



Revision Date 01/17/2023

	respirator complying with an approved standard if a risk as- sessment indicates this is necessary.
	The filter class for the respirator must be suitable for the max- imum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when han- dling the product. If this concentration is exceeded, self- contained breathing apparatus must be used.
Hand protection :	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Eye protection :	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin and body protection :	Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe- cific work-place.
Hygiene measures :	Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Remove contaminated clothing and protective equipment before entering eating areas. Wash thoroughly after handling. Avoid breathing dust.

# SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	powder
Color	:	gray
Odor	:	odorless
Odor Threshold	:	No data available
рН	:	Not applicable
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	Not applicable
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available

Revision Date 01/17/2023



Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Density	:	ca. 2.84 g/cm3 (23 °C (73 °F))
Solubility(ies) Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n- octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, dynamic		No data available
viscosity, dynamic	•	
Viscosity, kinematic	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds (VOC) content	:	Not applicable

# SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reac- tions	:	Stable under recommended storage conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	No data available
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

### SECTION 11. TOXICOLOGICAL INFORMATION

Not classified based on available information.

Revision	Date	01/17/2023
----------	------	------------



<b>Skin corrosio</b> Causes sever					
•	<b>damage/eye irritation</b> us eye damage.				
Respiratory of	or skin sensitization				
<b>Skin sensitiz</b> May cause ar	ation allergic skin reaction.				
Respiratory s	<b>sensitization</b> based on available information.				
	Germ cell mutagenicity Not classified based on available information.				
Carcinogenicity					
May cause ca IARC	ancer by inhalation. Group 1: Carcinogenic to humans Quartz (SiO2) >5μm (Silica dust, crystalline)	14808-60-7			
OSHA	OSHA specifically regulated carcinogen Quartz (SiO2) >5μm (crystalline silica)	14808-60-7			
NTP	Known to be human carcinogen Quartz (SiO2) >5µm (Silica, Crystalline (Respirable Size))	14808-60-7			

### **Reproductive toxicity**

Not classified based on available information.

#### STOT-single exposure

May cause respiratory irritation.

#### STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure. Prolonged exposure can cause silicosis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

#### **Aspiration toxicity**

Not classified based on available information.

#### **Further information**

#### Product:

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

Revision Date 01/17/2023



#### **SECTION 12. ECOLOGICAL INFORMATION**

<b>Ecotoxicity</b> No data available	
<b>Persistence and degradability</b> No data available	
<b>Bioaccumulative potential</b> No data available	
<b>Mobility in soil</b> No data available	
Other adverse effects	
<b>Product:</b> Additional ecological infor- : mation	Do not empty into drains; dispose of this material and its con- tainer in a safe way.

### SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods		
Waste from residues	:	Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Contaminated packaging	:	Empty containers should be taken to an approved waste han- dling site for recycling or disposal.

#### **SECTION 14. TRANSPORT INFORMATION**

#### **International Regulations**

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code Not regulated as a dang

Not regulated as a dangerous good

# Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### **Domestic regulation**

#### TDG

Not regulated as a dangerous good

Revision Date 01/17/2023



### **SECTION 15. REGULATORY INFORMATION**

#### **Canadian lists**

The following substance(s) is/are subject to a Significant New Activity Notification: Quinoline 91-22-5

## **SECTION 16. OTHER INFORMATION**

Full text of other abbreviation	IS
ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	: Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	: Canada. British Columbia OEL
CA ON OEL	: Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	: Québec. Regulation respecting occupational health and safe- ty, Schedule 1, Part 1: Permissible exposure values for air- borne contaminants
OSHA Z-3	: USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min- eral Dusts
ACGIH / TWA	: 8-hour, time-weighted average
CA AB OEL / TWA	: 8-hour Occupational exposure limit
CA BC OEL / TWA	: 8-hour time weighted average
CA ON OEL / TWA	: Time-Weighted Average Limit (TWA)
	: Time-weighted average exposure value
OSHA Z-3 / TWA	: 8-hour time weighted average
ADR CAS DNEL EC50 GHS IATA IMDG LD50 LC50 MARPOL	<ul> <li>Accord européen relatif au transport international des marchandises Dangereuses par Route</li> <li>Chemical Abstracts Service</li> <li>Derived no-effect level</li> <li>Half maximal effective concentration</li> <li>Globally Harmonized System</li> <li>International Air Transport Association</li> <li>International Maritime Code for Dangerous Goods</li> <li>Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)</li> <li>Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)</li> <li>International Convention for the Prevention of Pollution from</li> </ul>
MARPOL OEL PBT PNEC REACH	<ul> <li>International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978</li> <li>Occupational Exposure Limit</li> <li>Persistent, bioaccumulative and toxic</li> <li>Predicted no effect concentration</li> <li>Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi-</li> </ul>

Revision Date 01/17/2023



	cals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

Revision Date Date format	: 01/17/2023 : mm/dd/yyyy
Prepared by	: R & D of Sika Canada Inc.
Material number	: 98,696

CA / Z8