

# SAFETY DATA SHEET

## Sikalastic M 200 Formerly MSeal M 200 INTNL



Version 1.1      Revision Date: 01/08/2021      SDS Number: 000000265071      Date of last issue: 05/22/2020  
Date of first issue: 05/22/2020

---

### SECTION 1. IDENTIFICATION

Product name : Sikalastic M 200 Formerly MSeal M 200 INTNL

Product code : 000000000050380802

#### Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE  
Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

#### Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 3

Acute toxicity (Inhalation - vapour) : Category 3

Respiratory sensitization : Category 1

Skin sensitization : Category 1

Carcinogenicity : Category 2

Reproductive toxicity : Category 1B

Specific target organ toxicity - repeated exposure : Category 1 (Central nervous system)

#### GHS label elements

Hazard pictograms :   

Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapour.  
H331 Toxic if inhaled.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

---

# SAFETY DATA SHEET

## Sikalastic M 200 Formerly MSeal M 200 INTNL



Version 1.1      Revision Date: 01/08/2021      SDS Number: 000000265071      Date of last issue: 05/22/2020  
Date of first issue: 05/22/2020

---

H317 May cause an allergic skin reaction.  
H351 Suspected of causing cancer.  
H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.  
H360 May damage fertility or the unborn child.

Precautionary Statements :

**Prevention:**

P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P260 Do not breathe dust or mist.  
P201 Obtain special instructions before use.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P202 Do not handle until all safety precautions have been read and understood.  
P243 Take action to prevent static discharges.  
P284 In case of inadequate ventilation wear respiratory protection.  
P264 Wash face, hands and any exposed skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P242 Use only non-sparking tools.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.

**Response:**

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.  
P311 Call a POISON CENTER or doctor/ physician.

**Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.  
P233 Keep container tightly closed.  
P405 Store locked up.

**Disposal:**

P501 Dispose of contents/container to appropriate hazardous waste collection point.

**Other hazards**

CONTAINS ISOCYANATES. INHALATION OF ISOCYANATE MISTS OR VAPORS MAY CAUSE RESPIRATORY IRRITATION, BREATHLESSNESS, CHEST DISCOMFORT AND REDUCED PULMONARY FUNCTION. OVEREXPOSURE WELL ABOVE THE PEL MAY RESULT IN BRONCHITIS, BRONCHIAL SPASMS AND PULMONARY EDEMA. LONG-TERM

# SAFETY DATA SHEET

## Sikalastic M 200 Formerly MSeal M 200 INTNL



Version 1.1      Revision Date: 01/08/2021      SDS Number: 000000265071      Date of last issue: 05/22/2020  
Date of first issue: 05/22/2020

EXPOSURE TO ISOCYANATES HAS BEEN REPORTED TO CAUSE LUNG DAMAGE, INCLUDING REDUCED LUNG FUNCTION WHICH MAY BE PERMANENT. ACUTE OR CHRONIC OVEREXPOSURE TO ISOCYANATES MAY CAUSE SENSITIZATION IN SOME INDIVIDUALS, RESULTING IN ALLERGIC RESPIRATORY REACTIONS INCLUDING WHEEZING, SHORTNESS OF BREATH AND DIFFICULTY BREATHING. ANIMAL TESTS INDICATE THAT SKIN CONTACT MAY PLAY A ROLE IN CAUSING RESPIRATORY SENSITIZATION.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : isocyanate

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
Stoddard solvent	8052-41-3	$\geq 0 - < 20$
toluene-2,6-diisocyanate	91-08-7	$\geq 0.3 - < 3$
trimethoxy(3-(oxiranylmethoxy)propyl)silane	2530-83-8	$\geq 0 - < 1$
4-methyl-m-phenylene diisocyanate	584-84-9	$\geq 0.1 - < 0.3$
dibutyltin dilaurate	77-58-7	$\geq 0 - < 0.3$
Limestone	1317-65-3	$\geq 10 - < 50$
Titanium dioxide	13463-67-7	$\geq 0 - < 5$
Calcium sulphate	7778-18-9	$\geq 0 - < 5$
talc	14807-96-6	$\geq 0 - < 15$

### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : Call a physician or poison control center immediately.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

# SAFETY DATA SHEET

## Sikalastic M 200 Formerly MSeal M 200 INTNL



Version 1.1      Revision Date: 01/08/2021      SDS Number: 000000265071      Date of last issue: 05/22/2020  
Date of first issue: 05/22/2020

---

Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.  
Toxic if inhaled.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
Suspected of causing cancer.  
May damage fertility or the unborn child.  
Causes damage to organs through prolonged or repeated exposure.

Notes to physician : Treat symptomatically.

---

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

---

# SAFETY DATA SHEET

## Sikalastic M 200 Formerly MSeal M 200 INTNL



Version 1.1      Revision Date: 01/08/2021      SDS Number: 000000265071      Date of last issue: 05/22/2020  
Date of first issue: 05/22/2020

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : Prevent unauthorized access. no smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight.
- Further information on storage stability : No decomposition if stored and applied as directed.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
dibutyltin dilaurate	77-58-7	TWA value	0.1 mg/m <sup>3</sup> (tin (Sn))	ACGIHTLV
		STEL value	0.2 mg/m <sup>3</sup> (tin (Sn))	ACGIHTLV
		REL value	0.1 mg/m <sup>3</sup>	NIOSH

# SAFETY DATA SHEET

## Sikalastic M 200 Formerly MSeal M 200 INTNL



Version 1.1      Revision Date: 01/08/2021      SDS Number: 000000265071      Date of last issue: 05/22/2020  
 Date of first issue: 05/22/2020

			(tin (Sn))	
		PEL	0.1 mg/m3 (tin (Sn))	29 CFR 1910.1000 (Table Z-1)
		TWA value	0.1 mg/m3 (tin (Sn))	29 CFR 1910.1000 (Table Z-1-A)
		TWA	0.1 mg/m3 (Tin)	OSHA Z-1
		TWA	0.1 mg/m3 (Tin)	ACGIH
		STEL	0.2 mg/m3 (Tin)	ACGIH
		TWA	0.1 mg/m3 (Tin)	OSHA P0
		TWA	0.1 mg/m3 (Tin)	NIOSH REL
toluene-2,6-diisocyanate	91-08-7	STEL value (Inhalable fraction and vapor)	0.005 ppm	ACGIHTLV
		Skin Desig- nation (In- halable frac- tion and va- por)		ACGIHTLV
		TWA value (Inhalable fraction and vapor)	0.001 ppm	ACGIHTLV
		C	0.02 ppm 0.14 mg/m3	OSHA Z-1
		TWA (Inhal- able fraction and vapor)	0.001 ppm	ACGIH
		STEL (Inhal- able fraction and vapor)	0.005 ppm	ACGIH
		TWA	0.005 ppm 0.04 mg/m3	OSHA P0
		STEL	0.02 ppm 0.15 mg/m3	OSHA P0
4-methyl-m-phenylene diiso- cyanate	584-84-9	TWA value (Inhalable fraction and vapor)	0.001 ppm	ACGIHTLV
		Skin Desig- nation (In- halable frac- tion and va- por)		ACGIHTLV
		STEL value (Inhalable fraction and vapor)	0.005 ppm	ACGIHTLV

# SAFETY DATA SHEET

## Sikalastic M 200 Formerly MSeal M 200 INTNL



Version 1.1      Revision Date: 01/08/2021      SDS Number: 000000265071      Date of last issue: 05/22/2020  
 Date of first issue: 05/22/2020

		vapor)		
		CLV	0.02 ppm 0.14 mg/m3	29 CFR 1910.1000 (Table Z-1)
		C	0.02 ppm 0.14 mg/m3	OSHA Z-1
		TWA (Inhalable fraction and vapor)	0.001 ppm	ACGIH
		STEL (Inhalable fraction and vapor)	0.005 ppm	ACGIH
		TWA	0.005 ppm 0.04 mg/m3	OSHA P0
		STEL	0.02 ppm 0.15 mg/m3	OSHA P0
Limestone	1317-65-3	REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium carbonate)	NIOSH REL
Calcium sulphate	7778-18-9	TWA value (Inhalable fraction)	10 mg/m3	ACGIHTLV
		REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH

# SAFETY DATA SHEET

## Sikalastic M 200 Formerly MSeal M 200 INTNL



Version 1.1      Revision Date: 01/08/2021      SDS Number: 000000265071      Date of last issue: 05/22/2020  
 Date of first issue: 05/22/2020

		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Inhalable particulate matter)	10 mg/m3 (Calcium)	ACGIH
Titanium dioxide	13463-67-7	TWA value	10 mg/m3	ACGIHTLV
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
talc	14807-96-6	TWA value (Respirable fraction)	2 mg/m3	ACGIHTLV
		TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (respirable dust fraction)	2 mg/m3	OSHA P0
		TWA (Respirable)	2 mg/m3	NIOSH REL
		TWA	0.1 fibres per cubic centimeter	ACGIH
		TWA (Respirable par-	2 mg/m3	ACGIH



# SAFETY DATA SHEET

## Sikalastic M 200 Formerly MSeal M 200 INTNL



Version 1.1      Revision Date: 01/08/2021      SDS Number: 000000265071      Date of last issue: 05/22/2020  
 Date of first issue: 05/22/2020

		ticulate matter)		
Stoddard solvent	8052-41-3	TWA value	100 ppm	ACGIH TLV
		REL value	350 mg/m3	NIOSH
		Ceil_Time	1,800 mg/m3	NIOSH
		PEL	500 ppm 2,900 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	100 ppm 525 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	100 ppm	ACGIH
		TWA	350 mg/m3	NIOSH REL
		C	1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,900 mg/m3	OSHA Z-1
		TWA	100 ppm 525 mg/m3	OSHA P0

**Engineering measures** : Ensure adequate ventilation.

### Personal protective equipment

**Respiratory protection** : When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.  
 When atmospheric levels may exceed the occupational exposure limit (PEL or TLV) NIOSH-certified air-purifying respirators equipped with an organic vapor sorbent and particulate filter can be used as long as appropriate precautions and change out schedules are in place.  
 For emergency or non-routine, high exposure situations, including confined space entry, use a NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied-air respirator (SAR) with escape provisions.

### Hand protection

**Remarks** : Chemical resistant protective gloves should be worn to prevent all skin contact. Suitable materials may include chloroprene rubber (Neoprene) nitrile rubber (Buna N) chlorinated polyethylene polyvinylchloride (Pylox) butyl rubber fluoroelastomer (Viton) depending upon conditions of use. Manufacturer's directions for use should be observed because of great diversity of types.

**Eye protection** : Tightly fitting safety goggles (chemical goggles).  
 Wear face shield if splashing hazard exists.

**Skin and body protection** : Cover as much of the exposed skin as possible to prevent all skin contact.  
 Suitable materials may include saran-coated material depending upon conditions of use.

# SAFETY DATA SHEET

## Sikalastic M 200 Formerly MSeal M 200 INTNL



Version 1.1      Revision Date: 01/08/2021      SDS Number: 000000265071      Date of last issue: 05/22/2020  
Date of first issue: 05/22/2020

---

- Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Protective measures : Do not inhale dust/fumes/aerosols.  
Avoid contact with the skin, eyes and clothing.  
Avoid exposure - obtain special instructions before use.  
Handle in accordance with good building materials hygiene and safety practice.  
Wearing of closed work clothing is recommended.
- Hygiene measures : Avoid contact with skin, eyes and clothing.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and immediately after handling the product.
- 

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : gray
- Odor : solvent
- Odor Threshold : not determined
- pH : neutral to slightly alkaline
- Melting point : No applicable information available.
- Boiling point : approx. 347 °F / 175 °C
- Flash point : 109.9 °F / 43.3 °C
- Evaporation rate : No applicable information available.
- Flammability (liquids) : Flammable liquid and vapour.
- Upper explosion limit / Upper flammability limit : 7.0 %(V)
- Lower explosion limit / Lower flammability limit : 1.0 %(V)
- Vapor pressure : No data available
- Relative vapor density : No applicable information available.
- Relative density : No applicable information available.
-

# SAFETY DATA SHEET

## Sikalastic M 200 Formerly MSeal M 200 INTNL



Version 1.1      Revision Date: 01/08/2021      SDS Number: 000000265071      Date of last issue: 05/22/2020  
Date of first issue: 05/22/2020

---

Density : approx. 1.16 g/cm<sup>3</sup> (68 °F / 20 °C)

Solubility(ies)  
Water solubility : slightly soluble (68 °F / 20 °C)

Solubility in other solvents : No applicable information available.

Partition coefficient: n-octanol/water : not applicable for mixtures

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity  
Viscosity, dynamic : approx. 4,000 - 9,000 mPa.s

Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive  
Not explosive

Oxidizing properties : not fire-propagating

Sublimation point : No applicable information available.

Molecular weight : No data available

Metal corrosion rate : Corrosive effects to metal are not anticipated.

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability : The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.  
Vapors may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong acids  
Strong bases  
Strong oxidizing agents  
Strong reducing agents

Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

# SAFETY DATA SHEET

## Sikalastic M 200 Formerly MSeal M 200 INTNL



Version 1.1      Revision Date: 01/08/2021      SDS Number: 000000265071      Date of last issue: 05/22/2020  
Date of first issue: 05/22/2020

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Toxic if inhaled.

#### Product:

Acute inhalation toxicity : ATE: 5.73 mg/l  
Remarks: Determined for vapor

#### Skin corrosion/irritation

Not classified based on available information.

#### Serious eye damage/eye irritation

Not classified based on available information.

#### Respiratory or skin sensitization

##### Skin sensitization

May cause an allergic skin reaction.

##### Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Suspected of causing cancer.

#### Reproductive toxicity

May damage fertility or the unborn child.

#### STOT-single exposure

Not classified based on available information.

#### STOT-repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

#### Aspiration toxicity

Not classified based on available information.

#### Further information

#### Product:

Remarks : Solvents may decrease the skin.

Remarks : The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

# SAFETY DATA SHEET

## Sikalastic M 200 Formerly MSeal M 200 INTNL



Version 1.1      Revision Date: 01/08/2021      SDS Number: 000000265071      Date of last issue: 05/22/2020  
Date of first issue: 05/22/2020

---

### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

##### Product:

##### Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

##### Components:

##### **dibutyltin dilaurate:**

M-Factor (Acute aquatic toxicity) : 1

##### Persistence and degradability

No data available

##### Bioaccumulative potential

##### Components:

##### **Stoddard solvent:**

Partition coefficient: n-octanol/water : log Pow: 3.5 - 6.4 (68 °F / 20 °C)  
Method: Partition coefficient (n-octanol/water), HPLC method.

##### **toluene-2,6-diisocyanate:**

Partition coefficient: n-octanol/water : log Pow: 3.74  
Method: other (calculated)

##### **dibutyltin dilaurate:**

Partition coefficient: n-octanol/water : log Pow: 3.17 (69.4 °F / 20.8 °C)  
pH: 6.1 - 6.3  
Method: Partition coefficient (n-octanol/water), Shake-flask method  
GLP: yes

##### Mobility in soil

No data available

##### Other adverse effects

##### Product:

Additional ecological information : There is a high probability that the product is not acutely harmful to aquatic organisms.  
The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

# SAFETY DATA SHEET

## Sikalastic M 200 Formerly MSeal M 200 INTNL



Version 1.1      Revision Date: 01/08/2021      SDS Number: 000000265071      Date of last issue: 05/22/2020  
Date of first issue: 05/22/2020

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

- Waste from residues : Dispose of in accordance with national, state and local regulations.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Do not discharge into drains/surface waters/groundwater.
- Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.  
Do not burn, or use a cutting torch on, the empty drum.
- 

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

- UN number : UN 1263  
Proper shipping name : PAINT  
Class : 3  
Packing group : III  
Labels : 3

##### IATA-DGR

- UN/ID No. : UN 1263  
Proper shipping name : PAINT  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

##### IMDG-Code

- UN number : UN 1263  
Proper shipping name : PAINT  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Domestic regulation

##### 49 CFR

- UN/ID/NA number : UN 1263  
Proper shipping name : PAINT, COMBUSTIBLE LIQUID

# SAFETY DATA SHEET

## Sikalastic M 200 Formerly MSeal M 200 INTNL



Version 1.1      Revision Date: 01/08/2021      SDS Number: 000000265071      Date of last issue: 05/22/2020  
Date of first issue: 05/22/2020

Class : C  
Packing group : III  
Labels : Combustible Liquid  
ERG Code : 128  
Marine pollutant : no

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

### EPCRA - Emergency Planning and Community Right-to-Know

#### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
toluene-2,6-diisocyanate	91-08-7	100	14224

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

toluene-2,6-diisocyanate	91-08-7
4-methyl-m-phenylene diisocyanate	584-84-9

### US State Regulations

#### Pennsylvania Right To Know

toluene-2,6-diisocyanate	91-08-7
Limestone	1317-65-3
Calcium sulphate	7778-18-9
Titanium dioxide	13463-67-7
talc	14807-96-6
Stoddard solvent	8052-41-3
4-methyl-m-phenylene diisocyanate	584-84-9

#### New Jersey Right To Know

toluene-2,6-diisocyanate	91-08-7
Limestone	1317-65-3
Calcium sulphate	7778-18-9
Titanium dioxide	13463-67-7
talc	14807-96-6
Stoddard solvent	8052-41-3
4-methyl-m-phenylene diisocyanate	584-84-9

#### California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which is/are known to the State of California to cause cancer, and

# SAFETY DATA SHEET

## Sikalastic M 200 Formerly MSeal M 200 INTNL



Version 1.1      Revision Date: 01/08/2021      SDS Number: 000000265071      Date of last issue: 05/22/2020  
Date of first issue: 05/22/2020

toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL  
TSCA : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.


### TSCA list

The following substance(s) is/are subject to a Significant New Use Rule:  
toluene-2,6-diisocyanate      91-08-7


## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA 704:



#### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

### Full text of other abbreviations

29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)  
29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000  
ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)  
NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)  
NIOSH REL : USA. NIOSH Recommended Exposure Limits  
OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants



# SAFETY DATA SHEET

## Sikalastic M 200 Formerly MSeal M 200 INTNL



Version 1.1      Revision Date: 01/08/2021      SDS Number: 000000265071      Date of last issue: 05/22/2020  
Date of first issue: 05/22/2020

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts  
29 CFR 1910.1000 (Table Z-1-A) / TWA value : Time Weighted Average (TWA):  
29 CFR 1910.1000 (Table Z-1) / CLV : Ceiling Limit Value:  
29 CFR 1910.1000 (Table Z-1) / PEL : Permissible exposure limit  
ACGIH / TWA : 8-hour, time-weighted average  
ACGIH / STEL : Short-term exposure limit  
ACGIHTLV / Skin Designation : Skin Designation:  
ACGIHTLV / STEL value : Short Term Exposure Limit (STEL):  
ACGIHTLV / TWA value : Time Weighted Average (TWA):  
NIOSH / Ceil\_Time : Ceiling Limit Value and Time Period (if specified):  
NIOSH / REL value : Recommended exposure limit (REL):  
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek  
NIOSH REL / C : Ceiling value not be exceeded at any time.  
OSHA P0 / TWA : 8-hour time weighted average  
OSHA P0 / STEL : Short-term exposure limit  
OSHA Z-1 / TWA : 8-hour time weighted average  
OSHA Z-1 / C : Ceiling  
OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations;

# SAFETY DATA SHEET

## Sikalastic M 200 Formerly MSeal M 200 INTNL



Version	Revision Date:	SDS Number:	Date of last issue: 05/22/2020
1.1	01/08/2021	000000265071	Date of first issue: 05/22/2020

---

UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 01/08/2021

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN