

Sikalastic TC 295 Part A clear Formerly MSeal TC 295 Clear PTA

Version Revision Date: SDS Number: Date of last issue: 08/25/2020 2.0 10/05/2020 000001000688 Date of first issue: 08/25/2020

SECTION 1. IDENTIFICATION

Product name : Sikalastic TC 295 Part A clear Formerly MSeal TC 295 Clear

PTA

Product code : 00000000050721157

Other means of identification : MSeal TC 295 Clear PTA

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE

Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 4

Skin sensitization : Category 1A

Hazardous to the aquatic environment - acute hazard

Category 2

Hazardous to the aquatic environment - chronic hazard

Category 2

GHS label elements

Hazard pictograms :





Signal Word : Warning

Hazard Statements : H227 Combustible liquid.

H317 May cause an allergic skin reaction.

H401 Toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.



Sikalastic TC 295 Part A clear Formerly MSeal TC 295 Clear PTA

Version Revision Date: SDS Number: Date of last issue: 08/25/2020 2.0 10/05/2020 000001000688 Date of first issue: 08/25/2020

Precautionary Statements

Prevention:

P280 Wear protective gloves/ eye protection/ face protection. P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P273 Avoid release to the environment.

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P272 Contaminated work clothing should not be allowed out of the workplace.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Aspartic acid, N,N'-(methylenedi-4,1-cyclohexanediyl)bis-, 1,1',4,4'-	136210-30-5	>= 75 - < 100
tetraethyl ester		
Benzenepropanoic acid, 3-(2H-benzotriazol-2-yl)-5-(1,1- di-methylethyl)-4-hydroxy-, C7-9-branched and linear alkyl esters	127519-17-9	>= 5 - < 7
bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	41556-26-7	>= 3 - < 5
Diethyl fumarate	623-91-6	>= 0 - < 5
1,2,4-trimethylbenzene	95-63-6	>= 1 - < 5
Trimethylbenzene	25551-13-7	>= 1 - < 5
Methyl 1,2,2,6,6-pentamethyl-4- piperidyl sebacate	82919-37-7	>= 1 - < 3

SECTION 4. FIRST AID MEASURES



Sikalastic TC 295 Part A clear Formerly MSeal TC 295 Clear PTA

Version SDS Number: Date of last issue: 08/25/2020 Revision Date: 2.0 10/05/2020 000001000688 Date of first issue: 08/25/2020

General advice First aid personnel should pay attention to their own safety.

Immediately remove contaminated clothing.

If inhaled Keep patient calm, remove to fresh air.

If symptoms persist, seek medical advice.

In case of skin contact After contact with skin, wash immediately with plenty of water

and soap.

Under no circumstances should organic solvent be used.

If irritation develops, seek medical attention.

Contact lenses should be removed. Hold eyelids open and In case of eye contact

flush with copious amounts of clean, fresh water or a special

eyewash solution and seek medical advice.

If swallowed Immediately rinse mouth and then drink 200-300 ml of water,

seek medical attention.

Do not induce vomiting unless told to by a poison control cen-

ter or doctor.

Most important symptoms and effects, both acute and

delayed

May cause an allergic skin reaction.

Notes to physician Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam

Water spray Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

water jet

Hazardous combustion prod-

ucts

harmful vapours nitrogen oxides

fumes/smoke carbon black

Further information The degree of risk is governed by the burning substance and

the fire conditions.

If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not

allow to reach sewage or effluent systems.

Contaminated extinguishing water must be disposed of in

accordance with official regulations.

for fire-fighters

Special protective equipment: Wear a self-contained breathing apparatus.



Sikalastic TC 295 Part A clear Formerly MSeal TC 295 Clear PTA

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/25/2020

 2.0
 10/05/2020
 000001000688
 Date of first issue: 08/25/2020

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Wear eye/face protection.

Use personal protective clothing.

Handle in accordance with good building materials hygiene

and safety practice.

Environmental precautions : Contain contaminated water/firefighting water.

Do not discharge into drains/surface waters/groundwater.

Methods and materials for containment and cleaning up

Pick up with suitable appliance and dispose of.

Dispose of absorbed material in accordance with regulations.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

The product is neither self-ignitable, nor an explosion hazard,

nor does it promote fires.

Advice on safe handling : Avoid inhalation of dusts/mists/vapours.

Avoid skin contact.

Ensure adequate ventilation.

No special measures necessary provided product is used

correctly.

Further information on stor-

age conditions

Keep only in the original container in a cool, dry, well-

ventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	
1,2,4-trimethylbenzene	95-63-6	TWA value	25 ppm	ACGIHTLV
		REL value	25 ppm 125 mg/m3	NIOSH
		TWA value	25 ppm 125 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	25 ppm 125 mg/m3	NIOSH REL
		TWA	25 ppm	ACGIH
		TWA	25 ppm 125 mg/m3	OSHA P0
Trimethylbenzene	25551-13-7	TWA value	25 ppm	ACGIHTLV
		TWA value	25 ppm 125 mg/m3	29 CFR 1910.1000
			1=39,0	(Table Z-1-A)



Sikalastic TC 295 Part A clear Formerly MSeal TC 295 Clear PTA

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/25/2020

 2.0
 10/05/2020
 000001000688
 Date of first issue: 08/25/2020

REL value	25 ppm 125 mg/m3	NIOSH
TWA	25 ppm	ACGIH
TWA	25 ppm 125 mg/m3	OSHA P0

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Wear respiratory protection if ventilation is inadequate.

Wear a NIOSH-certified (or equivalent) respirator as neces-

sary.

Hand protection

Remarks : Chemical resistant protective gloves Manufacturer's direc-

tions for use should be observed because of great diversity of

types.

Eye protection : Safety glasses with side-shields.

Skin and body protection : Body protection must be chosen based on level of activity

and exposure.

Protective measures : Do not inhale dust/fumes/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.

Hands and/or face should be washed before breaks and at

the end of the shift.

At the end of the shift the skin should be cleaned and skin-

care agents applied.

Gloves must be inspected regularly and prior to each use.

Replace if necessary (e.g. pinhole leaks).

When using do not eat or drink.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : clear

Odor : ester-like

Odor Threshold : No data available



Sikalastic TC 295 Part A clear Formerly MSeal TC 295 Clear PTA

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/25/2020

 2.0
 10/05/2020
 000001000688
 Date of first issue: 08/25/2020

pH : No data available

Melting point : No data available

Boiling point/boiling range : No data available

Flash point : 186.80 °F / 86.00 °C

Evaporation rate : No data available

Flammability (solid, gas) : Combustible liquid.

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : No data available

Density : 1.05 g/cm3 (68 °F / 20 °C)

Solubility(ies)

Water solubility : not determined

Partition coefficient: n-

octanol/water

not applicable for mixtures

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Sublimation point : No data available

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY



Sikalastic TC 295 Part A clear Formerly MSeal TC 295 Clear PTA

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/25/2020

 2.0
 10/05/2020
 000001000688
 Date of first issue: 08/25/2020

Reactivity : No hazardous reactions if stored and handled as pre-

scribed/indicated.

Chemical stability : The product is stable if stored and handled as pre-

scribed/indicated.

Possibility of hazardous reac-

tions

The product is stable if stored and handled as pre-

scribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents
Strong reducing agents

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.



Sikalastic TC 295 Part A clear Formerly MSeal TC 295 Clear PTA

Version Revision Date: SDS Number: Date of last issue: 08/25/2020 2.0 10/05/2020 000001000688 Date of first issue: 08/25/2020

Further information

Product:

Remarks : Health injuries are not known or expected under normal use.

The product has not been tested. The statements on toxicology have been derived from the properties of the individual

components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Persistence and degradability

Product:

Biodegradability : Remarks: Taking into consideration the properties of several

ingredients, the product is estimated not to be readily biode-

gradable according to OECD classification.

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available.

Discharge into the environment must be avoided.

Components:

Aspartic acid, N,N'-(methylenedi-4,1-cyclohexanediyl)bis-, 1,1',4,4'-tetraethyl ester:

Partition coefficient: n- : log Pow: 5.16

octanol/water Method: other (calculated)

Benzenepropanoic acid, 3-(2H-benzotriazol-2-yl)-5-(1,1- dimethylethyl)-4-hydroxy-, C7-9-branched and linear alkyl esters:

Partition coefficient: n- : log Pow: 9.2

octanol/water Method: other (calculated)

GLP: yes

bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate:

Partition coefficient: n- : Remarks: No data available.

octanol/water

1,2,4-trimethylbenzene:



Sikalastic TC 295 Part A clear Formerly MSeal TC 295 Clear PTA

Version Revision Date: SDS Number: Date of last issue: 08/25/2020 2.0 10/05/2020 000001000688 Date of first issue: 08/25/2020

Remarks: No data available.

Partition coefficient: n- : log Pow: 3.63 (77 °F / 25 °C) octanol/water : Method: other (calculated)

Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

octanol/water

Mobility in soil
No data available

Other adverse effects

Partition coefficient: n-

Product:

Additional ecological infor-

mation

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Observe national and local legal requirements.

Disposal requirements are dependent on the hazard classification and will vary by location and the type of disposal se-

lected.

The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous

waste.

Residues should be disposed of in the same manner as the

substance/product.

Contaminated packaging : Contaminated packaging should be emptied as far as possi-

ble; then it can be passed on for recycling after being thor-

oughly cleaned.

Packs that cannot be cleaned should be disposed of in the

same manner as the contents.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(BENZOTRIAZOLE DERIVATIVE)

Class : 9
Subsidiary risk : EHSM
Packing group : III

Labels : 9 (EHSM)



Sikalastic TC 295 Part A clear Formerly MSeal TC 295 Clear PTA

Version Revision Date: SDS Number: Date of last issue: 08/25/2020 2.0 10/05/2020 000001000688 Date of first issue: 08/25/2020

IATA-DGR

UN/ID No. : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(BENZOTRIAZOLE DERIVATIVE)

Class : 9
Subsidiary risk : EHSM
Packing group : III

Labels : Miscellaneous, Environmentally hazardous

Packing instruction (cargo : 964

aircraft)

Packing instruction (passen-

964

ger aircraft)

IMDG-Code

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(BENZOTRIAZOLE DERIVATIVE)

Class : 9
Subsidiary risk : EHSM
Packing group : III
Labels : 9 (EHSM)

EmS Code : F-A, S-F Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : NA 1993

Proper shipping name : COMBUSTIBLE LIQUID, N.O.S.

(TRIMETHYLBENZENE)

Class : C Packing group : III

Labels : Combustible Liquid

ERG Code : 128 Marine pollutant : no

Remarks : Above applies only to containers over 119 gallons or 450 li-

ters. Not regulated if shipped in packages less than or equal

to 119 gallons (450 liters).

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity



Sikalastic TC 295 Part A clear Formerly MSeal TC 295 Clear PTA

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/25/2020

 2.0
 10/05/2020
 000001000688
 Date of first issue: 08/25/2020

Components	CAS-No.	Component RQ	Calculated product RQ	
		(lbs)	(lbs)	
xylene	1330-20-7	100	45600	

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

1,2,4- 95-63-6 >= 1 - < 5 %

trimethylbenzene

cumene 98-82-8 >= 0.1 - < 1 %

US State Regulations

Pennsylvania Right To Know

1,2,4-trimethylbenzene 95-63-6 Trimethylbenzene 25551-13-7

New Jersey Right To Know

1,2,4-trimethylbenzene 95-63-6

California Prop. 65

WARNING: This product can expose you to chemicals including benzene, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : All chemical substances in this product are either listed as

active on the TSCA Inventory or are in compliance with a

TSCA Inventory exemption.

DSL : All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION


Further information



Sikalastic TC 295 Part A clear Formerly MSeal TC 295 Clear PTA


Version SDS Number: Date of last issue: 08/25/2020 Revision Date: 2.0 10/05/2020 000001000688 Date of first issue: 08/25/2020

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

1-A)

ACGIH USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

NIOSH Pocket Guide to Chemical Hazards (US) NIOSH USA. NIOSH Recommended Exposure Limits NIOSH REL

OSHA P0 USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910,1000

29 CFR 1910.1000 (Table Z- :

1-A) / TWA value

8-hour, time-weighted average

ACGIH / TWA Time Weighted Average (TWA): ACGIHTLV / TWA value NIOSH / REL value Recommended exposure limit (REL):

NIOSH REL / TWA Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

Time Weighted Average (TWA):

8-hour time weighted average OSHA P0 / TWA

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Indus-



Sikalastic TC 295 Part A clear Formerly MSeal TC 295 Clear PTA

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/25/2020

 2.0
 10/05/2020
 000001000688
 Date of first issue: 08/25/2020

trial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB -Very Persistent and Very Bioaccumulative

Revision Date : 10/05/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE. WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE, NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN



Sikalastic TC 295 Part A clear Formerly MSeal TC 295 Clear PTA

Version 2.0

Revision Date: 10/05/2020

SDS Number: 000001000688

Date of last issue: 08/25/2020 Date of first issue: 08/25/2020