



SECTION I: PRODUCT INFORMATION

PRODUCT: **SikaForce®-7780 L-12/L-5 CA** PART A REVISION DATE: January 15th, 2015

USAGE: TWO COMPONENT URETHANE BASED ADHESIVE

SUPPLIER: SIKA CANADA INC.
601, avenue Delmar
Pointe Claire, QC
H9R 4A9

EMERGENCY TELEPHONE NUMBER: CANUTEC (collect) (613) 996-6666

TDG CLASSIFICATION: Not Regulated
UN NUMBER: Not Established
Packaging Group: Not ApplicableWHMIS Classification: D2B
Class: Not Applicable

SECTION II: HAZARDOUS INGREDIENTS

Hazardous ingredients	%	T.L.V.	# CAS	LD ₅₀ (species, route)	LC ₅₀ (species, route)
Castor oil	3-7	Not Available	8001-79-4	> 5000 (rat, oral)	Not Available

SECTION III: PHYSICAL CHARACTERISTICS

Physical State: Liquid
Appearance and Odor: Aromatic odor, colored liquid

Odor Threshold: Not Established
Evaporation Rate: Not Established
Vapor Density: Not Established
Vapor Pressure: Not EstablishedBoiling Point: Not Established
Freezing Point: Not Established
Density: 1.4 g/ml
Water Solubility: Not Established
pH: Not Established
% volatile: < 2
Water/Oil Distribution: Not Established

PRODUCT: **SikaForce®-7780 L-12/L-5 CA****PART A****SECTION IV: FIRE AND EXPLOSION HAZARDS**

Flammability: No

If Yes, under what conditions:

Extinguishing methods: Foam, dry chemical products, CO₂, water for large flames.

Special Methods: Firefighters must wear complete protective clothing with respiratory equipment and they must protect any exposed skin.

TDG inflammability Class: Not Regulated
Flammable upper limits (% vol.): Not Established
Flammable lower limits (% vol.): Not Established
Flash Point (method used): Not Established
Auto-ignition temperature: Not Established
Dangerous Combustion Products: CO, Nitrogen Oxide

Protect from mechanical impact: No

Protect from static discharge: No

SECTION V: REACTIVITY DATA

Chemical stability: Yes

If not, under what conditions

Incompatibility with other material: Yes

If Yes, which ones: Acid, strong oxidizer.

Dangerous decomposition products: CO, Nitrogen Oxide.

Polymerization Risks: No

PRODUCT: **SikaForce®-7780 L-12/L-5 CA**

PART A

SECTION VI: TOXIC PROPERTIES

ROUTE OF ENTRY / CONTACT

Eyes: Irritating.

Carcinogenicity: Not established

Skin Irritating.

Toxic effects
on reproduction: Not establishedInhalation: Vapor or mist from this product may
cause irritation.

Teratogenicity: Not established

Ingestion: May cause nausea, vomiting, diarrhea,
gastro-intestinal system disorder,
constipation.

Mutagenicity: Not established

Product with synergistic
effects: Not established

An acute or chronic exposure will increase the toxic effects mentioned in this section and may aggravate respiratory problems.

PRODUCT: **SikaForce®-7780 L-12/L-5 CA**

PART A

SECTION VII: PREVENTIVE MEASURES**PERSONAL PROTECTIVE EQUIPMENT**

Gloves: Use chemical resistant gloves.

Respiratory equipment: Not necessary under normal use.

Eyes: Full-face mask or safety glasses

Shoes: Leather

Clothing: Rubber Apron

Other: Eye wash station, shower

OTHERS

Ventilation: Sufficient ventilation required

Procedure in case of leaks: Absorb with sand or other absorbent material.

Handling and Equipment methods: Avoid skin, eye and clothing contact

Warehouse Requirements: Keep all containers closed in a cool, dry and well ventilated area.

Special Shipping Instructions: See TDG class

Waste Removal: Dispose of sand and rinse water according to municipal, provincial or federal laws for disposal of chemicals.



PRODUCT: SikaForce®-7780 L-12/L-5 CA

PART A

SECTION VIII: FIRST AID

Skin: Remove contaminated clothing and shoes.
Wash immediately with plenty of water.
Wash clothing before re-wearing.
Consult a physician if required.

Eyes: Rinse eyes immediately with plenty of water for several minutes, while holding eyelids wide open, to ensure a proper wash.
See a physician immediately.

Inhalation: In the case of overexposure, evacuate to fresh air.
Consult a physician if required.

Ingestion: Drink plenty of water. Do not induce vomiting.
See a physician immediately.
Do not give anything by mouth to an unconscious person.

SECTION IX: PREPARATION INFORMATION

Prepared By: R & D of Sika Canada Inc.
Telephone #: (514) 697-2610
Fax #: (514) 694-2792

Notice To Reader

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section IX of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

AQ 191 A

Date: 2012/02/01

App: S.G.



SECTION I: PRODUCT INFORMATION

PRODUCT: **SikaForce®-7780 L-12/L-5 CA PART B** REVISION DATE: March 17th, 2015

USAGE: TWO COMPONENT URETHANE BASED ADHESIVE

MANUFACTURER/SUPPLIER: Sika Canada Inc.
601, avenue Delmar
Pointe Claire, QC
H9R 4A9

EMERGENCY TELEPHONE NUMBER: CANUTEC (collect) (613) 996-6666

TDG CLASSIFICATION: Not regulated
UN NUMBER: Not regulated
Packaging Group: Not regulated

WHMIS Classification: D1A, D2A, D2B
Class: Not regulated

SECTION II: HAZARDOUS INGREDIENTS

Hazardous ingredients	%	T.L.V.	# CAS	LD ₅₀ (mg/kg) (species, route)	LC ₅₀ (species, route)
Diphenylmethane diisocyanate	30-60	Not listed	9016-87-9	> 10 000 (rat, oral)	490mg/m ³ /4H (rat)
Diphenylmethane-4,4'-diisocyanate	30-60	0.005 ppm	101-68-8	31 600 (rat, oral)	369mg/m ³ /4H (rat)

SECTION III: PHYSICAL CHARACTERISTICS

Physical State: Liquid
Appearance and Odor: Characteristic odor, colored liquid

Odor Threshold: Not Established
Evaporation Rate: Not Established
Vapor Density: Not Established
Vapor Pressure: Not Established

Boiling Point: Not Established
Freezing Point: Not Established
Density: 1.2 g/ml
Water Solubility: Not Established
pH: Not Established
% volatile: < 1
Water/Oil Distribution: Not Established

PRODUCT: **SikaForce®-7780 L-12/L-5 CA**

PART B

SECTION IV: FIRE AND EXPLOSION HAZARDS

Flammability: No

If Yes, under what conditions:

Extinguishing methods: Foam, dry chemical products, CO₂, water for large flames.

Special Methods: Firefighters must wear complete protective clothing with respiratory equipment and they must protect any exposed skin. Heated isocyanates react strongly with water.

TDG inflammability Class: Not regulated
Flammable upper limits (% vol.): Not Established
Flammable lower limits (% vol.): Not Established
Flash Point (method used): > 100°C
Auto-ignition temperature: Not Established
Dangerous Combustion Products: CO, Nitrogen Oxide.

Protect from mechanical impact: No

Protect from static discharge: No

SECTION V: REACTIVITY DATA

Chemical stability: Yes

If not, under what conditions

Incompatibility with other material: Yes

If Yes, which ones: Acid, strong oxidizer, amine

Dangerous decomposition products: CO, Nitrogen Oxide.

Polymerization Risks: No



PRODUCT: SikaForce®-7780 L-12/L-5 CA

PART B

SECTION VI: TOXIC PROPERTIES

ROUTE OF ENTRY / CONTACT

Eyes: Irritating.

Carcinogenicity: Not established

Skin Irritating. Contact may result in dermatitis, strong allergic reactions, and sensitization. May be absorbed by the skin.

Toxic effects on reproduction: Not established

Teratogenicity: Not established

Inhalation: Vapor or mist from this product may cause irritation. Strong allergic reactions.

Mutagenicity: Not established

Ingestion: May cause nausea, vomiting, diarrhea, gastro-intestinal system disorder, constipation. Small amount may create considerable health disorders.

Product with synergistic effects: Not established

Over exposure may cause breathing difficulties, sensitization, headaches, nausea, vomiting. May aggravate respiratory, skin, eye, lung problems and allergies.

If the product is applied according to the manufacturer, none of these symptoms should be encountered.

A person who is sensitized to isocyanates may have a reaction with a level of isocyanates well below the T.L.V.

An acute or chronic exposure will increase the toxic effects mentioned in this section and may aggravate respiratory problems.

PRODUCT: **SikaForce®-7780 L-12/L-5 CA**

PART B

SECTION VII: PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT

Gloves: Use chemical resistant gloves.

Respiratory equipment: Not necessary under normal use. If ventilation is insufficient a mask with vapor filter is recommended.

Eyes: Full-face mask or safety glasses

Shoes: Leather

Clothing: Rubber Apron

Other: Eye wash station, shower

OTHERS

Ventilation: Sufficient ventilation required

Procedure in case of leaks: Absorb with sand or other absorbent material.

Handling and Equipment methods: Avoid skin, eye and clothing contact

Warehouse Requirements: Keep all containers closed in a cool, dry and well ventilated area. Keep away from heat and open flame.

Special Shipping Instructions: See TDG class

Waste Disposal: Dispose of sand and rinse water according to municipal, provincial or federal laws for disposal of chemicals.



PRODUCT: SikaForce®-7780 L-12/L-5 CA

PART B

SECTION VIII: FIRST AID

Skin: Remove contaminated clothing and shoes.
Wash immediately with plenty of water.
Wash clothing before re-wearing.
Consult a physician if required.

Eyes: Rinse eyes immediately with plenty of water for several minutes to ensure a proper wash.
See a physician immediately.

Inhalation: In the case of overexposure, evacuate to fresh air.
Consult a physician if required.

Ingestion: Drink plenty of water. Do not induce vomiting.
See a physician immediately.
Do not give anything by mouth to an unconscious person.

SECTION IX: PREPARATION INFORMATION

Prepared By: R & D of Sika Canada Inc.
Telephone #: (514) 697-2610
Fax #: (514) 694-2792

Notice To Reader

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section IX of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.