



## PRODUCT DATA SHEET

# SikaProof® ExTape-100

Self-adhesive tape for external jointing of the SikaProof® A+ waterproofing system

### PRODUCT DESCRIPTION

SikaProof® ExTape-100 is a self-adhesive tape based on a butyl adhesive for external jointing and detailing of the SikaProof® A+ membrane system. The tape is composed of a grey aluminium/PET carrier and a divided release liner.

### WHERE TO USE

The product is used for:

- Sealing external joints and details within the SikaProof® A+ membrane system.

Please note:

- Do not use the Product in areas where it is permanently exposed to weathering or UV-light.

### CHARACTERISTICS / ADVANTAGES

- High adhesion and sealing ability
- Divided release liner for quick and easy installation

### PRODUCT INFORMATION

<b>CSC MasterFormat®</b>	<b>07 13 26   SELF-ADHERING SHEET WATERPROOFING</b>
<b>Packaging</b>	6 rolls packed in one box. Individual roll size: Length 20 m / Width 100 mm
<b>Shelf Life</b>	24 months from date of production
<b>Storage Conditions</b>	Product must be stored in original unopened and undamaged sealed packaging in dry conditions and temperatures between + 5 °C and + 25 °C (41 °F and 77 °F). Always refer to packaging.
<b>Appearance / Colour</b>	Grey carrier coated with black butyl adhesive covered by divided white release liner.
<b>Length</b>	20 m
<b>Width</b>	100 mm
<b>Thickness</b>	1.0 mm

# SYSTEMS

## System Structure

System Components  
SikaProof® A+ sheet membranes

## APPLICATION INFORMATION

### Ambient Air Temperature

Maximum	+35 °C (95 °F)
Minimum	+5 °C (41 °F)

### Substrate Temperature

Minimum	+5 °C (41 °F)
---------	---------------

## BASIS OF PRODUCT DATA

Product properties are typically averages, obtained under laboratory conditions. Reasonable variations can be expected on-site due to local factors, including environment, preparation, application, curing and test methods.

## FURTHER INFORMATION

Refer to the following Sika® Method Statement:  
Sika® Method Statement: SikaProof® A+

## LIMITATIONS

**The product is not suitable for permanent exposure UV rays or inclement weather.**

Protect as soon as possible, but no later than 90 days after application.

## ENVIRONMENT, HEALTH & SAFETY

This product is a manufactured article that does not require Safety Data Sheets to be marketed, transported or applied at the jobsite, according to the Hazardous Product Act - Section 2. Based on our current knowledge, this product is not classified as dangerous and does not contain any hazardous materials. Always wear personal protective equipment (including safety goggles and gloves) to manipulate and install Sika® products.

## APPLICATION INSTRUCTIONS

### IMPORTANT

#### Strictly follow installation procedures

Strictly follow installation procedures as defined in Method Statements, application manuals and working instructions which must always be adjusted to the actual site conditions.

### IMPORTANT

#### Application by trained personnel

The application of this Product must only be carried out by an applicator that is trained or approved by Sika. The applicator must also be experienced in this type of

application.

## SUBSTRATE QUALITY

The contact surface is the light yellow SikaProof® membrane side. It must be dry, clean and free of any materials that could impair adhesion.

### Application outside of specified application conditions

Note: Under certain circumstances, the Product can be applied in conditions other than the ones specified in this data sheet. However, this requires specific precautions and application methods.

1. Contact Sika technical services for more information.

## APPLICATION

1. Remove the release liner
2. Apply onto the yellow membrane side
3. Press firmly using a pressure roller

**Important note:** The Product is not resistant to permanent UV exposure or weathering. Protect as soon as possible but not later than 90 days after application.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

## LEGAL NOTES

The information, and in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any recommendations, or from any other advice offered. The information contained herein does not relieve the user of the products from testing them for the intended application and purpose. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or may be downloaded from our website at: [www.sika.ca](http://www.sika.ca)

### **Sika Canada Inc.**

Head Office  
601, avenue Delmar  
Pointe-Claire, Quebec  
H9R 4A9  
1-800-933-SIKA  
[www.sika.ca](http://www.sika.ca)

### **Other locations**

Boisbriand (Quebec)  
Brantford; Cambridge;  
Sudbury; Toronto (Ontario)  
Edmonton (Alberta)  
Surrey (British Columbia)

### **Product Data Sheet**

SikaProof® ExTape-100  
November 2023, Version 01.03  
02072030800000019

