Sika®

Revision Date 10/05/2022 Print Date 10/05/2022

SECTION 1. IDENTIFICATION

Product name : KING MS-D3

Other means of identification : KING MS-D3 SY, KING MS-D3 CI, KING MS-D3 G2, KING

MS-D3 STA, KING MS-D3 STB, KING MS-D3 STC, KING

MS-D3 STD, KING MS-D3 MF,

KING MS-D3 MFB, KING MS-D3 MFC, KING MS-D3

MFD,KING MS-D3 STA+, KING MS-D3 STB+, KING MS-D3

STC+, KING MS-D3 STD+, KING MS-D3 ST20,

KING MS-D3 ST25, KING MS-D3 ST30, KING MS-D3 ST35,

KING MS-D3 ST40, KING MS-D3 ST45, KING MS-D3

ST50,KING MS-D3 ST55,

KING MS-D3 X ST60, KING MS-D3 ST65, KING MS-D3 ST70, KING MS-D3 ST75, KING MS-D3 ST80, KING MS-D3

ST85, KING MS-D3 ST90,

KING MS-D3 ST95, KING MS-D3 ST100, KING MS-D3

ST105, KING MS-D3 ST110, KING MS-D3 CW, KING MS-D3

NE, KING MS-D3 RT, KING MS-D3 X,

KING MS-D3 X2, KING MS-D3 X3, KING MS-D3 X SY, KING MS-D3 X CI, KING MS-D3 X G2, KING MS-D3 X STA, KING

MS-D3 X STB,

KING MS-D3 X STC, KING MS-D3 X STD, KING MS-D3 X MF, KING MS-D3 X MFB, KING MS-D3 X MFC, KING MS-D3

X MFD, KING MS-D3 X STA+,

KING MS-D3 X STB+, KING MS-D3 X STC+, KING MS-D3 X STD+, KING MS-D3 X ST20, KING MS-D3 X ST25, KING

MS-D3 X ST30, KING MS-D3 X ST35

KING MS-D3 X ST40, KING MS-D3 X ST45, KING MS-D3 X ST50, KING MS-D3 X ST55, KING MS-D3 X ST60, KING MS-D3 X

D3 X ST65, KING MS-D3 X ST70,

KING MS-D3 X ST75, KING MS-D3 X ST80, KING MS-D3 X ST85, KING MS-D3 X ST90, KING MS-D3 X ST95, KING MS-D3 X

D3 X ST100,

KING MS-D3 X ST105, KING MS-D3 X ST110, KING MS-D3 X CW,KING MS-D3 X NE, KING MS-D3 X RT, KING MS-D3

X2 SY, KING MS-D3 X2 CI,

KING MS-D3 X2 G2, KING MS-D3 X2 STA, KING MS-D3 X2 STB, KING MS-D3 X2 STC, KING MS-D3 X2 STD, KING MS-D3 X2

D3 X2 MF, KING MS-D3 X2 RT,

KING MS-D3 X2 MFB, KING MS-D3 X2 MFC, KING MS-D3 X2 MFD, KING MS-D3 X2 STA+, KING MS-D3 X2 STB+,

KING MS-D3 X2 STC+,

KING MS-D3 X2 STD+, KING MS-D3 X2 ST20, KING MS-D3 X2 ST25, KING MS-D3 X2 ST30, KING MS-D3 X2 ST35,

KING MS-D3 X2 ST40,

KING MS-D3 X2 ST45, KING MS-D3 X2 ST50, KING MS-D3 X2 ST55, KING MS-D3 X2 ST60, KING MS-D3 X2 ST65,

KING MS-D3 X2 ST70

KING MS-D3 X2 ST75, KING MS-D3 X2 ST80, KING MS-D3 X2 ST85, KING MS-D3 X2 ST90, KING MS-D3 X2 ST95,

KING MS-D3 X2 ST100,

KING MS-D3 X2 ST105, KING MS-D3 X2 ST110, KING MS-



Revision Date 10/05/2022 Print Date 10/05/2022

D3 X2 CW, KING MS-D3 X2 NE, KING MS-D3 X3 RT, KING MS-D3 X3 CW.

KING MS-D3 X3 NE, KING MS-D3 X3 SY, KING MS-D3 X3 CI, KING MS-D3 X3 G2, KING MS-D3 X3 STA,KING MS-D3 X3 STB,

KING MS-D3 X3 STC, KING MS-D3 X3 STD, KING MS-D3 X3 MF, KING MS-D3 X3 MFB, KING MS-D3 X3 MFC, KING MS-D3 X3 MFD, KING MS-D3 X3 STA+,

KING MS-D3 X3 STB+, KING MS-D3 X3 STC+,MS-D3 X3 STD+, KING MS-D3 X3 ST20, KING MS-D3 X3 ST25, KING MS-D3 X3 ST30.

KING MS-D3 X3 ST35, KING MS-D3 X3 ST40, KING MS-D3 X3 ST45, KING MS-D3 X3 ST50, KING MS-D3 X3 ST55 KING MS-D3 X3 ST60, KING MS-D3 X3 ST65, KING MS-D3 X3 ST70, KING MS-D3 X3 ST75, KING MS-D3 X3 ST80, KING MS-D3 X3 ST85.

KING MS-D3 X3 ST90, KING MS-D3 X3 ST95, KING MS-D3 X3 ST100, KING MS-D3 X3 ST105, KING MS-D3 X3 ST110, KING MS-D3 SYCI,

KING MS-D3 SY G2, KING MS-D3 SY CW, KING MS-D3 X SY CI, KING MS-D3 X SY G2, KING MS-D3 X SY CW, KING MS-D3 X SY RT.

KING MS-D3 X SY NE, KING MS-D3 X2 SY CI, KING MS-D3 X2 SY G2, KING MS-D3 X2 SY CW, KING MS-D3 X2 SY RT,

KING MS-D3 X2 SY NE

KING MS-D3 X3 SY CI, KING MS-D3 X3 SY G2, KING MS-D3 X3 SY CW, KING MS-D3 X3 SY RT, KING MS-D3 X3 SY

ΝE

Company name : 601, avenue Delmar

Canada

Pointe-Claire, QC H9R 4A9

Sika Canada Inc. www.sika.ca

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

E-mail address : ehs@ca.sika.com

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

Recommended use of the chemical and restrictions on

use

For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Skin corrosion : Category 1C

Serious eye damage : Category 1



Revision Date 10/05/2022 Print Date 10/05/2022

Skin sensitization : Category 1

Carcinogenicity (Inhalation) : Category 1A

Specific target organ toxicity

- single exposure

: Category 3 (Respiratory system)

Specific target organ toxicity

- repeated exposure

Category 1 (Lungs)

GHS label elements

Hazard pictograms







Signal Word : Danger

Hazard Statements : H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. H350 May cause cancer by inhalation.

H372 Causes damage to organs (Lungs) through prolonged or

repeated exposure.

Precautionary Statements : Pre

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P308 + P313 IF exposed or concerned: Get medical advice/

attention.



Revision Date 10/05/2022 Print Date 10/05/2022

P333 + P313 If skin irritation or rash occurs: Get medical advice/

attention.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components

Chemical name	CAS-No.	Classification	Concentra-
			tion (% w/w)
Quartz (SiO2) >5µm	14808-60-7	Carc. 1A; H350i	>= 60 - < 80
		STOT RE 1; H372	
		STOT SE 3; H335	
Cement	65997-15-1	Skin Corr. 1C; H314	>= 10 - < 30
		Eye Dam. 1; H318	
		Skin Sens. 1; H317	
		STOT SE 3; H335	

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in attend-

ance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul-

ty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.



Revision Date 10/05/2022 Print Date 10/05/202

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

Clean mouth with water and drink afterwards plenty of water. If swallowed

Do not induce vomiting without medical advice.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

Health injuries may be delayed.

corrosive effects irritant effects sensitizing effects

Cough

Respiratory disorder Allergic reactions

Dermatitis

May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation. May cause cancer by inhalation.

Causes damage to organs through prolonged or repeated

exposure.

Causes severe burns.

Notes to physician Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

for fire-fighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Avoid breathing dust.

Deny access to unprotected persons.

Environmental precautions Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.



Revision Date 10/05/2022 Print Date 10/05/2022

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Avoid dust formation.

Provide appropriate exhaust ventilation at places where dust

is formed.

Advice on safe handling : Avoid formation of respirable particles.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage : Store in original container.

Keep in a well-ventilated place. Observe label precautions.

Store in accordance with local regulations.

Materials to avoid : Explosives

Oxidizing agents
Poisonous gases
Dangerous when wet
Flammable solids
Organic peroxides
Poisonous liquids

Spontaneously Combustible Substances

Further information on stor-

age stability

Keep in a dry place.

No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz (SiO2) >5μm	14808-60-7	TWA (Res- pirable par- ticulates)	0.025 mg/m3	CA AB OEL

Safety Data Sheet

KING MS-D3



Revision Date 10/05/2022 Print Date 10/05/2022

		TWA (Respirable fraction)	0.1 mg/m3	CA ON OEL
		TWAEV (respirable dust)	0.1 mg/m3	CA QC OEL
		TWA (Res- pirable)	0.025 mg/m3 (Silica)	CA BC OEL
		TWA (Res- pirable)	0.025 mg/m3	CA BC OEL
		TWA (Res- pirable)	0.025 mg/m3 (Silica)	CA BC OEL
		TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
_		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
Cement	65997-15-1	TWA	10 mg/m3	CA AB OEL
		TWA (Res- pirable)	1 mg/m3	CA BC OEL
		TWAEV (respirable dust)	5 mg/m3	CA QC OEL
		TWAEV (to- tal dust)	10 mg/m3	CA QC OEL
		TWA (Respirable particulate matter)	1 mg/m3	ACGIH
fumes, silica	69012-64-2	TWA (Total fume)	4 mg/m3	CA BC OEL
		TWA (Res- pirable fume)	1.5 mg/m3	CA BC OEL
		TWA (Res- pirable frac- tion - fume)	2 mg/m3	CA ON OEL
		TWAEV (Respirable fume)	2 mg/m3	CA QC OEL

Particles of nuisance dust



Revision Date 10/05/2022 Print Date 10/05/2022

Form of exposure	Value type	Control parameters	Basis
total dust	TWA	15 mg/m3	OSHA Z-3
respirable fraction	TWA	5 mg/m3	OSHA Z-3

Engineering measures : Use of adequate ventilation should be sufficient to control

worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommend-

ed or statutory limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed

respirator complying with an approved standard if a risk as-

sessment indicates this is necessary.

The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling

the product.

Remove contaminated clothing and protective equipment

before entering eating areas. Wash thoroughly after handling.

Avoid breathing dust.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder

Color : gray

Odor : odorless

Odor Threshold : No data available

pH : No data available



Revision Date 10/05/2022 Print Date

Melting point/range / Freezing :

point

: No data available

Boiling point/boiling range : No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Density : ca. 2.5 g/l (20 °C (68 °F))

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : insoluble

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds

(VOC) content

Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac-

ons

Stable under recommended storage conditions.



Revision Date 10/05/2022 Print Date 10/05/2022

Conditions to avoid : No data available

Incompatible materials : No data available

Hazardous decomposition

products

No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Not classified based on available information.

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer by inhalation.

IARC Group 1: Carcinogenic to humans

Quartz (SiO2) >5µm 14808-60-7

(Silica dust, crystalline)

OSHA OSHA specifically regulated carcinogen

Quartz (SiO2) >5µm 14808-60-7

(crystalline silica)

NTP Known to be human carcinogen

Quartz (SiO2) >5µm 14808-60-7

(Silica, Crystalline (Respirable Size))

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. Prolonged exposure can cause silicosis.



Revision Date 10/05/2022 Print Date 10/05/2022

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

Do not empty into drains; dispose of this material and its con-

tainer in a safe way.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good



Revision Date 10/05/2022 Print Date 10/05/2022

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)

CA BC OEL : Canada. British Columbia OEL

CA ON OEL : Ontario Table of Occupational Exposure Limits made under

the Occupational Health and Safety Act.

CA QC OEL : Québec. Regulation respecting occupational health and safe-

ty, Schedule 1, Part 1: Permissible exposure values for air-

borne contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

ACGIH / TWA : 8-hour, time-weighted average
CA AB OEL / TWA : 8-hour Occupational exposure limit
CA BC OEL / TWA : 8-hour time weighted average
CA ON OEL / TWA : Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEV : Time-weighted average exposure value

OSHA Z-3 / TWA : 8-hour time weighted average

ADR : Accord européen relatif au transport international des

marchandises Dangereuses par Route

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978



Revision Date 10/05/2022 Print Date 10/05/2022

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

Revision Date : 10/05/2022 Date format : mm/dd/yyyy

Prepared by : R & D of Sika Canada Inc.

Material number : 677,980

CA / Z8