



PRODUCT DATA SHEET

SikaProof® Tape A+

SELF-ADHESIVE TAPE FOR INTERNAL JOINTING OF SIKAPROOF® A+ MEMBRANE SYSTEM

PRODUCT DESCRIPTION

SikaProof® Tape A+ is a self-adhesive tape based on a polyacrylate adhesive with a carrier film and a release liner.

WHERE TO USE

SikaProof® Tape A+ may only be used by experienced professionals.

- Sealing and bonding overlap joints, connections and details within the SikaProof® A+ membrane system.

CHARACTERISTICS / ADVANTAGES

- Fully bonded to the concrete structure (identical to SikaProof® A+)
- No lateral water migration between the concrete structure and the membrane system
- High adhesion and sealing capability, especially in cold and damp conditions
- Simple and fast to install

APPROVALS / CERTIFICATES

- Watertightness of a Surface Sealing System SikaProof® A+ 12 / SikaProof® Tape A+, WISSBAU, Test report No. 2018-275

PRODUCT INFORMATION

CSC MasterFormat®	07 13 00 SHEET WATERPROOFING	
Packaging	2 rolls packed in one cardboard box	
	Individual roll size	Length: 25 m Width: 150 mm
Appearance / Colour	Top layer	Light grey hybrid bonding layer with yellow waterproofing layer
	Bottom layer	Transparent polyacrylate adhesive covered with a white release liner
Shelf Life	18 months from date of production	
Storage Conditions	Product must be stored in original unopened and undamaged sealed packaging in dry conditions and temperatures between 5 °C and 30 °C. Always refer to packaging.	
Thickness	1.80 mm	

SYSTEMS

System Structure

SikaProof® Tape A+ is a system component for internal jointing of the SikaProof® A+ membrane system. For more detailed information, refer to Sika® Method Statement: SikaProof® A+ system

APPLICATION INFORMATION

Ambient Air Temperature

5 °C min. / 45 °C max.

Substrate Temperature

5 °C min.

BASIS OF PRODUCT DATA

Product properties are typically averages, obtained under laboratory conditions. Reasonable variations can be expected on-site due to local factors, including environment, preparation, application, curing and test methods.

OTHER DOCUMENTS

- Sika® Method Statement: SikaProof® A+
- Product Data Sheet: SikaProof® A+ 08/12

LIMITATIONS

Installation work must only be carried out by Sika® trained, approved or competent contractors experienced in this type of application.

- Do not install SikaProof® Tape A+ during continuous or prolonged rain or snowfall.
- The substrate quality and conditions must be fulfilled or appropriate measures must be taken. Contact Sika® Technical Services for more information.
- SikaProof® Tape A+ is not permanently UV resistant.
- The structural concrete must be placed within 90 days after the SikaProof® A+ membrane system is installed.

ENVIRONMENT, HEALTH & SAFETY**HAZARDOUS PRODUCT ACT - SECTION 2**

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulations is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data

sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1% (w/w).

APPLICATION INSTRUCTIONS**SUBSTRATE QUALITY**

The contact surface is the grey SikaProof® A+ hybrid bonding layer. It must be dry (or slightly damp), clean and free of any materials that could impair the adhesion. If the substrate requirements are not achieved, suitable measures must be taken. Contact Sika® Technical Services for more information.

APPLICATION METHOD / TOOLS

Strictly follow installation procedures as defined in method statements, application manuals and working instructions which must always be adjusted to the actual site conditions.

Installation Procedure

Remove the release liner, apply onto the grey SikaProof® A+ membrane side and press tape firmly using a pressure roller.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information contained herein and any other advice are given in good faith based on Sika's current

knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. The information only applies to the application(s) and product(s) expressly referred to herein and is based on laboratory tests which do not replace practical tests. In case of changes in the parameters of the application, such as changes in substrates etc., or in case of a different application, consult Sika's Technical Service prior to using Sika products. The information contained herein does not relieve the user of the products from testing them for the intended application and purpose. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or may be downloaded from our website at: www.sika.ca.

Sika Canada Inc.

Head Office
601, avenue Delmar
Pointe-Claire, Quebec
H9R 4A9

Other locations

Boisbriand (Quebec)
Brantford; Cambridge;
Sudbury; Toronto (Ontario)
Edmonton (Alberta)
Surrey (British Columbia)

1-800-933-SIKA

www.sika.ca



Product Data Sheet

SikaProof® Tape A+
March 2021, Version 03.02
02072030800000007

SikaProofTapeA+-en-CA-(03-2021)-3-2.pdf

