



PACT-8000 Part B

Revision Date 12/05/2023

Print Date 10/12/2024

SECTION 1. IDENTIFICATION

Product name : PACT-8000 Part B

Other means of identification : No data available

Company name : www.sika.ca
Canada
Pointe-Claire, QC H9R 4A9
601, avenue Delmar
Sika Canada Inc.

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

E-mail address : ehs@ca.sika.com

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids : Category 3

Acute toxicity (Inhalation) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

Respiratory sensitization : Category 1

Skin sensitization : Category 1

Germ cell mutagenicity : Category 1B

Carcinogenicity : Category 1B

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

Aspiration hazard : Category 1

GHS label elements



PACT-8000 Part B

Revision Date 12/05/2023

Print Date 10/12/2024

Hazard pictograms :



Signal Word :

Danger

Hazard Statements :

H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H340 May cause genetic defects.
H350 May cause cancer.

Precautionary Statements :

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P261 Avoid breathing mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
P284 In case of inadequate ventilation wear respiratory protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy



PACT-8000 Part B

Revision Date 12/05/2023

Print Date 10/12/2024

to do. Continue rinsing.
 P308 + P313 IF exposed or concerned: Get medical advice/attention.
 P331 Do NOT induce vomiting.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
 P337 + P313 If eye irritation persists: Get medical advice/attention.
 P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.
 P362 + P364 Take off contaminated clothing and wash it before reuse.
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
 P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration $\geq 1\%$.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Aliphatic polyisocyanate	28182-81-2	Acute Tox. 4; H332 Skin Sens. 1; H317 STOT SE 3; H335	$\geq 60 - < 80$
Solvent naphtha (petroleum), light arom.	64742-95-6	Muta. 1B; H340 Carc. 1B; H350 Asp. Tox. 1; H304	$\geq 10 - < 30$
1,2,4-trimethylbenzene	95-63-6	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 STOT SE 3; H335	$\geq 10 - < 30$
mesitylene	108-67-8	Flam. Liq. 3; H226 STOT SE 3; H335	$\geq 1 - < 5$
hexamethylene-di-isocyanate	822-06-0	Acute Tox. 1; H330 Skin Irrit. 2; H315	$\geq 0.1 - < 1$



PACT-8000 Part B

Revision Date 12/05/2023

Print Date 10/12/2024

		Eye Irrit. 2A; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335	
cumene	98-82-8	Flam. Liq. 3; H226 STOT SE 3; H335 Asp. Tox. 1; H304 Carc. 2; H351	>= 0.1 - < 1

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not induce vomiting without medical advice.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
Harmful if inhaled.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause respiratory irritation.
May cause genetic defects.
May cause cancer.
Risk of serious damage to the lungs (by aspiration).
irritant effects
sensitizing effects
carcinogenic effects
Aspiration may cause pulmonary edema and pneumonitis.
Asthmatic appearance



PACT-8000 Part B

Revision Date 12/05/2023

Print Date 10/12/2024

Cough
Respiratory disorder
Allergic reactions
Excessive lachrymation
Erythema
Headache
Dermatitis

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : Water
High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.
- Further information : Use water spray to cool unopened containers.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).



PACT-8000 Part B

Revision Date 12/05/2023

Print Date 10/12/2024

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Use explosion-proof equipment.
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
Take precautionary measures against electrostatic discharges.
- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapors or spray mist.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).
Follow standard hygiene measures when handling chemical products.
- Conditions for safe storage : Prevent unauthorized access.
Store in original container.
Keep in a well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Store in accordance with local regulations.
- Materials to avoid : Explosives
Oxidizing agents
Poisonous gases
Poisonous liquids

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Aliphatic polyisocyanate	28182-81-2	TWA	0.005 ppm	CA BC OEL
		C	0.01 ppm	CA BC OEL



PACT-8000 Part B

Revision Date 12/05/2023

Print Date 10/12/2024

1,2,4-trimethylbenzene	95-63-6	TWA	25 ppm 123 mg/m3	CA AB OEL
		TWAEV	25 ppm	CA QC OEL
		TWA	25 ppm	CA BC OEL
		TWA	25 ppm	ACGIH
		TWA	10 ppm	ACGIH
mesitylene	108-67-8	TWA	25 ppm 123 mg/m3	CA AB OEL
		TWAEV	25 ppm	CA QC OEL
		TWA	25 ppm	CA BC OEL
		TWA	10 ppm	ACGIH
hexamethylene-di-isocyanate	822-06-0	TWA	0.005 ppm 0.03 mg/m3	CA AB OEL
		TWA	0.005 ppm	CA BC OEL
		C	0.01 ppm	CA BC OEL
		TWA	0.005 ppm	CA ON OEL
		C	0.02 ppm	CA ON OEL
		TWAEV	0.005 ppm 0.034 mg/m3	CA QC OEL
		TWA	0.005 ppm	ACGIH
cumene	98-82-8	TWA	50 ppm 246 mg/m3	CA AB OEL
		TWA	25 ppm	CA BC OEL
		STEL	75 ppm	CA BC OEL
		TWAEV	50 ppm 246 mg/m3	CA QC OEL
		TWA	5 ppm	ACGIH

Engineering measures : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.
The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling



PACT-8000 Part B

Revision Date 12/05/2023

Print Date 10/12/2024

	chemical products if a risk assessment indicates this is necessary.
Eye protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin and body protection	: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Hygiene measures	: Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Remove respiratory and skin/eye protection only after vapors have been cleared from the area. Remove contaminated clothing and protective equipment before entering eating areas. Wash thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Color	: transparent
Odor	: aromatic
Odor Threshold	: No data available
pH	: No data available
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: > 41 °C (> 106 °F) (Method: closed cup)
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower	: No data available



PACT-8000 Part B

Revision Date 12/05/2023

Print Date 10/12/2024

flammability limit	
Vapor pressure	: 4.9996 hpa
Relative vapor density	: No data available
Density	: ca. 1.035 g/ml (23.7 °C (74.7 °F))
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: 76 mm ² /s (23.7 °C (74.7 °F))
Explosive properties	: No data available
Oxidizing properties	: No data available
Volatile organic compounds (VOC) content	: 230 g/l A+B Combined

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Stable under recommended storage conditions. Vapors may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: No data available
Hazardous decomposition products	: No decomposition if stored and applied as directed.



PACT-8000 Part B

Revision Date 12/05/2023

Print Date 10/12/2024

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if inhaled.

Components:

Aliphatic polyisocyanate:

- Acute oral toxicity : LD50 Oral (Rat): > 2,500 mg/kg
- Acute inhalation toxicity : LC50: 1.5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgment
- Acute dermal toxicity : LD50 Dermal (Rat): > 2,000 mg/kg

hexamethylene-di-isocyanate:

- Acute oral toxicity : LD50 Oral (Rat): 746 mg/kg
- Acute inhalation toxicity : LC50 (Rat): 0.124 mg/l
Exposure time: 4 h
Test atmosphere: vapor
- Acute dermal toxicity : LD50 Dermal (Rat): > 7,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

May cause genetic defects.

Carcinogenicity

May cause cancer.

IARC Group 2B: Possibly carcinogenic to humans
cumene 98-82-8

OSHA Not applicable

NTP Reasonably anticipated to be a human carcinogen



PACT-8000 Part B

Revision Date 12/05/2023

Print Date 10/12/2024

cumene

98-82-8

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Not classified due to lack of data.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Aspiration toxicity

May be fatal if swallowed and enters airways.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.



PACT-8000 Part B

Revision Date 12/05/2023

Print Date 10/12/2024

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1263
Proper shipping name : Paint
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1263
Proper shipping name : PAINT

Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number : UN 1263
Proper shipping name : PAINT

Class : 3
Packing group : III
Labels : 3
ERG Code : 128
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Canadian lists

No substances are subject to a Significant New Activity Notification.



PACT-8000 Part B

Revision Date 12/05/2023

Print Date 10/12/2024

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA BC OEL / C	:	ceiling limit
CA ON OEL / C	:	Ceiling Limit (C)
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEV	:	Time-weighted average exposure value
ADR	:	Accord européen relatif au transport international des marchandises Dangereuses par Route
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative



PACT-8000 Part B

Revision Date 12/05/2023

Print Date 10/12/2024

Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

Revision Date : 12/05/2023
Date format : mm/dd/yyyy
Prepared by : R & D of Sika Canada Inc.
Material number : 718,847

CA / Z8