



# SikaWall®-485 MP Dilution

INORGANIC, POTASSIUM SILICATE-BASED MINERAL PRIMER AND PAINT DILUENT



3.78 L (1 US gal)

SikaWall®-485 MP Dilution is a mineral paint diluent and primer based on potassium silicate. It can be used alone as a surface pre-treatment or as a diluent in combination with other products from the SikaWall®-485 range. SikaWall®-485 MP Dilution adheres by creating a chemical bond with the mineral substrate, providing high durability.

## ADVANTAGES

- Ready-to-use, for exterior and interior use
- Extremely vapour-permeable, allows the system to breathe
- Non-flammable - Does not release toxic gases or smoke in case of fire
- Resistant to fungal growth and algae

## WHERE TO USE

- For use as a diluent for mineral paints and pre-treatment of absorbent surfaces such as concrete, brick, most stones, historic masonry, stucco, mortars, lime plasters, CMU, GFRC, cement boards and plasters, etc.

TO LEARN MORE



Our most current General Sales Conditions shall apply.  
Please consult the most current local Product Data Sheet prior to any use.

**Sika Canada Inc.**  
Head Office  
601, avenue Delmar  
Pointe-Claire, Québec  
H9R 4A9

**Other locations**  
Boisbriand (QC)  
Brantford; Cambridge;  
Sudbury; Toronto (ON)  
Edmonton (AB) Surrey (BC)

**1-800-933-SIKA**  
[www.sika.ca](http://www.sika.ca)  
© Sika Canada Inc. / 02.2025

**BUILDING TRUST**  
**CONSTRUIRE LA CONFiance**

