



SikaWall®-485 MS Dilution

INORGANIC, POTASSIUM SILICATE-BASED, MINERAL PRIMER & STAIN DILUENT



15.14 L (4 US gal) / 3.78 L (1 US gal)

TO LEARN MORE



Our most current General Sales Conditions shall apply.
Please consult the most current local Product Data Sheet prior to any use.

SikaWall®-485 MS Dilution is a potassium silicate-based diluent and primer to be used alone or with mineral stain (Lasur) SikaWall®-485 MS. SikaWall®-485 MS Dilution adheres by creating a chemical bond with the mineral substrate.

ADVANTAGES

- Ready-to-use, for exterior and interior applications
- Extremely vapour-permeable, allows the system to breathe
- Non-flammable - Does not release toxic gases or smoke in case of fire
- Resistant to fungal growth and algae

WHERE TO USE

- Application on absorbent surfaces such as concrete, brick, most stones, historic masonry, stucco, mortars, lime plasters, CMU, GFRC, cement boards and plasters, etc.

Sika Canada Inc.
Head Office
601, avenue Delmar
Pointe-Claire, Quebec
H9R 4A9

Other locations
Boisbriand (QC)
Brantford; Cambridge;
Sudbury; Toronto (ON)
Edmonton (AB) Surrey (BC)

1-800-933-SIKA
www.sika.ca
© Sika Canada Inc. / 02.2025

BUILDING TRUST
CONSTRUIRE LA CONFiance

