

SikaForce®-840 L07 (A) Part A

Revision Date 10/09/2024 Print Date 10/12/2024

SECTION 1. IDENTIFICATION

Product name : SikaForce®-840 L07 (A) Part A

Other means of identification : No data available

Company name : www.sika.ca

Canada

Pointe-Claire, QC H9R 4A9

601, avenue Delmar Sika Canada Inc.

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

E-mail address : ehs@ca.sika.com

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

Recommended use of the chemical and restrictions on

use

For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Skin sensitization : Sub-category 1A

GHS label elements

Hazard pictograms



Signal Word : Warning

Hazard Statements : H317 May cause an allergic skin reaction.

Precautionary Statements : Prevention:

P261 Avoid breathing mist or vapors.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.



SikaForce®-840 L07 (A) Part A

Revision Date 10/09/2024 Print Date 10/12/2024

P333 + P313 If skin irritation or rash occurs: Get medical advice/

attention.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

| Chemical name | CAS-No. | Classification | Concentra- |
|------------------------------------|------------|---------------------|--------------|
| | | | tion (% w/w) |
| ethylene bis(3-mercaptopropionate) | 22504-50-3 | Acute Tox. 4; H302 | >= 1 - < 5 |
| | | Acute Tox. 4; H312 | |
| | | Skin Sens. 1A; H317 | |

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in attend-

ance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not induce vomiting without medical advice.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.



SikaForce®-840 L07 (A) Part A

Revision Date 10/09/2024 Print Date 10/12/2024

Most important symptoms and effects, both acute and

delayed

sensitizing effects Allergic reactions

May cause an allergic skin reaction.

Notes to physician Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

for fire-fighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

tive equipment and emer-

gency procedures

Personal precautions, protec- : Use personal protective equipment.

Deny access to unprotected persons.

Do not flush into surface water or sanitary sewer system. **Environmental precautions**

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

fire and explosion

Advice on protection against : Normal measures for preventive fire protection.

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.



SikaForce®-840 L07 (A) Part A

Revision Date 10/09/2024 Print Date 10/12/2024

Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures : Use of adequate ventilation should be sufficient to control

worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommend-

ed or statutory limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed

respirator complying with an approved standard if a risk as-

sessment indicates this is necessary.

The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling

the product.

Remove contaminated clothing and protective equipment

before entering eating areas. Wash thoroughly after handling.



SikaForce®-840 L07 (A) Part A

Revision Date 10/09/2024 Print Date 10/12/2024

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Color : black

Odor : musty

Odor Threshold : No data available

pH : Not applicable substance/mixture is non-soluble (in water)

Melting point/ range / Freez-

ing point

No data available

Boiling point/boiling range : No data available

Flash point : $> 101 \, ^{\circ}\text{C} \, (214 \, ^{\circ}\text{F})$

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapor pressure : 0.01 hpa

Relative vapor density : No data available

Density : ca. 1.16 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature : No data available

Decomposition temperature : No data available



SikaForce®-840 L07 (A) Part A

Revision Date 10/09/2024 Print Date 10/12/2024

Viscosity

Viscosity, dynamic : ca. 10,000 mPa.s (20 °C (68 °F))

Viscosity, kinematic : $> 20.5 \text{ mm2/s} (40 ^{\circ}\text{C} (104 ^{\circ}\text{F}))$

Explosive properties : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

Hazardous decomposition

products

No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Components:

ethylene bis(3-mercaptopropionate):

Acute oral toxicity : LD50 Oral (Rat): >= 1,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 1,905 mg/kg

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.



SikaForce®-840 L07 (A) Part A

Revision Date 10/09/2024 Print Date 10/12/2024

Respiratory sensitization

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

IARC Group 2B: Possibly carcinogenic to humans

Carbon black, amorphous 1333-86-4

OSHA Not applicable

NTP Not applicable

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

Not classified due to lack of data.

STOT-repeated exposure

Not classified due to lack of data.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Aspiration toxicity

Not classified due to lack of data.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

ethylene bis(3-mercaptopropionate):

Toxicity to fish (Chronic tox- : LC50 (Fish): 4.85 mg/l icity) Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor- : Do not empty into drains; dispose of this material and its con-

mation tainer in a safe way.



SikaForce®-840 L07 (A) Part A

Revision Date 10/09/2024 Print Date 10/12/2024

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ADR : Accord européen relatif au transport international des

marchandises Dangereuses par Route

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration



SikaForce®-840 L07 (A) Part A

Revision Date 10/09/2024 Print Date 10/12/2024

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

Revision Date : 10/09/2024 Date format : mm/dd/yyyy

Prepared by : R & D of Sika Canada Inc.

Material number : 564,815



SikaForce®-840 L07 (A) Part A

Revision Date 10/09/2024 Print Date 10/12/2024

CA / Z8