



PRODUCT DATA SHEET

Open Post Flashing

PREFABRICATED BOOT OPEN ALONG ONE SIDE

PRODUCT DESCRIPTION

Open Post Flashing is 1.5 mm (60 mil) thick prefabricated boot open along one side to provide a simplified flashing solution for rooftop conduits and pipe penetrations when access is obstructed.

WHERE TO USE

For flashing rooftop conduits and pipe penetrations up to 32 mm (1.25 in) in diameter in Sarnafil® and Sikaplan® roofing and waterproofing details

Areas of Application

- Rooftop conduits/pipes
- Round diameter obstructed penetrations

CHARACTERISTICS / ADVANTAGES

- Time-saving and effective method to flash rooftop conduits and pipe penetrations
- Factory fabricated
- Only one open seam to heat weld in the field

PRODUCT INFORMATION

Composition / Manufacturing	Made from Sarnafil® G 410 1.5 mm (60 mil) roofing membrane
Packaging	Open Post Flashing can be individually ordered.
Appearance / Colour	White, Tan, or Reflective Grey
Shelf Life	N/A
Storage Conditions	N/A
Dimensions	Part 114610: 12.7 mm (0.5 in) – 19 mm (0.75 in) diameter Dimensions: 203 mm (8 in) high, 152 mm (6 in) flange, 330 mm (13 in) diameter base Part 185683: 19 mm (0.75 in) – 32 mm (1.25 in) diameter Dimensions: 203 mm (8 in) high, 152 mm (6 in) flange, 337 mm (13.25 in) diameter base

BASIS OF PRODUCT DATA

Product properties are typically averages, obtained under laboratory conditions. Reasonable variations can be expected on-site due to local factors, including environment, preparation, application, curing and test methods.

OTHER DOCUMENTS

Availability

Open Post Flashing is available directly from Sika Canada Authorized Applicators when used within a Sika® Sarnafil® Roofing or Waterproofing System. Contact Sika Canada or visit our website at www.sika.ca for further information.

Warranty

Upon successful completion of the installed roof by the Sika Canada Authorized Applicator, Sika Canada can provide a warranty to the Building Owner via the Authorized Applicator.

ENVIRONMENT, HEALTH & SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

APPLICATION

1. Install insulation and deck sheet tight to the penetration. Secure deck sheet around the penetration according to Sika details. Securement shall be tight to the penetration so that the base plate of the Open Post Flashing will adequately cover the fasteners.
2. Wrap the Open Post Flashing around the pipe with the vertical portion tight against the penetration.
3. Mark the penetration at the top edge of the flashing and remove the prefabricated piece.
4. Place sealant around the entire penetration at the mark.
5. Wrap the Open Post Flashing around the pipe with the vertical portion tight against the penetration.
6. Tack weld the back edge of the Open Post Flashing at the slit, being sure that tight contact is maintained between the flashing and the pipe.

- Heat weld the entire width of the vertical overlap.
- Pre-weld and finish weld the entire base plate to the deck sheet.
- Check all welds with a rounded screwdriver.
- Install a stainless steel hose clamp flush with the top of the flashing.

MAINTENANCE

Standard maintenance of roofs should include regular inspection of flashings, drains and termination sealants at least twice a year and after each storm.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any recommendations, or from any other advice offered. The information contained herein does not relieve the user of the products from testing them for the intended application and purpose. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or may be downloaded from our website at: www.sika.ca

Sika Canada Inc.

Head Office
601, avenue Delmar
Pointe-Claire, Quebec
H9R 4A9
1-800-933-SIKA
www.sika.ca

Other locations

Boisbriand (Quebec)
Brantford; Cambridge;
Sudbury; Toronto (Ontario)
Edmonton (Alberta)
Surrey (British Columbia)

Product Data Sheet

Open Post Flashing
April 2021, Version 02.01
020945012100001009