Revision Date 11/14/2022



### **SECTION 1. IDENTIFICATION**

Product name	:	Sikadur <sup>®</sup> -43 Patch-Pak Part B
Other means of identification	:	No data available
Company name	:	601, avenue Delmar Canada Pointe-Claire, QC H9R 4A9 Sika Canada Inc. www.sika.ca
Telephone	:	(514) 697-2610 / 1 (800) 933-7452
Telefax	:	(514) 694-2792
E-mail address	:	ehs@ca.sika.com
Emergency telephone	:	CANUTEC (collect) (613) 996-6666 (24 hours)
Recommended use of the chemical and restrictions on use	:	For further information, refer to product data sheet.

### **SECTION 2. HAZARDS IDENTIFICATION**

<b>GHS classification in accor</b> Acute toxicity (Oral)	dar :	nce with the Hazardous Products Regulations Category 4
Skin corrosion	:	Category 1B
Serious eye damage	:	Category 1
Skin sensitization	:	Sub-category 1A
Reproductive toxicity	:	Category 2
GHS label elements Hazard pictograms	:	
Signal Word	:	Danger
Hazard Statements	:	H302 Harmful if swallowed. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H361 Suspected of damaging fertility or the unborn child.

Revision Date 11/14/2022



Precautionary Statements	Prevention:
	<ul> <li>P201 Obtain special instructions before use.</li> <li>P202 Do not handle until all safety precautions have been read and understood.</li> <li>P261 Avoid breathing mist or vapors.</li> <li>P264 Wash skin thoroughly after handling.</li> <li>P270 Do not eat, drink or smoke when using this product.</li> <li>P272 Contaminated work clothing should not be allowed out of the workplace.</li> <li>P280 Wear protective gloves/ protective clothing/ eye protection face protection.</li> </ul>
	Response:
	<ul> <li>P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.</li> <li>P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.</li> <li>P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.</li> <li>P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.</li> <li>P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.</li> <li>P308 + P313 IF exposed or concerned: Get medical advice/ attention.</li> <li>P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.</li> <li>P362 + P364 Take off contaminated clothing and wash it before reuse.</li> </ul>
	Storage:
	P405 Store locked up.
	<b>Disposal:</b> P501 Dispose of contents/ container to an approved waste disposal plant.
Additional Labeling	inknown acute toxicity used in a mixture at a concentration >= 1%.
Other hazards	
None known.	

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Classification	Concentra-
			tion (% w/w)
Benzyl alcohol	100-51-6	Acute Tox. 4; H302	>= 10 - < 30
	2/13	,	



Revision Date 11/14/2022

		Acute Tox. 4; H332 Eye Irrit. 2A; H319	
Isophoronediamine	2855-13-2	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317	>= 10 - < 30
Phenol, 4-nonyl, branched	84852-15-3	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Repr. 2; H361	>= 10 - < 30
triethylenetetramine	112-24-3	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317	>= 10 - < 30
2,4,6- tris(dimethylaminomethyl)phenol	90-72-2	Skin Corr. 1C; H314 Eye Dam. 1; H318	>= 10 - < 30
Complex epoxy resin/amine adducts	Not Assigned	Acute Tox. 4; H302 Skin Sens. 1; H317	>= 5 - < 10
bis[(dimethylamino)methyl]phenol	71074-89-0	Skin Corr. 1B; H314	>= 1 - < 5

Actual concentration or concentration range is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

General advice	:	Move out of dangerous area. Consult a physician. Show this material safety data sheet to the doctor in attend- ance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul- ty.
In case of eye contact	:	Small amounts splashed into eyes can cause irreversible tis- sue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing.
If swallowed	:	Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting without medical advice. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Take victim immediately to hospital.
Most important symptoms	:	Health injuries may be delayed.

Revision Date 11/14/2022



and effects, both acute and delayed	corrosive effects sensitizing effects Gastrointestinal discomfort Allergic reactions Dermatitis Harmful if swallowed.
	May cause an allergic skin reaction. Causes serious eye damage. Suspected of damaging fertility or the unborn child. Causes severe burns.

## Notes to physician : Treat symptomatically.

## SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer- gency procedures		Use personal protective equipment. Deny access to unprotected persons.
Environmental precautions :	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for : containment and cleaning up		Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Advice on safe handling	:	Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8.





	Persons with a history of skin sensitization problems or asth- ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the ap- plication area. Follow standard hygiene measures when handling chemical products.
Conditions for safe storage	<ul> <li>Store in original container. Keep container tightly closed in a dry and well-ventilated place.</li> <li>Containers which are opened must be carefully resealed and kept upright to prevent leakage.</li> <li>Observe label precautions.</li> <li>Store in accordance with local regulations.</li> </ul>
Materials to avoid	: Explosives Oxidizing agents Poisonous gases Dangerous when wet Flammable solids Organic peroxides Poisonous liquids Spontaneously Combustible Substances

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Ingredients with workplace control parameters

ingredients with workplace							
Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis			
triethylenetetramine	112-24-3	TWA	0.5 ppm 3 mg/m3	CA ON OEL			
<b>Engineering measures</b> : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.							
Personal protective equipm	nent						
Respiratory protection	approved air-purifying approved standard if cessary.						
	The filter class for the respirator must be suitable for the max- imum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when han- dling the product. If this concentration is exceeded, self- contained breathing apparatus must be used.						

Revision Date 11/14/2022



Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec- essary.
Eye protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin and body protection	:	Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe- cific work-place.
Hygiene measures	:	Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Remove contaminated clothing and protective equipment before entering eating areas. Wash thoroughly after handling.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Color	:	yellow
Odor	:	amine-like
Odor Threshold	:	No data available
рН	:	Not applicable
Melting point/range / Freezing	:	No data available
point Boiling point/boiling range	:	No data available
Flash point	:	> 100 °C (> 212 °F) (Method: closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	0.07 hpa
Relative vapor density	:	No data available
Density	:	0.97 g/cm3 (23 °C (73 °F))

Revision Date 11/14/2022



Solubility(ies) Water solubility	:	soluble
Solubility in other solvents	:	No data available
Partition coefficient: n- octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20.5 mm2/s ( 40 °C (104 °F))
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds (VOC) content	:	2.3 g/l A+B+C Combined

## SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reac- tions	:	Stable under recommended storage conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	No data available
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

## SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity	
Harmful if swallowed.	
Components:	
Benzyl alcohol:	
Acute oral toxicity	: LD50 Oral (Rat): 1,620 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 4.178 mg/l Exposure time: 4 h
	7 / 13

Revision Date 11/14/2022



		Test atmosphere: dust/mist				
Isophoronediamine:						
Acute oral toxicity	:	LD50 Oral (Rat): 1,030 mg/kg				
Acute inhalation toxicity	:	LC50 (Rat): > 10 mg/l Exposure time: 4 h Test atmosphere: dust/mist				
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 - 5,000 mg/kg				
Phenol, 4-nonyl, branched:						
Acute oral toxicity	:	LD50 Oral (Rat): 1,412 mg/kg				
Acute dermal toxicity	:	LD50 Dermal (Rabbit): 3,160 mg/kg				
triethylenetetramine:						
Acute oral toxicity	:	LD50 Oral (Rat): 1,716 mg/kg				
Acute dermal toxicity	:	LD50 Dermal (Rabbit): 1,465 mg/kg				
2,4,6-tris(dimethylaminome	thy	l)phenol:				
Acute oral toxicity	:	LD50 Oral (Rat): 2,169 mg/kg				
Skin corrosion/irritation						
Causes severe burns.						
Components:						
2,4,6-tris(dimethylaminome	2,4,6-tris(dimethylaminomethyl)phenol:					
Species	:	Rabbit				
Assessment Method	:	Corrosive OECD Test Guideline 404				
Wethod	•					
Serious eye damage/eye irr	itat	ion				
Causes serious eye damage.						
Components:						
2,4,6-tris(dimethylaminomethyl)phenol:						
Species	:	Rabbit				
Assessment	-	Causes serious eye damage.				
Respiratory or skin sensitization						
Skin sensitization						
May cause an allergic skin reaction.						
Respiratory sensitization						

## Not classified based on available information.

# Sikadur®-43 Patch-Pak Part B

#### Revision Date 11/14/2022



**Germ cell mutagenicity** Not classified based on available information.

### Carcinogenicity

Not classified based on available information. **IARC** Not applicable

OSHA Not applicable

NTP Not applicable

#### **Reproductive toxicity**

Suspected of damaging fertility or the unborn child.

### STOT-single exposure

Not classified based on available information.

#### STOT-repeated exposure

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

#### Aspiration toxicity

Not classified based on available information.

### SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity		
Components:		
Benzyl alcohol:		
Toxicity to fish	:	LC50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h
Isophoronediamine:		
Toxicity to algae/aquatic plants	:	ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100 mg/l
		NOEC (Desmodesmus subspicatus (green algae)): 1.5 mg/l
Phenol, 4-nonyl, branched:		
triethylenetetramine:		
Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia): 10 - 100 mg/l Exposure time: 48 h
Toxicity to algae/aquatic	:	EC50 (Pseudokirchneriella subcapitata (green algae)): 10 -

# Sikadur®-43 Patch-Pak Part B

Print Date 11/14/2022

Revision Date 11/14/2022

plants	100 mg/l Exposure time: 72 h		
2,4,6-tris(dimethylaminomethy	l)phenol:		
Toxicity to algae/aquatic : plants	EC50 (Scenedesmus capricornutum (fresh water algae)): > 10 - 100 mg/l		
Persistence and degradability			
No data available			
Bioaccumulative potential			
No data available			
Mobility in soil			
No data available			
Other adverse effects			
Product:			
Additional ecological infor- : mation	Do not empty into drains; dispose of this material and its con- tainer in a safe way. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. May be harmful to the environment if released in large quanti- ties. Water polluting material.		

### **SECTION 13. DISPOSAL CONSIDERATIONS**

<b>Disposal methods</b> Waste from residues		Disposal of this product, solutions and any by-products should
	·	at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Contaminated packaging	:	Empty containers should be taken to an approved waste han- dling site for recycling or disposal.

## SECTION 14. TRANSPORT INFORMATION

## International Regulations

<b>IATA-DGR</b> UN/ID No. Proper shipping name	:	UN 3267 Corrosive liquid, basic, organic, n.o.s. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, 4- nonylphenol, branched)
Class	:	8
Packing group	:	ll
		10 / 13

Revision Date 11/14/2022



Labels Packing instruction (cargo aircraft) Packing instruction (passen- ger aircraft)	: :	Corrosive 855 851
<b>IMDG-Code</b> UN number Proper shipping name	:	UN 3267 CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, 4- nonylphenol, branched)
Class Packing group	:	8 II
Labels EmS Code	:	8 F-A, S-B
Marine pollutant	:	yes

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### **Domestic regulation**

TDG		
UN number	:	UN 3267
Proper shipping name	:	CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, Phenol, 4- nonyl, branched)
Class	:	8
Packing group	:	
Labels	:	8
ERG Code	:	153
Marine pollutant	:	no

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### **SECTION 15. REGULATORY INFORMATION**

#### **Canadian lists**

No substances are subject to a Significant New Activity Notification.

### **SECTION 16. OTHER INFORMATION**

Full text of other abbreviations			
CA ON OEL :	Ontario Table of Occupational Exposure Limits made under		
	the Occupational Health and Safety Act.		
CA ON OEL / TWA :	Time-Weighted Average Limit (TWA)		

Revision Date 11/14/2022



ADR	:	Accord européen relatif au transport international des marchandises Dangereuses par Route
CAS		Chemical Abstracts Service
DNEL	÷	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
ΙΑΤΑ	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at
		once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in
		air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from
		Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

#### Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

Revision Date	: 11/14/2022
Date format	: mm/dd/yyyy
Prepared by	: R & D of Sika Canada Inc.



Revision Date 11/14/2022

Material number

: 459,586

CA / Z8