

Revision Date 06/03/2022

Print Date 06/03/2022

#### **SECTION 1. IDENTIFICATION**

Product name : Sikalastic® 745 AL Part B

Other means of identification : No data available

Company name : 601, avenue Delmar

Canada

Pointe-Claire, QC H9R 4A9

Sika Canada Inc. www.sika.ca

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

E-mail address : ehs@ca.sika.com

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

Recommended use of the chemical and restrictions on

use

For further information, refer to product data sheet.

## **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with the Hazardous Products Regulations

Acute toxicity (Oral) : Category 4

Skin corrosion : Category 1C

Serious eye damage : Category 1

Skin sensitization : Sub-category 1A

Specific target organ toxicity

- repeated exposure (Oral)

Category 2

**GHS** label elements

Hazard pictograms :







Signal Word : Danger

Hazard Statements : H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H373 May cause damage to organs through prolonged or re-

peated exposure if swallowed.



Revision Date 06/03/2022 Print Date 06/03/2022

**Precautionary Statements** 

#### Prevention:

P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

### Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON

CENTER/ doctor if you feel unwell. Rinse mouth.

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P314 Get medical advice/ attention if you feel unwell.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

#### Storage:

P405 Store locked up.

#### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### **Additional Labeling**

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

#### Other hazards

None known.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Classification	Concentra- tion (% w/w)
Isophorondiamine-Isobutyraldimine	54914-37-3	Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317	>= 30 - < 60



Revision Date 06/03/2022 Print Date 06/03/2022

diethylmethylbenzenediamine	68479-98-1	Acute Tox. 4; H302	>= 30 - < 60
		Acute Tox. 4; H312	
		Eye Irrit. 2A; H319	
		STOT RE 2; H373	

Actual concentration or concentration range is withheld as a trade secret

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in attend-

ance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul-

ty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not induce vomiting without medical advice.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

Health injuries may be delayed.

corrosive effects sensitizing effects

Gastrointestinal discomfort

Allergic reactions

Dermatitis

Harmful if swallowed.

May cause an allergic skin reaction.

Causes serious eye damage.

May cause damage to organs through prolonged or repeated

exposure if swallowed. Causes severe burns.

Notes to physician : Treat symptomatically.

#### **SECTION 5. FIRE-FIGHTING MEASURES**



Revision Date 06/03/2022 Print Date 06/03/2022

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment :

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec-: tive equipment and emer-

gency procedures

Use personal protective equipment.

Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

## **SECTION 7. HANDLING AND STORAGE**

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage : Store in original container.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.



Revision Date 06/03/2022 Print Date 06/03/2022

Materials to avoid : Explosives

Oxidizing agents
Poisonous gases
Dangerous when wet
Flammable solids
Organic peroxides
Poisonous liquids

Spontaneously Combustible Substances

### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

### Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures : Use of adequate ventilation should be sufficient to control

worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommend-

ed or statutory limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed

respirator complying with an approved standard if a risk as-

sessment indicates this is necessary.

The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling

the product.

Remove contaminated clothing and protective equipment

before entering eating areas. Wash thoroughly after handling.



Revision Date 06/03/2022

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Color : black

Odor : amine-like

Odor Threshold : No data available

pH : Not applicable

Melting point/range / Freezing :

point

Boiling point/boiling range : 308 °C (586 °F)

Flash point : 200 °C (392 °F)

(Method: closed cup)

No data available

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : 0.0013332 hpa

Relative vapor density : No data available

Density : 0.94 g/cm3

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : ca.  $> 20.5 \text{ mm2/s} (40 ^{\circ}\text{C} (104 ^{\circ}\text{F}))$ 

Explosive properties : No data available

Oxidizing properties : No data available



Revision Date 06/03/2022 Print Date 06/03/2022

Volatile organic compounds

(VOC) content

0 g/l

Sikalastic 745 AL (A) + Sikalastic 745 AL (B) Combined

7.6 g/l

Sikalastic 745 Textured (A) + Sikalastic 745 AL (B) Combined

# **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

Hazardous decomposition

products

No decomposition if stored and applied as directed.

### **SECTION 11. TOXICOLOGICAL INFORMATION**

### **Acute toxicity**

Harmful if swallowed.

### **Components:**

## Isophorondiamine-Isobutyraldimine:

Acute oral toxicity : LD50 Oral (Rat): 4,150 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): > 5,000 mg/kg

### diethylmethylbenzenediamine:

Acute oral toxicity : LD50 Oral (Rat): 738 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): 2,500 mg/kg

### Skin corrosion/irritation

Causes severe burns.

### Serious eye damage/eye irritation

Causes serious eye damage.

### Respiratory or skin sensitization

### Skin sensitization

May cause an allergic skin reaction.



Revision Date 06/03/2022

Print Date 06/03/2022

### Respiratory sensitization

Not classified based on available information.

### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

IARC Not applicable

OSHA Not applicable

NTP Not applicable

### Reproductive toxicity

Not classified based on available information.

## STOT-single exposure

Not classified based on available information.

## STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure if swallowed.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

### **Aspiration toxicity**

Not classified based on available information.

#### **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

No data available

# Persistence and degradability

No data available

#### Bioaccumulative potential

No data available

#### Mobility in soil

No data available

### Other adverse effects

### **Product:**

Additional ecological infor-

mation

Do not empty into drains; dispose of this material and its con-

tainer in a safe way.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

Toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

May be harmful to the environment if released in large quanti-

ties.

Water polluting material.



Revision Date 06/03/2022 Print Date 06/03/2022

### **SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods

Waste from residues Disposal of this product, solutions and any by-products should

> at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

#### SECTION 14. TRANSPORT INFORMATION

# **International Regulations**

IATA-DGR

UN 1760 UN/ID No.

Proper shipping name Corrosive liquid, n.o.s.

(Isophorondiamine-Isobutyraldimine, diethylmethylben-

zenediamine)

Class 8 Packing group Ш

Labels Corrosive 856

Packing instruction (cargo

aircraft)

Packing instruction (passen-852

ger aircraft)

**IMDG-Code** 

**UN** number UN 1760

Proper shipping name CORROSIVE LIQUID, N.O.S.

(Isophorondiamine-Isobutyraldimine, diethylmethylben-

zenediamine)

Class 8 Ш Packing group Labels 8

EmS Code F-A, S-B Marine pollutant yes

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

# **Domestic regulation**

DOT: For Limited Quantity exceptions reference 49 CFR 173.154 (b)

IMDG: For Limited Quantity special provisions reference IMDG Code Chapter 3.4

**TDG** 

**UN** number UN 1760

Proper shipping name CORROSIVE LIQUID, N.O.S.

(Isophorondiamine-Isobutyraldimine)

Class 8 Packing group Ш



Revision Date 06/03/2022 Print Date 06/03/2022

Labels : 8 ERG Code : 154 Marine pollutant : no

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### **SECTION 15. REGULATORY INFORMATION**

### **Canadian lists**

No substances are subject to a Significant New Activity Notification.

#### **SECTION 16. OTHER INFORMATION**

#### Full text of other abbreviations

ADR : Accord européen relatif au transport international des

marchandises Dangereuses par Route

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

## Notice to Reader:

SVHC



Revision Date 06/03/2022 Print Date 06/03/2022

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

Revision Date : 06/03/2022 Date format : mm/dd/yyyy

Prepared by : R & D of Sika Canada Inc.

Material number : 189,348

CA / Z8