



FACT SHEET

SikaLevel®-02 EZ Primer^{CA}

ACRYLIC PRIMER FOR DIFFICULT, NON-POROUS SUBSTRATES

ADVANTAGES

- **Ready-to-use**
- **Quick drying** time
- **Solvent-free** and **Low VOC**

BUILDING TRUST
CONSTRUIRE LA CONFIANCE



FACT SHEET

SikaLevel®-02 EZ Primer^{CA}

ACRYLIC PRIMER FOR DIFFICULT, NON-ABSORBANT SUBSTRATES

SikaLevel®-02 EZ Primer^{CA} is a special acrylic primer for use on sound, smooth and non-porous substrates in interior areas. Used prior to the application of SikaLevel® products, SikaLevel®-02 EZ Primer^{CA} is ideal for the treatment of a variety of non-traditional substrates.

TYPICAL DATA

(Material and curing conditions @ 23 °C (73 °F) and 50 % R.H.)

Packaging	3,78 L (1 US gal.)
Colour	Yellow
Composition	Acrylic
Open Time	48 hours
Curing	30 minutes (minimum) to 60 minutes
Coverage	30.2 m ² to 46.4 m ² (325 ft ² to 500 ft ²) per unit
Pull-Off Strength	> 1.8 MPa (> 261 psi) - CAN/CSA-A23.2-6B modified

WHERE TO USE

- Smooth & low absorption concrete
- Over terrazzo, ceramic tiles, natural stone
- Existing substrates with properly prepared existing old carpet and vinyl composition tile (VCT) adhesive residues
- Engineered approved plywood underlayment
- Moisture Control Primer
- Steel and galvanized steel
- Epoxy moisture barrier
- Interior only

Always refer to current PDS and SDS for detailed performance specifications prior to use

FEATURES AND BENEFITS

- Provides excellent adhesion
- Suitable for application on subfloor radiant system
- Low consumption of material



The information contained herein and any other advice are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. The information only applies to the application(s) and product(s) expressly referred to herein and is based on laboratory tests which do not replace practical tests. In case of changes in the parameters of the application, such as changes in substrates etc., or in case of a different application, consult Sika's Technical Service prior to using Sika products. The information contained herein does not relieve the user of the products from testing them for the intended application and purpose. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or may be downloaded from our website at: www.sika.ca.

SIKA CANADA INC.

Head Office
601 Delmar Avenue
Pointe-Claire, Quebec
H9R 4A9

Other locations
Boisbriand (QC)
Brantford; Cambridge; Sudbury; Toronto (ON)
Edmonton (AB); Surrey (BC)

1-800-933-7452
www.sika.ca

© Sika Canada Inc. / 09.2023

BUILDING TRUST
CONSTRUIRE LA CONFIANCE

