



Sikafloor®-2002 Part B

Revision Date 10/04/2024

Print Date 10/12/2024

SECTION 1. IDENTIFICATION

Product name : Sikafloor®-2002 Part B

Other means of identification : No data available

Company name : www.sika.ca
Canada
Pointe-Claire, QC H9R 4A9
601, avenue Delmar
Sika Canada Inc.

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

E-mail address : ehs@ca.sika.com

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Acute toxicity (Oral) : Category 4

Skin corrosion : Category 1

Serious eye damage : Category 1

Skin sensitization : Sub-category 1A

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.



Sikafloor®-2002 Part B

Revision Date 10/04/2024

Print Date 10/12/2024

Precautionary Statements

:

Prevention:

P261 Avoid breathing mist or vapors.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration $\geq 1\%$.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Benzyl alcohol	100-51-6	Acute Tox. 4; H302 Eye Irrit. 2A; H319	≥ 30 - < 60



Sikafloor®-2002 Part B

Revision Date 10/04/2024

Print Date 10/12/2024

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	25513-64-8	Skin Sens. 1B; H317 Acute Tox. 4; H302 Skin Corr. 1A; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317	>= 10 - < 30
Isophoronediamine	2855-13-2	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317	>= 5 - < 10

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not induce vomiting without medical advice.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Health injuries may be delayed.
corrosive effects
sensitizing effects
Gastrointestinal discomfort
Allergic reactions
Dermatitis
Harmful if swallowed.
May cause an allergic skin reaction.
Causes serious eye damage.
Causes severe burns.



Sikafloor®-2002 Part B

Revision Date 10/04/2024

Print Date 10/12/2024

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Deny access to unprotected persons.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products.



Sikafloor®-2002 Part B

Revision Date 10/04/2024

Print Date 10/12/2024

- Conditions for safe storage : Store in original container.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Store in accordance with local regulations.
- Materials to avoid : Explosives
Oxidizing agents
Poisonous gases
Dangerous when wet
Flammable solids
Organic peroxides
Poisonous liquids
Spontaneously Combustible Substances

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

- Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protective equipment

- Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
- The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concen-



Sikafloor®-2002 Part B

Revision Date 10/04/2024

Print Date 10/12/2024

Hygiene measures : tration and amount of dangerous substances, and to the specific work-place.
: Avoid contact with skin, eyes and clothing.
Wash hands before breaks and immediately after handling the product.
Remove contaminated clothing and protective equipment before entering eating areas.
Wash thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : amber

Odor : amine-like

Odor Threshold : No data available

pH : not determined

Melting point/ range / Freezing point : No data available

Boiling point/boiling range : No data available

Flash point : 96 °C (205 °F)
(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : 0.07 hpa

Relative vapor density : No data available

Density : 1.008 g/ml (23 °C (73 °F))

Solubility(ies)



Sikafloor®-2002 Part B

Revision Date 10/04/2024

Print Date 10/12/2024

Water solubility	:	partly soluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 7 mm ² /s (40 °C (104 °F))
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds (VOC) content	:	24.9 g/l

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	No data available
		No data available
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed.

Components:

Benzyl alcohol:

Acute oral toxicity : LD50 Oral (Rat): 1,200 mg/kg



Sikafloor®-2002 Part B

Revision Date 10/04/2024

Print Date 10/12/2024

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine:

Acute oral toxicity : LD50 Oral (Rat): 910 mg/kg

Isophoronediamine:

Acute oral toxicity : LD50 Oral (Rat): 1,030 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 - 5,000 mg/kg

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

IARC Not applicable

OSHA Not applicable

NTP Not applicable

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

Not classified due to lack of data.

STOT-repeated exposure

Not classified due to lack of data.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Aspiration toxicity

Not classified due to lack of data.



Sikafloor®-2002 Part B

Revision Date 10/04/2024

Print Date 10/12/2024

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l
aquatic invertebrates Exposure time: 48 h

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine:

Toxicity to algae/aquatic : EC50 (Scenedesmus capricornutum (fresh water algae)): 29.5
plants mg/l

Toxicity to fish (Chronic tox- : LC50 (Leuciscus idus (Golden orfe)): 174 mg/l
icity) Exposure time: 48 h

Isophoronediamine:

Toxicity to algae/aquatic : ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100
plants mg/l

NOEC (Desmodesmus subspicatus (green algae)): 1.5 mg/l

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor- : Do not empty into drains; dispose of this material and its con-
mation tainer in a safe way.
Avoid dispersal of spilled material and runoff and contact with
soil, waterways, drains and sewers.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should
at all times comply with the requirements of environmental



Sikafloor®-2002 Part B

Revision Date 10/04/2024

Print Date 10/12/2024

protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 3066
Proper shipping name : Paint related material
Class : 8
Packing group : III
Labels : Corrosive
Packing instruction (cargo aircraft) : 856
Packing instruction (passenger aircraft) : 852

IMDG-Code

UN number : UN 3066
Proper shipping name : PAINT RELATED MATERIAL

Class : 8
Packing group : III
Labels : 8
EmS Code : F-A, S-B
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number : UN 3066
Proper shipping name : PAINT RELATED MATERIAL

Class : 8
Packing group : III
Labels : 8
ERG Code : 153
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.



Sikafloor®-2002 Part B

Revision Date 10/04/2024

Print Date 10/12/2024

SECTION 15. REGULATORY INFORMATION

Canadian lists

The following substance(s) is/are subject to a Significant New Activity Notification:
 α -chlorotoluene 100-44-7

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ADR	:	Accord européen relatif au transport international des marchandises Dangereuses par Route
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current



Sikafloor®-2002 Part B

Revision Date 10/04/2024

Print Date 10/12/2024

Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

Revision Date : 10/04/2024
Date format : mm/dd/yyyy
Prepared by : R & D of Sika Canada Inc.
Material number : 183,966

CA / Z8