



Sikafloor®-293 Part A

Revision Date 02/16/2024

Print Date 10/12/2024

SECTION 1. IDENTIFICATION

Product name : Sikafloor®-293 Part A

Other means of identification : No data available

Company name : www.sika.ca
Canada
Pointe-Claire, QC H9R 4A9
601, avenue Delmar
Sika Canada Inc.

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

E-mail address : ehs@ca.sika.com

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations


Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitization : Category 1

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.



Sikafloor®-293 Part A

Revision Date 02/16/2024

Print Date 10/12/2024

Precautionary Statements : **Prevention:**
 P261 Avoid breathing mist or vapors.
 P264 Wash skin thoroughly after handling.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P280 Wear protective gloves/ eye protection/ face protection.

Response:
 P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 P302 + P352 IF ON SKIN: Wash with plenty of water.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P331 Do NOT induce vomiting.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P337 + P313 If eye irritation persists: Get medical advice/ attention.
 P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:
 P405 Store locked up.

Disposal:
 P501 Dispose of contents/ container to an approved waste disposal plant.

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration $\geq 1\%$.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	25068-38-6	Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Skin Sens. 1; H317	$\geq 60 - < 80$
bis(isopropyl)naphthalene	38640-62-9	Asp. Tox. 1; H304	$\geq 10 - < 30$
bisphenol-F-(epichlorhydrin) epoxy resin	28064-14-4	Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Skin Sens. 1; H317	$\geq 5 - < 10$
oxirane, mono[(C12-14-alkyloxy)methyl]derivatives	68609-97-2	Skin Irrit. 2; H315 Skin Sens. 1; H317	$\geq 1 - < 5$
Benzyl alcohol	100-51-6	Acute Tox. 4; H302	$\geq 1 - < 5$



Sikafloor®-293 Part A

Revision Date 02/16/2024

Print Date 10/12/2024

		Acute Tox. 4; H332 Eye Irrit. 2A; H319	
--	--	---	--

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not induce vomiting without medical advice.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
Risk of serious damage to the lungs (by aspiration).
irritant effects
sensitizing effects
Aspiration may cause pulmonary edema and pneumonitis.
Allergic reactions
Excessive lachrymation
Erythema
Dermatitis
- Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Collect contaminated fire extinguishing water separately. This



Sikafloor®-293 Part A

Revision Date 02/16/2024

Print Date 10/12/2024

must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.
for fire-fighters

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products.

Conditions for safe storage : Store in original container.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Store in accordance with local regulations.



Sikafloor®-293 Part A

Revision Date 02/16/2024

Print Date 10/12/2024

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.
Wash hands before breaks and immediately after handling the product.
Remove contaminated clothing and protective equipment before entering eating areas.
Wash thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : milky



Sikafloor®-293 Part A

Revision Date 02/16/2024

Print Date 10/12/2024

Odor	:	odorless
Odor Threshold	:	No data available
pH	:	No data available
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	> 125 °C (257 °F)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	0.01 hpa
Relative vapor density	:	No data available
Density	:	1.14 g/ml
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	22000 mm ² /s
Explosive properties	:	No data available
Oxidizing properties	:	No data available



Sikafloor®-293 Part A

Revision Date 02/16/2024

Print Date 10/12/2024

Volatile organic compounds : 24 g/l
(VOC) content A+B Combined

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reactions : Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

Hazardous decomposition products : No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Components:

bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700):

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

bis(isopropyl)naphthalene:

Acute oral toxicity : LD50 Oral (Rat): > 3,900 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.64 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rat): > 4,500 mg/kg

bisphenol-F-(epichlorhydrin) epoxy resin:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Benzyl alcohol:

Acute oral toxicity : LD50 Oral (Rat): 1,620 mg/kg



Sikafloor®-293 Part A

Revision Date 02/16/2024

Print Date 10/12/2024

Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

IARC Not applicable

OSHA Not applicable

NTP Not applicable

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

Not classified due to lack of data.

STOT-repeated exposure

Not classified due to lack of data.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Aspiration toxicity

May be fatal if swallowed and enters airways.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l
Exposure time: 96 h



Sikafloor®-293 Part A

Revision Date 02/16/2024

Print Date 10/12/2024

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.8 mg/l
Exposure time: 48 h

Benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
May be harmful to the environment if released in large quantities.
Water polluting material.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR



Sikafloor®-293 Part A

Revision Date 02/16/2024

Print Date 10/12/2024

UN/ID No. : UN 3082
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
(epoxy resin, bis(isopropyl)naphthalene)
Class : 9
Packing group : III
Labels : Miscellaneous
Packing instruction (cargo : 964
aircraft)
Packing instruction (passen- : 964
ger aircraft)

IMDG-Code

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(epoxy resin, bis(isopropyl)naphthalene)
Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(bisphenol-A-(epichlorhydrin) epoxy resin,
bis(isopropyl)naphthalene)
Class : 9
Packing group : III
Labels : 9
ERG Code : 171
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Canadian lists

The following substance(s) is/are subject to a Significant New Activity Notification:

Oxirane, (chloromethyl)- Epichlorohydrin 106-89-8
 α -chlorotoluene 100-44-7



Sikafloor®-293 Part A

Revision Date 02/16/2024

Print Date 10/12/2024

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ADR	:	Accord européen relatif au transport international des marchandises Dangereuses par Route
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.



Sikafloor®-293 Part A

Revision Date 02/16/2024

Print Date 10/12/2024

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

Revision Date : 02/16/2024
Date format : mm/dd/yyyy
Prepared by : R & D of Sika Canada Inc.
Material number : 822,132

CA / Z8