

SAFETY DATA SHEET

SikaThorolastic-750 coarse neu fact tbse Formerly MProtect EL 750 CS Ser N



Version 1.1 Revision Date: 02/08/2023 SDS Number: 000000261434 Date of last issue: 09/29/2020
Date of first issue: 09/29/2020

SECTION 1. IDENTIFICATION

Product name : SikaThorolastic-750 coarse neu fact tbse Formerly MProtect EL 750 CS Ser N

Product code : 000000000051718554

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE
Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)


Carcinogenicity (Inhalation) : Category 1A

Specific target organ toxicity - repeated exposure (Oral) : Category 2 (Kidney)

Short-term (acute) aquatic hazard : Category 3

Long-term (chronic) aquatic hazard : Category 3

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H350 May cause cancer by inhalation.
H373 May cause damage to organs (Kidney) through prolonged or repeated exposure if swallowed.
H402 Harmful to aquatic life.

SAFETY DATA SHEET

SikaThorolastic-750 coarse neu fact tbse Formerly MProtect EL 750 CS Ser N



Version 1.1 Revision Date: 02/08/2023 SDS Number: 00000261434 Date of last issue: 09/29/2020
Date of first issue: 09/29/2020

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements :

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P273 Avoid release to the environment.

P260 Do not breathe dusts or mists.

Response:

P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.

P314 Get medical advice/ attention if you feel unwell.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Aqueous solution

Components

Chemical name	CAS-No.	Concentration (% w/w)
Limestone	1317-65-3	>= 15 - < 50
Perlite, expanded	93763-70-3	>= 5 - < 7
ethylene glycol	107-21-1	>= 1 - < 3
zinc oxide	1314-13-2	>= 0.3 - < 1
Quartz (SiO ₂)	14808-60-7	>= 0 - < 1
Isooctylphenol ethoxylate	9036-19-5	>= 0.2 - < 1
diuron	330-54-1	>= 0 - < 0.1
3-iodo-2-propynyl butylcarbamate	55406-53-6	>= 0 - < 0.1

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

If inhaled : If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

In case of skin contact : After contact with skin, wash immediately with plenty of water and soap.

SAFETY DATA SHEET

SikaThorolastic-750 coarse neu fact tbse Formerly MProtect EL 750 CS Ser N



Version 1.1	Revision Date: 02/08/2023	SDS Number: 000000261434	Date of last issue: 09/29/2020 Date of first issue: 09/29/2020
----------------	------------------------------	-----------------------------	---

Under no circumstances should organic solvent be used.
If irritation develops, seek medical attention.

- In case of eye contact : Remove contact lenses, if present.
Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.
Do NOT induce vomiting.
- Most important symptoms and effects, both acute and delayed : May cause cancer by inhalation.
May cause damage to organs through prolonged or repeated exposure if swallowed.
- Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam
Water spray
Dry powder
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : water jet
- Specific hazards during fire fighting : See SDS section 10 - Stability and reactivity.
- Hazardous combustion products : harmful vapours
nitrogen oxides
fumes/smoke
carbon black
carbon oxides
- Further information : The degree of risk is governed by the burning substance and the fire conditions.
If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.
Contaminated extinguishing water must be disposed of in accordance with official regulations.
- Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Do not breathe vapour/aerosol/spray mists.
Wear eye/face protection.
If exposed to high vapour concentration, leave area immedi-

SAFETY DATA SHEET

SikaThorolastic-750 coarse neu fact tbse Formerly MProtect EL 750 CS Ser N



Version 1.1 Revision Date: 02/08/2023 SDS Number: 00000261434 Date of last issue: 09/29/2020
Date of first issue: 09/29/2020

ately.
Use personal protective clothing.
Handle in accordance with good building materials hygiene and safety practice.

- Environmental precautions : Contain contaminated water/firefighting water.
Do not discharge into drains/surface waters/groundwater.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Do not breathe vapors/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.
Protect from direct sunlight.
- Recommended storage temperature : > 39 °F / > 4 °C
- Further information on storage stability : PROTECT FROM FREEZING DURING THE COLD-SEASON (BELOW 40°F / 5°C).

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethylene glycol	107-21-1	TWA (Vapor)	25 ppm	ACGIH
		STEL (Vapor)	50 ppm	ACGIH
		STEL (Inhalable fraction, Aerosol only)	10 mg/m3	ACGIH
		C	50 ppm	OSHA P0

SAFETY DATA SHEET

SikaThorolastic-750 coarse neu fact tbse Formerly MProtect EL 750 CS Ser N



Version 1.1 Revision Date: 02/08/2023 SDS Number: 00000261434 Date of last issue: 09/29/2020
 Date of first issue: 09/29/2020

			125 mg/m3	
diuron	330-54-1	TWA	10 mg/m3	ACGIH
		TWA	10 mg/m3	NIOSH REL
		TWA	10 mg/m3	OSHA P0
zinc oxide	1314-13-2	TWA (Respirable particulate matter)	2 mg/m3	ACGIH
		STEL (Respirable particulate matter)	10 mg/m3	ACGIH
		TWA (Dust)	5 mg/m3	NIOSH REL
		TWA (Fumes)	5 mg/m3	NIOSH REL
		ST (Fumes)	10 mg/m3	NIOSH REL
		C (Dust)	15 mg/m3	NIOSH REL
		TWA (Fumes)	5 mg/m3	OSHA Z-1
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Fumes)	5 mg/m3	OSHA P0
		STEL (Fumes)	10 mg/m3	OSHA P0
Limestone	1317-65-3	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium carbonate)	NIOSH REL
Perlite, expanded	93763-70-3	TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (Total dust)	15 mg/m3	OSHA P0

SAFETY DATA SHEET

SikaThorolastic-750 coarse neu fact tbse Formerly MProtect EL 750 CS Ser N



Version 1.1 Revision Date: 02/08/2023 SDS Number: 000000261434 Date of last issue: 09/29/2020
 Date of first issue: 09/29/2020

		TWA (respirable dust fraction)	5 mg/m ³	OSHA P0
Quartz (SiO ₂)	14808-60-7	TWA (Respirable dust)	0.05 mg/m ³	OSHA Z-1
		TWA (respirable)	10 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
		TWA (respirable dust fraction)	0.1 mg/m ³	OSHA P0
		TWA (Respirable particulate matter)	0.025 mg/m ³ (Silica)	ACGIH
		TWA (Respirable dust)	0.05 mg/m ³ (Silica)	NIOSH REL

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits may be exceeded.
 Use NIOSH approved respiratory protection.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Wear safety glasses with side shields or goggles.

Skin and body protection : Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit.

Protective measures : Do not inhale gases/vapours/aerosols.
 Avoid contact with the skin, eyes and clothing.
 Avoid exposure - obtain special instructions before use.
 Handle in accordance with good building materials hygiene and safety practice.
 Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.
 Hands and/or face should be washed before breaks and at the end of the shift.
 At the end of the shift the skin should be cleaned and skin-care agents applied.
 Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.
 Gloves must be inspected regularly and prior to each use.

SAFETY DATA SHEET

SikaThorolastic-750 coarse neu fact tbse Formerly MProtect EL 750 CS Ser N



Version 1.1 Revision Date: 02/08/2023 SDS Number: 000000261434 Date of last issue: 09/29/2020
Date of first issue: 09/29/2020

Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : pigmented

Odor : sweetish, slight odour

Odor Threshold : No data available

pH : 9.2 - 10.0

Melting point : No data available

Boiling point : 378 - 401 °F / 192 - 205 °C

Flash point : 200 °F / 93 °C

Evaporation rate : No data available

Flammability (liquids) : not highly flammable
Method: derived from flash point

Upper explosion limit / Upper flammability limit : 15.3 %(V)

Lower explosion limit / Lower flammability limit : 3.2 %(V)

Vapor pressure : No data available

Relative vapor density : Heavier than air.

Relative density : 1.2 - 1.4

Density : approx. 1.00 g/cm³ (68 °F / 20 °C)

Bulk density : Not applicable

Solubility(ies)
Water solubility : soluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : not applicable for mixtures

SAFETY DATA SHEET

SikaThorolastic-750 coarse neu fact tbse Formerly MProtect EL 750 CS Ser N



Version 1.1 Revision Date: 02/08/2023 SDS Number: 00000261434 Date of last issue: 09/29/2020
Date of first issue: 09/29/2020

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : Based on its structural properties the product is not classified as oxidizing.

Sublimation point : No data available

Molecular weight : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability : The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions : The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids
Strong bases
Strong oxidizing agents
Strong reducing agents

Hazardous decomposition products : irritant gases/vapours
carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

SAFETY DATA SHEET

SikaThorolastic-750 coarse neu fact tbse Formerly MProtect EL 750 CS Ser N



Version 1.1 Revision Date: 02/08/2023 SDS Number: 000000261434 Date of last issue: 09/29/2020
Date of first issue: 09/29/2020

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer by inhalation.

IARC	Group 1: Carcinogenic to humans Quartz (SiO ₂) (Silica dust, crystalline)	14808-60-7
-------------	---	------------

NTP	Known to be human carcinogen Quartz (SiO ₂) (Silica, Crystalline (Respirable Size))	14808-60-7
------------	---	------------

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

May cause damage to organs (Kidney) through prolonged or repeated exposure if swallowed.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Health injuries are not known or expected under normal use. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

diuron:

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 10

SAFETY DATA SHEET

SikaThorolastic-750 coarse neu fact tbse Formerly MProtect EL 750 CS Ser N



Version 1.1 Revision Date: 02/08/2023 SDS Number: 000000261434 Date of last issue: 09/29/2020
Date of first issue: 09/29/2020

3-iodo-2-propynyl butylcarbamate:

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 1

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regulations.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

SAFETY DATA SHEET

SikaThorolastic-750 coarse neu fact tbse Formerly MProtect EL 750 CS Ser N



Version 1.1 Revision Date: 02/08/2023 SDS Number: 000000261434 Date of last issue: 09/29/2020
Date of first issue: 09/29/2020

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
carbendazim	10605-21-7	10	27777

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

ethylene glycol 107-21-1 $\geq 1 - < 5 \%$

US State Regulations

Pennsylvania Right To Know

Limestone	1317-65-3
ethylene glycol	107-21-1
zinc oxide	1314-13-2
diuron	330-54-1
ammonia	7664-41-7
ammonia, aqueous solution	1336-21-6

New Jersey Right To Know

Limestone	1317-65-3
Perlite, expanded	93763-70-3
ethylene glycol	107-21-1
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0
Quartz (SiO ₂)	14808-60-7

California Prop. 65

WARNING: This product can expose you to chemicals including Quartz (SiO₂), which is/are known to the State of California to cause cancer, and ethylene glycol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : This product contains one or more components not listed on the Canadian DSL or NDSL. All other components are on the Canadian DSL.

SAFETY DATA SHEET

SikaThorolastic-750 coarse neu fact tbse Formerly MProtect EL 750 CS Ser N




Version 1.1 Revision Date: 02/08/2023 SDS Number: 000000261434 Date of last issue: 09/29/2020
Date of first issue: 09/29/2020


SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIH / STEL : Short-term exposure limit
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
- NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
- NIOSH REL / C : Ceiling value not be exceeded at any time.
- OSHA P0 / TWA : 8-hour time weighted average
- OSHA P0 / STEL : Short-term exposure limit
- OSHA P0 / C : Ceiling limit
- OSHA Z-1 / TWA : 8-hour time weighted average
- OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration asso-

SAFETY DATA SHEET

SikaThorolastic-750 coarse neu fact tbse Formerly MProtect EL 750 CS Ser N



Version	Revision Date:	SDS Number:	Date of last issue: 09/29/2020
1.1	02/08/2023	00000261434	Date of first issue: 09/29/2020

ciated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 02/08/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN