

**SECTION 1. IDENTIFICATION**

Product name : SikaPower®-880 Part B

Other means of identification : No data available

Company name : www.sika.ca  
Canada  
Pointe-Claire, QC H9R 4A9  
601, avenue Delmar  
Sika Canada Inc.

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

E-mail address : ehs@ca.sika.com

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the Hazardous Products Regulations**

Skin corrosion : Category 1C

Serious eye damage : Category 1

Skin sensitization : Sub-category 1A

Carcinogenicity (Inhalation) : Category 1A

Reproductive toxicity : Category 2

**GHS label elements**

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H350 May cause cancer by inhalation.  
H361 Suspected of damaging fertility or the unborn child.



Precautionary Statements : **Prevention:**

P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P261 Avoid breathing mist or vapors.  
 P264 Wash skin thoroughly after handling.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
 P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.  
 P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.  
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
 P362 + P364 Take off contaminated clothing and wash it before reuse.

**Storage:**

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Additional Labeling**

There are no ingredients with unknown acute toxicity used in a mixture at a concentration  $\geq 1\%$ .

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Components**

| Chemical name  | CAS-No.    | Classification   | Concentration (% w/w) |
|--|------------|--|-----------------------|
| 2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1- | 68683-29-4 | Skin Irrit. 2; H315<br>Eye Irrit. 2A; H319<br>Skin Sens. 1; H317 | $\geq 10 - < 30$      |



|  |              |   |              |
|--|--------------|---|--------------|
| piperaziny]ethyl]amino]butyl-terminated                              |              |   |              |
| Carbomonocyclic alkylated mixtures of poly-aza-alcanes, hydrogenated | 1173092-74-4 | Acute Tox. 4; H302<br>Skin Corr. 1C; H314<br>Eye Dam. 1; H318<br>Skin Sens. 1; H317                                     | >= 10 - < 30 |
| Polyoxypropylene diamine   | 9046-10-0    | Skin Corr. 1C; H314<br>Eye Dam. 1; H318   | >= 5 - < 10  |
| 2,4,6-tris(dimethylaminomethyl)phenol                                | 90-72-2      | Skin Corr. 1C; H314<br>Eye Dam. 1; H318   | >= 1 - < 5   |
| Phenolformaldehyd resin  | 9003-35-4    | Eye Irrit. 2A; H319<br>Skin Sens. 1; H317   | >= 1 - < 5   |
| aluminium dihydrogen triphosphate                                    | 13939-25-8   | Eye Irrit. 2A; H319   | >= 1 - < 5   |
| 1,3-Propanediamine, N1,N1-diethyl-                                   | 104-78-9     | Flam. Liq. 3; H226<br>Acute Tox. 4; H302<br>Acute Tox. 3; H311<br>Skin Corr. 1B; H314<br>Skin Sens. 1; H317             | >= 1 - < 5   |
| 1,3-Benzenedimethanamine, N-(2-phenylethyl) derivs.                  | 404362-22-7  | Acute Tox. 4; H302<br>Skin Corr. 1B; H314<br>Skin Sens. 1A; H317<br>STOT RE 2; H373                                     | >= 0.1 - < 1 |
| 2-piperazin-1-ylethylamine   | 140-31-8     | Acute Tox. 3; H311<br>Skin Corr. 1B; H314<br>Eye Dam. 1; H318<br>Skin Sens. 1; H317<br>Repr. 2; H361<br>STOT RE 1; H372 | >= 0.1 - < 1 |
| m-phenylenebis(methylamine)  | 1477-55-0    | Acute Tox. 4; H302<br>Acute Tox. 4; H332<br>Skin Corr. 1B; H314<br>Skin Sens. 1; H317                                   | >= 0.1 - < 1 |
| Quartz (SiO <sub>2</sub> ) >5µm                                      | 14808-60-7   | Carc. 1A; H350i<br>STOT RE 1; H372<br>STOT SE 3; H335   | >= 0.1 - < 1 |
| triethylenetetramine   | 112-24-3     | Acute Tox. 4; H302<br>Acute Tox. 4; H312<br>Skin Corr. 1B; H314<br>Eye Dam. 1; H318<br>Skin Sens. 1; H317               | >= 0.1 - < 1 |

Actual concentration or concentration range is withheld as a trade secret

#### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.



Wash off with soap and plenty of water.  
 Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.

- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
 In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
 Continue rinsing eyes during transport to hospital.  
 Remove contact lenses.  
 Keep eye wide open while rinsing.
  
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
 Do not induce vomiting without medical advice.  
 Do not give milk or alcoholic beverages.  
 Never give anything by mouth to an unconscious person.  
 Take victim immediately to hospital.
  
- Most important symptoms and effects, both acute and delayed : Health injuries may be delayed.  
 corrosive effects  
 sensitizing effects  
 Allergic reactions  
 Dermatitis  
 May cause an allergic skin reaction.  
 Causes serious eye damage.  
 May cause cancer by inhalation.  
 Suspected of damaging fertility or the unborn child.  
 Causes severe burns.
  
- Notes to physician : Treat symptomatically.

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
  
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
 Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
  
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
 Deny access to unprotected persons.
  
- Environmental precautions : Do not flush into surface water or sanitary sewer system.



If the product contaminates rivers and lakes or drains inform respective authorities.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

**SECTION 7. HANDLING AND STORAGE**

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products.

Conditions for safe storage : Store in original container.  
Keep container tightly closed in a dry and well-ventilated place.  
Observe label precautions.  
Store in accordance with local regulations.

Materials to avoid : Explosives  
Oxidizing agents  
Poisonous gases  
Dangerous when wet  
Flammable solids  
Organic peroxides  
Poisonous liquids  
Spontaneously Combustible Substances

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Ingredients with workplace control parameters**

| Components                  | CAS-No.   | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis     |
|-----------------------------|-----------|-------------------------------|--|-----------|
| m-phenylenebis(methylamine) | 1477-55-0 | (c)                           | 0.1 mg/m3                                      | CA AB OEL |
|                             |           | C                             | 0.1 mg/m3                                      | CA BC OEL |
|                             |           | C                             | 0.1 mg/m3                                      | CA QC OEL |



|                      |            |                                     |                      |           |
|----------------------|------------|-------------------------------------|----------------------|-----------|
|                      |            | C                                   | 0.018 ppm            | ACGIH     |
| Quartz (SiO2) >5µm   | 14808-60-7 | TWA (Respirable particulates)       | 0.025 mg/m3          | CA AB OEL |
|                      |            | TWA (Respirable fraction)           | 0.1 mg/m3            | CA ON OEL |
|                      |            | TWAEV (respirable dust)             | 0.1 mg/m3            | CA QC OEL |
|                      |            | TWA (Respirable)                    | 0.025 mg/m3 (Silica) | CA BC OEL |
|                      |            | TWA (Respirable)                    | 0.025 mg/m3          | CA BC OEL |
|                      |            | TWA (Respirable)                    | 0.025 mg/m3 (Silica) | CA BC OEL |
|                      |            | TWA (Respirable particulate matter) | 0.025 mg/m3          | ACGIH     |
|                      |            | TWA (Respirable particulate matter) | 0.025 mg/m3 (Silica) | ACGIH     |
|                      |            | TWA (Respirable particulate matter) | 0.025 mg/m3          | ACGIH     |
|                      |            | TWA (Respirable particulate matter) | 0.025 mg/m3 (Silica) | ACGIH     |
| triethylenetetramine | 112-24-3   | TWA                                 | 0.5 ppm<br>3 mg/m3   | CA ON OEL |

**Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

**Personal protective equipment**

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.



|                          |   |   |
|--------------------------|---|---|
| Hand protection          | : | Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.   |
| Eye protection           | : | Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.   |
| Skin and body protection | : | Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.  |
| Hygiene measures         | : | Avoid contact with skin, eyes and clothing.<br>Wash hands before breaks and immediately after handling the product.<br>Remove contaminated clothing and protective equipment before entering eating areas.<br>Wash thoroughly after handling. |

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

|  |   |  |
|--|---|--|
| Appearance                                       | : | paste  |
| Color  | : | gray   |
| Odor   | : | amine-like   |
| Odor Threshold                                   | : | No data available  |
| pH   | : | Not applicable substance/mixture is non-soluble (in water) |
| Melting point/range / Freezing point             | : | No data available  |
| Boiling point/boiling range                      | : | No data available  |
| Flash point                                      | : | > 101 °C (214 °F)<br>(Method: closed cup)                  |
| Evaporation rate                                 | : | No data available  |
| Flammability (solid, gas)                        | : | No data available  |
| Upper explosion limit / Upper flammability limit | : | No data available  |
| Lower explosion limit / Lower flammability limit | : | No data available  |



|  |   |   |
|--|---|---|
| Vapor pressure                           | : | 0.0133322 hpa                               |
| Relative vapor density                   | : | No data available                           |
| Density                                  | : | ca. 1.26 g/cm <sup>3</sup> (20 °C (68 °F))  |
| Solubility(ies)                          |   |   |
| Water solubility                         | : | No data available                           |
| Solubility in other solvents             | : | No data available                           |
| Partition coefficient: n-octanol/water   | : | No data available                           |
| Autoignition temperature                 | : | No data available                           |
| Decomposition temperature                | : | No data available                           |
| Viscosity                                |   |   |
| Viscosity, dynamic                       | : | ca. 200,000 mPa.s (20 °C (68 °F))           |
| Viscosity, kinematic                     | : | > 20.5 mm <sup>2</sup> /s ( 40 °C (104 °F)) |
| Explosive properties                     | : | No data available                           |
| Oxidizing properties                     | : | No data available                           |
| Volatile organic compounds (VOC) content | : | 16 g/l<br>A+B Combined                      |

---

## SECTION 10. STABILITY AND REACTIVITY

|                                    |   |   |
|------------------------------------|---|---|
| Reactivity                         | : | No dangerous reaction known under conditions of normal use. |
| Chemical stability                 | : | The product is chemically stable.                           |
| Possibility of hazardous reactions | : | Stable under recommended storage conditions.                |
| Conditions to avoid                | : | No data available   |
| Incompatible materials             | : | No data available   |
| Hazardous decomposition products   | : | No decomposition if stored and applied as directed.         |

---

## SECTION 11. TOXICOLOGICAL INFORMATION

### Acute toxicity

Not classified based on available information.



**Components:****Carbomonocyclic alkylated mixtures of poly-aza-alcanes, hydrogenated:**

Acute oral toxicity : LD50 Oral (Rat): 500 mg/kg

**Polyoxypropylene diamine:**

Acute oral toxicity : LD50 Oral (Rat): 2,880 mg/kg

**2,4,6-tris(dimethylaminomethyl)phenol:**

Acute oral toxicity : LD50 Oral (Rat): 2,169 mg/kg

**1,3-Propanediamine, N1,N1-diethyl-:**

Acute oral toxicity : LD50 Oral (Rat): 1,410 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 524 mg/kg

**1,3-Benzenedimethanamine, N-(2-phenylethyl) derivs.:**

Acute oral toxicity : LD50 Oral (Rat): 1,000 mg/kg

**2-piperazin-1-ylethylamine:**

Acute oral toxicity : LD50 Oral (Rat): 2,097 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): ca. 866 mg/kg

**m-phenylenebis(methylamine):**

Acute oral toxicity : LD50 Oral (Rat): 930 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1.34 mg/l  
 Exposure time: 4 h  
 Test atmosphere: dust/mist  
 Assessment: Corrosive to the respiratory tract.

Acute dermal toxicity : LD50 Dermal (Rat): &gt; 3,100 mg/kg

**triethylenetetramine:**

Acute oral toxicity : LD50 Oral (Rat): 1,716 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 1,465 mg/kg

**Skin corrosion/irritation**

Causes severe burns.

**Components:****2,4,6-tris(dimethylaminomethyl)phenol:**

Species : Rabbit  
 Assessment : Corrosive  
 Method : OECD Test Guideline 404



**Serious eye damage/eye irritation**

Causes serious eye damage.

**Components:**

**2,4,6-tris(dimethylaminomethyl)phenol:**

Species : Rabbit  
 Assessment : Causes serious eye damage.

**Respiratory or skin sensitization**

**Skin sensitization**

May cause an allergic skin reaction.

**Respiratory sensitization**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

May cause cancer by inhalation.

|             |  |            |
|-------------|--|------------|
| <b>IARC</b> | Group 1: Carcinogenic to humans<br>Quartz (SiO <sub>2</sub> ) >5µm<br>(Silica dust, crystalline)           | 14808-60-7 |
| <b>OSHA</b> | OSHA specifically regulated carcinogen<br>Quartz (SiO <sub>2</sub> ) >5µm<br>(crystalline silica)          | 14808-60-7 |
| <b>NTP</b>  | Known to be human carcinogen<br>Quartz (SiO <sub>2</sub> ) >5µm<br>(Silica, Crystalline (Respirable Size)) | 14808-60-7 |

**Reproductive toxicity**

Suspected of damaging fertility or the unborn child.

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Aspiration toxicity**

Not classified based on available information.

**Further information**

**Product:**

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding,



cutting, or other surface preparation activities.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

##### **Carbomonocyclic alkylated mixtures of poly-aza-alkanes, hydrogenated:**

Toxicity to algae/aquatic plants : EC50 (Raphidocelis subcapitata (freshwater green alga)): 0.56 mg/l  
Method: OECD Test Guideline 201

EC50 (Raphidocelis subcapitata (freshwater green alga)): 2.7662 mg/l  
Method: OECD Test Guideline 201

NOEC (Raphidocelis subcapitata (freshwater green alga)): 0.26 mg/l  
Method: OECD Test Guideline 201

NOEC (Raphidocelis subcapitata (freshwater green alga)): 0.445 mg/l  
Method: OECD Test Guideline 201

##### **Polyoxypropylene diamine:**

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (algae)): 15 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC50 (Daphnia magna (Water flea)): 80 mg/l  
Exposure time: 48 h

##### **2,4,6-tris(dimethylaminomethyl)phenol:**

Toxicity to algae/aquatic plants : EC50 (Scenedesmus capricornutum (fresh water algae)): > 10 - 100 mg/l

##### **1,3-Benzenedimethanamine, N-(2-phenylethyl) derivs.:**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 4 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.14 mg/l  
Exposure time: 21 d

##### **2-piperazin-1-ylethylamine:**

Toxicity to fish : LC50 (Fish): > 100 mg/l  
Exposure time: 96 h



**m-phenylenebis(methylamine):**

Toxicity to fish : LC50 (*Oryzias latipes* (Japanese medaka)): > 10 - 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): > 10 - 100 mg/l  
Exposure time: 48 h

**triethylenetetramine:**

Toxicity to fish : LC50 (*Pimephales promelas* (fathead minnow)): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia*): 10 - 100 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (*Pseudokirchneriella subcapitata* (green algae)): 10 - 100 mg/l  
Exposure time: 72 h

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

**Product:**

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

**SECTION 14. TRANSPORT INFORMATION**

**International Regulations**

**IATA-DGR**

UN/ID No. : UN 1760  
Proper shipping name : Corrosive liquid, n.o.s.  
(Carbomonocyclic alkylated mixtures of poly-aza-alcanes,  
hydrogenated)  
Class : 8  
Packing group : II  
Labels : Corrosive  
Packing instruction (cargo : 855  
aircraft)  
Packing instruction (passen- : 851  
ger aircraft)

**IMDG-Code**

UN number : UN 1760  
Proper shipping name : CORROSIVE LIQUID, N.O.S.  
(Carbomonocyclic alkylated mixtures of poly-aza-alcanes,  
hydrogenated)  
Class : 8  
Packing group : II  
Labels : 8  
EmS Code : F-A, S-B  
Marine pollutant : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****TDG**

UN number : UN 1760  
Proper shipping name : CORROSIVE LIQUID, N.O.S.  
(Carbomonocyclic alkylated mixtures of poly-aza-alcanes,  
hydrogenated)  
Class : 8  
Packing group : II  
Labels : 8  
ERG Code : 154  
Marine pollutant : no

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

**SECTION 15. REGULATORY INFORMATION****Canadian lists**

No substances are subject to a Significant New Activity Notification.




---

**SECTION 16. OTHER INFORMATION**
**Full text of other abbreviations**

|                   |   |  |
|-------------------|---|--|
| ACGIH             | : | USA. ACGIH Threshold Limit Values (TLV)  |
| CA AB OEL         | : | Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)  |
| CA BC OEL         | : | Canada. British Columbia OEL   |
| CA ON OEL         | : | Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.   |
| CA QC OEL         | : | Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants  |
| ACGIH / TWA       | : | 8-hour, time-weighted average  |
| ACGIH / C         | : | Ceiling limit  |
| CA AB OEL / TWA   | : | 8-hour Occupational exposure limit   |
| CA AB OEL / (c)   | : | ceiling occupational exposure limit  |
| CA BC OEL / TWA   | : | 8-hour time weighted average   |
| CA BC OEL / C     | : | ceiling limit  |
| CA ON OEL / TWA   | : | Time-Weighted Average Limit (TWA)  |
| CA QC OEL / TWAEV | : | Time-weighted average exposure value   |
| CA QC OEL / C     | : | Ceiling  |
|                   |   |  |
| ADR               | : | Accord européen relatif au transport international des marchandises Dangereuses par Route  |
| CAS               | : | Chemical Abstracts Service   |
| DNEL              | : | Derived no-effect level  |
| EC50              | : | Half maximal effective concentration   |
| GHS               | : | Globally Harmonized System   |
| IATA              | : | International Air Transport Association  |
| IMDG              | : | International Maritime Code for Dangerous Goods  |
| LD50              | : | Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)  |
| LC50              | : | Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)   |
| MARPOL            | : | International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978  |
| OEL               | : | Occupational Exposure Limit  |
| PBT               | : | Persistent, bioaccumulative and toxic  |
| PNEC              | : | Predicted no effect concentration  |
| REACH             | : | Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency |
| SVHC              | : | Substances of Very High Concern  |
| vPvB              | : | Very persistent and very bioaccumulative   |

Notice to Reader:



The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sika.ca](http://www.sika.ca) or 514-697-2610.

Revision Date : 05/13/2022  
Date format : mm/dd/yyyy  
  
Prepared by : R & D of Sika Canada Inc.  
  
Material number : 659,651

CA / Z8