



PRODUCT DATA SHEET
Edition 06.2018 (08.2009)

Sika® Remover-208

CLEANING AGENT FOR SURFACE PREPARATION AND REMOVAL OF UNCURED ADHESIVES AND SEALANTS

| | | |
|-----------------------|---|---|
| Technical Data | Chemical Base | Organic solvent |
| | Colour | Colourless, clear |
| | Density (CQP ¹ 006-3/ISO 2811-1) | 0.8 kg/l approx |
| | Flash Point (CQP 007-1/ISO 13736) | 24 °C (75 °F) |
| | Application Temperature | 5 °C to 40 °C (40 °F to 105 °F) |
| | Application | Wipe-on, wipe-off with lint-free clean paper towel |
| | Storage | Store in sealed container in a cool dry place below 25 °C |
| | Shelf Life | 24 months |

¹ CQP = Corporate Quality Procedures;

| | |
|-----------------------------|--|
| Description | Sika® Remover-208 is used to re-move traces of Sikaflex® products as well as for cleaning painted substrates. Sika® Remover-208 is manufactured in accordance with ISO 9001/14001, quality assurance system. |
| Aeras of Application | Sika® Remover-208 can be used to remove uncured excess Sikaflex® adhesive or sealant from application tools or soiled surfaces. Sika® Remover-208 can also be used for pre-cleaning strongly contaminated non-porous sub-strates. Sika® Remover-208 can be used to clean painted surfaces prior to bonding. This product is suitable for experienced professional users only. Tests with actual substrates and conditions must be performed to ensure adhesion and material compatibility. |

METHOD OF APPLICATION

| | |
|------------------------------------|--|
| Removal of Uncured Adhesive | Remove the bulk of the Sikaflex® residue with a knife or spatula. Moisten a rag or towel with Sika® Remover®-208 and wipe off the remaining adhesive or sealant. |
| Surface Cleaning | Wipe painted surfaces with a moistened rag or towel with Sika® Remover®-208. Wet the paper towel with solvent by pouring the liquid onto the cloth. Never dip the paper towel into the cleaner as it may contaminate it. Wipe the surface with the wetted paper towel. Use fresh paper towels regularly in order to retain the cleansing power. Before the solvent dries on the surface (evaporates), wipe it off with a different clean, dry paper towel. Repeat the last two steps until no contaminants show up on a white paper towel. Do not use on sensitive surfaces such as fresh paints. Tightly reseal container immediately after each use. |

| | |
|----------------------------|---|
| Further Information | Working instructions issued for a defined application may further specify technical data contained in this Product Data Sheet. Copies of the following publications are available upon request: <ul style="list-style-type: none"> ▪ <i>Safety Data Sheet</i> ▪ <i>Sika Pre-treatment Chart</i> |
|----------------------------|---|

| | |
|--------------------|---|
| Packaging | Can of 250 ml, 1 L and 5 L. |
| Value Bases | All technical data stated in this Product Data Sheet are laboratory test-based. Current measured values may vary due to factors beyond our influence. |

| | |
|--------------------------------------|---|
| Health and Safety Information | For information and advice on the safe handling, storage and disposal of chemical products, users should refer to the most recent SAFETY DATA SHEET containing physical, ecological, toxicological and other safety-related data. |
|--------------------------------------|---|

KEEP OUT OF REACH OF CHILDREN
FOR INDUSTRIAL USE ONLY

The Information, and in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions, within their shelflife. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any recommendations, or from any other advice offered. The information contained herein does not relieve the user of the products from testing them for the intended application and purpose. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or may be downloaded from our website at: www.sika.ca

SIKA CANADA INC.
Head Office
601, avenue Delmar
Pointe-Claire, Quebec
H9R 4A9

Other locations
Toronto
Edmonton
Vancouver

1-800-933-SIKA
www.sika.ca

An ISO 9001 certified company
Pointe-Claire: ISO 14001 certified EMS