



## SECTION I: PRODUCT INFORMATION

PRODUCT: **Sikadur® 31 SBA Slow Set (21-32°C) PART A** REVISION DATE: February 1<sup>st</sup>, 2015  
(70-90F)

USAGE: HIGH-MODULUS, HIGH-STRENGTH, STRUCTURAL, EPOXY PASTE ADHESIVE

MANUFACTURER/SUPPLIER: SIKA CANADA INC.  
601, avenue Delmar  
Pointe Claire, QC  
H9R 4A9

**EMERGENCY TELEPHONE NUMBER: CANUTEC (collect) (613) 996-6666**

TDG CLASSIFICATION: Not Regulated WHMIS Classification: D2A  
UN NUMBER: Not Established Class: Not Applicable  
Packaging Group: Not Applicable

## SECTION II: HAZARDOUS INGREDIENTS

Hazardous ingredients	%	T.L.V.	# CAS	LD <sub>50</sub> (mg/kg) (Species, route)	LC <sub>50</sub> (Species, route)
EPOXY RESIN	30-60	Not Available	25085-99-8	> 5000 (rat, oral)	Not Available
SILICA SAND	30-60	ACGIH 0.025 mg/m <sup>3</sup>	14808-60-7	Not Available	Not Available
TITANIUM DIOXIDE	0.1-1.0	10 mg/ m <sup>3</sup>	13463-67-7	Not Available	Not Available

## SECTION III: PHYSICAL CHARACTERISTICS

Physical State: Paste  
Appearance and Odor: Grey paste with mild aromatic odor  
Odor Threshold: Not Established  
Evaporation Rate: Slower than ether  
Vapor Density: > Air  
Vapor Pressure: Not Established

Boiling Point: Not Established  
Freezing Point: Not Established  
Density: ± 1.4 g/ml  
Water Solubility: Very low  
pH: Not Established  
% volatility: Not Established  
Water/Oil Distribution: Not Established



PRODUCT: Sikadur® 31 SBA Slow Set (21-32°C) PART A

SECTION IV: FIRE AND EXPLOSION HAZARDS

Flammability: If Yes, under what conditions:	No	TDG Flammability Class:	Not Regulated
Extinguishing methods:	Foam, dry chemical products, CO <sub>2</sub> , water hose.	Flammable upper limits (% vol.):	Not Applicable
Special Methods:	Fire fighters must wear usual protective clothing and respiratory equipment. A water hose may be used to cool the containers and dissipate the vapors.	Flammable lower limits (% vol.):	Not Applicable
		Flash Point (method used):	> 104.4°C
		Auto-ignition temperature:	Not Established
		Dangerous Combustion Products:	Carbon oxides, aldehydes and other organics
		Protect from mechanical impact:	No
		Protect from static discharge:	No

SECTION V: REACTIVITY

Chemical stability: If not, under what conditions:	Yes But excessive heat will degrade the resin.	Dangerous decomposition products:	Carbon oxides, aldehydes and other organics.
Incompatibility with other material: If Yes, which ones:	Yes Strong acid, base, and oxidizer.	Polymerization Risks:	May polymerize at very high temperatures.



PRODUCT: Sikadur® 31 SBA Slow Set (21-32°C) PART A

SECTION VI: TOXIC PROPERTIES

ROUTE OF ENTRY / CONTACT

Eyes: May cause eye irritations.

Skin: May be irritating to the skin, may cause sensitization.

Inhalation: May irritate lungs, may cause an allergic reaction.

Ingestion: May cause irritation to the gastrointestinal system

Carcinogenicity: According to the IARC, the quartz silica and the Titanium dioxide are probable cause of cancer.

Toxic effects on reproduction: Not Established

Teratogenicity: Not Established

Mutagenicity: Not Established

Product with synergistic effects: Not Known

An acute or chronic exposure will increase the toxic effects mentioned in this section and may aggravate respiratory problems.



PRODUCT: Sikadur® 31 SBA Slow Set (21-32°C) PART A

SECTION VII: PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT

Gloves: Chemical resistant gloves.

Respiratory equipment: Not needed with sufficient ventilation.

Eyes: Safety glasses

Shoes: Ordinary

Clothing: Rubber Apron

Other: No

OTHERS

Ventilation: Sufficient ventilation required.

Procedure in case of leaks: Absorb with sand or other absorbent material. Residue may be removed with steam or hot water and soap. All precautions should be taken when cleaning the spill with solvent.

Handling and Equipment methods: Avoid skin, eye and clothing contact

Warehouse Requirements: Keep all containers closed in a cool, dry area. Keep away from heat and open flame.

Special Shipping Instructions: See TDG class

Waste Disposal: Dispose of sand and rinse water according to municipal, provincial or federal laws for disposal of chemicals.



PRODUCT: Sikadur® 31 SBA Slow Set (21-32°C) PART A

## SECTION VIII: FIRST AID

Skin: Remove and clean all contaminated clothing.  
Wash immediately with plenty of soap and water.  
Consult a physician if required.

Eyes: Rinse with water for at least 15 minutes.  
Consult a physician immediately.

Inhalation: In the case of overexposure, evacuate to fresh air.  
Consult a physician if required.

Ingestion: Drink plenty of water. Do not induce vomiting.  
Do not give anything by mouth to an unconscious person.  
See a physician immediately.

## SECTION IX: PREPARATION INFORMATION

Prepared By: R & D of Sika Canada Inc.  
Telephone #: (514) 697-2610  
Fax #: (514) 694-2792

**Notice To Reader**

*The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section IX of this MSDS.*

**SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

*All sales of Sika products are subject to its current terms and conditions of sale available at [www.sika.ca](http://www.sika.ca) or 514-697-2610.*



## SECTION I: PRODUCT INFORMATION

PRODUCT: **Sikadur® 31 SBA Slow Set (21-32°C) PART B** REVISION DATE: January 21, 2015  
(70-90F)

USAGE: HIGH-MODULUS, HIGH-STRENGTH, STRUCTURAL, EPOXY PASTE ADHESIVE

MANUFACTURER/SUPPLIER: SIKA CANADA INC.  
601, avenue Delmar  
Pointe Claire, QC  
H9R 4A9

**EMERGENCY TELEPHONE NUMBER: CANUTEC (collect) (613) 996-6666**

TDG CLASSIFICATION: CORROSIVE SOLID, BASIC, ORGANIC, N.O.S. (POLYOXYPROPYLENEDIAMINE & 4,4'-METHYLENEBIS(CYCLOHEXYLAMINE))

WHMIS Classification: D2A, E

UN NUMBER: 3263

Class: 8

Packaging Group: III (Not regulated for road transport : Limited quantity)

## SECTION II: HAZARDOUS INGREDIENTS

Hazardous ingredients	%	T.L.V.	# CAS	LD <sub>50</sub> (mg/kg) (species, route)	LC <sub>50</sub> (species, route)
AMINE BLEND	15-40	Not available	Blend	Not available	Not available
SILICA SAND	40-70	ACGIH 0.025 mg/m <sup>3</sup>	14808-60-7	Not available	Not available

## SECTION III: PHYSICAL CHARACTERISTICS

Physical State: Paste  
Appearance and Odor: Dark Grey paste with amine odor  
Odor Threshold: Not Established  
Evaporation Rate: Slower than ether  
Vapor Density: > Air  
Vapor Pressure: Not Established

Boiling Point: Not Established  
Freezing Point: Not Established  
Density: ± 1.9 g/ml  
Water Solubility: Partial  
pH: Not Established  
% Volatility: Not Established  
Water/Oil Distribution: Not Established



PRODUCT: Sikadur® 31 SBA Slow Set (21-32°C) PART B

SECTION IV: FIRE AND EXPLOSION HAZARDS

Flammability: If Yes, under what conditions:	No	TDG Flammability Class:	Not Regulated
Extinguishing methods:	Foam, dry chemical products, CO <sub>2</sub> , water hose.	Flammable upper limits (% vol.):	Not Established
Special Methods:	Fire fighters must wear usual protective clothing and respiratory equipment. A water hose may be used to cool the containers and dissipate the vapors.	Flammable lower limits (% vol.):	Not Established
		Flash Point (method used):	> 104.4°C (TCC)
		Auto-ignition temperature:	Not Established
		Dangerous Combustion Products:	Carbon oxides, and nitrogen oxides.
		Protect from mechanical impact:	No
		Protect from static discharge:	No

SECTION V: REACTIVITY

Chemical stability: If not, under what conditions:	Yes	Dangerous decomposition products:	Carbon and nitrogen oxides.
Incompatibility with other material: If Yes, which ones:	Yes Acids, strong oxidizer and epoxy resins under uncontrolled conditions.	Polymerization Risks:	No



PRODUCT: Sikadur® 31 SBA Slow Set (21-32°C) PART B

SECTION VI: TOXIC PROPERTIES

ROUTE OF ENTRY / CONTACT

Eyes: May cause eye irritations. May cause severe burns.

Skin: May be irritating to the skin, may cause severe burns. May cause dermatitis, allergic reactions, and sensitization.

Inhalation: Vapors or mist of this product may cause irritation.

Ingestion: May cause severe burns to the mouth, throat, stomach. May cause nausea, vomiting, dizziness, diarrhea, damages to the lungs, and troubles to the gastro-intestinal system.

Carcinogenicity: According to the IARC, the quartz silica is a probable cause of cancer.

Toxic effects on reproduction: Not Established

Teratogenicity: Not Established

Mutagenicity: Not Established

Product with synergistic effects: Not Known

An over-exposure may cause breathing difficulty, headaches, nausea, vomiting, and damages to the lungs, sensitization, ulcers and dizziness.

May cause problems to the skin, eyes and lungs. May aggravate respiratory and allergic problems.

An acute or chronic exposure will increase the toxic effects mentioned in this section and may aggravate respiratory problems.





PRODUCT: Sikadur® 31 SBA Slow Set (21-32°C) PART B

SECTION VII: PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT

Gloves: Chemical resistant gloves.

Respiratory equipment: Not needed with sufficient ventilation.

Eyes: Full face mask or safety glasses

Shoes: Leather

Clothing: Rubber Apron

Other: Eye wash station, shower

OTHERS

Ventilation: Sufficient ventilation required.

Procedure in case of leaks: Absorb with sand or other absorbent material.

Handling and Equipment methods: Avoid skin, eye and clothing contact

Warehouse Requirements: Keep all containers closed in a cool, dry and well ventilated area. Keep away from heat and open flame.

Special Shipping Instructions: See TDG class

Waste Disposal: Dispose of sand and rinse water according to municipal, provincial or federal laws for disposal of chemicals.



PRODUCT: Sikadur® 31 SBA Slow Set (21-32°C) PART B

SECTION VIII: FIRST AID

**Skin:** Remove contaminated clothing and shoes.  
Wash immediately with plenty of soap and water.  
Throw away shoes that were soiled on the inside.  
Wash clothing before re-wearing.  
Consult a physician if required.

**Eyes:** Rinse eyes immediately with plenty of water for several minutes, while holding eyelids wide open, to ensure a proper wash.  
The eye rinse within the first minute is essential to ensure maximum protection.  
Consult a physician immediately.

**Inhalation:** In the case of overexposure, evacuate to fresh air.  
Consult a physician if required.

**Ingestion:** Drink plenty of water. Do not induce vomiting.  
Do not give anything by mouth to an unconscious person.  
See a physician immediately.

SECTION IX: PREPARATION INFORMATION

Prepared By: R & D of Sika Canada Inc.  
Telephone #: (514) 697-2610  
Fax #: (514) 694-2792

**Notice To Reader**

*The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section IX of this MSDS.*

**SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

*All sales of Sika products are subject to its current terms and conditions of sale available at [www.sika.ca](http://www.sika.ca) or 514-697-2610.*