



## Sikacrete®-751 3D CA Premix

Revision Date 05/21/2025

Print Date 05/21/2025

### SECTION 1. IDENTIFICATION

Product name : Sikacrete®-751 3D CA Premix

Other means of identification : No data available

Company name : www.sika.ca  
Canada  
Pointe-Claire, QC H9R 4A9  
601, avenue Delmar  
Sika Canada Inc.

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

E-mail address : ehs@ca.sika.com

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the Hazardous Products Regulations

Serious eye damage : Category 1

Carcinogenicity (Inhalation) : Category 1A

Specific target organ toxicity - repeated exposure : Category 1 (Lungs)

#### GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H318 Causes serious eye damage.  
H350 May cause cancer by inhalation.  
H372 Causes damage to organs (Lungs) through prolonged or repeated exposure.



## Sikacrete®-751 3D CA Premix

Revision Date 05/21/2025

Print Date 05/21/2025

### Precautionary Statements

:

#### Prevention:

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P260 Do not breathe dust.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

#### Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.

#### Storage:

P405 Store locked up.

#### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration  $\geq 1\%$ .

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
calcium oxide	1305-78-8	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335	$\geq 5 - < 10$
Quartz (SiO <sub>2</sub> ) $>5\mu\text{m}$	14808-60-7	Carc. 1A; H350 STOT RE 1; H372 STOT SE 3; H335	$\geq 1 - < 5$

Actual concentration or concentration range is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

### General advice

:

Move out of dangerous area.  
Consult a physician.



## Sikacrete®-751 3D CA Premix

Revision Date 05/21/2025

Print Date 05/21/2025

	Show this material safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	: Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	: Small amounts splashed into eyes can cause irreversible tissue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing.
If swallowed	: Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting without medical advice. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
Most important symptoms and effects, both acute and delayed	: Causes serious eye damage. May cause cancer by inhalation. Causes damage to organs through prolonged or repeated exposure. No known significant effects or hazards. Excessive lachrymation
Notes to physician	: Treat symptomatically.

---

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for fire-fighters	: In the event of fire, wear self-contained breathing apparatus.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency measures	: Use personal protective equipment. Avoid breathing dust.
---	---



## Sikacrete®-751 3D CA Premix

Revision Date 05/21/2025

Print Date 05/21/2025

gency procedures	Deny access to unprotected persons.
Environmental precautions	: Try to prevent the material from entering drains or water courses. If the product contaminates rivers and lakes or drains inform respective authorities. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	: Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.

### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	: Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.
Advice on safe handling	: Avoid formation of respirable particles. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products.
Conditions for safe storage	: Store in original container. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Store in accordance with local regulations.
Further information on storage stability	: Keep in a dry place. No decomposition if stored and applied as directed.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Limestone	1317-65-3	TWA	10 mg/m <sup>3</sup>	CA AB OEL
		TWAEV (total dust)	10 mg/m <sup>3</sup>	CA QC OEL
calcium oxide	1305-78-8	TWA	2 mg/m <sup>3</sup>	CA AB OEL
		TWA	2 mg/m <sup>3</sup>	CA BC OEL



## Sikacrete®-751 3D CA Premix

Revision Date 05/21/2025

Print Date 05/21/2025

		TWAEV	2 mg/m3	CA QC OEL
		TWA	2 mg/m3	ACGIH
magnesium oxide	1309-48-4	TWA (Fumes)	10 mg/m3	CA AB OEL
		TWA (Inhalable fume)	10 mg/m3 (Magnesium)	CA BC OEL
		TWA (Respirable dust and fume)	3 mg/m3 (Magnesium)	CA BC OEL
		STEL (Respirable dust and fume)	10 mg/m3 (Magnesium)	CA BC OEL
		TWAEV (inhalable dust)	10 mg/m3	CA QC OEL
Quartz (SiO <sub>2</sub> ) >5µm	14808-60-7	TWA (Respirable particulates)	0.025 mg/m3	CA AB OEL
		TWA (Respirable fraction)	0.1 mg/m3	CA ON OEL
		TWA (Respirable)	0.025 mg/m3 (Silica)	CA BC OEL
		TWAEV (respirable dust)	0.05 mg/m3	CA QC OEL
		TWA (Respirable)	0.025 mg/m3	CA BC OEL
		TWA (Respirable)	0.025 mg/m3 (Silica)	CA BC OEL
		TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH

**Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use pro-



## Sikacrete®-751 3D CA Premix

Revision Date 05/21/2025

Print Date 05/21/2025

cess enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

### Personal protective equipment

- Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
- The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Avoid contact with skin, eyes and clothing.  
Wash hands before breaks and immediately after handling the product.  
Remove contaminated clothing and protective equipment before entering eating areas.  
Wash thoroughly after handling.  
Avoid breathing dust.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : powder
- Color : white
- Odor : Not applicable
- Odor Threshold : No data available
- pH : No data available



## Sikacrete®-751 3D CA Premix

Revision Date 05/21/2025

Print Date 05/21/2025

Melting point/ range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: > 100 °C (212 °F)
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapor pressure	: No data available
Relative vapor density	: No data available
Density	: No data available
Bulk density	: 10,535 kg/l
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Volatile organic compounds (VOC) content	: Not applicable



## Sikacrete®-751 3D CA Premix

Revision Date 05/21/2025

Print Date 05/21/2025

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Stable under recommended storage conditions.
Conditions to avoid	: No data available
Incompatible materials	: No data available
Hazardous decomposition products	: No decomposition if stored and applied as directed.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified due to lack of data.

#### Skin corrosion/irritation

Not classified due to lack of data.

#### Serious eye damage/eye irritation

Causes serious eye damage.

#### Respiratory or skin sensitization

##### Skin sensitization

Not classified due to lack of data.

##### Respiratory sensitization

Not classified due to lack of data.

##### Germ cell mutagenicity

Not classified due to lack of data.

##### Carcinogenicity

May cause cancer by inhalation.

##### Reproductive toxicity

Not classified due to lack of data.

##### STOT-single exposure

Not classified due to lack of data.

##### STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure.  
Prolonged exposure can cause silicosis.





## Sikacrete®-751 3D CA Premix

Revision Date 05/21/2025

Print Date 05/21/2025

### Aspiration toxicity

Not classified due to lack of data.

### Further information

#### Product:

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

No data available

### Persistence and degradability

No data available

### Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### IATA-DGR

Not regulated as a dangerous good



## Sikacrete®-751 3D CA Premix

Revision Date 05/21/2025

Print Date 05/21/2025

### IMDG-Code

Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

### TDG

Not regulated as a dangerous good

### Special precautions for user

Not applicable

---

## SECTION 15. REGULATORY INFORMATION

### Canadian lists

The following substance(s) is/are subject to a Significant New Activity Notification:  
propylene oxide 75-56-9

---

## SECTION 16. OTHER INFORMATION

### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEV	:	Time-weighted average exposure value
ADR	:	Accord européen relatif au transport international des marchandises Dangereuses par Route
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System



## Sikacrete®-751 3D CA Premix

Revision Date 05/21/2025

Print Date 05/21/2025

IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

### Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sika.ca](http://www.sika.ca) or 514-697-2610.

Revision Date	:	05/21/2025
Date format	:	mm/dd/yyyy
Prepared by	:	R & D of Sika Canada Inc.
Material number	:	860,341



## **Sikacrete®-751 3D CA Premix**

Revision Date 05/21/2025

Print Date 05/21/2025

---

CA / Z8