



SAKRETE PRE-MIXED CONCRETE PATCH

SAKRETE Pre-Mixed Concrete Patch can be used directly from the container. Use this product to smooth unsightly surface defects, minor cracks and holes. SAKRETE Pre-Mixed Concrete Patch adheres tightly to the sides of properly-prepared cracks and joints, to help keep out moisture, thus reducing pavement break-up caused by freeze-thaw action. Use this product for filling and sealing cracks* or surfaces**, in concrete. This product may also be used for residential repairs of masonry walls and re-application of small broken pieces of concrete, or for tuck-pointing brick mortar joints.

FEATURES & BENEFITS

- Ready-to-use; no mixing or dilution required
- Fills and seals cracks up to 1" (2.5 cm) wide
- Extends the life of concrete areas
- Maintains bond and elasticity through extreme weather conditions
- Easy to apply
- 20 to 40 minute skim time

USES

- Vertical and horizontal patches
- Interior and exterior uses
- Concrete or masonry surfaces
- Repairs to rough surfaces and holes

READ ALL DIRECTIONS BEFORE STARTING WORK. ATTENTION: WEAR RUBBER GLOVES, SAFETY GLASSES AND PROTECTIVE CLOTHING!

PROCEDURES

Read all directions before starting work. For best results, apply in dry, warm weather. Do not apply when rain is forecasted, or when the ambient air temperature is expected to fall below 10 °C (50 °F), within 48 hours.

Surface Preparation: Clean all dirt, dust and loose materials from cracks or rough surfaces with a stiff broom or stream of water. Allow to dry prior to application of SAKRETE Pre-Mixed Concrete Patch.

Mixing: No mixing is required. Gently stir product before use. Do not dilute with water or solvents.

Placement: To fill cracks in the area to be smoothed, apply SAKRETE Pre-Mixed Concrete Patch with a cement trowel or putty knife by pressing material into crevices to improve the bond. Smooth finish the patch with a damp application tool. **For rough textured areas, trowel over surface up to a thickness of 1/8" (3 mm). Thicker applications will require longer curing and may be damaged if rain occurs before the surface cures. For deeper applications, up to a thickness of 1/4" (6 mm), apply in layers of 1/8" (3 mm) and allow 24 hours

of curing time between layers. *Do not apply in cracks over 1" (2.5 cm) wide or on surfaces over 1/8" (3 mm) thick.

CURING

This product will form a skin in 20 to 40 minutes and will harden within 4 to 6 hours. If painting is desired, allow SAKRETE Pre-Mixed Concrete Patch to cure for a minimum of 48 hours (when temperatures are between 18 °C to 24 °C/65 °F to 75 °F, with no rain) before painting. Use a high-quality, exterior, masonry grade, breathable acrylic latex paint. Curing time will vary with thickness of the application. The surface will usually cure in 48 hours, but weather and thickness may slow the drying process. Curing to the full depth of the crack may take 5 to 7 days. Keep traffic off the repair area during the curing period. If this cannot be done, sprinkle sand over the repair area to prevent tracking.

CLEAN UP

Clean hands with warm, soapy water, while product is still wet. Dried SAKRETE Pre-Mixed Concrete Patch is insoluble in water. Clean tools and spills before the product dries. Hardened product remaining on tools may be removed with mineral spirits.

YIELD

0.95 L (32 oz) will cover approximately 3 ft² (0.28 m²) at a thickness of 1/8" (3 mm).

PACKAGING

0.95 L (32 oz) tub 764661050452

UPC

STORAGE & SHELF LIFE

Store in tightly sealed, original, factory containers, off the floor and in a dry place. Unopened bottles have a shelf life of 12 months.

KEEP FROM FREEZING. WARNING: INJURIOUS TO EYES. KEEP OUT OF REACH OF CHILDREN.

SAFETY PROCEDURES

WARNING! CAUSES IRRITATION: Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Exposure may result in irritation of the skin. **FIRST AID:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get prompt medical attention; for skin, washing thoroughly with plenty of soap and water. If irritation persists, get medical attention. **KEEP OUT OF REACH OF CHILDREN.** Read and understand the Safety Data Sheet (SDS) before using this product.

WEBSITE

For more information and other projects, visit us at www.sakretecanada.com or call us at 866-725-7383.



.....
SAKRETE PRE-MIXED CONCRETE PATCH
.....

Warranty: This product is designed to meet the performance specifications outlined in this product data sheet. If the product is used in conditions for which it was not intended, or applied in a manner contrary to the written recommendations contained in the product data sheet, the product may not reach such performance specifications. The foregoing is in lieu of any other warranties, representations or conditions, expressed or implied, including, but not limited to, implied warranties or conditions of merchantable quality or fitness for particular purposes, and those arising by statute or otherwise in law or from a course of dealing or usage of trade. [REV.0003_07/18/19]

KING PACKAGED MATERIALS COMPANY
.....

Oakville Office
555 Michigan Dr.,
Oakville, ON
L6L 0G4

Montreal Office
3825 rue Alfred-Laliberté,
Boisbriand, QC
J7H 1P7

Brantford Office
541 Oak Park Rd.,
Brantford, ON
N3T 5L8

Sudbury Office
644 Simmons Rd.,
Dowling, ON
P0M 1R0