

MATERIAL SAFETY DATA SHEET

SECTION I: PRODUCT INFORMATION

		SECTION I. TRODA			
PRODUCT:	Sikaflex [®] 2c B	ooster	RE	EVISION DATE: Feb	uary 1 st , 2015
USAGE:	URETHANE A	CCELERATOR			
MANUFACTUF	RER/SUPPLIER:	SIKA CANADA INO 601, avenue Delma Pointe Claire, QC H9R 4A9			
EMERGENCY	TELEPHONE N	UMBER: CANUTE	C (collect) (613) 996	-6666	
TDG CLASSIF UN NUMBER: Packaging Gro		Not Regulated Not Established Not Applicable	WHMI Class:	S Classification: D2 No	B t Applicable
	S	ECTION II: HAZAR	DOUS INGREDIENT	S	
Hazardous ingredients	%	T.L.V.	# CAS	LD ₅₀ (species, route)	LC ₅₀ (species, route)
BISMUTH TRIS- NEODECANOATE	30-60	Not Available	34364-26-6	Not Available	Not Available
NEODECANOIC ACID	10-30	Not Available	26896-20-8	Not Available	Not Available
ZINC NEODECANOATE	10-30	Not Available	27253-29-8	Not Available	Not Available
	SE	CTION III: PHYSICA	L CHARACTERIST	ICS	
Physical State: Appearance and Odor: Odor Threshold: Evaporation Rate: Vapor Density: Vapor Tension:	Liquid Amber liquid wi Not Established Not Established Not Established 14 mm Hg (140		Boiling Point: Freezing Point: Density: Water Solubility: pH: % volatile: Water/Oil Distributi	>149°C Not Established 1.1 Negligible Not Established Not Established on: Not Established	



x [®] 2c Booster		
SECTION IV: FIRE AND	EXPLOSION HAZARDS	
No Foam, dry chemical products, CO ₂ , water for	TDG Flammability Class: Flammable upper limits (% vol.): Flammable lower limits (% vol.): Flash Point (method used): Auto-ignition temperature: Dangerous Combustion Products:	Not Regulated Not Established Not Established > 100°C Not Established Carbon oxides, Nitrogen oxides.
large names.	Protect from mechanical impact:	No
Firefighters must wear complete protective clothing with respiratory equipment and they must protect any exposed skin.	Protect from static discharge:	No
SECTION V: RE		
Yes	Dangerous decomposition products:	Carbon oxides, Nitrogen oxides.
al [.] Yes	Polymerization Risks:	No
Acid, strong oxidizer, amine		
	No Foam, dry chemical products, CO ₂ , water for large flames. Firefighters must wear complete protective clothing with respiratory equipment and they must protect any exposed skin. SECTION V: RE Yes al: Yes Acid, strong	SECTION IV: FIRE AND EXPLOSION HAZARDS No TDG Flammability Class: Flammable upper limits (% vol.): Flammable lower limits (% vol.): Flash Point (method used): Auto-ignition temperature: Dangerous Combustion Products: Foam, dry chemical products, CO ₂ , water for large flames. Protect from mechanical impact: Firefighters must wear complete protective clothing with respiratory equipment and they must protect any exposed skin. Protect from static discharge: SECTION V: REACTIVITY DATA Yes Jangerous decomposition products: Pangerous decomposition products: Yes Polymerization Risks: Acid, strong Polymerization Risks:



	DUCT: Sikaflex [®] 2c Booster		
	SECTION VI: TO		
ROUTE OF E	ENTRY / CONTACT		
Eyes:	Irritating	Carcinogenicity:	Not established
Skin	Irritating. Contact may result in dermatitis,	Toxic effects on reproduction:	Not established
Inhalation:	Vapor or mist from this product may cause irritation.	Teratogenicity:	Not established
Ingestion:	May cause nausea, vomiting, diarrhea, G.I. system disorder, constipation,	Mutagenicity:	Not established
d	damages to kidneys	Product with synergistic effects:	Not established
headaches, n skin, eye, lun applied accor	re may cause breathing difficulties, hausea, vomiting. May aggravate respiratory, g problems and allergies. If the product is rding to the manufacturer, none of these hould be encountered.		

An acute or chronic exposure will increase the toxic effects mentioned in this section and may aggravate respiratory problems.



PRODUCT:	Sikaflex [®] 2c Booster		
	SECTION VII: PREV	ENTIVE MEASURES	
PERSONAL PROTECT	IVE EQUIPMENT	OTHERS	
Gloves:	Use chemical resistant gloves. (ex: Neoprene)	Ventilation:	Sufficient ventilation required
Respiratory equipment:	If T.L.V. is exceeded, wear appropriate NIOSH approved respirator. (Self-contained breathing apparatus).	Procedure in case of leaks: Handling and Equipmer	Absorb with sand or other absorbent material. nt
Eyes:	Full-face mask or safety glasses	methods:	Avoid skin, eye and clothing contact
Shoes: Clothing:	Leather Rubber Apron	Warehouse Requirements:	Keep all containers closed in a cool, dry and well ventilated area.
Other:	Eye wash station, shower	Special Shipping Instructions:	See TDG class
		Waste Disposal:	Dispose of sand and rinse water according to municipal, provincial or federal laws for disposal of chemicals.



App: S.G.

PRODUCT:	Sikaflex [®] 2c Booster
	SECTION VIII: FIRST AID
Skin:	Remove contaminated clothing and shoes. Wash immediately with plenty of water. Wash clothing before re-wearing. Consult a physician if required.
Eyes:	Rinse eyes immediately with plenty of water for several minutes, while holding eyelids wide open, to ensure a proper wash. See a physician immediately.
Inhalation:	In the case of overexposure, evacuate to fresh air. Consult a physician if required.
Ingestion:	Drink plenty of water. Do not induce vomiting. Do not give anything by mouth to an unconscious person. See a physician immediately.
	SECTION IX: PREPARATION INFORMATION
Prepared By: Telephone #: Fax #:	
otice To Reader	
formation is not intended oduct or process. All of s of the date hereof. Prio	in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This to address, nor does it address the use or application of the identified Sika product in combination with any other material the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable r to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's t, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone of this MSDS.
te information contained formation is not intended oduct or process. All of of the date hereof. Prio rrent Product Data Shee mber listed in Section IX KA MAKES NO WARRA KA SHALL NOT BE LIA	to address, nor does it address the use or application of the identified Sika product in combination with any other materia. the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable r to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's t, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone of this MSDS. ANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. BLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL