

# **ECTRLV1** Part A

Revision Date 08/02/2023 Print Date 10/12/2024

#### **SECTION 1. IDENTIFICATION**

Product name : ECTRLV1 Part A

Other means of identification : No data available

Company name : www.sika.ca

Canada

Pointe-Claire, QC H9R 4A9

601, avenue Delmar Sika Canada Inc.

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

E-mail address : ehs@ca.sika.com

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

Recommended use of the

chemical and restrictions on

use

For further information, refer to product data sheet.

### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with the Hazardous Products Regulations

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitization : Category 1

**GHS** label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

Precautionary Statements : Prevention:

P261 Avoid breathing mist or vapors.



# **ECTRLV1** Part A

Revision Date 08/02/2023 Print Date 10/12/2024

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/ eye protection/ face protection.

## Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention

P362 + P364 Take off contaminated clothing and wash it before reuse.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

## **Additional Labeling**

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

#### Other hazards

None known.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

## Components

Chemical name	CAS-No.	Classification	Concentra-
			tion (% w/w)
bisphenol-A-(epichlorhydrin) epoxy	25068-38-6	Skin Irrit. 2; H315	>= 60 - < 80
resin		Eye Irrit. 2A; H319	
		Skin Sens. 1; H317	
bisphenol-F-(epichlorhydrin) epoxy	28064-14-4	Skin Irrit. 2; H315	>= 10 - < 30
resin		Eye Irrit. 2A; H319	
		Skin Sens. 1; H317	
oxirane, mono[(C12-14-	68609-97-2	Skin Irrit. 2; H315	>= 5 - < 10
alkyloxy)methyl]derivatives		Skin Sens. 1; H317	
Benzyl alcohol	100-51-6	Acute Tox. 4; H302	>= 1 - < 5
		Acute Tox. 4; H332	
		Eye Irrit. 2A; H319	

Actual concentration or concentration range is withheld as a trade secret

### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in attend-



# ECTRLV1 Part A

Revision Date 08/02/2023 Print Date 10/12/2024

ance.

If inhaled Move to fresh air.

Consult a physician after significant exposure.

Take off contaminated clothing and shoes immediately. In case of skin contact

> Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Clean mouth with water and drink afterwards plenty of water.

Do not induce vomiting without medical advice.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

irritant effects sensitizing effects Allergic reactions

**Excessive lachrymation** 

Erythema **Dermatitis** 

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

Notes to physician Treat symptomatically.

## **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

for fire-fighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec- :

tive equipment and emergency procedures

Use personal protective equipment.

Deny access to unprotected persons.



# **ECTRLV1** Part A

Revision Date 08/02/2023 Print Date 10/12/2024

Environmental precautions : Do not flush into surface water or sanitary sewer system.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Store in accordance with local regulations.

### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures : Use of adequate ventilation should be sufficient to control

worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommend-

ed or statutory limits.

### Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed

respirator complying with an approved standard if a risk as-

sessment indicates this is necessary.



# **ECTRLV1** Part A

Revision Date 08/02/2023 Print Date 10/12/2024

The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling

the product.

Remove contaminated clothing and protective equipment

before entering eating areas. Wash thoroughly after handling.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Color : light yellow

Odor : mild

Odor Threshold : No data available

pH : 8.2

No data available

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range : No data available

Flash point :  $> 93 \, ^{\circ}\text{C} \, (> 199 \, ^{\circ}\text{F})$ 

(Method: closed cup)

Evaporation rate : No data available

according to the Hazardous Products Regulations



# **ECTRLV1** Part A

Revision Date 08/02/2023 Print Date 10/12/2024

Flammability (solid, gas) : No data available

Upper explosion limit / Upper :

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapor pressure : 0.01 hpa

Relative vapor density : No data available

Density : ca. 1.13 g/ml (23.7 °C (74.7 °F))

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 1060 mm2/s ( 23.7 °C (74.7 °F))

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds

(VOC) content

: 14 g/l

A+B Combined

### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

Stable under recommended storage conditions.

Conditions to avoid : No data available

according to the Hazardous Products Regulations



# **ECTRLV1** Part A

Revision Date 08/02/2023 Print Date 10/12/2024

Incompatible materials : No data available

Hazardous decomposition

products

No decomposition if stored and applied as directed.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

### **Acute toxicity**

Not classified due to lack of data.

## **Components:**

# bisphenol-A-(epichlorhydrin) epoxy resin:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

### bisphenol-F-(epichlorhydrin) epoxy resin:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Benzyl alcohol:

Acute oral toxicity : LD50 Oral (Rat): 1,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

### Skin corrosion/irritation

Causes skin irritation.

## Serious eye damage/eye irritation

Causes serious eye irritation.

### Respiratory or skin sensitization

## Skin sensitization

May cause an allergic skin reaction.

### Respiratory sensitization

Not classified due to lack of data.

#### Germ cell mutagenicity

Not classified due to lack of data.

## Carcinogenicity

Not classified due to lack of data. **IARC** Not applicable

**OSHA** Not applicable

according to the Hazardous Products Regulations



## ECTRLV1 Part A

Print Date 10/12/2024 Revision Date 08/02/2023

**NTP** Not applicable

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

Not classified due to lack of data.

STOT-repeated exposure

Not classified due to lack of data.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Aspiration toxicity** 

Not classified due to lack of data.

#### **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

### **Components:**

bisphenol-A-(epichlorhydrin) epoxy resin:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.8 mg/l

Exposure time: 48 h

Benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

**Product:** 

Additional ecological infor-

mation

Do not empty into drains; dispose of this material and its con-

tainer in a safe way.

Avoid dispersal of spilled material and runoff and contact with

according to the Hazardous Products Regulations



## ECTRLV1 Part A

Revision Date 08/02/2023 Print Date 10/12/2024

soil, waterways, drains and sewers.

Toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

May be harmful to the environment if released in large quanti-

ties.

Water polluting material.

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

### **SECTION 14. TRANSPORT INFORMATION**

### **International Regulations**

**IATA-DGR** 

UN/ID No. : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

(epoxy resin)

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo

aircraft)

Packing instruction (passen-

964

964

ger aircraft)

**IMDG-Code** 

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(epoxy resin)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## **Domestic regulation**



# **ECTRLV1** Part A

Revision Date 08/02/2023 Print Date 10/12/2024

**TDG** 

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(bisphenol-A-(epichlorhydrin) epoxy resin)

Class : 9
Packing group : III
Labels : 9
ERG Code : 171
Marine pollutant : no

Remarks : Above applies only to containers over 119 gallons or 450 li-

ters. Not regulated if shipped in packages less than or equal

to 119 gallons (450 liters).

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### **SECTION 15. REGULATORY INFORMATION**

### **Canadian lists**

The following substance(s) is/are subject to a Significant New Activity Notification:

Oxirane, (chloromethyl)- Epichlorohydrin 106-89-8  $\alpha$ -chlorotoluene 100-44-7

#### **SECTION 16. OTHER INFORMATION**

### Full text of other abbreviations

ADR : Accord européen relatif au transport international des

marchandises Dangereuses par Route

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

according to the Hazardous Products Regulations



# **ECTRLV1** Part A

Revision Date 08/02/2023 Print Date 10/12/2024

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

### Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

Revision Date : 08/02/2023 Date format : mm/dd/yyyy

Prepared by : R & D of Sika Canada Inc.

Material number : 714,784

**CA / Z8**