

NOTES:

- POST AND BASE PLATE MUST BE CLEAN AND FREE OF CONTAMINATION OR LOOSE PARTICLES
- POST ASSEMBLY MUST BE PRIMED WITH THE APPROPRIATE PRIMER BEFORE APPLYING SIKALASTIC MEMBRANE
- GAPS IN THE BASE PLATE MUST BE FILLED IN PRIOR TO SIKALASTIC MEMBRANE APPLICATION
 PAINTERS TAPE OR METAL FOIL TAPE SHALL BE USED AT THE TOP OF THE POST FLASHING DURING SIKALASTIC MEMBRANE APPLICATION TO ENSURE A UNIFORM FINISH AND WILL BE REMOVED IMMEDIATELY AFTER MEMBRANE APPLICATION
- SEALANT IS NOT COVERED UNDER THE ROOFPRO WARRANTY



DETAIL NAME:

SURFACE MOUNTED POST

CONSTRUIRE LA CONFIANCE

BUILDING TRUST

SCALE: N.T.S. 06/22 LAM CAN 5-6

RODUCTS AND SERVICES ARE SUBJECT TO SIKA'S TERMS AND CONDITIONS OF SALE AVAILABLE AT <u>WWW.CAN.SIKA.COM</u>.