

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-40 BC Pronto Formerly MTop SRS 40TC

Version 2.0 Revision Date: 05/17/2024 SDS Number: 000000260445 Date of last issue: 01/12/2022
Date of first issue: 10/29/2020

SECTION 1. IDENTIFICATION

Product name : Sikafloor-40 BC Pronto Formerly MTop SRS 40TC

Product code : 000000000056430042

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE
Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Floor coating

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 2

Skin irritation : Category 2



Skin sensitization : Category 1B

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

Short-term (acute) aquatic hazard : Category 2

Long-term (chronic) aquatic hazard : Category 3

GHS label elements

Hazard pictograms :  

Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-40 BC Pronto Formerly MTop SRS 40TC

| | | | |
|----------------|------------------------------|-----------------------------|-------------------------------------------------------------------|
| Version 2.0 | Revision Date: 05/17/2024 | SDS Number: 000000260445 | Date of last issue: 01/12/2022 Date of first issue: 10/29/2020 |
|----------------|------------------------------|-----------------------------|-------------------------------------------------------------------|

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H401 Toxic to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

Prevention:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.
No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : methacrylates

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-40 BC Pronto Formerly MTop SRS 40TC

Version 2.0 Revision Date: 05/17/2024 SDS Number: 000000260445 Date of last issue: 01/12/2022
Date of first issue: 10/29/2020

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|------------------------------------------|----------|-----------------------|
| methyl methacrylate | 80-62-6 | >= 30 - < 60 |
| 2-ethylhexyl acrylate | 103-11-7 | >= 30 - < 60 |
| 2,2'-Ethylenedioxydiethyl dimethacrylate | 109-16-0 | >= 1 - < 5 |

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : First aid personnel should pay attention to their own safety.
Remove contaminated clothing.
- If inhaled : Remove the affected individual into fresh air and keep the person calm.
If breathing difficulties develop, aid in breathing and seek immediate medical attention.
- In case of skin contact : Wash thoroughly with soap and water
Under no circumstances should organic solvent be used.
If irritation develops, seek medical attention.
- In case of eye contact : Contact lenses should be removed. Hold eyelids open and flush with copious amounts of clean, fresh water or a special eyewash solution and seek medical advice.
- If swallowed : Rinse mouth and then drink 200-300 ml of water.
Do not induce vomiting due to aspiration hazard.
Do not induce vomiting unless told to by a poison control center or doctor.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
May cause an allergic skin reaction.
May cause respiratory irritation.
- Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Dry powder
Foam
Carbon dioxide (CO₂)
Water spray
Alcohol-resistant foam
- Unsuitable extinguishing media : water jet
- Hazardous combustion products : harmful vapours
nitrogen oxides
fumes/smoke

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-40 BC Pronto Formerly MTop SRS 40TC

| | | | |
|----------------|------------------------------|-----------------------------|-------------------------------------------------------------------|
| Version 2.0 | Revision Date: 05/17/2024 | SDS Number: 000000260445 | Date of last issue: 01/12/2022 Date of first issue: 10/29/2020 |
|----------------|------------------------------|-----------------------------|-------------------------------------------------------------------|

- carbon black
carbon oxides
- Further information : Containers may rocket or explode in heat of fire.
Keep containers cool by spraying with water if exposed to fire.
Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Run-off water from fire may cause pollution.
Contaminated extinguishing water must be disposed of in accordance with official regulations.
- Special protective equipment for fire-fighters : Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Can release flammable vapours.
Wind direction should be noted.
Avoid all sources of ignition: heat, sparks, open flame.
Use antistatic tools.
Breathing protection required.
Use personal protective clothing.
Avoid contact with the skin, eyes and clothing.
- Environmental precautions : Prevent spread over a wide area (e.g. by containment or oil barriers).
Contain contaminated water/firefighting water.
Do not discharge into drains/surface waters/groundwater.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).
Use only explosion-proof equipment.
Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.
- Advice on safe handling : Keep away from sources of ignition - No smoking.
Take precautionary measures against static discharges.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-40 BC Pronto Formerly MTop SRS 40TC

Version 2.0 Revision Date: 05/17/2024 SDS Number: 000000260445 Date of last issue: 01/12/2022
Date of first issue: 10/29/2020

Provide good room ventilation even at ground level (vapours are heavier than air).
Avoid formation of aerosol.
Do not breathe mist or vapors.
Avoid contact with skin and eyes.

Conditions for safe storage : Keep containers tightly closed in a cool, well-ventilated place.
Keep away from heat.
Keep away from sources of ignition - No smoking.

Materials to avoid : Segregate from foods and animal feeds.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|---------------------|---------|----------------------------------|------------------------------------------------|-----------|
| methyl methacrylate | 80-62-6 | TWA | 50 ppm | ACGIH |
| | | STEL | 100 ppm | ACGIH |
| | | TWA | 100 ppm 410 mg/m ³ | NIOSH REL |
| | | TWA | 100 ppm 410 mg/m ³ | OSHA Z-1 |
| | | TWA | 100 ppm 410 mg/m ³ | OSHA P0 |

Engineering measures : Provide local exhaust ventilation to maintain recommended P.E.L.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits may be exceeded.
Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Wear safety glasses with side shields or goggles.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Do not inhale gases/vapours/aerosols.
Avoid contact with the skin, eyes and clothing.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-40 BC Pronto Formerly MTop SRS 40TC

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 01/12/2022 |
| 2.0 | 05/17/2024 | 000000260445 | Date of first issue: 10/29/2020 |

Avoid prolonged and/or repeated contact with the skin.
Handle in accordance with good building materials hygiene and safety practice.
Wearing of closed work clothing is recommended.

Hygiene measures : Food, beverages, and tobacco products shall not be carried, stored, or consumed where this material is in use.
Hands and/or face should be washed before breaks and at the end of the shift.
Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--------------------------------------------------|--------------------------------------|
| Appearance | : liquid |
| Color | : amber, cloudy |
| Odor | : sweet, ester-like |
| Odor Threshold | : not determined |
| pH | : No data available |
| Melting point/freezing point | : -54 °F / -48 °C |
| Boiling point/boiling range | : 212 °F / 100 °C |
| Flash point | : 48 °F / 9 °C |
| Evaporation rate | : > 1 (Butyl Acetate=1.0) |
| Flammability (liquids) | : Highly flammable liquid and vapor. |
| Upper explosion limit / Upper flammability limit | : No data available |
| Lower explosion limit / Lower flammability limit | : No data available |
| Vapor pressure | : 27.8 mmHg (68 °F / 20 °C) |
| Relative vapor density | : 3.1 (Air = 1.0) |

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-40 BC Pronto Formerly MTop SRS 40TC

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 01/12/2022 |
| 2.0 | 05/17/2024 | 000000260445 | Date of first issue: 10/29/2020 |

| | | |
|----------------------------------------|---|----------------------------------------------------------|
| Relative density | : | 0.97 |
| Density | : | 0.97 g/ml (77 °F / 25 °C) 8.10 lb/gal (77 °F / 25 °C) |
| Bulk density | : | Not applicable |
| Solubility(ies) | : | |
| Water solubility | : | No data available |
| Solubility in other solvents | : | No data available |
| Partition coefficient: n-octanol/water | : | not applicable for mixtures |
| Autoignition temperature | : | 806 °F / 430 °C |
| Decomposition temperature | : | No data available |
| Viscosity | : | |
| Viscosity, dynamic | : | 200 cps (77 °F / 25 °C) |
| Viscosity, kinematic | : | No data available |
| Explosive properties | : | Not explosive |
| Oxidizing properties | : | Not an oxidizer. |
| Sublimation point | : | No data available |
| Molecular weight | : | Not applicable |

SECTION 10. STABILITY AND REACTIVITY

| | | |
|------------------------------------|---|------------------------------------------------------------------------------------------------------------|
| Reactivity | : | No hazardous reactions if stored and handled as prescribed/indicated. |
| Chemical stability | : | The product is stable if stored and handled as prescribed/indicated. |
| Possibility of hazardous reactions | : | No hazardous reactions if stored and handled as prescribed/indicated. |
| Conditions to avoid | : | Avoid all sources of ignition: heat, sparks, open flame. Avoid electro-static discharge. Avoid heat. |
| Incompatible materials | : | Strong bases |

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-40 BC Pronto Formerly MTop SRS 40TC

| | | | |
|----------------|------------------------------|-----------------------------|-------------------------------------------------------------------|
| Version 2.0 | Revision Date: 05/17/2024 | SDS Number: 000000260445 | Date of last issue: 01/12/2022 Date of first issue: 10/29/2020 |
|----------------|------------------------------|-----------------------------|-------------------------------------------------------------------|

Acids
Oxidizing agents

Hazardous decomposition products : carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC Group 2B: Possibly carcinogenic to humans
2-ethylhexyl acrylate

103-11-7

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

Remarks : Solvents may degrease the skin.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-40 BC Pronto Formerly MTop SRS 40TC

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 01/12/2022 |
| 2.0 | 05/17/2024 | 000000260445 | Date of first issue: 10/29/2020 |

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regulations.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Do not discharge into drains/surface waters/groundwater.
Residues should be disposed of in the same manner as the substance/product.

Contaminated packaging : Uncleaned empty vessels may contain product gases which can form explosive mixtures with air. Avoid all sources of ignition.
Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-40 BC Pronto Formerly MTop SRS 40TC

Version 2.0 Revision Date: 05/17/2024 SDS Number: 000000260445 Date of last issue: 01/12/2022
Date of first issue: 10/29/2020

UNRTDG

UN number : UN 1866
Proper shipping name : RESIN SOLUTION
Class : 3
Packing group : II
Labels : 3
Environmentally hazardous : no

IATA-DGR

UN/ID No. : UN 1866
Proper shipping name : Resin solution
Class : 3
Packing group : II
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353

IMDG-Code

UN number : UN 1866
Proper shipping name : RESIN SOLUTION
Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 1866
Proper shipping name : Resin solution

Class : 3
Packing group : II
Labels : FLAMMABLE LIQUID
ERG Code : 127
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

| Components | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|---------------------|---------|--------------------|-----------------------------|
| methyl methacrylate | 80-62-6 | 1000 | 2222 |

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-40 BC Pronto Formerly MTop SRS 40TC

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 01/12/2022 |
| 2.0 | 05/17/2024 | 000000260445 | Date of first issue: 10/29/2020 |

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

| | | |
|---------------------|---------|----------------|
| methyl methacrylate | 80-62-6 | >= 30 - < 50 % |
|---------------------|---------|----------------|

US State Regulations

Pennsylvania Right To Know

| | |
|-----------------------|----------|
| methyl methacrylate | 80-62-6 |
| 2-ethylhexyl acrylate | 103-11-7 |

New Jersey Right To Know

| | |
|-----------------------|----------|
| methyl methacrylate | 80-62-6 |
| 2-ethylhexyl acrylate | 103-11-7 |

California Prop. 65

WARNING: This product can expose you to chemicals including 2-ethylhexyl acrylate, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-40 BC Pronto Formerly MTop SRS 40TC


Version
2.0

Revision Date:
05/17/2024

SDS Number:
000000260445

Date of last issue: 01/12/2022
Date of first issue: 10/29/2020

NFPA 704:



HMIS® IV:

| | | |
|-----------------|--|--|
| HEALTH | | |
| FLAMMABILITY | | |
| PHYSICAL HAZARD | | |

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

| | | |
|-----------------|---|-------------------------------------------------------------------------------------------|
| ACGIH | : | USA. ACGIH Threshold Limit Values (TLV) |
| NIOSH REL | : | USA. NIOSH Recommended Exposure Limits |
| OSHA P0 | : | USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values) |
| OSHA Z-1 | : | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| ACGIH / TWA | : | 8-hour, time-weighted average |
| ACGIH / STEL | : | Short-term exposure limit |
| NIOSH REL / TWA | : | Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek |
| OSHA P0 / TWA | : | 8-hour time weighted average |
| OSHA Z-1 / TWA | : | 8-hour time weighted average |

AiIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Admin-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikafloor-40 BC Pronto Formerly MTop SRS 40TC

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 01/12/2022 |
| 2.0 | 05/17/2024 | 000000260445 | Date of first issue: 10/29/2020 |

istration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 05/17/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN