

KING CONSTRUCTION SAND

KING Construction Sand passes a 5 mm (3/16 inch) screen.

USES

For general uses including landscaping, soil conditioning and displays, as well as winter traction on roads, icy sidewalks or greasy areas. It may also be used with cement and sand to make custom concrete mixes.

YIELD

30KG (66lb) yields approximately:

Not Compacted	0.0212 m³ (60 cm x 30 cm x 11.25 cm)	
	0.75 ft³ (24" x 12" x 4.5")	
Compacted	0.0187 m³ (60 cm x 30 cm x 10 cm)	
	0.66 ft ³ (24" x 12" x 4.0")	

PACKAGING UPC

30 KG (66 lb) bag 055226141662

STORAGE & SHELF LIFE

Material should be stored in a dry covered area protected from the elements.

SAFETY PROCEDURES

Do not swallow. Do not get in eyes.

FIRST AID TREATMENT: If in eyes, rinse with water.

WEBSITE

For more information and other projects, visit us at www.sakretecanada.com or call us at 866-725-7383.



• • • • • •	• • • • • •	• • • • • • •	• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • • • • • • • •	• • •
KING (CONST	RUCTIO	N SAND			

Warranty: This product is designed to meet the performance specifications outlined in this product data sheet. If the product is used in conditions for which it was not intended, or applied in a manner contrary to the written recommendations contained in the product data sheet, the product may not reach such performance specifications. The foregoing is in lieu of any other warranties, representations or conditions, expressed or implied, including, but not limited to, implied warranties or conditions of merchantable quality or fitness for particular purposes, and those arising by statute or otherwise in law or from a course of dealing or usage of trade. [REV.0001_07/23/20]