



APPLICABLE BETWEEN  
-9 °C and 10 °C

# Sikaflex<sup>®</sup> -2c NS Arctic

## TWO-PART POLYURETHANE SEALANT FOR EXTREME COLD

- No pre-heating required before use
- Get projects done in extreme cold conditions
- Easy to mix, gun, and tool down to -9 °C
- Material will not stiffen after mixing
- Packaging available in 5.6 L (1.5 US gal.) units

BUILDING TRUST  
CONSTRUIRE LA CONFIANCE



# Sikaflex<sup>®</sup>-2c NS Arctic

## TWO-PART POLYURETHANE SEALANT FOR EXTREME COLD

### WHERE TO USE

- Intended for use in all properly designed working joints with a minimum depth of 6 mm
- Ideal for vertical and horizontal applications
- Adheres to most substrates commonly found in construction
- Mixable and placeable at temperatures as low as -9 °C
- Submerged environments, such as canal and reservoir joints
- Compatible with Exterior Insulation Finish Systems (EIFS)

### FEATURES AND BENEFITS

- Easy to mix, even at below freezing temperatures
- Chemical cure allows the sealant to be placed in greater depths for non-moving joints/cracks
- High elasticity with a tough, durable, flexible consistency
- Exceptional adhesion to most substrates without priming
- Exceptional cut and tear resistance
- Available in 35 standard architectural colours
- Colour uniformity via Color-pak system
- Paintable with water, oil, and rubber-based paints



\*Always refer to Current Product Data Sheet (PDS) for detailed performance specifications and Safety Data Sheet (SDS) prior to use.

*Our most current General Sales Conditions shall apply.  
Please consult the most current local Product Data Sheet prior to any use.*

#### SIKA CANADA INC.

**Head Office**  
601, avenue Delmar  
Pointe-Claire, Quebec  
H9R 4A9

**Other locations**  
Boisbriand (QC)  
Brantford; Cambridge; Sudbury; Toronto (ON)  
Edmonton (AB); Surrey (BC)

1-800-933-7452  
[www.sika.ca](http://www.sika.ca)

© Sika Canada Inc. / 12.2021

**BUILDING TRUST  
CONSTRUIRE LA CONFIANCE**

