

# SAFETY DATA SHEET

## Sikaflex-900 quick silver 263 Formerly MSeal 900 Qk Sil 263



Version 1.0      Revision Date: 08/10/2020      SDS Number: 000000597647      Date of last issue: -  
Date of first issue: 08/10/2020

---

### SECTION 1. IDENTIFICATION

Product name : Sikaflex-900 quick silver 263 Formerly MSeal 900 Qk Sil 263  
Product code : 000000000057612472

#### Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC  
Address : 201 POLITO AVE  
Lyndhurst NJ 07071  
Emergency telephone : ChemTel: +1-813-248-0585

#### Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals  
Restrictions on use : Reserved for industrial and professional use.

---

### SECTION 2. HAZARDS IDENTIFICATION

**GHS classification in accordance with 29 CFR 1910.1200**  
No need for classification according to GHS criteria for this product.

#### GHS label elements

The product does not require a hazard warning label in accordance with GHS criteria.

#### Other hazards

No data available.

---

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
Titanium dioxide	13463-67-7	$\geq 25 - < 50$
carbon black	1333-86-4	$\geq 1 - < 3$
aluminium hydroxide	21645-51-2	$\geq 1 - < 3$
Iron oxide	1309-37-1	$\geq 1 - < 3$

---

### SECTION 4. FIRST AID MEASURES

General advice : Do not leave the victim unattended.  
If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.

---

# SAFETY DATA SHEET

## Sikaflex-900 quick silver 263 Formerly MSeal 900 Qk Sil 263



Version 1.0      Revision Date: 08/10/2020      SDS Number: 000000597647      Date of last issue: -  
Date of first issue: 08/10/2020

---

- In case of skin contact : After contact with skin, wash immediately with plenty of water and soap.  
Under no circumstances should organic solvent be used.  
If irritation develops, seek medical attention.
- In case of eye contact : Remove contact lenses.  
Protect unharmed eye.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : None known.
- Notes to physician : Treat symptomatically.
- 

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Foam  
Dry powder  
Carbon dioxide (CO<sub>2</sub>)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : See SDS section 10 - Stability and reactivity.
- Hazardous combustion products : harmful vapours  
nitrogen oxides  
fumes/smoke  
carbon black  
carbon oxides
- Further information : Standard procedure for chemical fires.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
- 

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Do not breathe vapour/aerosol/spray mists.  
Wear eye/face protection.  
If exposed to high vapour concentration, leave area immediately.
-

# SAFETY DATA SHEET

## Sikaflex-900 quick silver 263 Formerly MSeal 900 Qk Sil 263



Version 1.0      Revision Date: 08/10/2020      SDS Number: 000000597647      Date of last issue: -  
Date of first issue: 08/10/2020

Use personal protective clothing.  
Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions : Contain contaminated water/firefighting water.  
Do not discharge into drains/surface waters/groundwater.

Methods and materials for containment and cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).  
Keep in suitable, closed containers for disposal.

### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.

Conditions for safe storage : Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.  
Protect from direct sunlight.

Materials to avoid : No applicable information available.  
No materials to be especially mentioned.

Further information on storage stability : No data available

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Iron oxide	1309-37-1	TWA value (Respirable fraction)	5 mg/m <sup>3</sup>	ACGIHTLV
		REL value (Dust and fume)	5 mg/m <sup>3</sup> (iron (Fe))	NIOSH
		PEL (fumes/smoke)	10 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1)
		TWA value (fumes/smoke)	10 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)

# SAFETY DATA SHEET

## Sikaflex-900 quick silver 263 Formerly MSeal 900 Qk Sil 263



Version 1.0      Revision Date: 08/10/2020      SDS Number: 000000597647      Date of last issue: -  
Date of first issue: 08/10/2020

		TWA (Respirable particulate matter)	5 mg/m3	ACGIH
		TWA (dust and fume)	5 mg/m3 (Iron)	NIOSH REL
		TWA (Fumes)	10 mg/m3	OSHA Z-1
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Fumes)	10 mg/m3	OSHA P0
carbon black	1333-86-4	TWA value (Inhalable fraction)	3 mg/m3	ACGIHTLV
		PEL	3.5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	3.5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		REL value	0.1 mg/m3 (Polycyclic aromatic hydrocarbons (PAH))	NIOSH
		TWA (Inhalable particulate matter)	3 mg/m3	ACGIH
		TWA	3.5 mg/m3	NIOSH REL
		TWA	3.5 mg/m3	OSHA Z-1
		TWA	3.5 mg/m3	OSHA P0
		TWA	0.1 mg/m3 (PAHs)	NIOSH REL
Titanium dioxide	13463-67-7	TWA value	10 mg/m3	ACGIHTLV
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
aluminium hydroxide	21645-51-2	TWA value (Respirable fraction)	1 mg/m3	ACGIHTLV
		TWA (Res-	1 mg/m3	ACGIH

# SAFETY DATA SHEET

## Sikaflex-900 quick silver 263 Formerly MSeal 900 Qk Sil 263



Version 1.0      Revision Date: 08/10/2020      SDS Number: 000000597647      Date of last issue: -  
Date of first issue: 08/10/2020

		pirable particulate matter)	(Aluminum)	
--	--	-----------------------------	------------	--

**Engineering measures** : No applicable information available.

### Personal protective equipment

Respiratory protection : Wear respiratory protection if ventilation is inadequate.

Hand protection

Remarks : impermeable gloves rubber Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Safety glasses

Skin and body protection : Protective suit

Protective measures : Do not inhale gases/vapours/aerosols.  
Avoid contact with the skin, eyes and clothing.  
Avoid exposure - obtain special instructions before use.  
Handle in accordance with good building materials hygiene and safety practice.  
Wearing of closed work clothing is recommended.

Hygiene measures : General industrial hygiene practice.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : pasty

Color : pigmented

Odor : product specific

Odor Threshold : No data available

pH : slightly alkaline

Melting point : No applicable information available.

Boiling point : > 392 °F / > 200 °C

Flash point : > 370 °F / > 188 °C

Evaporation rate : No applicable information available.

Flammability (solid, gas) : not highly flammable

# SAFETY DATA SHEET

## Sikaflex-900 quick silver 263 Formerly MSeal 900 Qk Sil 263



Version 1.0      Revision Date: 08/10/2020      SDS Number: 000000597647      Date of last issue: -  
Date of first issue: 08/10/2020

---

Upper explosion limit / Upper flammability limit : No applicable information available.

Lower explosion limit / Lower flammability limit : No applicable information available.

Vapor pressure : No applicable information available.

Relative vapor density : No applicable information available.

Relative density : No applicable information available.

Density : approx. 1.45 g/cm<sup>3</sup> (68 °F / 20 °C)

Solubility(ies)  
Water solubility : No data available

Solubility in other solvents : No applicable information available.

Partition coefficient: n-octanol/water : No applicable information available.

Autoignition temperature : not applicable

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity  
Viscosity, dynamic : No applicable information available.

Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive  
Not explosive

Oxidizing properties : Based on its structural properties the product is not classified as oxidizing.

Sublimation point : No applicable information available.

Molecular weight : No data available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : Stable under recommended storage conditions.  
No hazards to be specially mentioned.

Conditions to avoid : See SDS section 7 - Handling and storage.

---

# SAFETY DATA SHEET

## Sikaflex-900 quick silver 263 Formerly MSeal 900 Qk Sil 263



Version 1.0	Revision Date: 08/10/2020	SDS Number: 000000597647	Date of last issue: - Date of first issue: 08/10/2020
----------------	------------------------------	-----------------------------	--

---

Incompatible materials	:	Strong acids Strong bases Strong oxidizing agents Strong reducing agents
Hazardous decomposition products	:	No hazardous decomposition products if stored and handled as prescribed/indicated.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

#### **Product:**

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

#### Skin corrosion/irritation

Not classified based on available information.

#### Serious eye damage/eye irritation

Not classified based on available information.

#### Respiratory or skin sensitization

##### Skin sensitization

Not classified based on available information.

##### Respiratory sensitization

Not classified based on available information.

##### Germ cell mutagenicity

Not classified based on available information.

##### Carcinogenicity

Not classified based on available information.

##### Reproductive toxicity

Not classified based on available information.

##### STOT-single exposure

Not classified based on available information.

##### STOT-repeated exposure

Not classified based on available information.

##### Aspiration toxicity

Not classified based on available information.

# SAFETY DATA SHEET

## Sikaflex-900 quick silver 263 Formerly MSeal 900 Qk Sil 263



Version 1.0      Revision Date: 08/10/2020      SDS Number: 000000597647      Date of last issue: -  
Date of first issue: 08/10/2020

---

**Product:**

No aspiration hazard expected.

**Further information**

**Product:**

Remarks : No data available

---

### SECTION 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential**

**Components:**

**Titanium dioxide:**

Partition coefficient: n-octanol/water : Remarks: not applicable

**carbon black:**

Partition coefficient: n-octanol/water : Remarks: not applicable

**aluminium hydroxide:**

Partition coefficient: n-octanol/water : Remarks: The value has not been determined because the substance is inorganic.

**Iron oxide:**

Partition coefficient: n-octanol/water : Remarks: Study scientifically not justified.

**Mobility in soil**

No data available

**Other adverse effects**

**Product:**

Additional ecological information : There is a high probability that the product is not acutely harmful to aquatic organisms. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.



# SAFETY DATA SHEET

## Sikaflex-900 quick silver 263 Formerly MSeal 900 Qk Sil 263



Version 1.0      Revision Date: 08/10/2020      SDS Number: 000000597647      Date of last issue: -  
Date of first issue: 08/10/2020

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

- Waste from residues : Dispose of in accordance with national, state and local regulations.  
Do not discharge into drains/surface waters/groundwater.  
Residues should be disposed of in the same manner as the substance/product.
- Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

Not regulated as a dangerous good

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code

Not regulated as a dangerous good

##### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Domestic regulation

##### 49 CFR

Not regulated as a dangerous good

### SECTION 15. REGULATORY INFORMATION

#### US State Regulations

##### Pennsylvania Right To Know

Titanium dioxide	13463-67-7
carbon black	1333-86-4
Iron oxide	1309-37-1
listed	

##### New Jersey Right To Know

Titanium dioxide	13463-67-7
carbon black	1333-86-4
Iron oxide	1309-37-1
listedSpecial Hazard.	

##### California Prop. 65

# SAFETY DATA SHEET

## Sikaflex-900 quick silver 263 Formerly MSeal 900 Qk Sil 263



Version 1.0      Revision Date: 08/10/2020      SDS Number: 000000597647      Date of last issue: -  
Date of first issue: 08/10/2020

WARNING: This product can expose you to chemicals including carbon black, which is/are known to the State of California to cause cancer, and toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).


### The ingredients of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory


## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA 704:



#### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

### Full text of other abbreviations

- 29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)
- 29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)
- NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- 29 CFR 1910.1000 (Table Z-1-A) / TWA value : Time Weighted Average (TWA):
- 29 CFR 1910.1000 (Table Z-1) / PEL : Permissible exposure limit
- ACGIH / TWA : 8-hour, time-weighted average

# SAFETY DATA SHEET

## Sikaflex-900 quick silver 263 Formerly MSeal 900 Qk Sil 263



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/10/2020	000000597647	Date of first issue: 08/10/2020

ACGIHTLV / TWA value : Time Weighted Average (TWA):  
NIOSH / REL value : Recommended exposure limit (REL):  
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour  
workday during a 40-hour workweek  
OSHA P0 / TWA : 8-hour time weighted average  
OSHA Z-1 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 08/10/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

# SAFETY DATA SHEET

## Sikaflex-900 quick silver 263 Formerly MSeal 900 Qk Sil 263



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/10/2020	000000597647	Date of first issue: 08/10/2020

---

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN