# SikaThorocoat-250 neutral tint base Formerly MProtect C 250 neutral



Versio 1.0	n	Revision Date: 09/24/2020		DS Number: 0000261461	Date of last issue: - Date of first issue: 09/24/2020
SECT	ION 1	. IDENTIFICATION			
Ρ	roduc	t name	:	SikaThorocoat-25 neutral	50 neutral tint base Formerly MProtect C 250
Р	Product code		:	00000000005172	20356
Ν	lanufa	acturer or supplier's	deta	ails	
С	Compa	ny name of supplier	:	Sika MBCC US L	LC
A	Address		:	201 POLITO AVE Lyndhurst NJ 07071	
E	merge	ency telephone	:	ChemTel: +1-813	-248-0585
R	lecom	mended use of the c	hen	nical and restriction	ons on use
R	lecom	mended use	:	Product for const	ruction chemicals
R	Restric	tions on use	:	Reserved for indu	ustrial and professional use.

### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with 29 CFR 1910.1200 Carcinogenicity (Inhalation) : Category 1A					
Specific target organ toxicity - repeated exposure	:	Category 2 (Kidney)			
Short-term (acute) aquatic hazard	:	Category 3			
Long-term (chronic) aquatic hazard	:	Category 3			
GHS label elements Hazard pictograms	:				
Signal Word	:	Danger			
Hazard Statements	:	H350 May cause cancer. H373 May cause damage to organs (Kidney) through prolonged or repeated exposure. H402 Harmful to aquatic life. H412 Harmful to aquatic life with long lasting effects.			



# SikaThorocoat-250 neutral tint base Formerly MProtect C 250 neutral

Versic 1.0	on Revision Date: 09/24/2020	SDS Number: 000000261461	Date of last issue: - Date of first issue: 09/24/2020				
Ρ	Precautionary Statements	face protection P201 Obtain sp P202 Do not ha and understood P273 Avoid rel	<ul> <li>Prevention:</li> <li>P280 Wear protective gloves/ protective clothing/ eye protective face protection.</li> <li>P201 Obtain special instructions before use.</li> <li>P202 Do not handle until all safety precautions have been real and understood.</li> <li>P273 Avoid release to the environment.</li> <li>P260 Do not breathe dust or mist.</li> </ul>				
		CENTER/ doct	F exposed or concerned: Call a POISON or. ical advice/ attention if you feel unwell.				
		<b>Storage:</b> P405 Store loc	ked up.				
		<b>Disposal:</b> P501 Dispose waste collection	of contents/container to appropriate hazardous n point.				
c	Other hazards	P501 Dispose					

No data available.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical	nature
onounour	nataro

: No data available.

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
Limestone	1317-65-3	>= 15 - < 25
ethyleneglycol	107-21-1	>= 1 - < 3
Isobutyric acid, monoester with 2,2,4-	25265-77-4	>= 0 - < 3
trimethylpentane-1,3-diol		
Quartz (SiO2)	14808-60-7	>= 0.1 - < 0.3
Poly(oxy-1,2-ethanediyl), .alpha	9036-19-5	>= 0.1 - < 0.2
[(1,1,3,3-tetramethylbutyl)phenyl]-		
.omegahydroxy-		
diuron	330-54-1	>= 0 - < 0.2
3-iodo-2-propynyl butylcarbamate; 3-	55406-53-6	>= 0 - < 0.1
iodoprop-2-yn-1-yl butylcarbamate		

### **SECTION 4. FIRST AID MEASURES**

General advice	:	Move out of dangerous area. Show this material safety data sheet to the doctor in attend- ance. Do not leave the victim unattended.
If inhaled	:	If unconscious, place in recovery position and seek medical advice.



# SikaThorocoat-250 neutral tint base Formerly MProtect C 250 neutral

Version 1.0	Revision Date: 09/24/2020	SDS Number: 000000261461	Date of last issue: - Date of first issue: 09/24/2020
		If symptoms	persist, call a physician.
In cas	se of skin contact	and soap. Under no cir	t with skin, wash immediately with plenty of water cumstances should organic solvent be used. evelops, seek medical attention.
In case of eye contact		Remove cor Protect unha Keep eye wi	
lf swa	allowed	Keep respira Do not give Never give a If symptoms	ting immediately and call a physician. atory tract clear. milk or alcoholic beverages. anything by mouth to an unconscious person. persist, call a physician. immediately to hospital.
	important symptoms iffects, both acute and ed	: May cause o	cancer.
Notes	s to physician	: Treat sympton	omatically.

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Water spray Foam Dry powder Carbon dioxide (CO2)
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for fire-fighters	:	Wear self-contained breathing apparatus for firefighting if nec- essary.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :	Use personal protective equipment.
tive equipment and emer-	
gency procedures	

# SikaThorocoat-250 neutral tint base Formerly MProtect C 250 neutral



Version 1.0	n Revision Date: 09/24/2020		S Number: 0000261461	Date of last issue: - Date of first issue: 09/24/2020
Er	nvironmental precautions	:	Prevent further le	rom entering drains. akage or spillage if safe to do so. taminates rivers and lakes or drains inform ities.
	ethods and materials for ntainment and cleaning up	:	acid binder, unive	t absorbent material (e.g. sand, silica gel, ersal binder, sawdust). closed containers for disposal.

### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	Product is not explosive.
		Normal measures for preventive fire protection.
Advice on safe handling	:	Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap- plication area. Dispose of rinse water in accordance with local and national regulations.
Conditions for safe storage	:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
Further information on stor- age conditions	:	Keep only in the original container in a cool, dry, well- ventilated place away from ignition sources, heat or flame. Protect from direct sunlight.
Materials to avoid	:	Observe VCI storage rules.
Recommended storage tem- perature	:	41 °F / 5 °C
Further information on stor- age stability	:	Minimum storage temperature:

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Ingredients with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis
		(Form of	ters / Permissible	



sion	Revision Date: 09/24/2020	SDS Number: 000000261461	Date of las Date of firs	t issue: 09/24/2020	)
			exposure)	concentration	
ethyle	neglycol	107-21-1	TWA value (Vapor frac- tion)	25 ppm	ACGIHTL
			STEL value (Vapor frac- tion)	50 ppm	ACGIHTL
			STEL value (Aerosol, inhalable.)	10 mg/m3	ACGIHTL
			TWA (Vapor)	25 ppm	ACGIH
			STEL (Va- por)	50 ppm	ACGIH
			STEL (Inhal- able fraction, Aerosol only)	10 mg/m3	ACGIH
			С	50 ppm 125 mg/m3	OSHA PO
diuron		330-54-1	TWA value	10 mg/m3	ACGIHTL
			REL value	10 mg/m3	NIOSH
			TWA value	10 mg/m3	29 CFR 1910.100 (Table Z-
			TWA	10 mg/m3	ACGIH
			TWA	10 mg/m3	NIOSH R
			TWA	10 mg/m3	OSHA PC
Limes	tone	1317-65-3	REL value (Respirable)	5 mg/m3	NIOSH
			REL value (Total)	10 mg/m3	NIOSH
			PEL (Respir- able fraction)	5 mg/m3	29 CFR 1910.100 (Table Z-
			PEL (Total dust)	15 mg/m3	29 CFR 1910.100 (Table Z-
			TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.100 (Table Z-
			TWA value (Total dust)	15 mg/m3	29 CFR 1910.100 (Table Z-
			TWA (total dust)	15 mg/m3	OSHA Z-
			TWA (respir- able fraction)	5 mg/m3	OSHA Z-
			TWA (Total dust)	15 mg/m3	OSHA PO
			TWA (respir- able dust fraction)	5 mg/m3	OSHA PO
			TWA (Res-	5 mg/m3	NIOSH R



		S Number: 0000261461	Date of las Date of firs	t issue: - t issue: 09/24/2020			
				pirable)	(Calcium car- bonate)		
				TWA (total)	10 mg/m3 (Calcium car- bonate)	NIOSH RE	
Quart	z (SiO2)		14808-60-7	TWA value (Respirable fraction)	0.025 mg/m3	ACGIHTLV	
				TWA value	0.05 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050	
				OSHA Action level	0.025 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050	
				REL value (Respirable dust)	0.05 mg/m3	NIOSH	
				TWA (Res- pirable dust)	0.05 mg/m3	OSHA Z-1	
				TWA (respir- able)	10 mg/m3 / %SiO2+2	OSHA Z-3	
				TWA (respir- able)	250 mppcf / %SiO2+5	OSHA Z-3	
				TWA (respir- able dust fraction)	0.1 mg/m3	OSHA P0	
				TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m3 (Silica)	ACGIH	
				PEL (respir- able)	0.05 mg/m3	OSHA CAR	
				TWA (Res- pirable dust)	0.05 mg/m3 (Silica)	NIOSH REL	
Engir	neering measures	:	No applicable	information ava	ilable.		
Perso	onal protective equip	ment					
Respi	ratory protection	:	Wear respirat	ory protection if	ventilation is inadequ	uate.	
Hand	protection						
Re	emarks	:	The suitability for a specific workplace should be discussed with the producers of the protective gloves.				
Eye p	rotection	:	Eye wash bottle with pure water Tightly fitting safety goggles				
Skin a	and body protection	:	Impervious clothing Choose body protection according to the amount and con- centration of the dangerous substance at the work place.				
Protec	ctive measures		Do not inhale gases/vapours/aerosols.				



# SikaThorocoat-250 neutral tint base Formerly MProtect C 250 neutral

Version 1.0	Revision Date: 09/24/2020	SDS Number: 000000261461	Date of last issue: - Date of first issue: 09/24/2020
		Avoid exposure Handle in acco and safety prac	with the skin, eyes and clothing. e - obtain special instructions before use. ordance with good building materials hygiene ctice. sed work clothing is recommended.
Hygie	ne measures	When using do	o not eat or drink. o not smoke. efore breaks and at the end of workday.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Color	:	pigmented
Odor	:	sweetish, slight odour
Odor Threshold	:	No data available
рН	:	9.5 - 10.0
Melting point	:	No applicable information available.
Boiling point	:	379.00 - 401.00 °F / 192.78 - 205.00 °C
Flash point	:	200.01 °F / 93.34 °C
Evaporation rate	:	No applicable information available.
Flammability (solid, gas)	:	not highly flammable Method: derived from flash point
Upper explosion limit / Upper flammability limit	:	15.3 %(V)
Lower explosion limit / Lower flammability limit	:	3.2 %(V)
Vapor pressure	:	No data available.
Relative vapor density	:	Heavier than air.
Relative density	:	No applicable information available.
Density	:	1.41 g/cm3 (68 °F / 20 °C)
Bulk density	:	not applicable



# SikaThorocoat-250 neutral tint base Formerly MProtect C 250 neutral

Vers 1.0	sion	Revision Date: 09/24/2020		S Number: 000261461	Date of last issue: - Date of first issue: 09/24/2020	
	Solubili Wat	ty(ies) er solubility	:	partly soluble		
	Solu	bility in other solvents	:	No applicable info	ormation available.	
	Partition coefficient: n- octanol/water		:	not applicable		
	Autoign	ition temperature	:	No data available	)	
	Decomposition temperature		:	No decomposition if stored and handled as pre- scribed/indicated.		
	Viscosi Visc	ty osity, dynamic	:	No applicable info	ormation available.	
	Visc	osity, kinematic	:	No applicable info	ormation available.	
	Explosi	ve properties	:	Not explosive Not explosive		
	Oxidizir	ng properties	:	Based on its strue as oxidizing.	ctural properties the product is not classified	
	Sublima	ation point	:	No applicable info	ormation available.	
	Molecu	lar weight	:	No data available		

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reac- tions	:	No decomposition if stored and applied as directed.
Conditions to avoid	:	See SDS section 7 - Handling and storage.
Incompatible materials	:	Strong acids Strong bases Strong oxidizing agents Strong reducing agents
Hazardous decomposition products	:	irritant gases/vapours carbon oxides



Version 1.0	Revision Date: 09/24/2020	SDS Number: 000000261461	Date of last issue: - Date of first issue: 09/24/2020
SECTION	11. TOXICOLOGICA	L INFORMATION	
Acut	e toxicity		
	e toxicity classified based on ava	ailable information.	
Prod	uct:		
Acute	e oral toxicity	: Remarks: No	applicable information available.
Acute	e inhalation toxicity	: Remarks: No	applicable information available.
Acute	e dermal toxicity	: Remarks: No	applicable information available.
Skin	corrosion/irritation		
Not c	lassified based on ava	ailable information.	
	ous eye damage/eye i		
	lassified based on ava		
Resp	piratory or skin sensi	tization	
-	sensitization		
	lassified based on ava	ailable information.	
-	<b>biratory sensitization</b> classified based on ava	ilable information.	
	n cell mutagenicity classified based on ava	ailable information.	
	inogenicity		
•	cause cancer.		
-	oductive toxicity classified based on ava	ailable information	
	T-single exposure		
	lassified based on ava	ailable information.	
STO	T-repeated exposure		
Not c	lassified based on ava	ailable information.	
Aspi	ration toxicity		
Not c	lassified based on ava	ailable information.	
<u>Prod</u> No as	uct: spiration hazard expec	ted.	
Furth	ner information		
<u>Prod</u> Rema		: No data avail	able



ersion )	Revision Date: 09/24/2020	SDS Number: 000000261461		Date of last issue: - Date of first issue: 09/24/2020
CTION	12. ECOLOGICAL IN	NFORM	IATION	
	oxicity			
	ata available			
Persi	stence and degrada	bility		
<u>Com</u>	oonents:			
		.alpha		methylbutyl)phenyl]omegahydroxy-:
Biode	gradability	:	Result: Readily Biodegradation Exposure time:	
Bioad	ccumulative potentia	al		
<u>Comp</u>	oonents:			
ethyle	eneglycol:			
	ion coefficient: n- ol/water	:	Method: Calcul GLP: no data	x1.36 (73 °F / 23 °C) lation Hansch/Leo mation taken from reference works and the
Isobu	ityric acid, monoest	er with	2,2,4-trimethy	Ipentane-1,3-diol:
Partiti	ion coefficient: n- ol/water	:	log Pow: 3.2 (7 pH: 7	-
Quar	tz (SiO2):			
Partiti	ion coefficient: n- ol/water	:	Remarks: not a	applicable
Poly(	oxy-1,2-ethanediyl),	.alpha	[(1,1,3,3-tetra	methylbutyl)phenyl]omegahydroxy-:
Bioac	cumulation	:	Remarks: Accu	imulation in organisms is not to be expected
3-iod	o-2-propynyl hutyle	arbam	ate: 3-iodonron	-2-yn-1-yl butylcarbamate:
Partiti	ion coefficient: n- ol/water	:	log Pow: 2.81 (	
Mobil	lity in soil			
	ata available			





Version 1.0	Revision Date: 09/24/2020	SDS N 000000	umber: 261461	Date of last issue: - Date of first issue: 09/24/2020
Othe	r adverse effects			
Prod	uct:			
Addit matio	ional ecological infor- on	unp Har	rofessional ha	hazard cannot be excluded in the event of andling or disposal. c life. c life with long lasting effects.
SECTION	13. DISPOSAL CONS	IDERATI	ONS	
Disp	osal methods			
Wasi	e from residues	cal Dis tion	or used contai pose of in acco s.	te ponds, waterways or ditches with chemi- iner. ordance with national, state and local regula- into drains/surface waters/groundwater.

### Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

#### **SECTION 14. TRANSPORT INFORMATION**

#### **International Regulations**

#### UNRTDG

Not regulated as a dangerous good

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### **Domestic regulation**

**49 CFR** Not regulated as a dangerous good

### **SECTION 15. REGULATORY INFORMATION**

SARA 313

: The following components are subject to reporting levels established by SARA Title III, Section 313:

ethyleneglycol 107-21-1

#### **US State Regulations**

Pennsylvania Right To Know



# SikaThorocoat-250 neutral tint base Formerly MProtect C 250 neutral


Version 1.0	Revision Date: 09/24/2020	SDS Number: 000000261461	Date of last issue: - Date of first issue: 09/24/2020
	ethyleneglycol Limestone		107-21-1 1317-65-3
New 、	Jersey Right To Know ethyleneglycol Limestone Quartz (SiO2) Quartz (SiO2) Distillates (petrole	r um), hydrotreated hea	107-21-1 1317-65-3 14808-60-7 14808-60-7 vy naphthenic 64742-52-5
Califo	ornia Prop. 65	um), nyurureateu nea	vy naphtnenic 04742-52-5

WARNING: This product can expose you to chemicals including 1,4-dioxane, which is/are known to the State of California to cause cancer, and

ethyleneglycol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:TSCA:On the inventory, or in compliance with the inventory

### **SECTION 16. OTHER INFORMATION**



### Full text of other abbreviations

29 CFR 1910.1000 (Table Z- 1-A)	:	OSHA - Table Z-1-A (29 CFR 1910.1000)
/	:	OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
29 CFR 1910.1001-1050	:	OSHA - Specifically Regulated Substances (29 CFR 1910.1001-1050)



# SikaThorocoat-250 neutral tint base Formerly MProtect C 250 neutral

Version 1.0	Revision Date: 09/24/2020		OS Number: 0000261461	Date of last issue: - Date of first issue: 09/24/2020
ACGI ACGI		::		eshold Limit Values (TLV) ence of Governmental Industrial Hygienists - ues (US)
	H REL A CARC	: : : :	NIOSH Pocket G USA. NIOSH Rec OSHA Specifically	uide to Chemical Hazards (US) commended Exposure Limits y Regulated Chemicals/Carcinogens BLE Z-1 Limits for Air Contaminants -
OSHA	X Z-1	:	1910.1000 USA. Occupation its for Air Contam	al Exposure Limits (OSHA) - Table Z-1 Lim- inants
OSHA 29 CF	X Z-3 R 1910.1000 (Table Z-	:	USA. Occupation eral Dusts Time Weighted A	al Exposure Limits (OSHA) - Table Z-3 Min- verage (TWA):
1-A) / 29 CF	TWA value R 1910.1000 (Table Z-		Permissible expo	
	⊑∟ R 1910.1001-1050 / \ Action level	:	OSHA Action leve	əl:
TWA	R 1910.1001-1050 / value H / TWA	:	Time Weighted A	
ACGI ACGI ACGI NIOS	H / TWA H / STEL HTLV / STEL value HTLV / TWA value H / REL value H REL / TWA	· · ·	Time Weighted A Recommended ex Time-weighted av	ure limit sure Limit (STEL):
OSHA OSHA OSHA	A CARC / PEL A P0 / TWA A P0 / C A Z-1 / TWA A Z-3 / TWA	: : :	Permissible expose 8-hour time weigh Ceiling limit 8-hour time weigh 8-hour time weigh	sure limit (PEL) ited average ited average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance: ELx - Loading rate associated with x% response: EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New



## SikaThorocoat-250 neutral tint base Formerly MProtect C 250 neutral

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/24/2020	00000261461	Date of first issue: 09/24/2020

Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB -Very Persistent and Very Bioaccumulative

Revision Date

09/24/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN