



**PRODUCT DATA SHEET**

Edition 04.2019/v1  
CSC Master Format™ 07 19 16  
SILANE WATER REPELLENTS

# Sikagard® Natural Look Clear Sealer

WATER-BASED, LOW-VOC, WATER-REPELLING AND SALT SCREENING SILANE/SILOXANE SEALER FOR CONCRETE, MORTAR, MASONRY AND STONE

<b>Description</b>	Sikagard® Natural Look Clear Sealer is a commercial grade water repellent sealer that penetrates an absorbent surface to form a seal against the elements, such as water and chlorides, on concrete, masonry, mortar, brick and stone. Penetrates surface to form a seal against the elements such as water and chlorides, which can cause freeze thaw damage to the surface. Will not change the surface appearance and resists the growth of fungi and moss.														
<b>Where to Use</b>	Sikagard® Natural Look Clear Sealer may be used on concrete, masonry, mortar, brick and stone.														
<b>Advantages</b>	<ul style="list-style-type: none"> <li>▪ Will not alter the appearance of the treated surface.</li> <li>▪ Improves resistance to dirt penetration.</li> <li>▪ Resistant to mold and fungus.</li> <li>▪ For vertical and horizontal applications.</li> <li>▪ Protects against freeze-thaw damage.</li> <li>▪ Low-VOC content.</li> </ul>														
<p><b>Technical Data</b></p> <table border="0"> <tr> <td><b>Packaging</b></td> <td>20 L (5 US gal.) pail</td> </tr> <tr> <td><b>Colour &amp; Appearance</b></td> <td>Milky white when applied but dries clear</td> </tr> <tr> <td><b>Yield</b></td> <td>50 - 120 m<sup>2</sup> (500 - 1300 ft<sup>2</sup>) per pail <i>Coverage figures dependent upon surface porosity, absorption and profile. Consumption may be determined by a small test area.</i></td> </tr> <tr> <td><b>Shelf Life</b></td> <td>1 year in original, undamaged and unopened packaging. Store dry at temperatures between 7 - 32 °C (45 - 90 °F). Keep from freezing. Condition material to 18 - 24 °C (65 - 75 °F) before using.</td> </tr> <tr> <td><b>Dry Time</b></td> <td>Approximately 4 - 8 hours, depending on temperature. Wait 24 hours before exposing to foot/car traffic. Approximately 72 hours for maximum water repellency, depending on surface and atmospheric conditions.</td> </tr> <tr> <td><b>VOC Content</b></td> <td>39 g/L</td> </tr> <tr> <td><b>Chemical Resistance</b></td> <td>Contact Sika Canada</td> </tr> </table> <p><i>Product properties are typically averages, obtained under laboratory conditions. Reasonable variations can be expected on-site due to local factors, including environment, preparation, application, curing and test methods.</i></p>		<b>Packaging</b>	20 L (5 US gal.) pail	<b>Colour &amp; Appearance</b>	Milky white when applied but dries clear	<b>Yield</b>	50 - 120 m <sup>2</sup> (500 - 1300 ft <sup>2</sup> ) per pail <i>Coverage figures dependent upon surface porosity, absorption and profile. Consumption may be determined by a small test area.</i>	<b>Shelf Life</b>	1 year in original, undamaged and unopened packaging. Store dry at temperatures between 7 - 32 °C (45 - 90 °F). Keep from freezing. Condition material to 18 - 24 °C (65 - 75 °F) before using.	<b>Dry Time</b>	Approximately 4 - 8 hours, depending on temperature. Wait 24 hours before exposing to foot/car traffic. Approximately 72 hours for maximum water repellency, depending on surface and atmospheric conditions.	<b>VOC Content</b>	39 g/L	<b>Chemical Resistance</b>	Contact Sika Canada
<b>Packaging</b>	20 L (5 US gal.) pail														
<b>Colour &amp; Appearance</b>	Milky white when applied but dries clear														
<b>Yield</b>	50 - 120 m <sup>2</sup> (500 - 1300 ft <sup>2</sup> ) per pail <i>Coverage figures dependent upon surface porosity, absorption and profile. Consumption may be determined by a small test area.</i>														
<b>Shelf Life</b>	1 year in original, undamaged and unopened packaging. Store dry at temperatures between 7 - 32 °C (45 - 90 °F). Keep from freezing. Condition material to 18 - 24 °C (65 - 75 °F) before using.														
<b>Dry Time</b>	Approximately 4 - 8 hours, depending on temperature. Wait 24 hours before exposing to foot/car traffic. Approximately 72 hours for maximum water repellency, depending on surface and atmospheric conditions.														
<b>VOC Content</b>	39 g/L														
<b>Chemical Resistance</b>	Contact Sika Canada														

**HOW TO USE**

<b>Surface Preparation</b>	Surface must be clean, sound, dust-free and dry. Remove all dust, dirt, loose concrete, grease, curing compounds, paint and other particles by mechanical means (i.e. pressure wash, blast clean, etc.).
<b>Mixing</b>	No mixing required, the product is ready-to-use. Just shake the pail thoroughly before applying.
<b>Application</b>	Apply to surface by brushing, rolling or spraying over entire area moving in one direction uniformly. Avoid puddling of product in any area. A maximum of two (2) coats may be required, depending on porosity of surface. Recommended application temperature (ambient and substrate) is between 7 and 35 °C (45 - 95 °F) .  <b>Note:</b> Preliminary site test application is recommended (preferably on a small, prepared and inconspicuous surface) to determine satisfactory appearance and surface slip resistance.
<b>Clean Up</b>	Clean all tools and application equipment with water immediately after use. Dried material can only be mechanically removed.

---

**Limitations**

- Substrate must be dry prior to application (minimum 48 hours).
- Do not apply if rain is in the forecast (48 hours prior to or after application).
- Cannot seal visible cracks. Repair all cracks or surface defects before sealing.
- Do not use on concrete under seven (7) days old.
- Avoid puddling; apply even coats (when required).
- Do not attempt to build up thickness.
- Does not contain a antimicrobial additive.
- Not recommended for stained concrete.
- To penetrate denser surfaces, rinsing surface off with water may be necessary.

---

**Health and Safety Information**

For information and advice on the safe handling, storage and disposal of chemical products, users should refer to the most recent SAFETY DATA SHEET containing physical, ecological, toxicological and other safety-related data.

KEEP OUT OF REACH OF CHILDREN  
FOR INDUSTRIAL USE ONLY

---

The Information, and in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions, within their shelflife. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any recommendations, or from any other advice offered. The information contained herein does not relieve the user of the products from testing them for the intended application and purpose. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or may be downloaded from our website at: [www.sika.ca](http://www.sika.ca)

---

**SIKA CANADA INC.****Head Office**

601, avenue Delmar  
Pointe-Claire, Quebec  
H9R 4A9

**Other locations**

Toronto  
Edmonton  
Vancouver

**1-800-933-SIKA**  
**[www.sika.ca](http://www.sika.ca)**

Certified ISO 9001 (CERT-0102780)  
Certified ISO 14001 (CERT-0102791)

