

WARRANTY SELECTION GUIDE

**BUILDING TRUST
CONSTRUIRE LA CONFIANCE**



Sikaplan® Warranties

System	Membrane	Warranty Type	Warranty Length (Years)	High Wind Speed Warranty
Rhinobond, Inseam	Sikaplan® Fastened	Membrane or Standard	5, 10, 15 or 20	NA
		System		119 and 159 km/h
Adhered	Sikaplan® Adhered	Membrane or Standard	5, 10, 15 or 20	NA
		System		119 and 159 km/h
Ballasted	Sikaplan® Adhered	Membrane or Standard	5 or 10	NA
		System		

Sarnafil® Warranties

System	Membrane	Warranty Type	Warranty Length (Years)	High Wind Speed Warranty
Rhinobond, Sarnafast, Engineered	Sarnafil® S327	Membrane	5, 10, 15, 20, 25 ² or 30 ³	N.A.
		Standard	5, 10, 15, 20, 25 ^{2,4} or 30 ^{3,4}	N.A.
		System	5, 10, 15, 20, 25 ² or 30 ³	119, 159 & 193 km/h
Adhered	Sarnafil® G410, Sarnafil® G410 SA	Membrane	5, 10, 15, 20, 25 ^{1,2} or 30 ^{1,3}	N.A.
		Standard	5, 10, 15, 20, 25 ^{1,2,4} or 30 ^{1,3,4}	N.A.
		System	5, 10, 15, 20, 25 ^{1,2} or 30 ^{1,3}	119, 159 & 193 km/h
Adhered Décor	Sarnafil® G410, Sarnafil® G410 SA	Membrane or Standard	5, 10, 15 or 20	N.A.
		System	5, 10, 15 or 20	119, 159 & 193 km/h
PMR	Sarnafil® G410, Sarnafil® G476, Sarnafil® G476 SA	Membrane or Standard	5,10,15 or 20 ⁶	N.A.
		System		
Ballasted	Sarnafil® G410	Membrane or Standard	5,10,15 or 20 ⁶	N.A.
		System		

Notes:

- * System warranties require all materials from the structural deck up and supplied by Sika
- * Standard warranties require all materials for membrane/insulation fixation/adhesion to be supplied by Sika
- * All High Wind Speed and Hail warranties must be approved by the Sika Vice President Technical
- * PV Systems only permitted on Sarnafil adhered or mechanically attached roof systems. Sika approved cover board is required for any systems with a PV installation.
- * Sika approved vapour retarders are required for all wind warranties
- * Vegetative roofs are considered PMR systems. A Sika approved cover board is required in there is insulation below the membrane
- * XPS/EPS insulation, bitumen cannot come into contact with the membrane
- * Contact the Technical Representative if Coal Tar Pitch is present in the existing roof system
- ¹ Criteria for all 25 & 30 year warranties - Adhered Roofs. Mechanical fixation is required, for one of the layers (coverboard, insulation or thermal barrier) below the membrane, which incorporate Steel, Wood Plank or Plywood structural deck
- ² Criteria for all 25 year warranties: Sarnavap 6 NOT permitted, minimum 72 mil membrane, Sarnatherm CG or Rockwool DD and Sika approved cover board are required.
- ³ Criteria for all 30 year warranties: Sarnavap 6 NOT permitted, minimum 80 mil membrane, Sarnatherm CG or Rockwool DD and Sika approved cover board are required
- ⁴ Criteria for 25 & 30 year Standard warranty: Contact your Sales Representative
- ⁵ 72 mil membrane required
- ⁶ 80 mil membrane required

For up to date and accurate information, please consult the current Product Data Sheet for all Sika products at www.sika.ca