

# SAFETY DATA SHEET

## Sikaflex® Primer-449



Version  
1.1

Revision Date:  
01/12/2017

SDS Number:  
000000604366

---

### SECTION 1. IDENTIFICATION

Product name : Sikaflex® Primer-449

#### Manufacturer or supplier's details

Company name : Sika Canada Inc.  
601, avenue Delmar  
Pointe-Claire, QC H9R 4A9  
Canada  
www.sika.ca

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

Health and Safety Services's  
e-mail address : ehs@ca.sika.com

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

#### Recommended use of the chemical and restrictions on use

For further information, refer to product data sheet.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS Classification

Flammable liquids : Category 2

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitization : Category 1

Carcinogenicity (Inhalation) : Category 2

Reproductive toxicity : Category 2

Specific target organ system-  
ic toxicity - single exposure : Category 3 (Central nervous system)

Specific target organ system-  
ic toxicity - repeated expo-  
sure (Inhalation) : Category 2

#### GHS label elements

Version  
1.1Revision Date:  
01/12/2017SDS Number:  
000000604366

Hazard pictograms

:



Signal Word

: Danger

Hazard Statements

: H225 Highly flammable liquid and vapor.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.  
 H351 Suspected of causing cancer if inhaled.  
 H361 Suspected of damaging fertility or the unborn child.  
 H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

Precautionary Statements

: **Prevention:**  
 P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P233 Keep container tightly closed.  
 P240 Ground and bond container and receiving equipment.  
 P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
 P242 Use non-sparking tools.  
 P243 Take action to prevent static discharges.  
 P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.  
 P264 Wash skin thoroughly after handling.  
 P271 Use only outdoors or in a well-ventilated area.  
 P272 Contaminated work clothing must not be allowed out of the workplace.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
**Response:**  
 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
 P337 + P313 If eye irritation persists: Get medical advice/ attention.  
 P362 + P364 Take off contaminated clothing and wash it before reuse.  
 P370 + P378 In case of fire: Use dry sand, dry chemical or alco-

Version  
1.1Revision Date:  
01/12/2017SDS Number:  
000000604366

hol-resistant foam to extinguish.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Warning** : Reports have associated repeated and prolonged exposure to some of the chemicals in this product with permanent brain, liver, kidney and nervous system damage. Intentional misuse by deliberate concentration and inhalation of vapors may be harmful or fatal.

**Other hazards**

None known.

**Supplemental information**

If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS****Hazardous ingredients**

Chemical name	CAS-No.	Concentration (% w/w)
butanone	78-93-3	>= 50 - < 60
Toluene	108-88-3	>= 25 - < 35
Aliphatic polyisocyanate	28182-81-2	>= 5 - < 10
n-butyl acetate	123-86-4	>= 1 - < 2
xylene	1330-20-7	>= 1 - < 2
ethylbenzene	100-41-4	>= 0 - < 1

**SECTION 4. FIRST AID MEASURES**

**General advice** : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attendance.

**If inhaled** : Move to fresh air.  
Consult a physician after significant exposure.

**In case of skin contact** : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.

**In case of eye contact** : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.

Version  
1.1Revision Date:  
01/12/2017SDS Number:  
000000604366

	Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting without medical advice. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Obtain medical attention.
Most important symptoms and effects, both acute and delayed	: irritant effects sensitizing effects Respiratory disorder Allergic reactions Excessive lachrymation Erythema Dermatitis Loss of balance Vertigo See Section 11 for more detailed information on health effects and symptoms. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer if inhaled. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure if inhaled.
Notes to physician	: Treat symptomatically.

---

**SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO <sub>2</sub> ) Dry chemical
Unsuitable extinguishing media	: Water High volume water jet
Specific hazards during fire fighting	: Do not use a solid water stream as it may scatter and spread fire.
Further information	: Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for fire-fighters	: In the event of fire, wear self-contained breathing apparatus.



Version  
1.1

Revision Date:  
01/12/2017

SDS Number:  
000000604366

## SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Remove all sources of ignition.  
Deny access to unprotected persons.  
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

## SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
- Advice on safe handling : Do not breathe vapors or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharge.  
Open drum carefully as content may be under pressure.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).  
Follow standard hygiene measures when handling chemical products.
- Conditions for safe storage : Store in original container.  
Store in cool place.  
Keep in a well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Store in accordance with local regulations.

Version  
1.1Revision Date:  
01/12/2017SDS Number:  
000000604366

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis		
butanone	78-93-3	TWA	200 ppm 590 mg/m <sup>3</sup>	CA AB OEL		
		STEL	300 ppm 885 mg/m <sup>3</sup>	CA AB OEL		
		TWA	50 ppm	CA BC OEL		
		STEL	100 ppm	CA BC OEL		
		TWAEV	50 ppm 150 mg/m <sup>3</sup>	CA QC OEL		
		STEV	100 ppm 300 mg/m <sup>3</sup>	CA QC OEL		
		TWA	200 ppm	ACGIH		
Toluene	108-88-3	STEL	300 ppm	ACGIH		
		TWA	50 ppm 188 mg/m <sup>3</sup>	CA AB OEL		
		TWA	20 ppm	CA BC OEL		
		TWAEV	50 ppm 188 mg/m <sup>3</sup>	CA QC OEL		
		TWA	20 ppm	ACGIH		
		Aliphatic polyisocyanate	28182-81-2	TWA	0.005 ppm	CA ON OEL
				C	0.02 ppm	CA ON OEL
n-butyl acetate	123-86-4	TWA	150 ppm 713 mg/m <sup>3</sup>	CA AB OEL		
		STEL	200 ppm 950 mg/m <sup>3</sup>	CA AB OEL		
		TWA	20 ppm	CA BC OEL		
		TWAEV	150 ppm 713 mg/m <sup>3</sup>	CA QC OEL		
		STEV	200 ppm 950 mg/m <sup>3</sup>	CA QC OEL		
		TWA	150 ppm	ACGIH		
		STEL	200 ppm	ACGIH		
xylene	1330-20-7	TWA	100 ppm 434 mg/m <sup>3</sup>	CA AB OEL		
		STEL	150 ppm 651 mg/m <sup>3</sup>	CA AB OEL		
		TWAEV	100 ppm 434 mg/m <sup>3</sup>	CA QC OEL		
		STEV	150 ppm 651 mg/m <sup>3</sup>	CA QC OEL		
		TWA	100 ppm	CA BC OEL		
		STEL	150 ppm	CA BC OEL		
		TWA	100 ppm	ACGIH		
ethylbenzene	100-41-4	STEL	150 ppm	ACGIH		
		TWA	100 ppm 434 mg/m <sup>3</sup>	CA AB OEL		

Version  
1.1Revision Date:  
01/12/2017SDS Number:  
000000604366

		STEL	125 ppm 543 mg/m <sup>3</sup>	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	100 ppm 434 mg/m <sup>3</sup>	CA QC OEL
		STEV	125 ppm 543 mg/m <sup>3</sup>	CA QC OEL
		TWA	20 ppm	ACGIH
		STEL	125 ppm	ACGIH

**Biological occupational exposure limits**

Ingredients	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
butanone	78-93-3	methyl ethyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	2 mg/l	ACGIH BEI
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI
xylene	1330-20-7	Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI
ethylbenzene	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI

**Engineering measures** : Use of adequate ventilation should be sufficient to control

Version  
1.1Revision Date:  
01/12/2017SDS Number:  
00000604366

worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

#### Personal protective equipment

- Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
- The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection
- Remarks : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Avoid contact with skin, eyes and clothing.  
Wash hands before breaks and immediately after handling the product.  
Remove respiratory and skin/eye protection only after vapors have been cleared from the area.  
Remove contaminated clothing and protective equipment before entering eating areas.  
Wash thoroughly after handling.

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : No data available
- Odor : aromatic
- Odor Threshold : No data available



# SAFETY DATA SHEET

## Sikaflex® Primer-449



Version  
1.1

Revision Date:  
01/12/2017

SDS Number:  
000000604366

---

pH	: No data available
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: 22 °C (72 °F) Method: closed cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: 7 %(V)
Lower explosion limit	: 1 %(V)
Vapor pressure	: 88.9924 hpa (66.750 mmHg)
Relative vapor density	: No data available
Density	: 0.87 g/cm <sup>3</sup> (20 °C (68 °F) ( ))
Solubility(ies) Water solubility	: insoluble
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 20.5 mm <sup>2</sup> /s (40 °C)
Explosive properties	: No data available
Molecular weight	: No data available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Stable under recommended storage conditions. Vapors may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.

Version  
1.1Revision Date:  
01/12/2017SDS Number:  
000000604366

Incompatible materials : No data available

No decomposition if stored and applied as directed.

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Not classified based on available information.

**Product:**Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation methodAcute inhalation toxicity : Acute toxicity estimate: > 40 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation methodAcute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method**Ingredients:****butanone:**

Acute oral toxicity : LD50 Oral (Rat): 3,300 mg/kg

Acute inhalation toxicity : LC50 (Rat): 36 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 Dermal (Rabbit): &gt; 5,000 mg/kg

**Aliphatic polyisocyanate:**

Acute oral toxicity : LD50 Oral (Rat): &gt; 2,500 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 1.5 mg/l  
Test atmosphere: dust/mist  
Method: Expert judgment

Acute dermal toxicity : LD50 Dermal (Rat): &gt; 2,000 mg/kg

**n-butyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): &gt; 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 23.4 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 Dermal (Rabbit): &gt; 5,000 mg/kg

**Skin corrosion/irritation**

Causes skin irritation.

Version  
1.1Revision Date:  
01/12/2017SDS Number:  
000000604366**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Respiratory or skin sensitization**

Skin sensitization: May cause an allergic skin reaction.

Respiratory sensitization: Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Suspected of causing cancer if inhaled.

**IARC** Group 2B: Possibly carcinogenic to humans

ethylbenzene 100-41-4

**NTP** Not applicable**Reproductive toxicity**

Suspected of damaging fertility or the unborn child.

**STOT-single exposure**

May cause drowsiness or dizziness.

**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure if inhaled.

**Aspiration toxicity**

Not classified based on available information.

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Ingredients:****n-butyl acetate:**Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): 647.7 mg/l  
Exposure time: 72 h**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects****Product:**Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.  
Avoid dispersal of spilled material and runoff and contact with

Version  
1.1Revision Date:  
01/12/2017SDS Number:  
000000604366

---

 soil, waterways, drains and sewers.
 

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

- Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
- 

### SECTION 14. TRANSPORT INFORMATION

#### Domestic regulation

##### TDG (road/train)

- UN number : UN 1993
- Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(butanone, Toluene)
- Class : 3
- Packing group : II
- Labels : 3

#### International Regulations

##### IATA-DGR

- UN/ID No. : UN 1993
- Proper shipping name : Flammable liquid, n.o.s.  
(butanone, toluene)
- Class : 3
- Packing group : II
- Labels : Flammable Liquids
- Packing instruction (cargo aircraft) : 364
- Packing instruction (passenger aircraft) : 353

##### IMDG-Code

- UN number : UN 1993
- Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(butanone, toluene)
- Class : 3
- Packing group : II
- Labels : 3
- EmS Code : F-E, S-E
- Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

---

Version  
1.1Revision Date:  
01/12/2017SDS Number:  
00000604366**SECTION 15. REGULATORY INFORMATION****Canadian lists**

No substances are subject to a Significant New Activity Notification.

**SECTION 16. OTHER INFORMATION**

Revision Date : 01/12/2017  
Prepared by : R & D of Sika Canada Inc.

Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sika.ca](http://www.sika.ca) or 514-697-2610.

**Full text of other abbreviations**

ADR	Accord européen relatif au transport international des marchandises Dangereuses par Route
CAS	Chemical Abstracts Service
DNEL	Derived no-effect level
EC50	Half maximal effective concentration
GHS	Globally Harmonized System
IATA	International Air Transport Association
IMDG	International Maritime Code for Dangerous Goods
LD50	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	Occupational Exposure Limit
PBT	Persistent, bioaccumulative and toxic
PNEC	Predicted no effect concentration
REACH	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a

SAFETY DATA SHEET

**Sikaflex® Primer-449**



Version  
1.1

Revision Date:  
01/12/2017

SDS Number:  
000000604366

---

SVHC  
vPvB

European Chemicals Agency  
Substances of Very High Concern  
Very persistent and very bioaccumulative

CA / Z8