

# Sable Marco® Asphalte Froide

Print Date 10/25/2024 Revision Date 10/25/2024

**SECTION 1. IDENTIFICATION** 

Product name Sable Marco® Asphalte Froide

Other means of identification: No data available

Company name www.sika.ca

Canada

Pointe-Claire, QC H9R 4A9

601, avenue Delmar Sika Canada Inc.

Telephone (514) 697-2610 / 1 (800) 933-7452

Telefax (514) 694-2792

E-mail address ehs@ca.sika.com

CANUTEC (collect) (613) 996-6666 (24 hours) Emergency telephone

Recommended use of the chemical and restrictions on

use

For further information, refer to product data sheet.

### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with the Hazardous Products Regulations

Skin irritation Category 2

Serious eye damage Category 1

Carcinogenicity Category 2

Carcinogenicity (Inhalation) Category 1A

Specific target organ toxicity

- single exposure

Category 3 (Respiratory system)

Specific target organ toxicity:

- repeated exposure

Category 1 (Lungs)

Specific target organ toxicity :

- repeated exposure

Category 2 (thymus, Liver, Bone marrow)

**GHS** label elements



# Sable Marco® Asphalte Froide

Revision Date 10/25/2024 Print Date 10/25/2024

Hazard pictograms







Signal Word Danger

**Hazard Statements** H315 Causes skin irritation.

> H318 Causes serious eye damage. H335 May cause respiratory irritation. H350 May cause cancer by inhalation. H351 Suspected of causing cancer.

H372 Causes damage to organs (Lungs) through prolonged or

repeated exposure.

H373 May cause damage to organs (thymus, Liver, Bone mar-

row) through prolonged or repeated exposure.

**Precautionary Statements** 

#### Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eve protection/

face protection/ hearing protection.

## Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P308 + P313 IF exposed or concerned: Get medical advice/

P332 + P313 If skin irritation occurs: Get medical advice/ atten-

P362 + P364 Take off contaminated clothing and wash it before reuse.

### Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P405 Store locked up.

# Disposal:

P501 Dispose of contents/ container to an approved waste dis-



# Sable Marco® Asphalte Froide

Revision Date 10/25/2024 Print Date 10/25/2024

posal plant.

## **Additional Labeling**

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

#### Other hazards

None known.

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

## Components

Chemical name	CAS-No.	Classification	Concentra- tion (% w/w)
calcium oxide	1305-78-8	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335	>= 30 - < 60
Asphalt	8052-42-4	Carc. 2; H351	>= 1 - < 5
Quartz (SiO2) >5µm	14808-60-7	Carc. 1A; H350 STOT RE 1; H372 STOT SE 3; H335	>= 1 - < 5
Diesel	68476-30-2	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Carc. 2; H351 STOT RE 2; H373 Asp. Tox. 1; H304	>= 1 - < 5

Actual concentration or concentration range is withheld as a trade secret

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in attend-

ance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.



# Sable Marco® Asphalte Froide

Revision Date 10/25/2024 Print Date 10/25/2024

If swallowed Clean mouth with water and drink afterwards plenty of water.

Do not induce vomiting without medical advice.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

Causes skin irritation.

Causes serious eye damage. May cause respiratory irritation. May cause cancer by inhalation. Suspected of causing cancer.

Causes damage to organs through prolonged or repeated

exposure. irritant effects Cough

Respiratory disorder **Excessive lachrymation** 

Erythema **Dermatitis** 

Notes to physician Treat symptomatically.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

for fire-fighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

# **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec- : tive equipment and emer-

gency procedures

Use personal protective equipment. Deny access to unprotected persons.

**Environmental precautions** Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.



Print Date 10/25/2024 Revision Date 10/25/2024

## **SECTION 7. HANDLING AND STORAGE**

fire and explosion

Advice on protection against : Normal measures for preventive fire protection.

Advice on safe handling : Avoid formation of respirable particles.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage Store in original container.

> Keep in a well-ventilated place. Observe label precautions.

Store in accordance with local regulations.

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

# Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
calcium oxide	1305-78-8	TWA	2 mg/m3	CA AB OEL
		TWA	2 mg/m3	CA BC OEL
		TWAEV	2 mg/m3	CA QC OEL
		TWA	2 mg/m3	ACGIH
magnesium oxide	1309-48-4	TWA (Fumes)	10 mg/m3	CA AB OEL
		TWA (Inhal- able fume)	10 mg/m3 (Magnesium)	CA BC OEL
		TWA (Respirable dust and fume)	3 mg/m3 (Magnesium)	CA BC OEL
		STEL (Respirable dust and fume)	10 mg/m3 (Magnesium)	CA BC OEL
		TWAEV (in- halable dust)	10 mg/m3	CA QC OEL
		TWA (Inhal- able particu- late matter)	10 mg/m3	ACGIH
Asphalt	8052-42-4	TWA (Fumes)	5 mg/m3	CA AB OEL



Revision Date 10/25/2024 Print Date 10/25/2024

				=
		TWA (Inhalable fume)	0.5 mg/m3 (benzene soluble aerosol)	CA BC OEL
		TWAEV (Fumes)	5 mg/m3	CA QC OEL
		TWA (Fume, inhalable fraction)	0.5 mg/m3 (benzene soluble aerosol)	ACGIH
Quartz (SiO2) >5μm	14808-60-7	TWA (Respirable particulates)	0.025 mg/m3	CA AB OEL
		TWA (Respirable fraction)	0.1 mg/m3	CA ON OEL
		TWA (Respirable)	0.025 mg/m3 (Silica)	CA BC OEL
		TWAEV (respirable dust)	0.05 mg/m3	CA QC OEL
		TWA (Respirable)	0.025 mg/m3	CA BC OEL
		TWA (Respirable)	0.025 mg/m3 (Silica)	CA BC OEL
		TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
Diesel	68476-30-2	TŴA	100 mg/m3 (total hydrocar- bons)	CA AB OEL
		TWA (Va- pour and inhalable aerosols)	100 mg/m3 (total hydrocar- bons)	CA BC OEL
		TWA (Inhal- able fraction and vapor)	100 mg/m3 (total hydrocar- bons)	ACGIH
aluminium oxide	1344-28-1	TWA TWA (Res-	10 mg/m3 1 mg/m3	CA AB OEL CA BC OEL
		I MA (VG2-	i ilig/ilio	OA BO UEL



Revision Date 10/25/2024 Print Date 10/25/2024

		pirable)	(Aluminum)	
		TWAEV (respirable dust)	5 mg/m3	CA QC OEL
		TWA (Respirable particulate matter)	1 mg/m3 (Aluminum)	ACGIH
Diiron trioxide	1309-37-1	TWA (Respirable)	5 mg/m3	CA AB OEL
		TWA (Fumes)	5 mg/m3 (Iron)	CA BC OEL
		TWA (Dust)	5 mg/m3 (Iron)	CA BC OEL
		STEL (Fumes)	10 mg/m3 (Iron)	CA BC OEL
		TWAEV (fume and dust)	5 mg/m3 (Iron)	CA QC OEL
		TWA (Res- pirable par- ticulate mat- ter)	5 mg/m3	ACGIH

#### **Engineering measures**

Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

### Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed

respirator complying with an approved standard if a risk as-

sessment indicates this is necessary.

The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.



Revision Date 10/25/2024 Print Date 10/25/2024

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling

the product.

Remove contaminated clothing and protective equipment

before entering eating areas. Wash thoroughly after handling.

Avoid breathing dust.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : granules

Color : black

Odor : No data available

Odor Threshold : No data available

pH : No data available

Melting point/ range / Freez-

ing point

No data available

Boiling point/boiling range : No data available

Flash point :  $> 93 \,^{\circ}\text{C} \, (199 \,^{\circ}\text{F})$ 

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Density : No data available



Revision Date 10/25/2024 Print Date 10/25/2024

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : insoluble

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : No data available

Oxidizing properties : No data available

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

Hazardous decomposition

products

No decomposition if stored and applied as directed.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

Not classified due to lack of data.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization

Not classified due to lack of data.



# Sable Marco® Asphalte Froide

Revision Date 10/25/2024 Print Date 10/25/2024

### Respiratory sensitization

Not classified due to lack of data.

## Germ cell mutagenicity

Not classified due to lack of data.

# Carcinogenicity

May cause cancer by inhalation. Suspected of causing cancer.

IARC Group 1: Carcinogenic to humans

Quartz (SiO2) >5µm 14808-60-7

(Silica dust, crystalline)

Group 2B: Possibly carcinogenic to humans

Asphalt 8052-42-4

(Bitumens, occupational exposure to straight-run bitumens and their emissions

during road paving)

**OSHA** OSHA specifically regulated carcinogen

Quartz (SiO2) >5µm 14808-60-7

(crystalline silica)

NTP Known to be human carcinogen

Quartz (SiO2) >5µm 14808-60-7

(Silica, Crystalline (Respirable Size))

### Reproductive toxicity

Not classified due to lack of data.

#### STOT-single exposure

May cause respiratory irritation.

### STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure.

May cause damage to organs (thymus, Liver, Bone marrow) through prolonged or repeated exposure.

Prolonged exposure can cause silicosis.

## **Aspiration toxicity**

Not classified due to lack of data.

#### **Further information**

#### Product:

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.



# Sable Marco® Asphalte Froide

Revision Date 10/25/2024 Print Date 10/25/2024

#### **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

**Product:** 

Additional ecological infor-

mation

Do not empty into drains; dispose of this material and its con-

tainer in a safe way.

### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

### **SECTION 14. TRANSPORT INFORMATION**

## **International Regulations**

IATA-DGR

Not regulated as a dangerous good

**IMDG-Code** 

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

**Domestic regulation** 

**TDG** 

Not regulated as a dangerous good



# Sable Marco® Asphalte Froide

Revision Date 10/25/2024 Print Date 10/25/2024

#### **SECTION 15. REGULATORY INFORMATION**

#### **Canadian lists**

No substances are subject to a Significant New Activity Notification.

#### **SECTION 16. OTHER INFORMATION**

### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)

CA BC OEL : Canada. British Columbia OEL

CA ON OEL : Ontario Table of Occupational Exposure Limits made under

the Occupational Health and Safety Act.

CA QC OEL : Québec. Regulation respecting occupational health and safe-

ty, Schedule 1, Part 1: Permissible exposure values for air-

borne contaminants

ACGIH / TWA : 8-hour, time-weighted average
CA AB OEL / TWA : 8-hour Occupational exposure limit
CA BC OEL / TWA : 8-hour time weighted average
CA BC OEL / STEL : short-term exposure limit

CA ON OEL / TWA : Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEV : Time-weighted average exposure value

ADR : Accord européen relatif au transport international des

marchandises Dangereuses par Route

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency



Revision Date 10/25/2024 Print Date 10/25/2024

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

#### Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

Revision Date : 10/25/2024 Date format : mm/dd/yyyy

Prepared by : R & D of Sika Canada Inc.

Material number : 780.919

**CA / Z8**